

1. IDENTIFICATION OF THE SUBSTANCE AND THE COMPANY UNDERTAKING

1.1 Product identifier

Product name Solu-Cal HUMIC Plus #11025

1.2 Relevant use of the product

Applications Fertilizers

1.3 Manufacturer, Importer or Responsible Party

| Name Address | NORTHEAST AGRICULTURAL SALES, INC. PO Box 5 Lyndonville, VT 05851 USA |
|-----------------|---|
| Telephone | 802-626-3351 |
| Contact email | nate@neag.net |

1.4 Emergency phone number

Telephone

USA National Capital Poison Center: 1 800 222 1222

2. HAZARDS IDENTIFICATION

2.1. The hazard classification of the chemical according to HCS 2012 (US-GHS)

| Skin Irrit 2 | H315 |
|--------------|------|
| Eye Irrit. 1 | H318 |
| STOT SE 3 | H335 |
| Carc. 1A | H350 |
| STOT RE 1 | H372 |

- 2.2. Danger symbols
- 2.3. Signal word
- 2.4. Hazard statements



- Hents H315 Causes skin irritation H318 Causes serious eye damage H335 May cause respiratory irritation H350 May cause cancer. H372 May cause damage to organs (lungs) through prolonged or repeated exposure if inhaled.
- 2.5. Precautionary
 - statements Prevention

P201 Obtain special instructions before use.



| | P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust. P264 Wash hands thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. |
|----------|---|
| | P280 Wear protective gloves/protective clothing/eye protection/face protection. |
| Response | P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| | P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. |
| | Remove contact lenses, if present and easy to do. Continue rinsing. |
| | P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. P330 Rinse mouth. |
| | P302+P352 IF ON SKIN: Wash with plenty of water. |
| | P362+P364 Take off contaminated clothing and wash it before reuse. |
| | P314 Get medical advice/attention if you feel unwell. |
| Storage | P405 Store locked up. |
| Disposal | P501 Dispose of contents/container according to local regulations. |

- 2.6. Description of any hazards not otherwise Not applicable. classified
- 2.7. % ingredient(s) with unknown acute toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name | | CAS-Nr. | Concentration % |
|---------------|----------------------------|------------|-------------------|
| | Limestone | 1317-65-3 | C =80 % - 99 % |
| | Silicon Dioxide(1) | 7631-86-9 | C = <1 % |
| | SiO2 Aluminum Oxide, Al2O3 | 1344-28-1 | C = < 1 % |
| | Ferric Oxide, Fe2O3 | 1309-37-1 | C = <1 % |
| | Magnesium Oxide, MgO | 1309-48-4 | C = 0.25 % -1.5 % |
| Gypsum mix | Calcium Oxide, CaO | 1305-78-8 | C = 0 % - 4.3 % |
| | Sodium Oxide, Na2O | 1313-59-3 | C = < 1 % |
| | Potassium Oxide K2O | 12136-45-7 | C = < 1 % |
| | Calcium Carbonate CaCO3 | 471-34-1 | C = 36-100 % |
| | Sodium Salt Lignin | 8068-05-1 | C =3 % -5 % |
| | Crude Soybean Oil | 8001-22-7 | C = < 1.5 % |

(1): The composition of SiO2 may be up to 100% crystalline silica



4. FIRST AID MEASURES

| 4.1 | First | Aid | measures | after | Inhalation |
|-----|-------|-----|----------|-------|------------|
| | | | measures | a | |

| Following inhalation | Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided by a qualified operator. Get medical attention if irritation develops and persists. |
|-----------------------------------|--|
| 4.2 First Aid measures after Skir | exposure |
| Following skin contact | Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Get medical attention if irritation develops and persists. |
| 4.3 First Aid measures after Eye | exposure |
| Following eye contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation develops and persists. |
| 4.4 First Aid measures after Inge | estion |
| Following ingestion | Induce vomiting, but only if victim is fully conscious. Never give anything by mouth to an unconscious person. Drink 1 or 2 glasses of water. Do not give milk or alcoholic beverages. Call a physician. |
| 4.5 Most important symptoms a | and effects, both acute and delayed |
| INHALATION | May cause respiratory irritation. |
| SKIN | Causes skin irritation. |
| EYES | Causes eye damage. If burning, redness, itching, pain or other symptoms persist or develop, consult a physician. |
| INGESTION | None known |

4.6 Indication of any immediate medical attention and special treatment needed

| Notes to physician: | Treat symptomatically. |
|---------------------|------------------------|
| Notes to physician. | freat symptomatically. |

5. FIREFIGHTING MEASURES

| 5.1 Extinguishing media | <u>Suitable</u> : Use extinguishing agent suitable for type of surrounding fire. Avoid excessive water to minimize runoff. Prevent firefighter water from entering the environment. Small fires: Water spray, foam, dry chemical or CO2 Large fires: Water spray, fog or foam. |
|--|--|
| | <u>Unsuitable</u> : Not applicable. |
| 5.2 Special hazards arising from chemical or mixture during the fire | Container may rupture on heating. Cool closed containers exposed to fire with water spray. Do not allow run-off from firefighting to enter drains or water courses. Explosive reactions with oxidizing agents such as potassium chlorate and/or peroxides. In case of fire hazardous decomposition products may be produced such as: - Ammonia - Carbon monoxide - Carbon dioxide (CO2) |
| 5.3 Special Protective Precautions or equipment for firefighters | In the event of fire and/or explosion do not breathe fumes. In the case of respirable dust and/or fumes, use self-contained breathing apparatus and dust impervious protective suit. |



SAFETY DATA SHEET Solu-Caluse Solu-Cal HUMIC Plus #11025

6. ACCIDENTAL RELEASE MEASURES

| 6.1 Personal precautions, protective equipment | Wear personal protective equipment. |
|--|---|
| 6.2 Emergency procedures | Unprotected persons must be kept away. |
| | Evacuate personnel to safe areas. |
| | Provide adequate ventilation. |
| | Avoid dust formation. |
| | Avoid breathing dust. |
| | Avoid contact with skin, eyes and clothing. |
| 6.3 Methods and materials | Do not flush into surface water or sanitary sewer system. |
| used for containment | Prevent further leakage or spillage if safe to do so. |
| | Do not let product enter drains. |
| 6.4 Clean-up procedures | Use mechanical handling equipment. |
| | Clean contaminated surface thoroughly. |
| | Pick up and arrange disposal without creating dust. |
| | Use a suitable vacuum cleaner. |

7. HANDLING AND STORAGE

| 7.1 Precautions for safe handling | Handle with care. Wear personal protective equipment. Use only in well-ventilated areas. Avoid dust formation. Provide exhaust ventilation if dust is formed. Dust must be extracted directly at the point of origin. Avoid breathing dust. Avoid contact with skin, eyes and clothing. |
|-----------------------------------|--|
| 7.2 Conditions for safe storage | Keep containers tightly closed in a dry, cool and well-ventilated place. Containers should be protected against falling down. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store away from incompatible substances. |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ACGIH-Threshold Limit Value (TLV)

Exposure limit values of the components:

Respirable crystalline silica dust: ACGIH TLV[®] = 0,025 mg/m³

8.2 OSHA-Permissible Exposure Limit (PEL)

Exposure limit values of the components:

| Component / CAS | PEL, 8H (OSHA) | |
|--------------------|---|--|
| | mg/m ³ | |
| Quartz (SiO2) | Total dust: 30 mg/m ³ / %SiO2+2 (OSHA Z-3) | |
| CAS N°: 14808-60-7 | Respirable: 10 mg/m ³ / %SiO2+2 (OSHA Z-3) | |
| | Respirable: 250 mppcf / %SiO2+5 (OSHA Z-3) | |



| Gypsum | Total dust: 15 mg/m ³ (OSHA Z-1) |
|--------------------|---|
| CAS N°: 13397-24-5 | Respirable: 5 mg/m ³ (OSHA Z-1) |

8.3 Any other exposure limit used or recommended by chemical manufacturer

Non applicable

8.4 Engineering Controls

Provide exhaust ventilation if dust is formed. Dust must be extracted directly at the point of origin. Apply technical measures to comply with the occupational exposure limits.

8.5 Personal Protective Equipment

Hand protection: Gloves Gloves must be inspected prior to use. Replace when worn.

Eve protection: Do not wear contact lenses. Wear as appropriate: Safety glasses with side-shields

Body protection: Long sleeved clothing

<u>Respiratory protection</u>: A NIOSH approved air purifying respirator with a type 95 (R or P) particulate filter may be used under conditions where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited (see manufacturer's respirator selection guide). Use a positive pressure air supplied respirator if there is potential for uncontrolled release, exposure levels are not known or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed if workplace conditions warrant a respirator use.

<u>Hygiene measures</u>: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use. Keep working clothes separately.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information of basic physical and chemical properties

| Appearance (physical state, colour, etc.) | White to off white |
|---|--------------------|
| Odour | Low to no odour |
| Odour threshold | Not applicable |
| рН | No data available |
| Melting point/freezing point; | No data available |
| Boiling point | Not applicable |
| Boiling Range | Not applicable |
| Flash point | No data available |



SAFETY DATA SHEET Solu-Cal use Solu-Cal HUMIC Plus #11025

| Evaporation rate | Not applicable |
|--|-----------------------|
| Flammability | Not flammable |
| Upper/lower flammability or explosive limits | No data available |
| Oxidising properties | No data available |
| Vapour pressure | Not applicable |
| Vapour density | No data available |
| Density | 67 lb/ft ³ |
| Solubility in water | Partially soluble |
| Other Solvents | No data available |
| Partition coefficient (n- octanol/water) | No data available |
| Auto ignition temperature | No data available |
| | |
| Decomposition temperature | No data available |

10. STABILITY AND REACTIVITY

| 10.1 Reactivity 10.2 Chemical stability | Contains Limestone which reacts with acids. It forms carbon dioxide (CO2). This displaces the oxygen in the air in closed spaces. (danger of suffocation) Stable under recommended storage conditions. |
|--|--|
| 10.3 Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| 10.4 Conditions to avoid | Contact with incompatible materials |
| 10.5 Incompatible materials | None known. |
| 10.6 Hazardous decomposition products | Gypsum ignites on contact with fluorine and is incompatible with acids, ammonium salts and magnesium. |

11. TOXICOLOGICAL INFORMATION

11.1 Measures of Toxicity



SAFETY DATA SHEET **Solu-Caluse** SAFETY DATA SHEET Solu-Cal HUMIC Plus #11025

| Acute toxicity: | Gypsum: Acute toxicity: LD50 Oral (Rat): > 5,000 mg/kg |
|------------------------------------|--|
| | Silica: Acute toxicity: LD50 (Rat): > 5,000 mg/kg (Mouse): >15000 mg/Kg |
| Skin corrosion/irritation: | No data available |
| Serious eye damage/irritation: | No data available |
| Respiratory or skin sensitisation: | Product: no data available |
| 11.2 Listed in IARC or considered | Quartz (SiO2) |
| carcinogen by NTP or OSHA | CAS N°: 14808-60-7 |
| | Group 1 (IARC), Volume 68, 100C |
| 11.3 Further information | This product contains prismatic tremolite (e.g., cleavage fragments) as an impurity. Sufficient exposure to respirable prismatic tremolite dust may cause serious lung problems. |

12. ECOLOGICAL INFORMATION

Ingredients:

12.1 Toxicity

| | Silica (quartz): |
|--|---|
| | Toxicity to fish : LC50: > 10,000 mg/l Exposure time: 96 h Species: <i>Oncorhynchus mykiss</i> (rainbow trout) |
| | Toxicity to daphnia and other aquatic invertebrates: EC50: >1000mg/l (Exposure time:48 h) Species: <i>Daphnia magna</i> (Water flea) EC50: 200 mg/l (Exposure time:72h) Species: <i>Desmodesmus subspicatus</i> (green algae) |
| | Gypsum: This product has no known effect on ecology. Toxicity studies of gypsum performed with fish, aquatic invertebrates and aquatic plants showed no toxic effects. |
| 12.2 Persistence and degradability 12.3 Bioaccumulative potential | No data available No data available |



SAFETY DATA SHEET Solu-Caluse Solu-Cal HUMIC Plus #11025

| 12.4 Mobility in soil | No data available |
|----------------------------|--|
| 12.5 Other adverse effects | May release ammonium ions that are toxic to fish. Un-ionized ammonia concentrations above 0.02 mg/l are considered toxic in fresh water. May release phosphates which will result in algae growth, increased turbidity, and depleted oxygen. At extremely high concentrations, this may be hazardous to fish or other marine organisms. Release to watercourses may cause effects downstream. Fish 96 hour LC50, OECD Guidelines 203 (rainbow trout): >86mg/L. |

13. DISPOSAL CONSIDERATIONS

| 13.1 Disposal methods to employ | Recover or recycle if possible. Properly characterize all waste materials. Consult federal, state/provincial and local regulations regarding the proper disposal of this material. Prevent material from entering sewers, storm drains, other unauthorized treatment drainage systems, and natural waterways. Empty containers should be taken to an approved waste handling site for recycling or disposal. |
|---|---|
| 13.2 Description of appropriate disposal containers to use | No data available |
| 13.3 Description of the physical and chemical properties that may affect disposal activities | No data available |
| 13.4 Language discouraging sewage disposal. | No data available |
| 13.5 Any special precautions for landfills or incineration activities | No data available |

14. TRANSPORT INFORMATION

| UN Number | |
|-----------------------------|--|
| UN proper shipping name | |
| Transport hazard classes | |
| Packing group | |
| Environmental hazards | |



| Guidance On transport | |
|-------------------------|--|
| in bulk | |
| Special precautions for | |
| user | |

15. REGULATORY INFORMATION

National and/or regional regulatory information of the chemical or mixtures

Inventories:

US. Toxic Substances Control Act: No data available

OSHA Hazards: Carcinogen

<u>Clean Air Act:</u> This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

16. OTHER INFORMATION

Indications on the revision

First edition: 01/05/16 Addition of all fields as required by regulation (US) HCS 1910.1200 [HCS 2012]. Update of the classification information and update of related sections accordingly.

Abbreviations and acronyms used

ACGIH: American conference of governmental and industrial hygienist CAS N°.: Chemical Abstract Service Number CFR: Code of Federal Regulations EC50: Half maximal effective concentration IARC: International agency for the research on cancer IC50: Half maximal inhibitory concentration HCS: Hazard communication standard NIOSH: National institute of occupational safety and health LC50: Half maximal lethal concentration LD50: Half maximal lethal dose OSHA: Occupational safety and health administration STOT SE: Specific target organ toxicity Single exposure UN N°.: United Nations Number **Methods of evaluation for the classification of mixtures**

The classification of the mixture was set based on the regulation (US) HCS 1910.1200 [HCS 2012].

Other information

This information is based on our present knowledge and is provided according to the relevant national regulations. This information is intended as a characterization of the product in order to provide guidance for the relevant safety issues. However, this document does not provide any warranty, expressed or implied, regarding the properties of the product.