





A SUPERIOR QUALITY FERROUS SULFATE HEPTAHYDRATE

Extreme Green 16 is an iron and manganese nutritional supplement that is used to help promote dark green color in turf and foliage of plants.

GUARANTEED ANALYSIS:

Sulfur (S)	12.0%
12.0% Combined Sulfur	
Iron (Fe)	16.0%
16.0% Water Soluble Iron	
Manganese (Mn)	4.0%
4.0% Water Soluble Manganese	

Derived from: Ferrous sulfate heptahydrate and

manganese sulfate.



KEEP OUT OF REACH OF CHILDREN DANGER

HARMFUL IF SWALLOWED.

CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

PRECAUTIONARY STATEMENTS

Do not breathe dust / mist / spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Specific treatment see First Aid section on this label.

Personal Protective Equipment

Wear protective gloves / protective clothing / eye protection / face protection. Wash contaminated clothing before reuse. **FIRST AID**

Immediately call a poison center / doctor.

If Swallowed: Call a poison center / doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting.

If On Skin (Or Hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.

If Inhaled: Remove person to fresh air and keep comfortable for breathing.

If In Eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

STORAGE AND DISPOSAL

Storage: Store locked up.

Disposal: Dispose of contents / container in accordance with local / regional / national regulations.

IN CASE OF EMERGENCY CALL CHEMTREC 1-800-424-9300

DIRECTIONS FOR USE:

Application rates should be based on tissue or petiole analysis. On plants with waxy leaf surfaces, 12 ounces (355 mL) of a non-ionic wetting agent per 100 gallons (380 L) of finished spray will aid leaf penetration. Add Extreme Green 16 to half of the water, then agitate while adding remaining water. Add urea or other fertilizers. Add herbicides last while continuing to agitate tank contents.


Apply Extreme Green 16 at a rate of 0.125 - 0.5 lbs. (2-8 ounces-dry weight) per 1,000 ft² (5.5 - 22 lbs. / Acre). Apply every 2 - 8 weeks based on desired color response.

Spray solution as soon as possible. Extreme Green 16 tank mixes are generally stable; however, agitate prior to spraving if mix has been standing for over 24 hours. Use sufficient water for good coverage. For optimum results, do not apply water for at least 4 hours following application. Do not apply to flower buds or blossoms of flowers, shrubs and trees.

COMPATIBILITY WITH OTHER MATERIALS:

Extreme Green 16 is most effective when plants are growing rapidly and is least effective when plants are dormant or suffering from stress. Extreme Green 16 is compatible with most pesticides and fertilizers, with the exception of amine formulation herbicides and high phosphate fertilizers. Do not use in tank mix with high phosphate fertilizers. Tank mixes with amines should not be attempted unless adequate agitation exists. Do not pre-mix Extreme Green 16 with any high-pH herbicides without performing a jar test.

Information regarding the contents and levels of metals in this product is available on the Internet at: http://www.regulatory-info-jr.com



www.P65Warnings.ca.gov

Extreme Green®, ColorPack® and Simplot® are registered trademarks of the J.R. Simplot Company.

DISCLAIMER OF WARRANTIES

J.R. Simplot Company warrants that the composition of this product conforms to the description and is reasonably fit for the purpose as stated on the label only when used in accordance with label directions under normal conditions of use. This warranty is expressly in lieu of all other warranties and representations expressed, implied, or statutory, including warranties of merchantability and fitness for a particular use. Timing, rate and method of application, weather and crop conditions, and mixtures not specifically recommended on this label or an accompanying written recommendation, are beyond the control of the seller. Buyer assumes all risks of use, storage and handling of this material not in strict accordance with directions given herewith. Buyer further agrees in the event of damages resulting from, but not limited to, weather or soil conditions, presence of other materials, or failure to follow label directions will be assumed by the Buyer or User; and to accept a replacement of the product or a refund of the purchase price of the product, at buyer's option, as full discharge of seller's liability. No one is authorized to make any other warranty, guarantee or directions concerning this product, and no such warranties, guarantees or directions shall be valid or binding upon seller.

F1470



1234850L GHS version: 18245

