Specifying Roller Assemblies and Part Number Legend

When ordering Competition Rollers it is helpful to provide descriptive information to help confirm correct part number. Examples as follows:

- a) Mower brand, model number, mowing application, front or rear position on the mower.
 - Example: "JD 7500 fairway, front roller with QA-5 mower heads (5" reels)".
- b) Roller body diameter, length and style
 - Example: "3" dia. x 22.25" grooved body".
- c) Roller shaft length and special features on shaft ends to fit the receiving bracket of mower head. Example: "shaft is 25.5" with 3/8"-24 tap in both ends of shaft".
- d) Specify other upgrades or special features by adding a note to your purchase order.

 Example: "Add upgrade to stainless steel bearings in roller body (part #BU-COMPSS)".

Our Competition Roller assembly part numbers include component specs as follows:

1st **digit** - letter denoting brand of mower such as "D" for John Deere, "J" for Jacobsen, "T" for Toro or for TruTurf or Turfline, etc.

next 2 digits - numbers denoting length of shaft (rounded down to whole number).

next 2 digits - numbers denoting length of roller body (rounded down to whole number). Most Competition Roller polyurethane bodies are an additional .45" longer than this number, steel bodies are .25" longer.

next digit - letter denoting shaft end configuration or special machined features (such as milled flats, taps or cross holes). Example: "C" for round 5/8" dia. with one milled flat on one end of shaft.

next 1 or 2 digits - number or numbers denoting diameter of roller body.

Examples: "25" for 2.5" dia., "2" for 2" dia., "3" for 3" dia., "35" for 3.5" dia., "4" for 4" dia., "5" for 5" dia., etc.

next 1 or 2 digits - letters denoting body style as follows:

- "CG" for cast urethane wide grooves without flat on ends
- "CGF" for cast urethane wide grooves with @1" wide flat (smooth section) on ends
- "NG" for cast urethane narrow grooves without flat on ends
- "NGF" for cast urethane narrow grooves with @1" wide flat (smooth section) on ends
- "CG.22C" for cast urethane wide grooves with @2.2" flat (smooth section) on ends
- "C" for cast urethane smooth surface (no grooves)
- "S" for steel smooth surface (no grooves)

Example: D2522C2CGF would be for a John Deere mower with 25.5" shaft, 22.45" body, shaft has 1 milled flat on 1 end, 2" diameter body, wide grooved polyurethane body style with @1" wide flat (smooth section) on the ends.

Special add-on codes for part number:

- a) "2" added at front of part number for double row bearing upgrade.
- b) "t" added at end of part number for roller assembly with twin bodies on a shaft.
- c) "3" added at end of part number for roller assembly with 3 bodies on a shaft.
- d) "4" added at end of part number for roller assembly with 4 bodies on a shaft.

For upgrade to stainless steel bearings in each roller body you must add part number "BU-COMPSS" as a separate line item (each roller body requires one upgrade. Therefore, a four-body roller assembly requires four upgrades at additional cost each).



GOLFCO INTERNATIONAL COMPETITION ROLLERS 2024

for Jacobsen mowers		Roller Assemblies		shaft # included
Jacobsen ALL 22" GREENS MOWERS including GREENSKING	, GM, I	E-Plex, G-Plex, GP40	0 & ECLIPSE 122 & 322 MOWERS - FRONT RO	
2" dia. SINGLE body rollers				
2" wide grooved Urethane no flats	6.5 lb	J2522A2CG	22.45" body, 25.87" shaft	SHA2522AJ
2" narrow grooved Urethane no flats	6.7 lb	J2522A2NG	22.45" body, 25.87" shaft	SHA2522AJ
2" wide grooved Urethane 1" flats	6.5 lb	J2522A2CGF	22.45" body, 25.87" shaft	SHA2522AJ
2" narrow grooved Urethane 1" flats		J2522A2NGF	22.45" body, 25.87" shaft	SHA2522AJ
2" smooth Urethane	8 lb	J2522A2C	22.25" body, 25.87" shaft	SHA2522AJ
2" smooth Steel heavy (1/4" wall)	11.5 lb	J2522A2S	22.25" body, 25.87" shaft	SHA2522AJ
2" dia. TWO body rollers			non-striping, non-skidding for tight turns & ground un	
2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats		J2504A2CGt	2 short twin bodies at ends of a 25.87" shaft	SHA2504AJNt
2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats		J2504A2NGt	2 short twin bodies at ends of a 25.87" shaft	SHA2504AJNt
2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats		J2504A2CGFt	2 short twin bodies at ends of a 25.87" shaft	SHA2504AJNt
2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats		J2504A2NGFt	2 short twin bodies at ends of a 25.87° shaft	SHA2504AJNt
2 bodies 2" smooth Urethane (2x2" wide bodies)		J2502A2Ct	2 short twin bodies at ends of a 25.87" shaft	SHA2502AJNt
2 bodies 2" smooth Urethane (2x4.75" wide bodies)	4.2 lb	J2504A2Ct	2 short twin bodies at ends of a 25.87° shaft	SHA2504AJNt
2" dia. THREE body rollers			non-skidding for tight turns & ground undulations	
3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies)		J3122A2CG+2C	22.45" center body + 2 short outer bodies, 31.87" shaft	SHA3122AJN+2
3 bodies 2" narrow grooved Urethane (22.45" inner+2x2" outer bodies)		J3122A2NG+2C	22.45" center body + 2 short outer bodies, 31.87" shaft	SHA3122AJN+2
3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies)		J3122A2C+2C	22.25" center body + 2 short outer bodies, 31.87" shaft	SHA3122AJN+2
3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies)	13 lb	J3122A2S+2S	22.25" center body + 2 short outer bodies, 31.87" shaft	SHA3122AJN+2
2" dia. FOUR body rollers			non-skidding for tight turns & ground undulations	
4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats		J2522A2CG4	4 short bodies, 25.87" shaft	SHA2522AJN4
4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats		J2522A2NG4	4 short bodies, 25.87" shaft	SHA2522AJN4
4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats		J2522A2CGF4	4 short bodies, 25.87" shaft	SHA2522AJN4
4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats		J2522A2NGF4	4 short bodies, 25.87" shaft	SHA2522AJN4
4 bodies 2" smooth Urethane (4x5.55" wide bodies)		J2522A2C4	4 short bodies, 25.87" shaft	SHA2522AJN4
4 bodies 2" smooth Steel heavy (4x5.55" wide bodies)	12 lb	J2522A2S4	4 short bodies, 25.87" shaft	SHA2522AJN4
2" dia. SIX body rollers			non-skidding for tight turns & ground undulations	
6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies)		J3122A2CG4+2C	4 center bodies + 2 short outer bodies, 31.87" shaft	SHA3122AJN4+2
6 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies)		J3122A2NG4+2C	4 center bodies + 2 short outer bodies, 31.87" shaft	SHA3122AJN4+2
6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats		J3122A2CGF4+2C	4 center bodies + 2 short outer bodies, 31.87" shaft	SHA3122AJN4+2
6 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats		J3122A2NGF4+2C	4 center bodies + 2 short outer bodies, 31.87" shaft	SHA3122AJN4+2
6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies)		J3122A2C4+2C	4 center bodies + 2 short outer bodies, 31.87" shaft	SHA3122AJN4+2
6 bodies 2" smooth Steel heavy (4x5.55" inner+2x2" outer bodies)	13 lb	J3122A2S4+2S	4 center bodies + 2 short outer bodies, 31.87" shaft	SHA3122AJN4+2
2.5" dia. SINGLE body rollers				
2.5" wide grooved (1" spacing) Urethane no flats		J2522A25CG	22.45" body, 25.87" shaft	SHA2522AJ
2.5" narrow grooved (1/2" spacing) Urethane no flats		J2522A25NG	22.45" body, 25.87" shaft	SHA2522AJ
2.5" smooth Urethane		J2522A25C	22.25" body, 25.87" shaft	SHA2522AJ
2.5" smooth Steel	10 lb	J2522A25S	22.25" body, 25.87" shaft	SHA2522AJ
2.5" dia. TWO body rollers		1000110000	non-striping, non-skidding for tight turns & ground un	
2 bodies 2.5" grooved Urethane (2x4.75" wide bodies) no flats		J2504A25CGt	2 short twin bodies at ends of a 25.87° shaft	SHA2504AJNt
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies)	4.2 lb	J2504A25Ct	2 short twin bodies at ends of a 25.87" shaft	SHA2504AJNt
2.5" dia. FOUR body rollers	10.5.11	10500405004	non-skidding for tight turns & ground undulations	011105001 1111
4 bodies 2.5" grooved Urethane (4x5.55" wide bodies) no flats		J2522A25CG4	4 short bodies, 25.87" shaft	SHA2522AJN4
4 bodies 2.5" smooth Urethane (4x5.55" wide bodies)		J2522A25C4	4 short bodies, 25.87" shaft	SHA2522AJN4
4 bodies 2.5" smooth Steel (4x5.55" wide bodies)	12 10	J2522A25S4	4 short bodies, 25.87" shaft	SHA2522AJN4
2.5" dia. SIX body rollers	4415	10400405004.00	non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 31.87" shaft	CHARACON INVA-D
6 bodies 2.5" grooved Urethane (4x5.55" inner+2x2" outer bodies)		J3122A25CG4+2C		SHA3122AJN4+2
Jacobsen ALL 22" GREENS MOWERS including GREENSKING 2" dia. SINGLE body rollers w/ 3/8" taps in shaft	, GIVI, I	E-Flex, G-Flex,GF400	A ECLIFSE 122 & 322 MOVVERS - BACK ROL	LEK
2" wide grooved Urethane no flats	6.5 lb	J2422S2CG	22.45" body, 24.25" shaft-3/8" taps	SHA2422SJ
2" narrow grooved Urethane no flats		J2422S2NG	22.45" body, 24.25" shaft-3/8" taps	SHA2422SJ
2" wide grooved Urethane 1" flats		J2422S2CGF	22.45" body, 24.25" shaft-3/8" taps	SHA2422SJ
2" narrow grooved Urethane 1" flats		J2422S2NGF	22.45" body, 24.25" shaft-3/8" taps	SHA2422SJ
2" smooth Urethane		J2422S2C	22.25" body, 24.25" shaft-3/8" taps	SHA2422SJ
2" smooth Steel heavy (1/4" wall)		J2422S2S	22.25" body, 24.25" shaft-3/8" taps	SHA2422SJ
2" dia. SINGLE body rollers w/ 7/16" taps in shaft	11.010	02422020	ELEO DOUJ, E4.20 Sharrord taps	0117242200
2" wide grooved Urethane no flats	6.5 lb	J2422G2CG	22.45" body, 24.25" shaft-7/16" taps	SHA2422GJ
2" narrow grooved Urethane no flats		J2422G2NG	22.45" body, 24.25" shaft-7/16" taps	SHA2422GJ
2" wide grooved Urethane 1" flats		J2422G2CGF	22.45" body, 24.25" shaft-7/16" taps	SHA2422GJ
[1] [1] 전 1 전 1 전 1 전 1 전 1 전 1 전 1 전 1 전 1 전		J2422G2NGF	22.45" body, 24.25" shaft-7/16" taps	SHA2422GJ
2" narrow grooved Urethane 1" flats 2" smooth Urethane		J2422G2NGF J2422G2C	22.25" body, 24.25" shaft-7/16" taps	SHA2422GJ SHA2422GJ
2" smooth Steel heavy (1/4" wall)		J2422G2C J2422G2S	22.25 body, 24.25 shaft-7/16 taps 22.25" body, 24.25" shaft-7/16" taps	SHA2422GJ
2" dia. TWO body rollers w/ 3/8" taps in shaft	11.010	02722020	non-striping, non-skidding for tight turns & ground un	
2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats	4 lb	J2404S2CGt	2 short twin bodies at ends of a 24.25" shaft-3/8" taps	SHA2404SJNt
2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats		J2404S2NGt	2 short twin bodies at ends of a 24.25" shaft-3/8" taps	SHA2404SJNt
2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats		J2404S2CGFt	2 short twin bodies at ends of a 24.25" shaft-3/8" taps	SHA2404SJNt
2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats		J2404S2NGFt	2 short twin bodies at ends of a 24.25" shaft-3/8" taps	SHA2404SJNt
2 bodies 2" smooth Urethane (2x2" wide bodies)		J2402S2Ct	2 short twin bodies at ends of a 24.25" shaft-3/8" taps	SHA2404SJNt
: 2019년 1월 10일 시에 전 시에 대한 1일 1일 2일 1일 2일 1일 2일		J2402S2Ct J2404S2Ct	2 short twin bodies at ends of a 24.25 shaft-3/8 taps 2 short twin bodies at ends of a 24.25 shaft-3/8 taps	SHA2404SJNt
2 bodies 2" smooth Urethane (2x4.75" wide bodies)	4.Z ID	J24043201		
2" dia. TWO body rollers w/ 7/16" taps in shaft	4.15	1240462004	non-striping, non-skidding for tight turns & ground un	
2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats		J2404G2CGt	2 short twin bodies at ends of a 24.25" shaft-7/16" taps	SHA2404GJNt
2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats		J2404G2NGt	2 short twin bodies at ends of a 24.25" shaft-7/16" taps	SHA2404GJNt
2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats		J2404G2CGFt	2 short twin bodies at ends of a 24.25" shaft-7/16" taps	SHA2404GJNt
2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats		J2404G2NGFt	2 short twin bodies at ends of a 24.25" shaft-7/16" taps	SHA2404GJNt
2 bodies 2" smooth Urethane (2x2" wide bodies)		J2402G2Ct	2 short twin bodies at ends of a 24.25" shaft-7/16" taps	SHA2404GJNt
2 bodies 2" smooth Urethane (2x4.75" wide bodies)	4.2 ID	J2404G2Ct	2 short twin bodies at ends of a 24.25" shaft-7/16" taps	SHA2404GJNt



2" dia. THREE body rollers w/ 3/8" taps in shaft		non-skidding for tight turns & ground undulations	
3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies)	12 lb J3022S2CG+2C	22.45" center body + 2 short outer bodies, 30.25" shaft-3/8" taps	SHA3022SJN+2
3 bodies 2" narrow grooved Urethane (22.45" inner+2x2" outer bodies)	12 lb J3022S2NG+2C	22.45" center body + 2 short outer bodies, 30.25" shaft-3/8" taps	SHA3022SJN+2
3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies)	13 lb J3022S2C+2C	22.25" center body + 2 short outer bodies, 30.25" shaft-3/8" taps	SHA3022SJN+2
3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies)	13 lb J3022S2S+2S	22.25" center body + 2 short outer bodies, 30.25" shaft-3/8" taps	SHA3022SJN+2
2" dia. THREE body rollers w/ 7/16" taps in shaft	, , , , , , , , , , , , , , , , , , , ,	non-skidding for tight turns & ground undulations	
3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies)	12 lb J3022G2CG+2C	22.45" center body + 2 short outer bodies, 30.25" shaft-7/16" taps	SHA3022GJN+2
3 bodies 2" narrow grooved Urethane (22.45" inner+2x2" outer bodies)	12 lb J3022G2NG+2C	22.45" center body + 2 short outer bodies, 30.25" shaft-7/16" taps	SHA3022GJN+2
3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies)	13 lb J3022G2C+2C	22.25" center body + 2 short outer bodies, 30.25" shaft-7/16" taps	SHA3022GJN+2
3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies)	13 lb J3022G2S+2S	22.25" center body + 2 short outer bodies, 30.25" shaft-7/16" taps	SHA3022GJN+2
2" dia. FOUR body rollers w/ 3/8" taps in shaft		non-skidding for tight turns & ground undulations	
4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats	8.5 lb J2422S2CG4	4 short bodies, 24.25" shaft-3/8" taps	SHA2422SJN4
4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats	8.5 lb J2422S2NG4	4 short bodies, 24.25" shaft-3/8" taps	SHA2422SJN4
4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb J2422S2CGF4	4 short bodies, 24.25" shaft-3/8" taps	SHA2422SJN4
4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb J2422S2NGF4	4 short bodies, 24.25" shaft-3/8" taps	SHA2422SJN4
4 bodies 2" smooth Urethane (4x5.55" wide bodies)	8.5 lb J2422S2C4	4 short bodies, 24.25" shaft-3/8" taps	SHA2422SJN4
4 bodies 2" smooth Steel heavy (4x5.55" wide bodies)	12 lb J2422S2S4	4 short bodies, 24.25" shaft-3/8" taps	SHA2422SJN4
2" dia. FOUR body rollers w/ 7/16" taps in shaft		non-skidding for tight turns & ground undulations	1200020222000
4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats	8.5 lb J2422G2CG4	4 short bodies, 24.25" shaft-7/16" taps	SHA2422GJN4
4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats	8.5 lb J2422G2NG4	4 short bodies, 24.25" shaft-7/16" taps	SHA2422GJN4
4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb J2422G2CGF4	4 short bodies, 24.25" shaft-7/16" taps	SHA2422GJN4
4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb J2422G2NGF4	4 short bodies, 24.25" shaft-7/16" taps	SHA2422GJN4
4 bodies 2" smooth Urethane (4x5.55" wide bodies)	8.5 lb J2422G2C4 12 lb J2422G2S4	4 short bodies, 24.25" shaft-7/16" taps	SHA2422GJN4 SHA2422GJN4
4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) 2" dia. SIX body rollers w/ 3/8" taps in shaft	12 ID 32422G2S4	4 short bodies, 24.25" shaft-7/16" taps	SHAZ4ZZGJN4
6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies)	13 lb J3022S2CG4+2C	non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 30.25" shaft-3/8" taps	SHA3022SJN4+2
6 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies)	13 lb J3022S2CG4+2C	4 center bodies + 2 short outer bodies, 30.25" shaft-3/8" taps	SHA3022SJN4+2
6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats	13 lb J3022S2CGF4+2C	4 center bodies + 2 short outer bodies, 30.25" shaft-3/8" taps	SHA3022SJN4+2
6 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats		4 center bodies + 2 short outer bodies, 30.25" shaft-3/8" taps	SHA3022SJN4+2
6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies)	13 lb J3022S2C4+2C	4 center bodies + 2 short outer bodies, 30.25" shaft-3/8" taps	SHA3022SJN4+2
6 bodies 2" smooth Steel heavy (4x5.55" inner+2x2" outer bodies)	13 lb J3022S2S4+2S	4 center bodies + 2 short outer bodies, 30.25" shaft-3/8" taps	SHA3022SJN4+2
2" dia. SIX body rollers w/ 7/16" taps in shaft	10 10 000220201120	non-skidding for tight turns & ground undulations	
6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies)	13 lb J3022G2CG4+2C	4 center bodies + 2 short outer bodies, 30.25" shaft-7/16" taps	SHA3022GJN4+2
6 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies)	13 lb J3022G2NG4+2C	4 center bodies + 2 short outer bodies, 30.25" shaft-7/16" taps	SHA3022GJN4+2
6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats	13 lb J3022G2CGF4+2C	4 center bodies + 2 short outer bodies, 30.25" shaft-7/16" taps	SHA3022GJN4+2
6 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats		4 center bodies + 2 short outer bodies, 30.25" shaft-7/16" taps	SHA3022GJN4+2
6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies)	13 lb J3022G2C4+2C	4 center bodies + 2 short outer bodies, 30.25" shaft-7/16" taps	SHA3022GJN4+2
6 bodies 2" smooth Steel heavy (4x5.55" inner+2x2" outer bodies)	13 lb J3022G2S4+2S	4 center bodies + 2 short outer bodies, 30.25" shaft-7/16" taps	SHA3022GJN4+2
Jacobsen TC-22 GREENSMOWERS - FRONT ROLLER			
2" dia. SINGLE body rollers			
2" wide grooved Urethane no flats	6.5 lb J2522J2CG	22.45" body, 25.87" shaft	SHA2522JJ
2" narrow grooved Urethane no flats	6.7 lb J2522J2NG	22.45" body, 25.87" shaft	SHA2522JJ
2" wide grooved Urethane 1" flats	6.5 lb J2522J2CGF	22.45" body, 25.87" shaft	SHA2522JJ
2" narrow grooved Urethane 1" flats	6.7 lb J2522J2NGF	22.45" body, 25.87" shaft	SHA2522JJ
2" smooth Urethane	8 lb J2522J2C	22.25" body, 25.87" shaft	SHA2522JJ
2" smooth Steel heavy (1/4" wall)	11.5 lb J2522J2S	22.25" body, 25.87" shaft	SHA2522JJ
2" dia. FOUR body rollers		non-skidding for tight turns & ground undulations	
4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats	8.5 lb J2522J2CG4	4 short bodies, 25.87" shaft	SHA2522JJN4
4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats	8.5 lb J2522J2NG4	4 short bodies, 25.87" shaft	SHA2522JJN4
4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb J2522J2CGF4	4 short bodies, 25.87" shaft	SHA2522JJN4
4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb J2522J2NGF4	4 short bodies, 25.87" shaft	SHA2522JJN4
4 bodies 2" smooth Urethane (4x5.55" wide bodies)	8.5 lb J2522J2C4	4 short bodies, 25.87" shaft	SHA2522JJN4
4 bodies 2" smooth Steel heavy (4x5.55" wide bodies)	12 lb J2522J2S4	4 short bodies, 25.87" shaft	SHA2522JJN4
Jacobsen TC-22 GREENSMOWERS - BACK ROLLER			
2" dia. SINGLE body rollers 2" wide grooved Urethane no flats	6.5 lb J2522V2CG	22.45" body, 25.87" shaft	SHA2522VJ
2" narrow grooved Urethane no flats	6.7 lb J2522V2NG	22.45" body, 25.87" shaft	SHA2522VJ
2" wide grooved Urethane 1" flats	6.5 lb J2522V2CGF	LL TO DOUG, LOUIS STATE	
2" narrow grooved Urethane 1" flats		22 45" body 25 87" shaft	
		22.45" body, 25.87" shaft 22.45" body, 25.87" shaft	SHA2522VJ
	6.7 lb J2522V2NGF	22.45" body, 25.87" shaft	SHA2522VJ SHA2522VJ
2" smooth Urethane			SHA2522VJ
	6.7 lb J2522V2NGF 8 lb J2522V2C	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft	SHA2522VJ SHA2522VJ SHA2522VJ
2" smooth Urethane 2" smooth Steel heavy (1/4" wall)	6.7 lb J2522V2NGF 8 lb J2522V2C	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft	SHA2522VJ SHA2522VJ SHA2522VJ
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft non-skidding for tight turns & ground undulations	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2CG4	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.87" shaft	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.87" shaft 4 short bodies, 25.87" shaft	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA2522VJN4
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2CGF4	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.87" shaft 4 short bodies, 25.87" shaft 4 short bodies, 25.87" shaft	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA2522VJN4 SHA2522VJN4
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2CGF4 8.5 lb J2522V2NGF4	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.87" shaft	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies)	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2CGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2CG4 12 lb J2522V2S4	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.87" shaft	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2CGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2C4 12 lb J2522V2S4 14 lb J2522V2S4 15 lb J2522V2S4 16 lb J2522V2S4	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.87" shaft 5 short bodies, 25.87" shaft	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2C4 12 lb J2522V2C4 12 lb J2522V2S4 14 lb J2522V2S4 15 lb J2119A2CG	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 4 short bodies, 25.87" shaft 5 short bodies, 25.87" shaft 1 short bodies, 25.87" shaft	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2C4 12 lb J2522V2C4 12 lb J2522V2S4 6K 518) - FRONT & BACK RO 6.2 lb J2119A2NG	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 4 short bodies, 25.87" shaft 9 short bodies, 25.87" shaft 1 short bodies, 25.87" shaft 22.25" shaft w/o taps	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA252VJN4 SHA252VJN4 SHA252VJN4 SHA252VJN4
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2CG 12 lb J2522V2C4 12 lb J2522V2S4 6.2 lb J2119A2CG 6.4 lb J2119A2CG 6.2 lb J2119A2CGF	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.87" shaft 9 short bodies, 25.87" shaft 1 short bodies, 25.87" shaft wio taps 1 short body, 21.25" shaft wio taps 1 short body, 21.25" shaft wio taps 1 short body, 21.25" shaft wio taps	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2C4 12 lb J2522V2C4 12 lb J2522V2S4 6K 518) - FRONT & BACK RO 6.2 lb J2119A2CG 6.4 lb J2119A2NG 6.2 lb J2119A2NGF	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.87" shaft 9LLERS (SHAFT is 21.25" without taps in either 19.45" body, 21.25" shaft w/o taps	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2C 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2C4 12 lb J2522V2C4 12 lb J2522V2S4 6K 518) - FRONT & BACK RO 6.2 lb J2119A2CG 6.4 lb J2119A2NG 6.2 lb J2119A2NGF 7.5 lb J2119A2NGF	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.87" shaft 9LLERS (SHAFT is 21.25" without taps in either 19.45" body, 21.25" shaft w/o taps 19.25" body, 21.25" shaft w/o taps	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall)	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2C4 12 lb J2522V2C4 12 lb J2522V2S4 6K 518) - FRONT & BACK RO 6.2 lb J2119A2CG 6.4 lb J2119A2NG 6.2 lb J2119A2NGF	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 4 short bodies, 25.87" shaft 9 LLERS (SHAFT is 21.25" without taps in either 19.45" body, 21.25" shaft w/o taps 19.25" body, 21.25" shaft w/o taps	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2NG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2C4 12 lb J2522V2C4 12 lb J2522V2S4 IK 518) - FRONT & BACK RO 6.2 lb J2119A2NG 6.2 lb J2119A2NG 6.4 lb J2119A2NGF 7.5 lb J2119A2NGF 7.5 lb J2119A2S	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.87" shaft 9 LLERS (SHAFT is 21.25" without taps in either 19.45" body, 21.25" shaft w/o taps 19.45" body, 21.25" shaft w/o taps 19.45" body, 21.25" shaft w/o taps 19.25" body, 21.25" shaft w/o taps	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2119AJ
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" vide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2NG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2C4 12 lb J2522V2C4 12 lb J2522V2S4 6K 518) - FRONT & BACK RO 6.2 lb J2119A2CG 6.4 lb J2119A2NG 6.2 lb J2119A2NG 6.2 lb J2119A2NGF 7.5 lb J2119A2CGF 6.4 lb J2119A2CGF 6.4 lb J2119A2CGF 6.5 lb J2119A2CGF 6.6 lb J2119A2CGF 6.7 lb J2119A2CGF	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 4 short bodies, 25.87" shaft 9 short bodies, 25.87" shaft 1 short bodies, 25.87" shaft wio taps 19.45" body, 21.25" shaft wio taps 19.25" body, 21.25" shaft wio taps	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA252VJN4 SHA2522VJN4 SHA252VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA252VJN4 SHA252VJN4 SHA252VJN4 SHA252VJN4 SHA252VJN4 SHA252VJN
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2NG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2C4 12 lb J2522V2C4 12 lb J2522V2S4 12 lb J2119A2CG 6.4 lb J2119A2NG 6.2 lb J2119A2NG 6.2 lb J2119A2NGF 7.5 lb J2119A2CG 6.4 lb J2119A2CGF 6.4 lb J2119A2CGF 6.5 lb J2119A2CGF	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 4 short bodies, 25.87" shaft 9 short bodies, 25.87" shaft 1 short bodies, 25.87" shaft 2 short body, 21.25" shaft w/o taps 19.45" body, 21.25" shaft w/o taps 19.25" body, 21.25" shaft w/o taps	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2119AJ SHA210AJNt SHA210AJNt SHA210AJNt
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2C 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2CG 12 lb J2522V2C4 12 lb J2522V2S4 6K 518) - FRONT & BACK RO 6.2 lb J2119A2CG 6.4 lb J2119A2NG 6.2 lb J2119A2NGF 7.5 lb J2119A2CG 10.5 lb J2119A2C 4 lb J2104A2CGt 4 lb J2104A2CGt 4 lb J2104A2CGF	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.87" shaft 9LLERS (SHAFT is 21.25" without taps in either 19.45" body, 21.25" shaft w/o taps 19.25" body, 21.25" shaft w/o taps	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA2119AJ SHA210AJNt SHA210AJNt SHA210AJNt SHA210AJNt
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" marrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2CG 12 lb J2522V2C4 12 lb J219A2CG 6.4 lb J2119A2NG 6.2 lb J2119A2CGF 6.4 lb J2119A2CGF 7.5 lb J2119A2C 10.5 lb J2119A2C 4 lb J2104A2CGt 4 lb J2104A2CGFt 4 lb J2104A2CGFt 4 lb J2104A2CGFt	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 4 short bodies, 25.87" shaft 9 SLEERS (SHAFT is 21.25" without taps in either 19.45" body, 21.25" shaft w/o taps 19.25" body, 21.25" shaft w/o taps	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA219AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA210AJNt SHA210AJNt SHA210AJNt SHA210AJNt SHA210AJNt
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2C4 12 lb J2522V2C4 12 lb J2522V2S4 12 lb J2522V2S4 12 lb J2119A2CG 6.4 lb J2119A2CG 6.4 lb J2119A2CGF 6.4 lb J2119A2CGF 7.5 lb J2119A2CG 10.5 lb J2119A2CG 4 lb J2119A2CG 4 lb J2104A2CGT 4 lb J2104A2CGT 4 lb J2104A2CGF	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 4 short bodies, 25.87" shaft 9 short bodies, 25.87" shaft 1 short bodies, 25.87" shaft 2 short bwin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA2522VJN4 SHA219AJ SHA2119AJ SHA210AJNt
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" vide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2S 8.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2CG 12 lb J2522V2C4 12 lb J219A2CG 6.4 lb J2119A2NG 6.2 lb J2119A2CGF 6.4 lb J2119A2CGF 7.5 lb J2119A2C 10.5 lb J2119A2C 4 lb J2104A2CGt 4 lb J2104A2CGFt 4 lb J2104A2CGFt 4 lb J2104A2CGFt	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 4 short bodies, 25.87" shaft 4 short body, 21.25" shaft w/o taps 19.45" body, 21.25" shaft w/o taps 19.45" body, 21.25" shaft w/o taps 19.25" bod	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA219AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA210AJNt SHA210AJNt SHA210AJNt SHA210AJNt SHA210AJNt
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" marrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies)	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2C 11.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2CG 12 lb J2522V2C4 12 lb J2522V2S4 6K 518) - FRONT & BACK RO 6.2 lb J2119A2CG 6.4 lb J2119A2NG 6.2 lb J2119A2NGF 7.5 lb J2119A2CGF 6.4 lb J2119A2CGF 6.4 lb J2119A2CG 10.5 lb J2119A2C 10.5 lb J2119A2C 10.5 lb J2119A2CG 4 lb J2104A2NGF 6.2 lb J2104A2NGF 8 lb J2104A2NGF 8 lb J2104A2NGF 8 lb J2104A2NGF 8 lb J2104A2CCC	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 4 short bodies, 25.87" shaft 9 short bodies, 25.87" shaft 19.45" body, 21.25" shaft w/o taps 19.45" body, 21.25" shaft w/o taps 19.45" body, 21.25" shaft w/o taps 19.25" body, 21.25" shaft aps 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA219AJ SHA2119AJ SHA210AJNt
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies)	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2C 11.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2CG 12 lb J2522V2C4 12 lb J2522V2C4 12 lb J2522V2C4 12 lb J2119A2CG 6.4 lb J2119A2NG 6.2 lb J2119A2CG 6.4 lb J2119A2CGF 6.4 lb J2119A2CG 10.5 lb J2119A2C 10.5 lb J2119A2C 4 lb J2104A2CGT 4 lb J2104A2NGT 4 lb J2104A2CGT 4 lb J2104A2CCT 4 lb J2104A2CCT	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 4 short bodies, 25.87" shaft 9 short bodies, 25.87" shaft 1 short bodies, 25.87" shaft 1 short bodies, 25.87" shaft 2 short bodies, 25.87" shaft 1 short bodies, 25.87" shaft 2 short body, 21.25" shaft w/o taps 19.45" body, 21.25" shaft w/o taps 19.45" body, 21.25" shaft w/o taps 19.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA210AJNt
2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) Jacobsen ALL 18" GREENSMOWERS (Eclipse 118, GK 418 & G 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" marrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies)	6.7 lb J2522V2NGF 8 lb J2522V2C 11.5 lb J2522V2C 11.5 lb J2522V2CG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NG4 8.5 lb J2522V2NGF4 8.5 lb J2522V2NGF4 8.5 lb J2522V2CG 12 lb J2522V2C4 12 lb J2522V2S4 6K 518) - FRONT & BACK RO 6.2 lb J2119A2CG 6.4 lb J2119A2NG 6.2 lb J2119A2NGF 7.5 lb J2119A2CGF 6.4 lb J2119A2CGF 6.4 lb J2119A2CG 10.5 lb J2119A2C 10.5 lb J2119A2C 10.5 lb J2119A2CG 4 lb J2104A2NGF 6.2 lb J2104A2NGF 8 lb J2104A2NGF 8 lb J2104A2NGF 8 lb J2104A2NGF 8 lb J2104A2CCC	22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 4 short bodies, 25.87" shaft 9 short bodies, 25.87" shaft 19.45" body, 21.25" shaft w/o taps 19.45" body, 21.25" shaft w/o taps 19.45" body, 21.25" shaft w/o taps 19.25" body, 21.25" shaft aps 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft	SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJ SHA2522VJN4 SHA219AJ SHA2119AJ SHA210AJNt



			non-skidding for tight turns & ground undulations	
2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats	8.5 lb	J2119A2CG4	4 short bodies, 21.25" shaft	SHA2119AJN4
4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) no flats		J2119A2NG4	4 short bodies, 21.25" shaft	SHA2119AJN4
4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) 1" flats	8.5 lb	J2119A2CGF4	4 short bodies, 21.25" shaft	SHA2119AJN4
4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats	8.5 lb	J2149A2NGF4	4 short bodies, 21.25" shaft	SHA2119AJN4
4 bodies 2" smooth Urethane (4x4.75" wide bodies)	8.5 lb	J2119A2C4	4 short bodies, 21.25" shaft	SHA2119AJN4
4 bodies 2" smooth Steel heavy (4x4.75" wide bodies)	12 lb	J2119A2S4	4 short bodies, 21.25" shaft	SHA2119AJN4
2" dia. SIX body rollers			non-skidding for tight turns & ground undulations	
6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) no flats	13 lb	J2719A2CG4+2C	4 center bodies + 2 short outer bodies, 27.25" shaft	SHA2719AJN4+2
6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies)	13 lb	J2719A2NG4+2C	4 center bodies + 2 short outer bodies, 27.25" shaft	SHA2719AJN4+2
6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats	13 lb	J2719A2CGF4+2C	4 center bodies + 2 short outer bodies, 27.25" shaft	SHA2719AJN4+2
6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats		J2719A2NGF4+2C	4 center bodies + 2 short outer bodies, 27.25" shaft	SHA2719AJN4+2
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies)	1077-137	J2719A2C4+2C	4 center bodies + 2 short outer bodies, 27.25" shaft	SHA2719AJN4+2
6 bodies 2" smooth steel heavy (4x4.75" inner+2x2" outer bodies)		J2719A2S4+2S	4 center bodies + 2 short outer bodies, 27.25" shaft	SHA2719AJN4+2
Jacobsen 18" Eclipse2 118F GREENSMOWERS - FRONT ROLL 2" dia. SINGLE body rollers	ERS	SHAFT is 21.25" with tap	os in both ends)	
2" wide grooved Urethane no flats	621	J2119S2CG	19.45" body, 21.25" shaft-3/8" taps	SHA2119SJ
2" narrow grooved Urethane no flats		J2119S2NG	19.45" body, 21.25" shaft-3/8" taps	SHA2119SJ
2" wide grooved Urethane 1" flats		J2119S2CGF	19.45" body, 21.25" shaft-3/8" taps	SHA2119SJ
2" narrow grooved Urethane 1" flats		J2119S2NGF	19.45" body, 21.25" shaft-3/8" taps	SHA2119SJ
2" smooth Urethane		J2119S2C	19.25" body, 21.25" shaft-3/8" taps	SHA2119SJ
2" smooth Steel heavy (1/4" wall)		J2119S2S	19.25" body, 21.25" shaft-3/8" taps	SHA2119SJ
2" dia. TWO body rollers			non-striping, non-skidding for tight turns & ground undula	tions
2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats	4 lt	J2104S2CGt	2 short twin bodies at ends of a 21.25" shaft-3/8" taps	SHA2104SJNt
2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats		J2104S2NGt	2 short twin bodies at ends of a 21.25" shaft-3/8" taps	SHA2104SJNt
2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats		J2104S2CGFt	2 short twin bodies at ends of a 21.25" shaft-3/8" taps	SHA2104SJNt
2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats	4 lb	J2104S2NGFt	2 short twin bodies at ends of a 21.25" shaft-3/8" taps	SHA2104SJNt
2 bodies 2" smooth Urethane (2x2" wide bodies)	4 lb	J2102S2Ct	2 short twin bodies at ends of a 21.25" shaft-3/8" taps	SHA2102SJNt
2 bodies 2" smooth Urethane (2x4.75" wide bodies)	4.2 lb	J2104S2Ct	2 short twin bodies at ends of a 21.25" shaft-3/8" taps	SHA2104SJNt
2" dia. THREE body rollers			non-skidding for tight turns & ground undulations	
3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies)	12 lb	J2719S2CG+2C	19.45" center body +2 short outer bodies, 27.25" shaft-3/8" taps	SHA2719SJN+2
3 bodies 2" narrow grooved Urethane (19.45" inner+2x2" outer bodies)	12 lb	J2719S2NG+2C	19.45" center body +2 short outer bodies, 27.25" shaft-3/8" taps	SHA2719SJN+2
3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies)	13 lb	J2719S2C+2C	19.25" center body +2 short outer bodies, 27.25" shaft-3/8" taps	SHA2719SJN+2
2" dia. FOUR body rollers			non-skidding for tight turns & ground undulations	
4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats	8.5 lb	J2119S2CG4	4 short bodies, 21.25" shaft-3/8" taps	SHA2119SJN4
4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) no flats	8.5 lb	J2119S2NG4	4 short bodies, 21.25" shaft-3/8" taps	SHA2119SJN4
4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) 1" flats	8.5 lb	J2119S2CGF4	4 short bodies, 21.25" shaft-3/8" taps	SHA2119SJN4
4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats		J2119S2NGF4	4 short bodies, 21.25" shaft-3/8" taps	SHA2119SJN4
4 bodies 2" smooth Urethane (4x4.75" wide bodies)		J2119S2C4	4 short bodies, 21.25" shaft-3/8" taps	SHA2119SJN4
4 bodies 2" smooth steel heavy (4x4.75" wide bodies)	12 lb	J2119S2S4	4 short bodies, 21.25" shaft-3/8" taps	SHA2119SJN4
2" dia. SIX body rollers			non-skidding for tight turns & ground undulations	
6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) no flats		J2719S2CG4+2C	4 center bodies +2 short outer bodies, 27.25" shaft-3/8" taps	SHA2719SJN4+2
6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies)		J2719S2NG4+2C	4 center bodies +2 short outer bodies, 27.25" shaft-3/8" taps	SHA2719SJN4+2
6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats		J2719S2CGF4+2C	4 center bodies +2 short outer bodies, 27.25" shaft-3/8" taps	SHA2719SJN4+2
6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats		J2719S2NGF4+2C	4 center bodies +2 short outer bodies, 27.25" shaft-3/8" taps	SHA2719SJN4+2
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies)		J2719S2C4+2C	4 center bodies +2 short outer bodies, 27.25" shaft-3/8" taps	SHA2719SJN4+2
6 bodies 2" smooth steel heavy (4x4.75" inner+2x2" outer bodies) Jacobsen 18" Eclipse2 118F GREENSMOWERS - REAR ROLLE		J2719S2S4+2S	4 center bodies +2 short outer bodies, 27.25" shaft-3/8" taps	SHA2719SJN4+2
2" dia. SINGLE body rollers	,,0 ,0	THE T IS 20.0 WITH TOPS I	in both chas	
2" wide grooved Urethane no flats	621	J2019S2CG	19.45" body, 20.5" shaft-3/8" taps	SHA2119SJ
		OLUTOCLOO		
		J2019S2NG		SHA2119SJ
2" narrow grooved Urethane no flats	6.4 lk	J2019S2NG J2019S2CGF	19.45" body, 20.5" shaft-3/8" taps	SHA2119SJ SHA2019SJ
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats	6.4 lb 6.2 lb	J2019S2CGF		
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats	6.4 lb 6.2 lb 6.4 lb	J2019S2CGF J2019S2NGF	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps	SHA2019SJ
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats	6.4 lb 6.2 lb 6.4 lb 7.5 lb	J2019S2CGF	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps	SHA2019SJ SHA2119SJ
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane	6.4 lb 6.2 lb 6.4 lb 7.5 lb	J2019S2CGF J2019S2NGF J2019S2C	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps	SHA2019SJ SHA2119SJ SHA2019SJ SHA2019SJ
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall)	6.4 lb 6.2 lb 6.4 lb 7.5 lb 10.5 lb	J2019S2CGF J2019S2NGF J2019S2C	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps	SHA2019SJ SHA2119SJ SHA2019SJ SHA2019SJ
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers	6.4 lk 6.2 lk 6.4 lk 7.5 lk 10.5 lk	J2019S2CGF J2019S2NGF J2019S2C J2019S2S	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-striping, non-skidding for tight turns & ground undula	SHA2019SJ SHA2119SJ SHA2019SJ SHA2019SJ tions
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats	6.4 lk 6.2 lk 6.4 lk 7.5 lk 10.5 lk 4 lk 4 lk	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/3" taps 19.25" body, 20.5" shaft-3/3" taps non-stripling, non-skidding for tight turns & ground undula 2 short twin bodies at ends of a 20.5" shaft-3/8" taps	SHA2019SJ SHA2119SJ SHA2019SJ SHA2019SJ tions SHA2004SJNt
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats	6.4 lk 6.2 lk 6.4 lk 7.5 lk 10.5 lk 4 lk 4 lk	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-striping, non-skidding for tight turns & ground undula 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps	SHA2019SJ SHA2119SJ SHA2019SJ SHA2019SJ tions SHA2004SJNt SHA2004SJNt
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2CGFt	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-striping, non-skidding for tight turns & ground undula 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps	SHA2019SJ SHA2119SJ SHA2019SJ SHA2019SJ tions SHA2004SJNt SHA2004SJNt SHA2004SJNt
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats	6.4 lk 6.2 lk 6.4 lk 7.5 lk 10.5 lk 4 lk 4 lk 4 lk 4 lk	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2NGFt	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-striping, non-skidding for tight turns & ground undular 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps	SHA2019SJ SHA2119SJ SHA2019SJ SHA2019SJ tions SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies)	6.4 lk 6.2 lk 6.4 lk 7.5 lk 10.5 lk 4 lk 4 lk 4 lk 4 lk	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2002S2Ct	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-striping, non-skidding for tight turns & ground undular 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps	SHA2019SJ SHA2119SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies)	6.4 lk 6.2 lk 6.4 lk 7.5 lk 10.5 lk 4 lk 4 lk 4 lk 4.2 lk	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2002S2Ct	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps	SHA2019SJ SHA2119SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2.75" wide bodies) 2 bodies 2" smooth Urethane (2x2.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies)	6.4 lk 6.2 lk 6.4 lk 7.5 lk 10.5 lk 4 lk 4 lk 4 lk 4 lk 4 lk 4 lk 12 lk	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2CGFt J2004S2NGFt J2004S2NGFt J2004S2CCt	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-stripling, non-skidding for tight turns & ground undula 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps	SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" narrow grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies)	6.4 lk 6.2 lk 6.4 lk 7.5 lk 10.5 lk 4 lk 4 lk 4 lk 4 lk 4 lk 12 lk	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2002S2Ct J2004S2CT	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-striping, non-skidding for tight turns & ground undula 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 10.55 shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps	SHA2019SJ SHA2019SJ SHA2019SJ HA2019SJ HONE SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2002SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 dia. THREE body rollers 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" narrow grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 2" dia. FOUR body rollers	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 4.2 lt 12 lt 13 lt 13 lt 13 lt 15 lt 16 lt 17	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2004S2CC J2004S2Ct J2004S2Ct J2019S2Ct J2619S2CG+2C J2619S2CG+2C	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/6" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps	SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2002SJNt SHA2002SJNt SHA2004SJNt SHA2619SJN+2 SHA2619SJN+2 SHA2619SJN+2
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats	6.4 lk 6.2 lk 6.4 lk 7.5 lk 10.5 lk 4 lk 4 lk 4 lk 4 lk 12 lk 12 lk 13 lk 8.5 lk 8.5 lk	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2004S2CC J2019S2Ct J2019S2Ct J2619S2CG+2C J2619S2CG+2C J2019S2CG4	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-stripling, non-skidding for tight turns & ground undular 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps	SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2619SJN+2
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2.75" wide bodies) 2 bodies 2" smooth Urethane (2x2.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" narrow grooved Urethane (19.45" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) no flats	6.4 lk 6.2 lk 6.4 lk 7.5 lk 10.5 lk 4 lk 4 lk 4 lk 4 lk 12 lk 12 lk 13 lk 8.5 lk 8.5 lk 8.5 lk	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2CGFt J2004S2NGFt J2004S2CC J2004S2CC J2004S2CC J2004S2CC J2004S2CC J2004S2CC J2019S2CC J2019S2CG+2C J2019S2CC-2C J2019S2CG4 J2019S2CG4	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-striping, non-skidding for tight turns & ground undulal 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps non-skidding for tight turns & ground undulations 4 short bodies, 20.5" shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2002SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2019SJN4 SHA2019SJN4
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" narrow grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) 1" flats	6.4 lk 6.2 lk 6.4 lk 7.5 lk 10.5 lk 4 lk 4 lk 4 lk 4 lk 4 lk 12 lk 12 lk 13 lk 8.5 lk 8.5 lk 8.5 lk 8.5 lk	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2004S2CC J2004S2CC J2019S2C J2619S2CG+2C J2619S2NG+2C J2619S2CG4 J2019S2CG4 J2019S2CG4 J2019S2NG4 J2019S2NG4 J2019S2NG4	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-striping, non-skidding for tight turns & ground undulat 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps non-skidding for tight turns & ground undulations 4 short bodies, 20.5" shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps	SHA2019SJ SHA2019SJ SHA2019SJ HA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" narrow grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 2 dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) 1" flats	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 4 lt 12 lt 13 lt 8.5 lt 8.5 lt 8.5 lt 8.5 lt 8.5 lt 8.5 lt	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2002S2Ct J2004S2Ct J2619S2NG+2C J2619S2NG+2C J2619S2CG4 J2019S2CG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NGF4	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" narrow grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 12 lt 13 lt 8.5 lt 8.5 lt 8.5 lt 8.9 lt 8.9 lt 8.9 lt	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2004S2CCt J2004S2CCt J2019S2CCt J2619S2NG+2C J2619S2NG+2C J2619S2CG4 J2019S2CG4 J2019S2NG4 J2019S2NG4 J2019S2NGF4 J2019S2NGF4 J2019S2NGF4 J2019S2NGF4 J2019S2CGF4	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2002SJNt SHA2002SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (19.4.75" wide bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" narrow grooved Urethane (19.45" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies)	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 12 lt 13 lt 8.5 lt 8.5 lt 8.5 lt 8.9 lt 8.9 lt 8.9 lt	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2002S2Ct J2004S2Ct J2619S2NG+2C J2619S2NG+2C J2619S2CG4 J2019S2CG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NGF4	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +3 shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4
2" narrow grooved Urethane 1" flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x2.7" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 2" dia. SIX body rollers	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 12 lt 12 lt 13 lt 8.5 lt 8.5 lt 8.5 lt 8.9 lt 12 lt 12 lt 12 lt 12 lt 12 lt 13 lt 8.5 lt 12 lt 12 lt 12 lt 12 lt 13 lt 8.5 lt	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2004S2CC J2019S2C J2019S2CC J2019S2CC J2619S2CG+2C J2619S2CG+2C J2019S2CG4 J2019S2CG4 J2019S2NG4 J2019S2NG4 J2019S2NGF4 J2019S2CG4 J2019S2C4 J2019S2C4	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-stripling, non-skidding for tight turns & ground undulat 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps non-skidding for tight turns & ground undulations 4 short bodies, 20.5" shaft-3/8" taps	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4
2" narrow grooved Urethane 1" flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" narrow grooved Urethane (19.45" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" vide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 2" dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) no flats	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 4 lt 12 lt 12 lt 13 lt 8.5 lt 8.5 lt 8.9 lt 12 lt 13 lt 13 lt 13 lt 13 lt 14 lt 14 lt 15 lt 1	J2019S2CGF J2019S2NGF J2019S2S J2019S2S J2004S2CGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2004S2NGFt J2004S2CC J2619S2CG+2C J2619S2NG+2C J2619S2CG-4 J2019S2CG4 J2019S2NG4 J2019S2NG4 J2019S2NGF4 J2019S2CG4 J2019S2CA	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-striping, non-skidding for tight turns & ground undulal 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps	SHA2019SJ SHA2019SJ SHA2019SJ Itions SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2002SJNt SHA2004SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4
2" narrow grooved Urethane 1" flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" narrow grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 2" dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) no flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies)	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 4 lt 12 lt 13 lt 8.5 lt 8.5 lt 8.9 lt 12 lt 13 lt 1	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2NGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2002S2Ct J2019S2C J2619S2NG+2C J2619S2NG+2C J2019S2CG4 J2019S2NG4	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-striping, non-skidding for tight turns & ground undulat 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.55" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.55" center body +2 short outer bodies, 26.5" shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps 5 shaft bodies, 20.5" shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps 5 short bodies, 20.5" shaft-3/8" taps 6 short bodies, 20.5" shaft-3/8" taps 7 shaft-3/8" taps 8 short bodies, 20.5" shaft-3/8" taps 9 short bodies, 20.5" shaft-3/8" taps	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNI SHA2004SJNI SHA2004SJNI SHA2004SJNI SHA2004SJNI SHA2004SJNI SHA2004SJNI SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2619SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4
2" narrow grooved Urethane 1" flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (4y.45" inner+2x2" outer bodies) 3 bodies 2" marrow grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 2" dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) no flats 6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 4 lt 12 lt 12 lt 13 lt 8.5 lt 8.5 lt 8.5 lt 12 lt 13 lt 1	J2019S2CGF J2019S2NGF J2019S2C J2019S2S J2004S2CGt J2004S2CGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2002S2Ct J2004S2CC J2619S2NG+2C J2619S2NG+2C J2619S2CG4 J2019S2CG4 J2019S2NG4 J2019S2CG4 J2019S2NG4 J2019S2CG4 J2019S2NG4 J2019S2CG4 J2019S2NG4 J2019S2NG4 J2019S2NG4+2C J2619S2NG4+2C	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-striping, non-skidding for tight turns & ground undula 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.55" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.55" center body +2 short outer bodies, 26.5" shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps 4 short bodies 20.5" shaft-3/8" taps 5 shaft-3/8" taps 6 shaft-3/8" taps 6 shaft-3/8" taps 7 shaft-3/8" taps 8 shaft-3/8" taps 8 shaft-3/8" taps 9 shaft-	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2619SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4
2" narrow grooved Urethane 1" flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" narrow grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 2 " dia. FOUR body rollers 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 2 " and row grooved Urethane (4x4.75" wide bodies) 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 2 " dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) no flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 4 lt 12 lt 13 lt 8.5 lt 8.5 lt 8.5 lt 8.5 lt 13 lt	J2019S2CGF J2019S2NGF J2019S2S J2019S2S J2004S2CGt J2004S2NGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2004S2NGFt J2004S2CCt J2004S2CCt J2019S2CG+ J2619S2NG+2C J2619S2CG+2C J2019S2NG4 J2019S2NG4+2C J2619S2NG4+2C J2619S2NGF4+2C	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4
2" narrow grooved Urethane 1" flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x2.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 2 bodies 2" wide grooved Urethane (19.45" wide bodies) 2 bodies 2" marrow grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 2" smooth Urethane (4x4.75" wide bodies) 2" smooth Urethane (4x4.75" wide bodies) 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" marrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 2" dia. SIX body rollers 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies)	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 4 lt 12 lt 12 lt 13 lt 8.5 lt 8.5 lt 8.5 lt 12 lt 13 lt 1	J2019S2CGF J2019S2NGF J2019S2S J2019S2S J2004S2CGt J2004S2NGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2002S2Ct J2004S2CC J2619S2NG+2C J2619S2NG+2C J2619S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2CG4 J2019S2NG4 J2019S2CG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NG4+2C J2619S2NG4+2C J2619S2NGF4+2C J2619S2NGF4+2C J2619S2NGF4+2C	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-stripling, non-skidding for tight turns & ground undulat 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short o	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2002SJNt SHA2002SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN4 SHA2019SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2
2" narrow grooved Urethane 1" flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x2.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" narrow grooved Urethane (19.45" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 2 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 5 marrow grooved Urethane (4x4.75" wide bodies) 7 marrow grooved Urethane (4x4.75" wide bodies) 8 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) no flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" marrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" mooth Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1" flats	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 12 lt 12 lt 13 lt 8.5 lt 8.5 lt 8.5 lt 12 lt 13 lt 13 lt 13 lt 13 lt 12 lt 12 lt 12 lt 13 lt 13 lt 13 lt 13 lt 12 lt 12 lt 12 lt 12 lt 12 lt 13 lt	J2019S2CGF J2019S2NGF J2019S2S J2019S2S J2019S2S J2004S2CGt J2004S2NGt J2004S2CGFt J2004S2NGFt J2004S2CGT J2004S2CC J2019S2C J2019S2CC J2619S2NG+2C J2619S2NG+2C J2019S2CG4 J2019S2NG4 J2019S2CGF4 J2019S2NGF4 J2019S2CG+ J2019S2CG++2C J2619S2CGF++2C J2619S2NGF+4-2C J2619S2NGF+4-2C J2619S2NGF+4-2C J2619S2NGF+4-2C J2619S2CGF+4-2C	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-stripling, non-skidding for tight turns & ground undulal 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps non-skidding for tight turns & ground undulations 4 short bodies, 20.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4
2" narrow grooved Urethane 1" flats 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" vide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 2" dia. SIX body rollers 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) no flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 3 7 acobsen ALL 26" GREE	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 12 lt 12 lt 13 lt 8.5 lt 8.5 lt 8.5 lt 12 lt 13 lt 13 lt 13 lt 13 lt 12 lt 12 lt 12 lt 13 lt 13 lt 13 lt 13 lt 12 lt 12 lt 12 lt 12 lt 12 lt 13 lt	J2019S2CGF J2019S2NGF J2019S2S J2019S2S J2019S2S J2004S2CGt J2004S2NGt J2004S2CGFt J2004S2NGFt J2004S2CGT J2004S2CC J2019S2C J2019S2CC J2619S2NG+2C J2619S2NG+2C J2019S2CG4 J2019S2NG4 J2019S2CGF4 J2019S2NGF4 J2019S2CG+ J2019S2CG++2C J2619S2CGF++2C J2619S2NGF+4-2C J2619S2NGF+4-2C J2619S2NGF+4-2C J2619S2NGF+4-2C J2619S2CGF+4-2C	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-stripling, non-skidding for tight turns & ground undulal 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps non-skidding for tight turns & ground undulations 4 short bodies, 20.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2002SJNt SHA2002SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN4 SHA2019SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2
2" narrow grooved Urethane 1" flats 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" marrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x2.75" wide bodies) 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 2 bodies 2" marrow grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 2" dia. SIX body rollers 6 bodies 2" smooth Grooved Urethane (4x4.75" inner+2x2" outer bodies) 2" dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1" flats	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 4 lt 12 lt 13 lt 12 lt 13 lt 13 lt 13 lt 13 lt 12 lt 12 lt 12 lt 13 lt 13 lt 12 lt 14 lt 15 lt 16 l	J2019S2CGF J2019S2NGF J2019S2S J2019S2S J2004S2CGt J2004S2NGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2004S2CGt J2004S2CC J2019S2CC J2619S2CG+2C J2619S2NG+2C J2619S2NG4 J2019S2NG4 J2019S2NG4+2C J2619S2NG4+2C J2619S2NGF4+2C J261PS2NGF4+2C	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-striping, non-skidding for tight turns & ground undulal 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.55" center body +2 short outer bodies, 26.5" shaft-3/8" taps 4 short bodies, 20.5" shaft-3/8" taps 4 short bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" shaft	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNI SHA2004SJNI SHA2004SJNI SHA2004SJNI SHA2004SJNI SHA2004SJNI SHA2004SJNI SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2619SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2
2" narrow grooved Urethane 1" flats 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 4 bodies 2" smooth Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 2" dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 7 dia. SIX body rollers 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 7 hats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 8 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 9 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1 hats 1 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1 hats 1 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1 hats 1 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies)	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 4 lt 12 lt 12 lt 13 lt 13 lt 13 lt 12 lt 12 lt 13 lt 12 lt 15 l	J2019S2CGF J2019S2NGF J2019S2S J2019S2S J2004S2CGt J2004S2NGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2002S2Ct J2004S2CC J2619S2NG+2C J2619S2NG+2C J2619S2NG4 J2019S2NG4 J2019S2NG4+2C J2619S2NGF4+2C	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-stripling, non-skidding for tight turns & ground undula 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps non-skidding for tight turns & ground undulations 4 short bodies, 20.5" shaft-3/8" taps 4 short bodies +2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies +2 short outer bodies,	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2
2" narrow grooved Urethane 1" flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" narrow grooved Urethane (19.45" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 2 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 2" dia. SIX body rollers 6 bodies 2" smooth steel heavy (4x4.75" wide bodies) 2" dia. SIX body rollers 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 7 dia. SIX body rollers 8 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 9 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 1 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 2 chais SINGLE body rollers 2 wide grooved Urethane no flats	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 4 lt 12 lt 12 lt 13 lt 8.5 lt 8.5 lt 8.5 lt 12 lt 13 lt 12 lt 13 lt 12 lt 13 lt 12 lt 13 lt 13 lt 12 lt 13 lt 1	J2019S2CGF J2019S2NGF J2019S2S J2019S2S J2019S2S J2004S2CGt J2004S2CGt J2004S2NGt J2004S2NGFt J2002S2Ct J2004S2CCt J2004S2CCt J2004S2CCt J2019S2CG+2C J2619S2NG+2C J2619S2CG+2C J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2NG4 J2019S2CG+2C J2619S2NG4+2C J2619S2NG4+2C J2619S2NG4+2C J2619S2NGF4+2C	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-stripling, non-skidding for tight turns & ground undulat 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps non-skidding for tight turns & ground undulations 4 short bodies, 20.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies + 2 short outer bodies, 26.5" sh	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2926AJ SHA2926AJ
2" narrow grooved Urethane 1" flats 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x2" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies) 4 bodies 2" smooth Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x4.75" wide bodies) 2" dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 7 dia. SIX body rollers 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 7 hats 6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 8 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 9 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1 hats 1 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1 hats 1 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 1 hats 1 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies)	6.4 lt 6.2 lt 6.4 lt 7.5 lt 10.5 lt 4 lt 4 lt 4 lt 4 lt 12 lt 12 lt 13 lt 8.5 lt 8.5 lt 8.5 lt 12 lt 13 lt 1	J2019S2CGF J2019S2NGF J2019S2S J2019S2S J2004S2CGt J2004S2NGt J2004S2NGt J2004S2NGFt J2004S2NGFt J2002S2Ct J2004S2CC J2619S2NG+2C J2619S2NG+2C J2619S2NG4 J2019S2NG4 J2019S2NG4+2C J2619S2NGF4+2C	19.45" body, 20.5" shaft-3/8" taps 19.45" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps non-stripling, non-skidding for tight turns & ground undula 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 2 short twin bodies at ends of a 20.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.45" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps 19.25" center body +2 short outer bodies, 26.5" shaft-3/8" taps non-skidding for tight turns & ground undulations 4 short bodies, 20.5" shaft-3/8" taps 4 short bodies +2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 4 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies +2 short outer bodies, 26.5" shaft-3/8" taps 5 center bodies +2 short outer bodies,	SHA2019SJ SHA2019SJ SHA2019SJ SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2004SJNt SHA2019SJN+2 SHA2619SJN+2 SHA2619SJN+2 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4 SHA2019SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2 SHA2619SJN4+2



			\$45700 Fe1 \$77000 B) 51 0.0700	
2" dia. FOUR body rollers	10 11	J2926A2CG4	non-skidding for tight turns & ground undulations 4 short bodies, 29.75" shaft	SHA2926AJN4
4 bodies 2" wide grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2" smooth Urethane (4x6.5" wide bodies)) J2926A2CG4) J2926A2C4	4 short bodies, 29.75" shaft	SHA2926AJN4
4 bodies 2" smooth steel heavy (4x6.5" wide bodies)		J2926A2S4	4 short bodies, 29.75" shaft	SHA2926AJN4
2.5" dia. SINGLE body rollers				
2.5" grooved Urethane no flats		J2926A25CG	26.45" body, 29.75" shaft	SHA2926AJ
2.5" smooth Urethane		J2926A25C	26.45" body, 29.75" shaft	SHA2926AJ
2.5" smooth Steel	11 1	J2926A25S	26.25" body, 29.75" shaft	SHA2926AJ
2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats	10 1	J2926A25CG4	non-skidding for tight turns & ground undulations 4 short bodies, 29.75" shaft	SHA2926AJN4
4 bodies 2.5" smooth Urethane (4x6.5" wide bodies)		J2926A25C4	4 short bodies, 29.75" shaft	SHA2926AJN4
4 bodies 2.5" smooth Steel (4x6.5" wide bodies)		J2926A25S4	4 short bodies, 29.75" shaft	SHA2926AJN4
2.5" dia. SIX body rollers			non-skidding for tight turns & ground undulations	
6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies)		J3526A25CG4+2C	4 center bodies + 2 short outer bodies, 35.75" shaft	SHA3526AJN4+2
6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies)		J3526A25C4+2C	4 center bodies + 2 short outer bodies, 35.75" shaft	SHA3526AJN4+2
Jacobsen 26" LF3810 & TRIKING 1471 & 1671 - FRONT & BA 2.5" dia. SINGLE body rollers	ACK ROL	LEKS	(Sectional rollers with 4 bodies also available)	able)
2.5" grooved Urethane no flats	9.5 1	J2826A25CG	26.45" body, 28.375" shaft	SHA2826AJ
2.5" smooth Urethane	11 li	J2826A25C	26.45" body, 28.375" shaft	SHA2826AJ
2.5" smooth Steel	11 II	J2826A25S	26.25" body, 28.375" shaft	SHA2826AJ
3" dia. SINGLE body rollers				
3" grooved Urethane no flats		J2826A3CG	26.45" body, 28.375" shaft	SHA2826AJ
3" smooth Urethane 3" smooth Steel) J2826A3C) J2826A3S	26.45" body, 28.375" shaft 26.25" body, 28.375" shaft	SHA2826AJ SHA2826AJ
Jacobsen 26" TR-3 - FRONT & BACK ROLLERS	13.31	J2020A33	(Sectional rollers with 4 bodies also avail	
2.5" dia. SINGLE body rollers			(Sectional Folicis With 4 Bodies disc dvall	abicy
2.5" grooved Urethane no flats	9.5 II	J3126X25CG	26.45" body, 31.25" shaft-1/2" dia. ends	SHA3126XJ
2.5" smooth Urethane		J3126X25C	26.45" body, 31.25" shaft-1/2" dia. ends	SHA3126XJ
2.5" smooth Steel	11 1	J3126X25S	26.45" body, 31.25" shaft-1/2" dia. ends	SHA3126XJ
3" dia. SINGLE body rollers	12 11	J3126X3CG	26.45" body, 31.25" shaft-1/2" dia. ends	SHA3126XJ
3" grooved Urethane no flats 3" smooth Urethane		J3126X3C	26.45" body, 31.25" shaft-1/2" dia. ends	SHA3126XJ
3" smooth Steel		J3126X3S	26.45" body, 31.25" shaft-1/2" dia. ends	SHA3126XJ
Jacobsen 30" TRIKING 1684D & 1900D - FRONT & BACK RO				
2.5" dia. SINGLE body rollers				
2.5" grooved Urethane no flats		J3229A25CG	29.45" body, 32.19" shaft	SHA3229AJ
2.5" smooth Urethane		J3229A25C	29.45" body, 32.19" shaft	SHA3229AJ SHA3229AJ
2.5" smooth Steel 3" dia. SINGLE body rollers	121	J3229A25S	29.45" body, 32.19" shaft	SHAJZZBAJ
3" grooved Urethane no flats	12 4 II	J3229A3CG	29.45" body, 32.19" shaft	SHA3229AJ
3" smooth Urethane		J3229A3C	29.45" body, 32.19" shaft	SHA3229AJ
2ll amounth Otabal	45.00			
3" smooth Steel	15 1	J3229A3S	29.45" body, 32.19" shaft	SHA3229AJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F		J3229A3S	29.45° body, 32.19° shaft (Sectional rollers with 4 bodies also avail-	
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers	ROLLER		(Sectional rollers with 4 bodies also available)	able)
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats	ROLLER 9 II) J2119A3CG	(Sectional rollers with 4 bodies also avail. 19.45" body, 21.25" shaft	able) SHA2119AJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane	9 II 10.5 II) J2119A3CG) J2119A3C	(Sectional rollers with 4 bodies also avail. 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft	SHA2119AJ SHA2119AJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel	9 II 10.5 II 11 II) J2119A3CG	(Sectional rollers with 4 bodies also avail. 19.45" body, 21.25" shaft	able) SHA2119AJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane	9 II 10.5 II 11 II) J2119A3CG) J2119A3C	(Sectional rollers with 4 bodies also avail. 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft	SHA2119AJ SHA2119AJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane	9 II 10.5 II 11 II of reels 8.5 II 6.5 II	D J2119A3CG D J2119A3C D J2119A3S D J2119A3CG.22C D J2016G2C	(Sectional rollers with 4 bodies also avail. 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft call for proper application specifics	sha2119aJ Sha2119aJ Sha2119aJ Sha2119aJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO	9 II 10.5 II 11 II of reels 8.5 II 6.5 II	D J2119A3CG D J2119A3C D J2119A3S D J2119A3CG.22C D J2016G2C	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO	9 II 10.5 II 11 II of reels 8.5 II 6.5 II	D J2119A3CG D J2119A3C D J2119A3S D J2119A3CG.22C D J2016G2C With 7/16-20 tap)	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane	9 II 10.5 II 11 II of reels 8.5 II 6.5 II OLLER (v	D J2119A3CG D J2119A3C D J2119A3C D J2119A3CG.22C D J2016G2C Vith 7/16-20 tap)	(Sectional rollers with 4 bodies also avail: 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45" body, 20.5" shaft-7/16" taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall)	9 10.5 10.5 11 16 reels 8.5 6.5 OLLER (v 6.5 8.5	D J2119A3CG D J2119A3C D J2119A3S D J2119A3CG.22C D J2016G2C D J2016G2C D J2016G2C D J2016G2C	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane	9 II 10.5 II 10.5 II 11 II of reels 8.5 II 6.5 II OLLER (v 6.5 II 8.5 II	D J2119A3CG D J2119A3C D J2119A3C D J2119A3CG.22C D J2016G2C Vith 7/16-20 tap)	(Sectional rollers with 4 bodies also avail. 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45" body, 20.5" shaft-7/16" taps 16.45" body, 20.5" shaft-7/16" taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2016GJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane	9 II 10.5 II 10.5 II 11 II of reels 8.5 II 6.5 II OLLER (v 6.5 II 8.5 II	2 J2119A3CG 2 J2119A3C 2 J2119A3S 2 J2119A3CG.22C 2 J2016G2C 2 J2016G2C 3 J2016G2C 3 J2016G2C 3 J2016G2C 3 J2016G2C	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2016GJ SHA2016GJ SHA2019SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall) 2.5" dia. SINGLE body rollers	9 10.5 11 of reels 8.5 6.5 OLLER (v 6.5 8.5 11 11	D J2119A3CG D J2119A3C D J2119A3S D J2119A3S D J2119A3CG.22C D J2016G2C D J2016G2C D J2016G2S D J2016G2S D J2019S2S D J2019S2S	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.45° body, 20.5° shaft-3/8° taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019GJ SHA2019SJ SHA2019SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall) 2.5" dia. SINGLE body rollers 2.5" smooth Urethane 2.5" smooth Urethane	9 II 10.5 II 10.5 II 11 II II	2) J2119A3CG 2) J2119A3C 2) J2119A3C 3) J2119A3CG.22C 3) J2016G2C 4) J2016G2C 3) J2016G2C 3) J2016G2C 3) J2019S2C 3) J2019S2C 3) J2019S2C 3) J2019S2S 3) J2019S2S	(Sectional rollers with 4 bodies also avail: 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.45° body, 20.5° shaft-3/8° taps 19.45° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2016GJ SHA2019SJ SHA2019SJ SHA2019SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" dia. SINGLE body rollers 2.5" smooth Urethane	9 II 10.5 II 10.5 II 11 II II	2) J2119A3CG 2) J2119A3C 2) J2119A3C 3) J2119A3CG.22C 3) J2016G2C 4) J2016G2C 3) J2016G2C 3) J2016G2C 3) J2019S2C 3) J2019S2C 3) J2019S2C 3) J2019S2S 3) J2019S2S	(Sectional rollers with 4 bodies also avail: 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.45° body, 20.5° shaft-3/8° taps 19.45° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2016GJ SHA2019SJ SHA2019SJ SHA2019SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall) 2.5" dia. SINGLE body rollers 2.5" smooth Urethane 2.5" smooth Urethane	9 II 10.5 II 1	2) J2119A3CG 2) J2119A3C 2) J2119A3C 3) J2119A3CG.22C 3) J2016G2C 4) J2016G2C 3) J2016G2C 3) J2016G2C 3) J2019S2C 3) J2019S2C 3) J2019S2C 3) J2019S2S 3) J2019S2S	(Sectional rollers with 4 bodies also avail: 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.45° body, 20.5° shaft-3/8° taps 19.45° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2016GJ SHA2019SJ SHA2019SJ SHA2019SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Urethane 2" smooth Urethane 2" smooth Urethane 2.5" dia. SINGLE body rollers 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3.5" smooth Urethane 3.5" smooth Urethane	9 10.5 11 of reels 8.5 6.5 DLLER (v 6.5 11 11 11 11 12 9.4	2) J2119A3CG 2) J2119A3C 2) J2119A3C 3) J2119A3CG.22C 3) J2016G2C 4) J2016G2C 3) J2016G2C 3) J2016G2C 3) J2019S2C 3) J2019S2C 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 4) J2019S2S 5) J2019S2S	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2016GJ SHA2019SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" dia. SINGLE body rollers 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel Jacobsen 22" LIGHT FAIRWAY- FRONT (Excludes 18" & 26" 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane	9 10.5 10.5 10.5 10.5 11.5 10.5 1	2) J2119A3CG 2) J2119A3C 2) J2119A3S 2) J2119A3CG.22C 2) J2016G2C 2) J2016G2C 2) J2016G2C 2) J2019S2C 2) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.25° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.55° body, 25.87° shaft 22.25° body, 25.87° shaft	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" smooth Urethane 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" dia. SINGLE body rollers 2.5" smooth Urethane 2.5" smooth Urethane 3.5" smooth Steel Jacobsen 22" LIGHT FAIRWAY-FRONT (Excludes 18" & 26" 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane	9 10.5 10.5 11 15 16	2) J2119A3CG 2) J2119A3C 2) J2119A3C 3) J2119A3CG.22C 3) J2016G2C 4) J2016G2C 3) J2016G2C 3) J2019S2C 3) J2019S2C 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2522A3CG 4) J2522A3CG 4) J2522A3C 5) J2522A3C	(Sectional rollers with 4 bodies also avail. 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45" body, 20.5" shaft-7/16" taps 16.45" body, 20.5" shaft-7/16" taps 19.25" body, 20.5" shaft-3/8" taps 22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft call for proper application specifics	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2016GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2021SSJ SHA2021SSJ SHA2021SSJ SHA2021SSJ SHA2022SJ SHA2022AJ SHA2522AJ SHA2522AJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel Jacobsen 22" LIGHT FAIRWAY- FRONT (Excludes 18" & 26" 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane	9 10.5 1	2) J2119A3CG 2) J2119A3C 2) J2119A3C 3) J2119A3CG.22C 3) J2016G2C 4) J2016G2C 3) J2016G2C 3) J2019S2C 3) J2019S2C 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2522A3CG 4) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 25.87° shaft 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft call for proper application specifics front roller for rear mower heads-use with J2419S2C	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2020SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3.5" smooth Steel Jacobsen 22" LIGHT FAIRWAY - FRONT (Excludes 18" & 26" 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane	9 10.5 1	2) J2119A3CG 2) J2119A3C 2) J2119A3S 2) J2119A3CG.22C 2) J2016G2C 2) J2016G2C 3) J2016G2C 3) J2019S2C 3) J2019S2C 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2522A3CG 3) J2522A3CG 3) J2522A3C 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 25.8° shaft-3/8° taps 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft call for proper application specifics front roller for rear mower heads-use with J2522A3CG.22C	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA202SZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" dia. SINGLE body rollers 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3.5" smooth Urethane 3.5" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 22" LIGHT FAIRWAY- REAR (Excludes 18" & 26" and the smooth of	9 10.5 1	2) J2119A3CG 2) J2119A3C 2) J2119A3S 2) J2119A3CG.22C 2) J2016G2C 2) J2016G2C 3) J2016G2C 3) J2019S2C 3) J2019S2C 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2522A3CG 3) J2522A3CG 3) J2522A3C 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 25.8° shaft-3/8° taps 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft call for proper application specifics front roller for rear mower heads-use with J2522A3CG.22C	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA202SZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3.5" smooth Steel Jacobsen 22" LIGHT FAIRWAY - FRONT (Excludes 18" & 26" 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane	9 10.5 111 17 reels 8.5 6.5 0LLER (v 6.5 11 11 11 1 LF530, 3 9.4 12 11.5 15 freels 9.5 7 LF530, S	2) J2119A3CG 2) J2119A3C 2) J2119A3S 2) J2119A3CG.22C 2) J2016G2C 2) J2016G2C 3) J2016G2C 3) J2019S2C 3) J2019S2C 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2522A3CG 3) J2522A3CG 3) J2522A3C 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 25.8° shaft-3/8° taps 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft call for proper application specifics front roller for rear mower heads-use with J2522A3CG.22C	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA202SZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ SHA252ZAJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3." grooved Urethane no flats 3" grooved Urethane no flats 3" smooth Urethane 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 22" LIGHT FAIRWAY- REAR (Excludes 18" & 26" of the smooth Urethane 2" smooth Urethane of flats 2" dia. SINGLE body rollers w/ 3/8" taps in shaft 2" wide grooved Urethane no flats 2" wide grooved Urethane no flats	9 10.5 10.5 11 15 15 15 15 15 15	2) J2119A3CG 2) J2119A3CG 2) J2119A3S 2) J2119A3CG.22C 2) J2016G2C 2) J2016G2C 2) J2016G2C 2) J2019S2C 2) J2019S2S 2) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 4) J2522A3CG 5) J2522A3CG 5) J2522A3CG 6) J2522A3CG 6) J2522A3CG 7) J2522A3CG 7) J2522A3CG 8) J2522A3CG	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps 22.45° body, 25.87° shaft 22.25° body, 25.87° shaft 22.25° body, 25.87° shaft 22.25° body, 25.87° shaft 22.15° body, 25.87° shaft 22.15° body, 25.87° shaft 22.25° body, 25.87° shaft 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 24.45° body, 24.25° shaft-3/8° taps 22.45° body, 24.25° shaft-3/8° taps 22.45° body, 24.25° shaft-3/8° taps 22.45° body, 24.25° shaft-3/8° taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2021SJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2419SJ railable) SHA2422SJ SHA2422SJ SHA2422SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel Jacobsen 22" LIGHT FAIRWAY - FRONT (Excludes 18" & 26" 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Verenae with 2" wide smooth ends 2" smooth Urethane Jacobsen 22" LIGHT FAIRWAY - REAR (Excludes 18" & 26" 10" 10" 10" 10" 10" 10" 10" 10" 10" 10	9 10.5 1	2) J2119A3CG 2) J2119A3C 2) J2119A3S 2) J2119A3CG.22C 2) J2016G2C 2) J2016G2C 2) J2016G2C 3) J2019S2C 3) J2019S2C 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 4) J2522A3CG 3) J2522A3CG 4) J2522A3CG 4) J2522A3CG 5) J2522A3CG 6) J2522A3CG 7) J2522A3CG 7) J2522A3CG 8) J2522A3CG 8) J2522A3CG 8) J2522A3CG 8) J2522A3CG 8) J2522A3CG	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 25.87° shaft 22.45° body, 25.87° shaft call for proper application specifics front roller for rear mower heads-use with J2419S2C back roller for rear mower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rear mower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rear mower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rear mower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rear mower heads-use with J2522A3CG.22C	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2016GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2419SJ Vailable) SHA2422SJ SHA2422SJ SHA2422SJ SHA2422SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel Jacobsen 22" LIGHT FAIRWAY - FRONT (Excludes 18" & 26" 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 22" LIGHT FAIRWAY - REAR (Excludes 18" & 26" 12" dia. SINGLE body rollers w/ 3/8" taps in shaft 2" wide grooved Urethane no flats 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats	9 10.5 1	2) J2119A3CG 2) J2119A3C 2) J2119A3C 3) J2119A3CG.22C 3) J2016G2C 4) J2016G2C 4) J2016G2C 3) J2019S2C 3) J2019S2C 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2522A3CG 4) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 4) J2522A3CG 3) J2522A3CG 4) J2522A3CG 4) J2522A3CG 4) J2522A3CG 5) J2522A3CG 6) J2522A3CG 7) J2522A3CG 8) J2522A3CG 9) J2522A3CG 9) J2422S2CG 9) J2422S2CGG 9) J2422S2CGF 9) J2422S2CGF	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 25.87° shaft 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.55° body, 25.87° shaft 22.45° body, 24.25° shaft-3/8° taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2522AJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Utethane 2" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel beavy (1/4" wall) 2.5" smooth Urethane 3." smooth Urethane 3" smooth Urethane 3" grooved Urethane no flats 3" smooth Urethane 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 22" LIGHT FAIRWAY- REAR (Excludes 18" & 26" and 2" dia. SINGLE body rollers w/ 3/8" taps in shaft 2" wide grooved Urethane no flats 2" wide grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane	9 10.5 1	2) J2119A3CG 2) J2119A3C 2) J2119A3C 2) J2119A3CG 2) J2119A3CG 2) J2016G2C 2) J2016G2C 3) J2016G2C 3) J2019S2C 3) J2019S2C 3) J2019S2S 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CS 3) J2522A3CS 3) J2522A3CS 3) J2522A3CS 3) J2522A3CS 3) J2522A3CS 3) J2522A3CS 4) J2522A3CS 4) J2522A3CS 5) J2422S2CGS 5) J2422S2CGS	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.25° body, 24.25° shaft-3/8° taps 22.45° body, 24.25° shaft-3/8° taps 22.55° body, 24.25° shaft-3/8° taps 22.55° body, 24.25° shaft-3/8° taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA219SJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2422SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall) 2.5" dia. SINGLE body rollers 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel Jacobsen 22" LIGHT FAIRWAY-FRONT (Excludes 18" & 26" 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 22" LIGHT FAIRWAY-REAR (Excludes 18" & 26" 12" dia. SINGLE body rollers w/ 3/8" taps in shaft 2" wide grooved Urethane no flats 2" marrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane	9 10.5 11.5 15 reels 8.5 6.5 0LLER (v 6.5 11 11 11 12 15 reels 9.5 16.7 6.7 6.8 11.5 11.5 11.5 11.5 11.5 11.5 11.5 11.5 11.5 11.5 11.5 11.5 11.5 11.5 11.5	2) J2119A3CG 2) J2119A3C 2) J2119A3S 2) J2119A3CG.22C 2) J2016G2C 2) J2016G2C 3) J2019S2C 3) J2019S2C 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 4) J242S2CG 4) J242S2CGG 5) J2422S2CGG 5) J2422S2CGG 5) J2422S2CGG 5) J2422S2CGG 5) J2422S2CGG 6) J2422S2CGG	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 2011 for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.45° body, 20.5° shaft-3/8° taps 19.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.15° body, 25.87° shaft 22.25° body, 24.25° shaft-3/8° taps 22.45° body, 24.25° shaft-3/8° taps 22.25° body, 24.25° shaft-3/8° taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2522AJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Utethane 2" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel beavy (1/4" wall) 2.5" smooth Urethane 3." smooth Urethane 3" smooth Urethane 3" grooved Urethane no flats 3" smooth Urethane 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 22" LIGHT FAIRWAY- REAR (Excludes 18" & 26" and 2" dia. SINGLE body rollers w/ 3/8" taps in shaft 2" wide grooved Urethane no flats 2" wide grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane	9 10.5 10.5 11.5	2) J2119A3CG 2) J2119A3C 2) J2119A3C 2) J2119A3CG 2) J2119A3CG 2) J2016G2C 2) J2016G2C 3) J2016G2C 3) J2019S2C 3) J2019S2C 3) J2019S2S 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CS 3) J2522A3CS 3) J2522A3CS 3) J2522A3CS 3) J2522A3CS 3) J2522A3CS 3) J2522A3CS 4) J2522A3CS 4) J2522A3CS 5) J2422S2CGS 5) J2422S2CGS	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.25° body, 24.25° shaft-3/8° taps 22.45° body, 24.25° shaft-3/8° taps 22.55° body, 24.25° shaft-3/8° taps 22.55° body, 24.25° shaft-3/8° taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2422SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" smooth Urethane 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 22" LIGHT FAIRWAY- REAR (Excludes 18" & 26" of 18" and 18"	9 II 10.5 II 1	2) J2119A3CG 2) J2119A3C 2) J2119A3C 2) J2119A3CG 2) J2119A3CG 2) J2119A3CG 2) J2016G2C 2) J2016G2C 2) J2016G2C 2) J2019S2C 2) J2019S2S 2) J2019S2S 3) J2019S2S 3) J2522A3CG 3) J2522A3CG 3) J2522A3C 3) J2522A3C 3) J2522A3C 3) J2522A3C 4) J242S2CG 4) J242S2CG 5) J2422S2NG 5) J2422S2NGF 5) J2422S2NGF 5) J2422S2CG 5) J2419S2CGF	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-7/16° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 25.87° shaft 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.55° body, 25.87° shaft 22.45° body, 25.87° shaft 22.25° body, 24.25° shaft-3/8° taps 22.45° body, 24.25° shaft-3/8° taps 22.25° body, 24.25° shaft-3/8° taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2016GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2422SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Urethane 2" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3.5" smooth Steel Jacobsen 22" LIGHT FAIRWAY- FRONT (Excludes 18" & 26" 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 22" LIGHT FAIRWAY- REAR (Excludes 18" & 26" In a supposed Urethane no flats 2" smooth Urethane Jacobsen 22" LIGHT FAIRWAY- REAR (Excludes 18" & 26" In a supposed Urethane no flats 2" wide grooved Urethane no flats 2" wide grooved Urethane no flats 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1" flats 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1" flats 2" smooth Urethane	9 II 10.5 II 1	2) J2119A3CG 2) J2119A3CG 2) J2119A3C 2) J2119A3CG 2) J2119A3CG 2) J2119A3CG 2) J2016G2C 2) J2016G2C 2) J2016G2C 2) J2019S2C 2) J2019S2S 2) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2522A3CG 4) J242S2CG 4) J242S2CG 4) J242S2CGF 5) J2422S2CGF 5) J2419S2CGF	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 22.45° body, 25.87° shaft 22.25° body, 25.87° shaft call for proper application specifics front roller for rear mower heads-use with J2419S2C back roller for rear mower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the shaft s	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2422SJ SHA242SJ SHA242SJ SHA242SJ SHA242SJ SHA242SJ SHA242SJ SHA2419SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK ROZ" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall) 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" dia. SINGLE body rollers 2.5" smooth Steel Jacobsen 22" LIGHT FAIRWAY-FRONT (Excludes 18" & 26" 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 22" LIGHT FAIRWAY-REAR (Excludes 18" & 26" 2" dia. SINGLE body rollers w/ 3/8" taps in shaft 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1" flats 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall)	9 10.5 1	2) J2119A3CG 2) J2119A3C 2) J2119A3S 2) J2119A3CG.22C 2) J2016G2C 2) J2016G2C 3) J2016G2C 3) J2019S2C 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2522A3CG 3) J242S2CGG 3) J242S2CGG	(Sectional rollers with 4 bodies also avail. 19.45' body, 21.25" shaft 19.45' body, 21.25" shaft 19.45' body, 21.25" shaft 19.45' body, 21.25" shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45" body, 20.5" shaft-7/16" taps 16.45" body, 20.5" shaft-7/16" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 19.25" body, 20.5" shaft-3/8" taps 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.25" body, 24.25" shaft-3/8" taps 22.45" body, 24.25" shaft-3/8" taps 22.45" body, 24.25" shaft-3/8" taps 22.45" body, 24.25" shaft-3/8" taps 22.25" body, 24.25" shaft-3/8" taps 19.25" body, 24.25" shaft-3/8" taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA219SJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2422SJ SHA2422SJ SHA2422SJ SHA2422SJ SHA2419SJ SHA2422GJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" dia. SINGLE body rollers 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel Jacobsen 22" LIGHT FAIRWAY-FRONT (Excludes 18" & 26" 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 22" LIGHT FAIRWAY-REAR (Excludes 18" & 26" 12" dia. SINGLE body rollers w/ 3/8" taps in shaft 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1" flats 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1" flats 2" smooth Steel heavy (1/4" wall) 2" dia. SINGLE body rollers w/ 7/16" taps in shaft 2" wide grooved Urethane 10 flats 2" smooth Steel heavy (1/4" wall) 2" dia. SINGLE body rollers w/ 7/16" taps in shaft 2" wide grooved Urethane no flats 2" smooth Steel heavy (1/4" wall) 2" dia. SINGLE body rollers w/ 7/16" taps in shaft 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" narrow grooved Urethane no flats	9 10.5 10.5 10.5 11.5 10.5 11.5 10.5	2) J2119A3CG 2) J2119A3C 2) J2119A3C 2) J2119A3CG 2) J2119A3CG 2) J2119A3CG.22C 2) J2016G2C 2) J2016G2C 2) J2019S2C 2) J2019S2C 2) J2019S2S 3) J2019S2S 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 4) J2419S2C 4) J2419S2C 5) J2422S2CG 5) J2422S2CG 6) J2422S2CG 6) J2422S2CG 6) J2422S2CG 6) J2422S2CG 6) J242S2CG	(Sectional rollers with 4 bodies also avail. 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45" body, 20.5" shaft-7/16" taps 16.45" body, 20.5" shaft-7/16" taps 19.25" body, 20.5" shaft-3/8" taps 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.25" body, 25.87" shaft call for proper application specifics front roller for rear mower heads-use with J2419S2C back roller for rear mower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rear mower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for the prower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for the prower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for the prower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rear mover heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rear mover heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rear mover heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rear mover heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rea	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2422SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK Roogen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK Roogen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK Roogen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK Roogen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK Roogen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK Roogen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK Roogen 18" See a summer se	9 10.5	2) J2119A3CG 2) J2119A3C 2) J2119A3C 2) J2119A3CG 2) J2119A3CG 2) J2119A3CG 2) J2016G2C 2) J2016G2C 2) J2016G2C 2) J2019S2C 2) J2019S2S 2) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2419S2C 4) J2422S2CG 4) J2422S2CG 4) J2422S2CG 4) J242S2CG 5) J242S2S 5) J2419S2C 5) J2419S2C 5) J2419S2C 5) J242S2CG 5) J242SS 6) J242SSS 6) J242SSS 6) J2419S2C 6) J242SSS 6) J2419S2C 6) J242SSS 6) J2419S2C 6) J242SCG 6) J242SCGC 6) J242SCGC 6) J242SCGC 6) J242SCGCG 6) J242CGCCG 6) J242CGCCG 6) J242CCCGCG	(Sectional rollers with 4 bodies also avail. 19.45° body, 21.25° shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45° body, 20.5° shaft-7/16° taps 16.45° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 19.25° body, 20.5° shaft-3/8° taps 22.45° body, 25.87° shaft 22.25° body, 25.87° shaft 22.25° body, 25.87° shaft 22.25° body, 25.87° shaft 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.45° body, 25.87° shaft 22.25° body, 24.25° shaft-3/8° taps 22.45° body, 24.25° shaft-3/8° taps 22.25° body, 24.25° shaft-3/8° taps 19.25° body, 24.25° shaft-3/8° taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2419SJ SHA2422SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK RO 2" dia. SINGLE body rollers 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall) 2.5" dia. SINGLE body rollers 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel Jacobsen 22" LIGHT FAIRWAY-FRONT (Excludes 18" & 26" 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel Jacobsen 22" LIGHT FAIRWAY- FRONT (Excludes 18" & 26" smooth Urethane 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 22" LIGHT FAIRWAY- REAR (Excludes 18" & 26" smooth Urethane 2" smooth Urethane no flats 2" wide grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1" flats 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1 flats 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1 flats 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1 flats 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1 flats 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1 flats 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1 flats 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1 flats 2" narrow grooved Urethane 1 flats	9 10.5 1	2) J2119A3CG 2) J2119A3C 2) J2119A3C 2) J2119A3C 2) J2119A3CG 2) J2119A3CG 2) J2016G2C 2) J2016G2C 2) J2016G2C 2) J2019S2C 2) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2522A3CG 3) J252A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J252A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J252A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J252A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J252A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J252A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J252A3CG 3) J2522A3CG 3) J2522CG 3) J2422CSCCG 3) J2422CSCCG 3) J242CGCCG 3) J2422CGCCG 3) J2422CGCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC	(Sectional rollers with 4 bodies also avail. 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft 19.45" body, 21.25" shaft call for proper application specifics front roller for rear mower heads-use with J2016G2C back roller for rear mower heads-use with J2119A3CG.22C 16.45" body, 20.5" shaft-7/16" taps 16.45" body, 20.5" shaft-7/16" taps 19.25" body, 20.5" shaft-3/8" taps 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.25" body, 25.87" shaft call for proper application specifics front roller for rear mower heads-use with J2419S2C back roller for rear mower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rear mower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for the prower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for the prower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for the prower heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rear mover heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rear mover heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rear mover heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rear mover heads-use with J2522A3CG.22C LF3810) (Sectional rollers with 4 bodies also available of the proper application specifics front roller for rea	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2422SJ
Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - FRONT F 3" dia. SINGLE body rollers 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2" wide smooth ends 2" smooth Urethane Jacobsen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK Roogen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK Roogen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK Roogen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK Roogen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK Roogen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK Roogen 18" LIGHT FAIRWAY LF530 & SLF1880 - BACK Roogen 18" See a summer se	9 10.5 1	2) J2119A3CG 2) J2119A3C 2) J2119A3C 2) J2119A3CG 2) J2119A3CG 2) J2119A3CG 2) J2016G2C 2) J2016G2C 2) J2016G2C 2) J2019S2C 2) J2019S2S 2) J2019S2S 3) J2019S2S 3) J2019S2S 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2522A3CG 3) J2419S2C 4) J2422S2CG 4) J2422S2CG 4) J2422S2CG 4) J242S2CG 5) J242S2S 5) J2419S2C 5) J2419S2C 5) J2419S2C 5) J242S2CG 5) J242SS 6) J242SSS 6) J242SSS 6) J2419S2C 6) J242SSS 6) J2419S2C 6) J242SSS 6) J2419S2C 6) J242SCG 6) J242SCGC 6) J242SCGC 6) J242SCGC 6) J242SCGCG 6) J242CGCCG 6) J242CGCCG 6) J242CCCGCG	(Sectional rollers with 4 bodies also avail. 19.45' body, 21.25' shaft 19.45' body, 20.5' shaft-7/16' taps 16.45' body, 20.5' shaft-7/16' taps 19.25' body, 20.5' shaft-3/8' taps 19.25' body, 25.87' shaft 22.45' body, 24.25' shaft-3/8' taps 22.25' body, 24.25' shaft-3/8' taps 19.25' body, 24.25' shaft-3/8' taps 22.45' body, 24.25' shaft-3/8' taps 19.25' body, 24.25' shaft-3/8' taps	SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2119AJ SHA2016GJ SHA2016GJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2019SJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2522AJ SHA2422SJ SHA2422SJ SHA2422SJ SHA2422SJ SHA2422SJ SHA2422SJ SHA2422SJ SHA2422SJ SHA2419SJ SHA2419SJ SHA2419SJ SHA2419SJ SHA2419SJ SHA2419SJ SHA2419SJ SHA2419SJ SHA2422GJ



2" dia. FOUR body rollers w/ 3/8" taps in shaft			
		non-skidding for tight turns & ground undulations	
4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats	8.5 lb J2422S2CG4	4 short bodies, 24.25" shaft-3/8" taps	SHA2422SJN4
4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats	8.5 lb J2422S2NG4	4 short bodies, 24.25" shaft-3/8" taps	SHA2422SJN4
4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb J2422S2CGF4	4 short bodies, 24.25" shaft-3/8" taps	SHA2422SJN4
4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb J2422S2NGF4	4 short bodies, 24.25" shaft-3/8" taps	SHA2422SJN4
4 bodies 2" smooth Urethane (4x5.55" wide bodies)	8.5 lb J2422S2C4	4 short bodies, 24.25" shaft-3/8" taps	SHA2422SJN4
4 bodies 2" smooth Steel heavy (4x5.55" wide bodies)	12 lb J2422S2S4	4 short bodies, 24.25" shaft-3/8" taps	SHA2422SJN4
2" dia. FOUR body rollers w/ 7/16" taps in shaft		non-skidding for tight turns & ground undulations	V2003-2022-2004-1
4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats	8.5 lb J2422G2CG4	4 short bodies, 24.25" shaft-7/16" taps	SHA2422GJN4
4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats	8.5 lb J2422G2NG4	4 short bodies, 24.25" shaft-7/16" taps	SHA2422GJN4
4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb J2422G2CGF4	4 short bodies, 24.25" shaft-7/16" taps	SHA2422GJN4
4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb J2422G2NGF4	4 short bodies, 24.25" shaft-7/16" taps	SHA2422GJN4
4 bodies 2" smooth Urethane (4x5.55" wide bodies)	8.5 lb J2422G2C4	4 short bodies, 24.25" shaft-7/16" taps	SHA2422GJN4
4 bodies 2" smooth Steel heavy (4x5.55" wide bodies)	12 lb J2422G2S4	4 short bodies, 24.25" shaft-7/16" taps	SHA2422GJN4
2.5" dia. SINGLE body rollers w/ 3/8" taps in shaft			
2.5" grooved Urethane no flats	8.5 lb J2421S25CG	21.45" body, 24.25" shaft-3/8" taps	SHA2421SJ
2.5" smooth Urethane	8.8 lb J2421S25C	21.25" body, 24.25" shaft-3/8" taps	SHA2421SJ
2.5" smooth Steel	9.5 lb J2421S25S	21.25" body, 24.25" shaft-3/8" taps	SHA2421SJ
2.5" dia. SINGLE body rollers w/ 7/16" taps in shaft			
2.5" grooved Urethane no flats	8.5 lb J2421G25CG	21.45" body, 24.25" shaft-7/16" taps	SHA2421GJ
2.5" smooth Urethane	8.8 lb J2421G25C	21.25" body, 24.25" shaft-7/16" taps	SHA2421GJ
2.5" smooth Steel	9.5 lb J2421G25S	21.25" body, 24.25" shaft-7/16" taps	SHA2421GJ
Jacobsen 26" LIGHT FAIRWAY LF2500 & 3050 - FRONT & BA	ACK ROLLERS	(Sectional rollers with 4 bodies also availab	ole)
3" dia. SINGLE body rollers			
3" grooved Urethane no flats	13 lb J3026X3CG	26.45" body, 30.5" shaft-1/2" dia. ends	SHA3026XJ
3" smooth Urethane	13.5 lb J3026X3C	26.45" body, 30.5" shaft-1/2" dia. ends	SHA3026XJ
3" smooth Steel	13.5 lb J3026X3S	26.25" body, 30.5" shaft-1/2" dia. ends	SHA3026XJ
Jacobsen 30" ST5111, FAIRWAY, GANG, HF5 & HF15 - FROM	IT & BACK ROLLERS		
3" dia. SINGLE body rollers			
3" grooved Urethane no flats	12.4 lb J3329A3CG	29.45" body, 33" shaft	SHA3329AJ
3" smooth Urethane	15 lb J3329A3C	29.45" body, 33" shaft	SHA3329AJ
3" smooth Steel	15 lb J3329A3S	29.25" body, 33" shaft	SHA3329AJ
Jacobsen ROTARY AR-522 & AR-722 26" DECK - FRONT RO		emperatory from the state of the control of the con	
5" grooved Urethane (4" wide body)	10 lb J0404G5CG2	Shaft includes sleeves & bolts for mounting to fork	SHA0404GJ
5" smooth Urethane (4" wide body)	11 lb J0404G5C	Shaft includes sleeves & bolts for mounting to fork	SHA0404GJ
Jacobsen ROTARY AR-522, AR-722, & AR-5 26" DECK - BAC			
3" dia. SINGLE body rollers	OK KOLLEK (must commin si	iait comiguration on ends)	
1 CANA 1	12.5 lb J2926R3CG	26.45" body, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ
3" grooved Urethane no flats			
3" smooth Urethane	13.2 lb J2926R3C	26.45" body, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ
3" smooth Steel	14 lb J2926R3S	26.25" body, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ
3" grooved Urethane no flats	12.5 lb J2926Q3CG	26.45" body, 29.42" shaft-1 large milled flat end & 1 round end	SHA2926QJ
3" smooth Urethane	13.2 lb J2926Q3C	26.45" body, 29.42" shaft-1 large milled flat end & 1 round end	SHA2926QJ
3" smooth Steel	14 lb J2926Q3S	26.25" body, 29.42" shaft-1 large milled flat end & 1 round end	SHA2926QJ
3.5" dia. SINGLE body rollers			
3.5" smooth Urethane	18 lb J2926R7C	26.45" body, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ
3.5" smooth Urethane	18 lb J2926Q7C	26.45" body, 29.42" shaft-1 large milled flat end & 1 round end	SHA2926QJ
4" dia. SINGLE body rollers			
4" dia. SINGLE body rollers 4" smooth Urethane	29 lb J2926R4C	26.45" body, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ
	29 lb J2926R4C 27 lb J2926R4S	26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.25" body, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ SHA2926RJ
4" smooth Urethane			SHA2926RJ
4" smooth Urethane 4" smooth Steel		26.25" body, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers	27 lb J2926R4S	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skildding for tight turns & ground undula	SHA2926RJ ations
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats	27 lb J2926R4S 5.8 lb J2905R3CGt	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ ations SHA2905RJNt
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies)	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ sha2905RJNt SHA2905RJNt
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt
4" smooth Urethane 4" smooth Steel 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies)	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies)	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3St	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations	SHA2926RJ Itions SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies)	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies)	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4
4" smooth Urethane 4" smooth Steel 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 8 mooth Urethane (4x6.5" wide bodies) 9 mooth Urethane (4x6.5" wide bodies)	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat end & 1 round end 4 short bodies, 29.42" shaft-large milled flat end & 1 round end 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must co	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat end & 1 round end 4 short bodies, 29.42" shaft-large milled flat end & 1 round end 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ ttions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 5 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must compared to the steel of th	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3C4 onfirm shaft configuration o	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ sha2905RJNt SHA2905RJNt SHA2905RJNt SHA2905GJNt SHA2905GJNt SHA2905GJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x5.2" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must common street of the s	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3C4 onfirm shaft configuration of	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 5 short bodies, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA2926QJN4 SHA2926QJN4
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must compared to the state of the stat	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 0nfirm shaft configuration of	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat at D in tound end 4 short bodies, 29.42" shaft-large milled flat pin hole on ends n ends) 26.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 30" shaft-specify configuration of shaft ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA2926QJN4 SHA2926QJN4 SHA2926QJN4
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3 bodies 3" grooved Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 grooved Urethane (4x6.5" bodies body rollers 3" grooved Urethane no flats 3" grooved Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Steel	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3C4 onfirm shaft configuration of	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 5 short bodies, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA2926QJN4 SHA2926QJN4
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3 dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must compared to the steel of the	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J3926D3CG 13 lb J3026D3C 14 lb J3026D3S	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat end & 1 round end 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 5 short bodies, 29.42" shaft-large milled flat end & 1 round end 5 short bodies, 29.42" shaft-large milled flat end & 1 round end 5 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end 8 short bodies, 29.42" shaft-large milled flat & pin hole on ends 6 short bodies, 29.42" shaft-large milled flat & pin hole on ends 7 short bodies, 29.42" shaft-large milled flat & pin hole on ends 8 short bodies, 29.42" shaft-large milled flat & pin hole on ends 8 short bodies, 29.42" shaft-large milled flat & pin hole on ends 8 short bodies, 29.42" shaft-large milled flat & pin hole on ends 9 short bodies, 29.42	SHA2926RJ sha2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ SHA3026DJ SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3 dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 5 dodies 3" smooth Urethane (4x6.5" wide bodies) 5 dodies 3" grooved Urethane (4x6.5" wide bodies) 5 dodies 3" smooth Urethane no flats 5 dia. SINGLE body rollers 5 dia. SINGLE body rollers 5 dia. SINGLE body rollers 6 dia. SINGLE body rollers 7 dia. SINGLE body rollers	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 0nfirm shaft configuration of	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat at D in tound end 4 short bodies, 29.42" shaft-large milled flat pin hole on ends n ends) 26.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 30" shaft-specify configuration of shaft ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA2926QJN4 SHA2926QJN4 SHA2926QJN4
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must compared by the steel of t	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3Ct 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J3926D3CG 13.2 lb J3026D3C 14 lb J3026D3C 17 lb J3026D7C	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat at pin hole on ends 4 short bodies, 29.42" shaft-large milled flat at pin hole on ends 50.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 30" shaft-specify configuration of shaft ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA2926QJN4 SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must compared by the steel of	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2905Q3CGt 6.8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3CG4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3C4 onfirm shaft configuration of 13 lb J3026D3CG 13.2 lb J3026D3C 14 lb J3026D7C 29 lb J2926R4C	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat end & 1 round end 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 5 short bodies, 29.42" shaft-large milled flat end & 1 round end 5 short bodies, 29.42" shaft-large milled flat end & 1 round end 5 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end & 1 round end 6 short bodies, 29.42" shaft-large milled flat end 8 short bodies, 29.42" shaft-large milled flat & pin hole on ends 6 short bodies, 29.42" shaft-large milled flat & pin hole on ends 7 short bodies, 29.42" shaft-large milled flat & pin hole on ends 8 short bodies, 29.42" shaft-large milled flat & pin hole on ends 8 short bodies, 29.42" shaft-large milled flat & pin hole on ends 8 short bodies, 29.42" shaft-large milled flat & pin hole on ends 9 short bodies, 29.42	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926DJN5 SHA2926DJN5 SHA3026DJ SHA3026DJ SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must compared by the steel of t	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3Ct 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J3926D3CG 13.2 lb J3026D3C 14 lb J3026D3C 17 lb J3026D7C	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat and & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground unduations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 30" shaft-specify configuration of shaft ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 grooved Urethane (4x6.5" wide bodies) 3 grooved Urethane (4x6.5" wide bodies) 3 grooved Urethane (4x6.5" body rollers 3 grooved Urethane no flats 3 grooved Urethane 3 grooved Urethane 3 grooved Urethane 4 dia. SINGLE body rollers 4 dia. SINGLE body rollers 4 dia. SINGLE body rollers	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2905Q3CGt 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3CG4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3C4 onfirm shaft configuration of 13 lb J3026D3CG 13.2 lb J3026D3C 14 lb J3026D7C 29 lb J2926R4C	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat at end & 1 round end 4 short bodies, 29.42" shaft-large milled flat at end & 1 round end 26.45" body, 30" shaft-specify configuration of shaft ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 5 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 5 bodies 3" smooth Urethane (4x6.5" wide bodies) 5 bodies 3" smooth Urethane (4x6.5" wide bodies) 6 bodies 3" smooth Urethane (4x6.5" bloody rollers 6 bodies 3" grooved Urethane no flats 7 grooved Urethane 8 grooved Urethane 10 single body rollers 10 single body rollers 10 single body rollers 11 dia. SINGLE body rollers 12 dia. SINGLE body rollers 13 smooth Urethane 4" dia. SINGLE body rollers 4" smooth Urethane 4" dia. SINGLE body rollers	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2905Q3CGt 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3CG4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3C4 onfirm shaft configuration of 13 lb J3026D3CG 13.2 lb J3026D3C 14 lb J3026D7C 29 lb J2926R4C	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat and & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground unduations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 30" shaft-specify configuration of shaft ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 5 bodies 3" grooved Urethane (4x6.5" wide bodies) 5 bodies 3" smooth Urethane (4x6.5" wide bodies) 5 bodies 3" grooved Urethane (4x6.5" wide bodies) 5 bodies 3" grooved Urethane (4x6.5" bodies bodies) 5 bodies 3" grooved Urethane (4x6.5" bodies bodies) 5 grooved Urethane (4x6.5" bodies body rollers 6 grooved Urethane 7 grooved Urethane 7 grooved Urethane 8 grooved Urethane 9 grooved Urethane 1 grooved Urethane 1 grooved Urethane 2 grooved Urethane 3 grooved Urethane 4 grooved Urethane 3 grooved Urethane 4 grooved Urethane	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J3026D3CG 13 lb J3026D3CG 14 lb J3026D3C 14 lb J3026D7C 29 lb J2926R4C 27 lb J2926R4S	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 50.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.25" body, 29.42" shaft-large milled flat & pin hole on ends 26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undulations and shaft ends 26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undulations and shaft ends 26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undulations and shaft ends 26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undulations and shaft ends 26.25" body, 29.42" shaft-large milled flat & pin hole on ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 cobsen ROTARY AR-5 26" DECK - BACK ROLLER (must compared by the steel of	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J3026D3CG 13.2 lb J3026D3C 14 lb J3026D3C 14 lb J3026D7C 29 lb J2926R4C 27 lb J2926R4S 6.3 lb J3005D3CGt	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 50.45" body, 30" shaft-specify configuration of shaft ends 50.25" body, 30" shaft-specify configuration of shaft ends 50.45" body, 30" shaft-specify configuration of shaft ends 50.45" body, 30" shaft-specify configuration of shaft ends 50.45" body, 20.42" shaft-large milled flat & pin hole on ends 50.45" body, 29.42" shaft-large milled flat & pin hole on ends 50.55" body, 29.42" shaft-large milled flat & pin hole on ends 50.55" body, 29.42" shaft-large milled flat & pin hole on ends 50.55" body, 20.42" shaft-large milled flat & pin hole on ends 50.55" body, 20.42" shaft-large milled flat & pin hole on ends 50.55" body, 20.42" shaft-large milled flat & pin hole on ends 50.55" body, 20.42" shaft-large milled flat & pin hole on ends 50.55" body, 20.42" shaft-large milled flat & pin hole on ends 50.55" body, 20.42" shaft-large milled flat & pin hole on ends 50.55" body, 20.42" shaft-large milled flat & pin hole on ends 50.55" body, 20.42" shaft-large milled flat & pin hole on ends 50.55" body, 20.42" shaft-large milled flat & pin hol	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926DJ SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3 dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must c 3" dia. SINGLE body rollers 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 4" dia. SINGLE body rollers 4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies)	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J3926D3CG 13.1 lb J3026D3CG 13.2 lb J3026D3C 14 lb J3026D3C 14 lb J3026D3C 29 lb J2926R4C 27 lb J2926R4S 6.3 lb J3005D3CGt 6.3 lb J3005D3CGt 6.3 lb J3004D3Ct	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 30" shaft-specify configuration of shaft ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must compared by the state of the sta	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J3926D3CG 13.1 lb J3026D3CG 13.2 lb J3026D3C 14 lb J3026D3C 14 lb J3026D3C 29 lb J2926R4C 27 lb J2926R4S 6.3 lb J3005D3CGt 6.3 lb J3005D3CGt 6.3 lb J3004D3Ct	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat end & 1 round end 4 short bodies, 29.42" shaft-large milled flat to defend the ends 26.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must c 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 4" dia. SINGLE body rollers 4" smooth Urethane 4" dia. SINGLE body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 3" dia. FOUR body rollers 3" dia. FOUR body rollers 4" bodies 3" grooved Urethane (2x4" wide bodies) 3" dia. FOUR body rollers	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J3026D3C 14 lb J3026D3C 14 lb J3026D3C 29 lb J2926R4C 27 lb J2926R4C 27 lb J2926R4S 6.3 lb J3005D3CGt 6.3 lb J3004D3Ct 8 lb J3004D3St 12.5 lb J3026R3CG4	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undulat 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground unduations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ SHA3007BJNt
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 grooved Urethane (4x6.5" wide bodies) 3 grooved Urethane no flats 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 4" dia. SINGLE body rollers 4" smooth Urethane 4" dia. SINGLE body rollers 4" smooth Urethane 4" smooth Steel 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x5.2" wide bodies) no flats 4 bodies 3" grooved Urethane (4x5.2" wide bodies)	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3CG4 13.5 lb J2926Q3CG4 0nfirm shaft configuration of 13 lb J3026D3CG 13.2 lb J3026D3C 14 lb J3026D3C 14 lb J3026D7C 29 lb J2926R4C 27 lb J2926R4S 6.3 lb J3005D3CGt 6.3 lb J3004D3Ct 8 lb J3004D3St 12.5 lb J3026R3CG4 13.5 lb J3026R3CG4 13.5 lb J3026R3CG4	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undulat 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 50.45" body, 30" shaft-specify configuration of shaft ends 50.25" body, 30" shaft-specify configuration of shaft ends 50.45" body, 30" shaft-specify configuration of shaft ends 50.45" body, 30" shaft-specify configuration of shaft ends 50.45" body, 29.42" shaft-large milled flat & pin hole on ends 50.55" body, 29.42" shaft-large milled flat & pin hole on ends 50.55" body, 29.42" shaft-large milled flat & pin hole on ends 50.55" body, 29.42" shaft-specify configuration of shaft ends 50.55" body, 20.55" shaft-specify configuration of shaft ends 50.55" shaft-specify	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926QJNt SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA2926QJN4 SHA3026DJ SHA304DJNt
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 grooved Urethane (4x6.5" wide bodies) 3 grooved Urethane (4x6.5" wide bodies) 3 grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 4" dia. SINGLE body rollers 4" smooth Urethane 4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x5.2" wide bodies) no flats 4 bodies 3" grooved Urethane (4x5.2" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x5.2" wide bodies)	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3CG4 13.5 lb J2926Q3CG4 0nfirm shaft configuration of 13 lb J3026D3CG 13.2 lb J3026D3C 14 lb J3026D3C 14 lb J3026D7C 29 lb J2926R4C 27 lb J2926R4S 6.3 lb J3005D3CGt 6.3 lb J3004D3Ct 8 lb J3004D3St 12.5 lb J3026R3CG4 13.5 lb J3026R3CG4 13.5 lb J3026R3CG4	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undulat 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 50.45" body, 30" shaft-specify configuration of shaft ends 50.25" body, 30" shaft-specify configuration of shaft ends 50.45" body, 30" shaft-specify configuration of shaft ends 50.45" body, 30" shaft-specify configuration of shaft ends 50.45" body, 29.42" shaft-large milled flat & pin hole on ends 50.55" body, 29.42" shaft-large milled flat & pin hole on ends 50.55" body, 29.42" shaft-large milled flat & pin hole on ends 50.55" body, 29.42" shaft-specify configuration of shaft ends 50.55" body, 20.55" shaft-specify configuration of shaft ends 50.55" shaft-specify	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ SHA3026DJ SHA3026DJ SHA3026DJ SHA3007BJNt
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3 dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 cobsen ROTARY AR-5 26" DECK - BACK ROLLER (must compared by the standard body rollers 3" smooth Urethane no flats 3" smooth Urethane 3" smooth Urethane 4" dia. SINGLE body rollers 4" smooth Urethane 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 3 bodies 3" smooth Urethane (4x5.2" wide bodies)	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3CG4 13.5 lb J2926Q3CG4 0nfirm shaft configuration of 13 lb J3026D3C 14 lb J3026D3C 14 lb J3026D3C 29 lb J2926R4C 27 lb J2926R4S 6.3 lb J3005D3CGt 6.3 lb J3004D3Ct 8 lb J3004D3St 12.5 lb J3026R3CG4 13.5 lb J3026R3CA4 0nfirm shaft configuration of	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 50.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 50.25" body, 29.42" shaft-large milled flat & pin hole on ends 50.5" body, 29.42" shaft-large milled flat & pin hole on ends 50.5" body, 29.42" shaft-large milled flat & pin hole on ends 50.5" body, 29.42" shaft-large milled flat & pin hole on ends 50.5" body, 29.42" shaft-large milled flat & pin hole on ends 50.5" body, 29.42" shaft-large milled flat & pin hole on ends 50.5" body, 29.42" shaft-large milled flat & pin hole on ends 50.5" shaft-large milled flat & pin hole on ends 50.5" shaft-large milled flat & pin hole on ends 50.5" shaft-large milled flat & pin hole on ends 50.5" shaft-large milled flat & pin hole on ends 50.5" shaft-large milled flat & pin hole on ends 50.5" shaft-large milled flat & pin hole on ends 50.5" shaft-large milled flat & pin hole on ends 50.5" shaft-large milled flat & pin hole	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3 " dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must of a sum of a s	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3Ct 5.8 lb J2904R3Ct 5.8 lb J2904Q3Ct 6 lb J2904Q3Ct 7 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2926R3CG4 13.5 lb J2926R3CG4 13.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J3026D3C 13.2 lb J3026D3C 14 lb J3026D3C 14 lb J3026D3C 15 lb J3026D3C 16 lb J3026D3C 17 lb J3026D3C 17 lb J3026D3C 18 lb J3026D3C 19 lb J2926R4C 19 lb J2926R4C 10 lb J2926R4C 10 lb J2926R4C 10 lb J2926R4C 10 lb J3004D3Ct 10 lb J3004D3Ct 11 lb J3004D3Ct 11 lb J3004D3Ct 12 lb J3026R3CG4 13.5 lb J3026R3CG4 13.5 lb J3026R3CG4 13.5 lb J3026R3CG4 13.5 lb J3024P3CG	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 5 short bodies, 29.42" shaft-large milled flat & pin hole on ends 6 short bodies, 29.42" shaft-large milled flat & pin hole on ends 6 short bodies, 29.42" shaft-large milled flat & pin hole on ends 6 short body, 30" shaft-specify configuration of shaft ends 6 short body, 30" shaft-specify configuration of shaft ends 6 short body, 29.42" shaft-large milled flat & pin hole on ends 6 short win bodies, 30" shaft-specify configuration of shaft ends 7 short win bodies, 30" shaft-specify configuration of shaft ends 7 short twin bodies, 30" shaft-specify configuration of shaft ends 7 short twin bodies, 30" shaft-specify configuration of shaft ends 7 short twin bodies, 30" shaft-specify configuration of shaft ends 7 short bodies, 30" shaft-specify configuration of shaft ends 7 short bodies, 30.5" shaft-large milled flat & pin hole on ends 7 short bodies, 30.5" shaft-large milled flat & pin hole on ends 8 short bodies, 30.5" shaft-large milled flat & pin hole on ends 9 short bodies, 30.5" shaft-large milled flat & pin hole on ends 9 short bodies, 30.5" shaft-large milled flat & pin hole on ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 bodies 3" smooth Urethane no flats 3 smooth Urethane 3 smooth Urethane 3 smooth Urethane 4 dia. SINGLE body rollers 4 smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 3 dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x5.2" wide bodies) no flats 4 bodies 3" grooved Urethane (4x5.2" wide bodies) 3 dia. FOUR body rollers 4 bodies 3" smooth Urethane (4x5.2" wide bodies) 3 dia. SINGLE body rollers 3 dia. SINGLE body rollers 3 dia. SINGLE body rollers 3 grooved Urethane (4x5.2" wide bodies) 3 dia. SINGLE body rollers 3 grooved Urethane (4x5.2" wide bodies) 3 dia. SINGLE body rollers 3 grooved Urethane (4x5.2" wide bodies)	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2904R3St 5.8 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2904Q3Ct 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J2926Q3C4 onfirm shaft configuration of 13 lb J3026D3C 14 lb J3026D3C 14 lb J3026D3C 29 lb J2926R4C 27 lb J2926R4C 27 lb J2926R4S 6.3 lb J3004D3Ct 8 lb J3004D3St 12.5 lb J3026R3CG4 13.5 lb J3429R3CG 15 lb J3429R3CG	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat a pin hole on ends 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-large milled flat and & 1 round end non-skidding for tight turns & ground unduations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 30" shaft-specify configuration of shaft ends 26.25" body, 29.42" shaft-large milled flat & pin hole on ends 26.25" body, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short by bodies, 30" shaft-specify configuration of shaft ends 2 short by bodies, 30" shaft-specify configuration of shaft ends 2 short by bodies, 30" shaft-specify configuration of shaft ends 2 short by bodies, 30" shaft-specify configuration of shaft ends 2 short by bodies, 30"	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ SHA3026RJ SHA3004DJNt SHA3004DJNt SHA3004DJNt SHA3026RJN4 SHA3026RJN4 SHA3026RJN4
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3 " dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must c 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 4" dia. SINGLE body rollers 4" smooth Urethane 4" dia. SINGLE body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x5.2" wide bodies) 3" dia. TWO body rollers 4 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" smooth Urethane (2x5.2" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x5.2" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" smooth Urethane (4x5.2" wide bodies) 3" dia. SINGLE body rollers 3" dia. FOUR body rollers 3" dia. SINGLE body rollers 4 bodies 3" smooth Urethane (4x5.2" wide bodies) 3" dia. SINGLE body rollers 3" grooved Urethane (4x5.2" wide bodies) 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane no flats 3" smooth Urethane	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3Ct 5.8 lb J2904R3Ct 5.8 lb J2904Q3Ct 6 lb J2904Q3Ct 7 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2926R3CG4 13.5 lb J2926R3CG4 13.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J3026D3C 13.2 lb J3026D3C 14 lb J3026D3C 14 lb J3026D3C 15 lb J3026D3C 16 lb J3026D3C 17 lb J3026D3C 17 lb J3026D3C 18 lb J3026D3C 19 lb J2926R4C 19 lb J2926R4C 10 lb J2926R4C 10 lb J2926R4C 10 lb J2926R4C 10 lb J3004D3Ct 10 lb J3004D3Ct 11 lb J3004D3Ct 11 lb J3004D3Ct 12 lb J3026R3CG4 13.5 lb J3026R3CG4 13.5 lb J3026R3CG4 13.5 lb J3026R3CG4 13.5 lb J3024P3CG	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 5 short bodies, 29.42" shaft-large milled flat & pin hole on ends 6 short bodies, 29.42" shaft-large milled flat & pin hole on ends 6 short bodies, 29.42" shaft-large milled flat & pin hole on ends 6 short body, 30" shaft-specify configuration of shaft ends 6 short body, 30" shaft-specify configuration of shaft ends 6 short body, 29.42" shaft-large milled flat & pin hole on ends 6 short win bodies, 30" shaft-specify configuration of shaft ends 7 short win bodies, 30" shaft-specify configuration of shaft ends 7 short twin bodies, 30" shaft-specify configuration of shaft ends 7 short twin bodies, 30" shaft-specify configuration of shaft ends 7 short twin bodies, 30" shaft-specify configuration of shaft ends 7 short bodies, 30" shaft-specify configuration of shaft ends 7 short bodies, 30.5" shaft-large milled flat & pin hole on ends 7 short bodies, 30.5" shaft-large milled flat & pin hole on ends 8 short bodies, 30.5" shaft-large milled flat & pin hole on ends 9 short bodies, 30.5" shaft-large milled flat & pin hole on ends 9 short bodies, 30.5" shaft-large milled flat & pin hole on ends	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must c 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 4" dia. SINGLE body rollers 3.5" smooth Urethane 4" smooth Steel 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) 3 bodies 3" smooth Urethane (2x5.2" wide bodies) 3 bodies 3" smooth Urethane (2x5.2" wide bodies) 3 bodies 3" smooth Urethane (4x5.2" wide bodies)	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905R3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2904Q3Ct 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3C4 onfirm shaft configuration of 13 lb J3026D3C 14 lb J3026D3C 14 lb J3026D3C 14 lb J3026D3C 29 lb J2926R4C 27 lb J2926R4C 27 lb J2926R4S 6.3 lb J3004D3Ct 8 lb J3004D3Ct 8 lb J3004D3Ct 8 lb J3004D3Ct 9 lb J2926R3CG4 13.5 lb J3026R3CG4 13.5 lb J3429R3CG 15 lb J3429R3C 15 lb J3429R3S	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 50.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30.5" shaft-large milled flat & pin hole on ends 4 short bodies, 30.5" shaft-large milled flat & pin hole on ends 4 short bodies, 30.5" shaft-large milled flat & pin hole on ends 29.45" body, 34.25" shaft-large milled flat & pin hole on ends 29.45" body, 34.25" shaft-large milled flat & pin hole on ends 29.45" body, 34.25" shaft-large mil	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 grooved Urethane (4x6.5" wide bodies) 3 grooved Urethane (4x6.5" wide bodies) 3 grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 4" dia. SINGLE body rollers 3.5" smooth Urethane 4" smooth Steel 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 3" dia. TWO body rollers 4 bodies 3" grooved Urethane (4x5.2" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x5.2" wide bodies) 3 grooved Urethane no flats	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2904R3St 5.8 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2904Q3Ct 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3CG4 13.5 lb J2926Q3C4 onfirm shaft configuration of 13 lb J3026D3C 14 lb J3026D3C 14 lb J3026D3C 29 lb J2926R4C 27 lb J2926R4C 27 lb J2926R4S 6.3 lb J3004D3Ct 8 lb J3004D3St 12.5 lb J3026R3CG4 13.5 lb J3429R3CG 15 lb J3429R3CG	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat a pin hole on ends 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-large milled flat and & 1 round end non-skidding for tight turns & ground unduations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 30" shaft-specify configuration of shaft ends 26.25" body, 29.42" shaft-large milled flat & pin hole on ends 26.25" body, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short by bodies, 30" shaft-specify configuration of shaft ends 2 short by bodies, 30" shaft-specify configuration of shaft ends 2 short by bodies, 30" shaft-specify configuration of shaft ends 2 short by bodies, 30" shaft-specify configuration of shaft ends 2 short by bodies, 30"	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ SHA3026RJ SHA3004DJNt SHA3004DJNt SHA3004DJNt SHA3004DJNt SHA3026RJN4 SHA3026RJN4 SHA3026RJN4
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 3 bodies 3" smooth Urethane no flats 3 smooth Urethane 3 smooth Urethane 3 smooth Urethane 4 dia. SINGLE body rollers 4 smooth Urethane 4 smooth Steel 3 dia. TWO body rollers 4 smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" grooved Urethane (2x5.2" wide bodies) 5 bodies 3" smooth Urethane (2x4" wide bodies) 5 bodies 3" smooth Urethane (2x4" wide bodies) 5 bodies 3" smooth Urethane (2x5.2" wide bodies) 5 bodies 3" smooth Urethane (4x5.2" wide bodies) 5 bodies 3" smooth Urethane (4x5.2" wide bodies) 5 codies 3" smooth Urethane (4x5.2" wide bodies) 5 codies 3" smooth Urethane (4x5.2" wide bodies) 5 codies 3" smooth Urethane (4x5.2" wide bodies) 7 dia. SINGLE body rollers 8 grooved Urethane no flats 8 grooved Urethane no flats 9 grooved Urethane no flats	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3CG4 13.5 lb J2926Q3CG4 0nfirm shaft configuration of 13 lb J3026D3C 14 lb J3026D3C 14 lb J3026D3S 17 lb J3026D3C 29 lb J2926R4C 27 lb J2926R4S 6.3 lb J3004D3Ct 8 lb J3004D3Ct 8 lb J3004D3St 12.5 lb J3026R3CG4 13.5 lb J3026R3CG 15 lb J3429R3C 15 lb J3429R3C 15 lb J3429R3S 18 lb J3429R7C	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 50.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 50.5" body, 29.42" shaft-large milled flat & pin hole on ends 50.5" body, 29.42" shaft-large milled flat & pin hole on ends 50.5" body, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-large milled flat & pin hole on ends 4 short bodies, 30.5" shaft-large milled flat & pin hole on ends 4 short bodies, 30.5" shaft-large milled flat & pin hole on ends 29.45" body, 34.25" shaft-large milled flat & pin hole on ends 29.45" body, 34.25" shaft-large milled flat & pin hole on ends 29.45" body, 34.25" shaft-large milled flat	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ SHA3026DJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must of 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3.5" dia. SINGLE body rollers 4" smooth Urethane 4" dia. SINGLE body rollers 4" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" grooved Urethane (2x5.2" wide bodies) 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x5.2" wide bodies) 3 dia. FOUR body rollers 4 bodies 3" smooth Urethane (4x5.2" wide bodies) 3 dia. FOUR body rollers 3 grooved Urethane (4x5.2" wide bodies) 3 dia. SINGLE body rollers 3 grooved Urethane (4x5.2" wide bodies) 3 dia. SINGLE body rollers 3" grooved Urethane (4x5.2" wide bodies) 3 grooved Urethane (4x5.2" wide bodies)	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2904R3St 5.8 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2904Q3Ct 12.5 lb J2926R3CG4 13.5 lb J2926R3C4 12.5 lb J2926Q3CG4 13.5 lb J2926Q3C4 onfirm shaft configuration of 13 lb J3026D3C 14 lb J3026D3C 14 lb J3026D3C 29 lb J2926R4C 27 lb J2926R4C 27 lb J2926R4C 27 lb J2926R4C 3.1 lb J3004D3Ct 8 lb J3004D3St 12.5 lb J3026R3CG4 13.5 lb J3429R3C 15 lb J3429R3C 15 lb J3429R3C 15 lb J3429R3C 15 lb J3429R7C 29 lb J3429R7C	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat a pin hole on ends 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-large milled flat a pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 26.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 26.25" body, 29.42" shaft-large milled flat & pin hole on ends 26.5" body, 29.42" shaft-large milled flat & pin hole on ends 26.5" body, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30.5" shaft-large milled flat & pin hole on ends 4 short bodies, 30.5" shaft-large milled flat & pin hole on ends 29.45" body, 34.25" shaft-large milled flat & pin hole on ends 29.45" body, 34.25" shaft-large milled flat & pin hole on ends 29.45" body, 34.25" shaft-large milled flat & pin hole on ends 29.45" body, 34.25" shaft-large milled flat & pin hole on ends 29.45" body, 34.25" shaft	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ SHA3026RJ SHA3026RJ SHA3026RJ SHA3024DJNt SHA3004DJNt SHA3004DJNt SHA3026RJN4 SHA3026RJN4 SHA3429RJ SHA3429RJ SHA3429RJ SHA3429RJ SHA3429RJ
4" smooth Urethane 4" smooth Steel 3" dia. TWO body rollers 2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Urethane (2x5.2" wide bodies) no flats 2 bodies 3" smooth Urethane (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 2 bodies 3" smooth Steel (2x4" wide bodies) 3" dia. FOUR body rollers 4 bodies 3" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 3" grooved Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) 4 bodies 3" smooth Urethane (4x6.5" wide bodies) Jacobsen ROTARY AR-5 26" DECK - BACK ROLLER (must constitution of the state of the	27 lb J2926R4S 5.8 lb J2905R3CGt 6.2 lb J2904R3Ct 8 lb J2904R3St 5.8 lb J2905Q3CGt 5.8 lb J2904Q3Ct 8 lb J2904Q3Ct 8 lb J2904Q3St 12.5 lb J2926R3CG4 13.5 lb J2926R3CG4 13.5 lb J2926Q3CG4 0nfirm shaft configuration of 13 lb J3026D3C 14 lb J3026D3C 14 lb J3026D3S 17 lb J3026D3C 29 lb J2926R4C 27 lb J2926R4S 6.3 lb J3004D3Ct 8 lb J3004D3Ct 8 lb J3004D3St 12.5 lb J3026R3CG4 13.5 lb J3026R3CG 15 lb J3429R3C 15 lb J3429R3C 15 lb J3429R3S 18 lb J3429R7C	26.25" body, 29.42" shaft-large milled flat & pin hole on ends non-striping, non-skidding for tight turns & ground undula 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat & pin hole on ends 2 short twin bodies, 29.42" shaft-large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end 2 short twin bodies, 29.42" shaft-1 large milled flat end & 1 round end non-skidding for tight turns & ground undulations 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 4 short bodies, 29.42" shaft-large milled flat & pin hole on ends 50.45" body, 30" shaft-specify configuration of shaft ends 26.45" body, 29.42" shaft-large milled flat & pin hole on ends 50.5" body, 29.42" shaft-large milled flat & pin hole on ends 50.5" body, 29.42" shaft-large milled flat & pin hole on ends 50.5" body, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-specify configuration of shaft ends 2 short twin bodies, 30" shaft-large milled flat & pin hole on ends 4 short bodies, 30.5" shaft-large milled flat & pin hole on ends 4 short bodies, 30.5" shaft-large milled flat & pin hole on ends 29.45" body, 34.25" shaft-large milled flat & pin hole on ends 29.45" body, 34.25" shaft-large milled flat & pin hole on ends 29.45" body, 34.25" shaft-large milled flat	SHA2926RJ stions SHA2905RJNt SHA2905RJNt SHA2905RJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2905QJNt SHA2926RJN4 SHA2926RJN4 SHA2926RJN4 SHA2926QJN4 SHA3026DJ SHA3026DJ



3" dia. TWO body rollers		non-striping, non-skidding for tight turns & ground undu	lations
2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats	6.5 lb J3405R3CGt	2 short twin bodies, 34.25" shaft-large milled flat & pin hole on ends	SHA3405RJNt
2 bodies 3" smooth Urethane (2x4" wide bodies)	6.5 lb J3404R3Ct	2 short twin bodies, 34.25" shaft-large milled flat & pin hole on ends	SHA3404RJNt
2 bodies 3" smooth Steel (2x4" wide bodies)	8.5 lb J3404R3St	2 short twin bodies, 34.25" shaft-large milled flat & pin hole on ends	SHA3404RJNt
3" dia. FIVE body rollers		non-skidding for tight turns & ground undulations	
5 bodies 3" grooved Urethane (5x5.2" wide bodies) no flats	13.5 lb J3429R3CG5	5 short bodies, 34.25" shaft-large milled flat & pin hole on ends	SHA3429RJN5
5 bodies 3" smooth Urethane (5x5.2" wide bodies)	14 lb J3429R3C5	5 short bodies, 34.25" shaft-large milled flat & pin hole on ends	SHA3429RJN5
Jacobsen ROTARY AR-250, AR-2500 DECK - BACK ROLLER	07 15 10700 40	20 45" hada 27 25" ahab 470" da anga	SHA2722XJ
4" smooth Urethane 4" smooth Steel	27 lb J2722X4C 27 lb J2722X4S	22.45" body, 27.25" shaft-1/2" dia. ends 22.25" body, 27.25" shaft-1/2" dia. ends	SHA2722XJ
	27 10 32722743	acted body, arted shall read that	OT INET EEN
for JOHN DEERE mowers	EDG. EDGUE DOLLED		
John Deere 18" 180B & 180C & 180SL WALKING GREENSMOW 2" dia. SINGLE body rollers	ERS - FRONT ROLLER		
2" wide grooved Urethane no flats	6.5 lb D2119A2CG	19.45" body, 21.25" shaft	SHA2119AD
2" narrow grooved Urethane no flats	6.7 lb D2119A2NG	19.45" body, 21.25" shaft	SHA2119AD
2" wide grooved Urethane 1" flats	6.5 lb D2119A2CGF	19.45" body, 21.25" shaft	SHA2119AD
2" narrow grooved Urethane 1" flats	6.7 lb D2119A2NGF	19.45" body, 21,25" shaft	SHA2119AD
2" smooth Urethane	7.5 lb D2119A2C	19.25" body, 21.25" shaft	SHA2119AD
2" smooth Steel heavy (1/4" wall)	10.5 lb D2119A2S	19.25" body, 21.25" shaft	SHA2119AD
2" dia. TWO body rollers	7.1 W PO1011000	non-striping, non-skidding for tight turns & ground undu	
2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats	4 lb D2104A2CGt	2 short twin bodies at ends of a 21.25" shaft 2 short twin bodies at ends of a 21.25" shaft	SHA2104ADNt SHA2104ADNt
2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats	4 lb D2104A2NGt 4 lb D2104A2CGFt	2 short twin bodies at ends of a 21.25 shart 2 short twin bodies at ends of a 21.25 shart	SHA2104ADNt
2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats	4 lb D2104A2NGFt	2 short twin bodies at ends of a 21.25" shaft	SHA2104ADNt
2 bodies 2" smooth Urethane (2x2" wide bodies)	4 lb D2102A2Ct	2 short twin bodies at ends of a 21.25" shaft	SHA2102ADNt
2 bodies 2" smooth Urethane (2x4.75" wide bodies)	4.2 lb D2104A2Ct	2 short twin bodies at ends of a 21.25" shaft	SHA2104ADNt
2" dia. THREE body rollers		non-skidding for tight turns & ground undulations	
3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies)	12 lb D2719A2CG+2C	19.45" center body + 2 short outer bodies, 27.25" shaft	SHA2719ADN+2
3 bodies 2" narrow grooved Urethane (22.45" inner+2x2" outer bodies)	12 lb D2719A2NG+2C	19.45" center body + 2 short outer bodies, 27.25" shaft	SHA2719ADN+2
3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies)	13 lb D2719A2C+2C	19.25" center body + 2 short outer bodies, 27.25" shaft	SHA2719ADN+2
3 bodies 2" smooth Steel heavy (19.25" inner+2x2" outer bodies)	13 lb D2719A2S+2S	19.25" center body + 2 short outer bodies, 27.25" shaft	SHA2719ADN+2
2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats	8.5 lb D2119A2CG4	non-skidding for tight turns & ground undulations 4 short bodies, 21.25" shaft	SHA2119ADN4
4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) no flats	8.5 lb D2119A2NG4	4 short bodies, 21.25" shaft	SHA2119ADN4
4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) 1" flats	8.5 lb D2119A2CGF4	4 short bodies, 21.25" shaft	SHA2119ADN4
4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats	8.5 lb D2119A2NGF4	4 short bodies, 21.25" shaft	SHA2119ADN4
4 bodies 2" smooth Urethane (4x4.75" wide bodies)	8 lb D2119A2C4	4 short bodies, 21.25" shaft	SHA2119ADN4
4 bodies 2" smooth Steel heavy (4x4.75" wide bodies)	12 lb D2119A2S4	4 short bodies, 21.25" shaft	SHA2119ADN4
2" dia. SIX body rollers		non-skidding for tight turns & ground undulations	
6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies)	12 lb D2719A2CG4+2C	4 center bodies + 2 short outer bodies, 27.25" shaft	SHA2719ADN4+2
6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies)	12 lb D2719A2NG4+2C	4 center bodies + 2 short outer bodies, 27.25" shaft	SHA2719ADN4+2
6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats	12 lb D2719A2CGF4+2C	4 center bodies + 2 short outer bodies, 27.25" shaft	SHA2719ADN4+2
	40 IL DOTAGNONIOTA DO		
6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats		4 center bodies + 2 short outer bodies, 27.25" shaft	SHA2719ADN4+2
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies)	12 lb D2719A2C4+2C	4 center bodies + 2 short outer bodies, 27.25" shaft	SHA2719ADN4+2
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft	
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft	SHA2719ADN4+2
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S (00, 2750 & 2243 RIDING G 6.5 lb D2522C2CG	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S (00, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 000, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2CGF	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2CGF 6.7 lb D2522C2NGF	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S (00, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2CGF 6.7 lb D2522C2NGF 7.9 lb D2522C2CC	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2CGF 6.7 lb D2522C2NGF	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.25" body, 25.5" shaft 22.25" body, 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 100, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2CGF 6.7 lb D2522C2NGF 7.9 lb D2522C2CC 11.5 lb D2522C2C	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.25" body, 25.5" shaft 22.25" body, 25.5" shaft 22.25" body, 25.5" shaft 20.25" body, 25.5" shaft 20.25" body, 25.5" shaft 20.25" body, 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S (00, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2CGF 6.7 lb D2522C2NGF 7.9 lb D2522C2CC	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.25" body, 25.5" shaft 22.25" body, 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2CGF 6.7 lb D2522C2NGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGt	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA252CD SHA252CD SHA252CD SHA252CD SHA252CD SHA252CD
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 00, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2NGF 7.9 lb D2522C2NGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGt 4 lb D2504C2NGt	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 23.25" body, 25.5" shaft 25.5" shaft 25.5" shaft 25.5" shaft 25.5" shaft 27.5" shaft 28.55" shaft 29.55" shaft 29.55" shaft 29.55" shaft 29.55" shaft 29.55" shaft 20.55" shaft 20.55" shaft 20.55" shaft 20.55" shaft 20.55" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA252CD SHA252CD SHA2504CDNt SHA2504CDNt
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S (00, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGt 4 lb D2504C2CGt 4 lb D2504C2CGFt 4 lb D2504C2CCT	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.25" body, 25.5" shaft 22.25" body, 25.5" shaft 22.25" body, 25.5" shaft 22.55" shaft 23 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA252CD SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" marrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S (00, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2NGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGt 4 lb D2504C2NGt 4 lb D2504C2NGF 4 lb D2504C2NGF 4 lb D2504C2NGFt 4 lb D2504C2NGFt	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.55" shaft 23 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA252CD SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" vide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" vide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGt 4 lb D2504C2CGt 4 lb D2504C2NGF 4 lb D2504C2NGF 4 lb D2504C2NGF 4.2 lb D2504C2NGF 4.2 lb D2504C2CGt 4.3.7 lb D2502C2Ct	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 23.50" shaft 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA252CD SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x2.4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGt 4 lb D2504C2CGt 4 lb D2504C2CGt 4 lb D2504C2CGFt 4 lb D2504C2CGFt 4 lb D2504C2CGFt 4 lb D2504C2CGFt 4 lb D2504C2CGTt 1.2 lb D3122C2CCG+2C	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.55" shaft 23.55" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 3 short twin bodies at ends of a 25.5" shaft 3 chart twin bodies at ends of a 25.5" shaft 3 chart twin bodies at ends of a 25.5" shaft 3 chart twin bodies at ends of a 25.5" shaft 3 chart twin bodies at ends of a 25.5" shaft 3 chart twin bodies at ends of a 25.5" shaft 3 chart twin bodies at ends of a 25.5" shaft 3 chart twin bodies at ends of a 25.5" shaft 3 chart twin bodies at ends of a 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA2504CDNt
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 todies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2NGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGt 4 lb D2504C2NGt 4 lb D2504C2NGt 4 lb D2504C2NGF 4 lb D2504C2CGFt 4 lb D2504C2CGFt 4 lb D2504C2NGFt 4 lb D2504C2CCGFt 4 lb D2504C2CCGFt 4 lb D2504C2CCGFt 4 lb D2504C2CCGFt 4 lb D2504C2CCCT 12 lb D3122C2CCG+2C 12 lb D3122C2CNG+2C	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 23.55" shaft 24.55" shaft 25.55" shaft 2	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2504CDNt
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" narrow grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2NGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGt 4 lb D2504C2NGt 4 lb D2504C2NGF 4 lb D2504C2NGF 4 lb D2504C2CGF 4 lb D2504C2CGF 4 lb D2504C2NGF 4 lb D2504C2NGF 4 lb D2504C2NGF 5 lb D2504C2CC 12 lb D3122C2CG+2C 12 lb D3122C2NG+2C 13 lb D3122C2NG+2C	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.55" shaft 22.55" shaft 23 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 3 short twin bodies at ends of a 25.5" shaft 3 short twin bodies at ends of a 25.5" shaft 4 short twin bodies at ends of a 25.5" shaft 5 short twin bodies at ends of a 25.5" shaft 6 short twin bodies at ends of a 25.5" shaft 7 shaft 8 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA2504CDNt
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2NGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGt 4 lb D2504C2NGt 4 lb D2504C2NGt 4 lb D2504C2NGF 4 lb D2504C2CGFt 4 lb D2504C2CGFt 4 lb D2504C2NGFt 4 lb D2504C2CCGFt 4 lb D2504C2CCGFt 4 lb D2504C2CCGFt 4 lb D2504C2CCGFt 4 lb D2504C2CCCT 12 lb D3122C2CCG+2C 12 lb D3122C2CNG+2C	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 23.55" shaft 24.55" shaft 25.55" shaft 2	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2504CDNt
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" narrow grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2NGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGt 4 lb D2504C2NGt 4 lb D2504C2NGF 4 lb D2504C2NGF 4 lb D2504C2CGF 4 lb D2504C2CGF 4 lb D2504C2NGF 4 lb D2504C2NGF 4 lb D2504C2NGF 5 lb D2504C2CC 12 lb D3122C2CG+2C 12 lb D3122C2NG+2C 13 lb D3122C2NG+2C	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.55" shaft 23.55" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 3 short twin bodies at ends of a 25.5" shaft 3 short twin bodies at ends of a 25.5" shaft 3 short twin bodies at ends of a 25.5" shaft 3 short twin bodies at ends of a 25.5" shaft 3 short twin bodies at ends of a 25.5" shaft 3 short twin bodies at ends of a 25.5" shaft 3 short twin bodies at ends of a 25.5" shaft 3 short twin bodies at ends of a 25.5" shaft 3 short twin bodies at ends of a 25.5" shaft 3 short twin bodies at ends of a 25.5" shaft 4 short twin bodies at ends of a 25.5" shaft 5 short twin bodies at ends of a 25.5" shaft 6 short twin bodies at ends of a 25.5" shaft 7 short twin bodies at ends of a 25.5" shaft 8 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short twin bodies at ends of a 25.5" shaft 9 short	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA2504CDNt
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" marrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 2" dia. FOUR body rollers	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 6.7 lb D2522C2C 11.5 lb D2522C2C 11.5 lb D2522C2C 11.5 lb D2524C2CGf 4 lb D2504C2CGf 4 lb D2504C2CGf 4 lb D2504C2CGf 4 lb D2504C2CGF 3.7 lb D2502C2C 12 lb D3122C2CC 12 lb D3122C2CG+2C 13 lb D3122C2C+2C 13 lb D3122C2C+2C 13 lb D3122C2CS+2S	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.55" shaft 23.55" shaft 25.55" shaft 25	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2504CDNt SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" marrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGf 5.7 lb D2502C2C 12 lb D3122C2CG+2C 12 lb D3122C2CG+2C 13 lb D3122C2CS+2C 13 lb D3122C2CS+2C 13 lb D3122C2CS+2S 8.5 lb D2522C2CG4 8.5 lb D2522C2CGF 8.5 lb D2522C2CGF4 8.5 lb D2522C2CGF4	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 23.55" shaft 24.55" shaft 25.55" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA2504CDNt SHA2502CDNt SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2NGF 6.7 lb D2522C2NGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGt 4 lb D2504C2NGt 4 lb D2504C2NGF 4 lb D2504C2NGF 4 lb D2504C2CGF 4 lb D2504C2NGF 4 lb D2504C2NGF 5 lb D2502C2C 12 lb D3122C2CG+2C 12 lb D3122C2CG+2C 13 lb D3122C2NG+2C 13 lb D3122C2NG+2C 13 lb D3122C2C+2C 13 lb D3122C2CS+2S 8.5 lb D2522C2CGG 8.5 lb D2522C2CGG4 8.5 lb D2522C2NGF4 8.5 lb D2522C2NGF4	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.55" shaft 22.55" shaft 23.55" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short bodies at ends of a 25.5" shaft 2 short bodies at ends of a 25.5" shaft 4 short bodies, 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA252CD SHA2504CDNt SHA2522CDN4 SHA2522CDN4 SHA2522CDN4
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" smooth Urethane (2x2" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 4 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" vide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 7.9 lb D2522C2C 11.5 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGf 12 lb D3122C2CG+2C 12 lb D3122C2CG+2C 13 lb D3122C2CS+2C 13 lb D3122C2CS+2C 13 lb D3122C2CGF 8.5 lb D2522C2CGF 8.5 lb D2522C2CCGF 8.5 lb D2522C2CGF 8.5 lb D2522C2CCGF	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.55" shaft 23.55" shaft 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2504CDNt
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" vide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" marrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" marrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2NGF 6.7 lb D2522C2NGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGt 4 lb D2504C2NGt 4 lb D2504C2NGF 4 lb D2504C2NGF 4 lb D2504C2CGF 4 lb D2504C2NGF 4 lb D2504C2NGF 5 lb D2502C2C 12 lb D3122C2CG+2C 12 lb D3122C2CG+2C 13 lb D3122C2NG+2C 13 lb D3122C2NG+2C 13 lb D3122C2C+2C 13 lb D3122C2CS+2S 8.5 lb D2522C2CGG 8.5 lb D2522C2CGG4 8.5 lb D2522C2NGF4 8.5 lb D2522C2NGF4	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 23 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA252CD SHA2504CDNt SHA2522CDN4 SHA2522CDN4 SHA2522CDN4
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" vide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" marrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2" flats	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGf 13.7 lb D2502C2C 12 lb D3122C2CC 13 lb D3122C2CG+2C 13 lb D3122C2C+2C 13 lb D3122C2C+2C 13 lb D3122C2CS+2S 8.5 lb D2522C2CG4 8.5 lb D2522C2CGF 8.5 lb D2522C2CSA	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.55" body, 25.5" shaft 23.50" short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 4 short bodies, 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA252CD SHA2504CDNt SHA2502CDNt SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA2522CDN4
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.4.5" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2" dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CG 6.5 lb D2522C2CGF 6.7 lb D2522C2CGF 7.9 lb D2522C2C 11.5 lb D2522C2CS 4 lb D2504C2CGt 13.7 lb D2502C2C 12 lb D3122C2CC 13 lb D3122C2CG+2C 13 lb D3122C2CG+2C 13 lb D3122C2CS+2S 8.5 lb D2522C2CG4 8.5 lb D2522C2CGF4 8.5 lb D2522C2CGGF4 8.5 lb D2522C2CGGF4 8.5 lb D2522C2CGGF4 8.5 lb D2522C2CGGF4 8.5 lb D2522C2CSGF4 8.5 lb D2522C2CGF4 8.5 lb D2522C2CSGF4 8.5 lb D3122C2CGGF4	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 23 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2504CDNt
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" arrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) 2" dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGf 13.7 lb D2502C2C 12 lb D3122C2CC 13 lb D3122C2CG+2C 13 lb D3122C2C+2C 13 lb D3122C2C+2C 13 lb D3122C2CS+2S 8.5 lb D2522C2CG4 8.5 lb D2522C2CGF 8.5 lb D2522C2CSA	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 23.55" shaft 24.55" shaft 25.55" shaft 2	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2502CDNt SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA252CDN4 SHA252CDN4
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.4.5" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2" dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2NGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGt 4 lb D2504C2NGt 4 lb D2504C2NGF 4 lb D2504C2NGF 4 lb D2504C2NGF 4 lb D2504C2CGF 4 lb D2504C2NGF 4 lb D2504C2CGF 13.7 lb D2502C2Ct 12 lb D3122C2CG+2C 13 lb D3122C2NG+2C 13 lb D3522C2NGF 8.5 lb D2522C2NGF 8.5 lb D3122C2CSF 8.5 lb D3122C2CGF 8.5 lb D3122C2CGGF 9.5 lb D312CCCGGF 9.5 lb D312CCCGGF 9.5 lb D312CCCGGF	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 23.55" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 4 short bodies, 25.5" shaft 5 center bodies + 2 short outer bodies, 31.5" shaft 6 center bodies + 2 short outer bodies, 31.5" shaft 7 center bodies + 2 short outer bodies, 31.5" shaft 8 center bodies + 2 short outer bodies, 31.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA252CD SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2502CDNt SHA2502CDNt SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA2522CDN4
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 3 bodies 2" smooth Urethane (2x4.75" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 4 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2" dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies) 2" dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2NG 6.5 lb D2522C2NGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGt 4 lb D2504C2NGt 4 lb D2504C2NGF 4 lb D2504C2NGF 4 lb D2504C2NGF 4 lb D2504C2CGF 4 lb D2504C2NGF 4 lb D2504C2CGF 13.7 lb D2502C2Ct 12 lb D3122C2CG+2C 13 lb D3122C2NG+2C 13 lb D3522C2NGF 8.5 lb D2522C2NGF 8.5 lb D3122C2CSF 8.5 lb D3122C2CGF 8.5 lb D3122C2CGGF 9.5 lb D312CCCGGF 9.5 lb D312CCCGGF 9.5 lb D312CCCGGF	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.55" shaft 23 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short bodies at ends of a 25.5" shaft 3 short bodies at ends of a 25.5" shaft 4 short bodies, 25.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2502CDNt SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA3122CDN4+2 SHA3122CDN4+2 SHA3122CDN4+2 SHA3122CDN4+2 SHA3122CDN4+2
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" marrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" smooth Urethane (2x2" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2" dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies) 2" dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies)	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGf 4 lb D2504C2CGf 4 lb D2504C2CGF 4 lb D2504C2CGF 3.7 lb D2502C2C 12 lb D3122C2CGF 13 lb D3122C2CGF 13 lb D3122C2CGF 13 lb D3122C2CGF 13 lb D3122C2CGF 14 lb D2504C2CGF 15 lb D3122C2CGF 16 lb D3122C2CGF 17 lb D3122C2CGF 18 lb D3122C2CGF 19 lb D3122C2CGF 19 lb D3122C2CGF 10 lb D3122C2CGF 10 lb D3122C2CGF 11 lb D3122C2CGF 12 lb D3122C2CGF 13 lb D3122C2CGF 14 lb D3122C2CGF 15 lb D2522C2CGF 16 lb D2522C2CGF 17 lb D3122C2CGF 18 lb D3122C2CGF 19 lb D3122C2CGF 10 lb D3122C2CGF 11 lb D3122C2CGF 12 lb D3122C2CGF 12 lb D3122C2CGF 13 lb D3122C2CGF 14 lb D3122C2CGF 15 lb D3122C2CGF 16 lb D3122C2CGF 17 lb D3122C2CGF 18 lb D3122C2CGF 19 lb D3122C2CGF 10 lb D3122C2CGF 11 lb D3122C2CGF 12 lb D3122C2CGF 12 lb D3122C2CGF 12 lb D3122C2CGF 14 lb D3122C2CGF 15 lb D3122C2CGF 16 lb D3122C2CGF 17 lb D3122C2CGF 17 lb D3122C2CGF 18 lb D3122C2CGF 19 lb D312CCCGF 19 lb D312CCCGF 19 lb D312CCCGF 10 lb D312CCCCGF 10 lb D312CCCCCGF 10 lb D312CCCCCGF 10 lb D312CCCCCGF 10 lb D312CCCCGF 10 lb D312CCCCCGF 10 lb D312CCCCCGF 10 lb D312CCCCCGF 10 lb D312CCCCCCCGF 10 lb D312CCCCCCGF 10 lb D312CCCCCCCCCCCCCCCCCCCCCC	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.55" shaft 23 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short bodies 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft 6 center bodies + 2 short outer bodies, 31.5" shaft 7 center bodies + 2 short outer bodies, 31.5" shaft 8 center bodie	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA252CD SHA2504CDNt SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA3122CDN4+2 SHA3122CDN4+2 SHA3122CDN4+2 SHA3122CDN4+2 SHA3122CDN4+2 SHA3122CDN4+2
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x2.45" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) 2" dia. SIX body rollers 6 bodies 2" smooth steel heavy (4x5.55" inner+2x2" outer bodies) 2" dia. SIX body rollers 6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies) 6 bodies 2" marrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 2" dia. SIX body rollers 6 bodies 2" marrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 2" dia. SIX body rollers 2" dia. SIX body rollers	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 00, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGF 13.7 lb D2502C2C 12 lb D3122C2CCC 13 lb D3122C2CG+2C 13 lb D3122C2CS+2C 13 lb D3122C2CGF 8.5 lb D2522C2CG 8.5 lb D2522C2CG 8.5 lb D2522C2CG4 8.5 lb D2522C2CGF 8.5 lb D3122C2CGFF 8.5 lb D3122C2CGGF 8.5 lb D3122C2CGGF 8.5 lb D3122C2CGGF 9.5 lb D3122C2CCGF 9.5 lb D3122C2CCGF 9.5 lb D3122C2CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 23 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 4 short bodies, 25.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 5 center bodies + 2 short outer bodies, 31.5" shaft 5 center bodies + 2 short outer bodies, 31.5" shaft 6 center bodies + 2 short outer bodies, 31.5" shaft 7 center bodies + 2 short outer bodies, 31.5" shaft 8 center bodies + 2 short outer bodies, 31.5" shaft 9 center bodies + 2 short outer bodies, 31.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2502CDNt SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA252CDN4 SHA2522CDN4 SHA3122CDN4+2
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 2205L WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" smooth Urethane (2x2.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 4 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 5 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 7 dia. SIX body rollers 6 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 7 diats 6 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 7 diats 8 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 8 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 9 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 1 flats 10 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 2 bodies 2" smooth Ur	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGf 3.7 lb D2502C2C 12 lb D3122C2CG+2C 12 lb D3122C2CG+2C 13 lb D3122C2CG+2C 13 lb D3122C2CG+2C 13 lb D3122C2CGF 8.5 lb D2522C2CGF 8.5 lb D3122C2CGF 8.5 lb D3122C2CGF 8.5 lb D3122C2CGF 8.5 lb D3122C2CGGF 8.5 lb D3122C2CGF 8.5 lb D3122C2CGGF 8.5 lb D312CC2CGF 8.5 lb D312C	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 22.35" body, 25.5" shaft 23 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 4 short bodies, 25.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 5 center bodies + 2 short outer bodies, 31.5" shaft 6 center bodies + 2 short outer bodies, 31.5" shaft 7 center bodies + 2 short outer bodies, 31.5" shaft	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2502CDNt SHA2502CDNt SHA2502CDNt SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA3122CDN4+2 SHA312CDN4+2 SHA3122CDN4+2 SHA312CDN4+2
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) 2" dia. SIX body rollers 6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 5 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 7 dia. SIX body rollers 6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 7 dia. SINGLE body rollers 7 wide grooved Urethane (4x5.55" inner+2x2" outer bodies) 8 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 9 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 1" flats 1 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 1" flats 1	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGf 3.7 lb D2502C2C 12 lb D3122C2CGF 13 lb D3122C2CGF 13 lb D3122C2CGF 13 lb D3122C2CGF 14 lb D2504C2CGF 15 lb D2502C2C 16 lb D3122C2CGF 17 lb D3122C2CGF 18 lb D3122C2CGF 19 lb D3122C2CGF 19 lb D3122C2CGF 10 lb D3122C2CGF 10 lb D3122C2CGF 11 lb D3122C2CGF 12 lb D3122C2CGF 13 lb D3122C2CGF 14 lb D3122C2CGF 15 lb D2522C2CGF 16 lb D3122C2CGF 17 lb D3122C2CGF 18 lb D3122C2CGF 19 lb D3122C2CGF 10 lb D3122C2CGF 11 lb D3122C2CGF 12 lb D3122C2CGF 13 lb D3122C2CGF 14 lb D3122C2CGF 15 lb D3122C2CGF 16 lb D3122C2CGF 17 lb D312CCCGF 18 lb D312C2CGGF 18 lb D312C2CGGF 19 lb D312CCCGF 19 lb D312CCCGF 10 lb D312CCCGF 10 lb D312CCCGF 11 lb D312CCCGF 12 lb D312CCCGF 12 lb D312CCCGF 13 lb D312CCCGF 14 lb D312CCCGF 15 lb D312CCCGF 16 lb D312CCCGF 17 lb D312CCCGF 17 lb D312CCCGF 18 lb D312CCCGF 18 lb D312CCCGF 19 lb D312CCCGF 19 lb D312CCCGF 10 lb D312CCCGF 10 lb D312CCCGF 11 lb D312CCCGF 12 lb D312CCCGF 12 lb D312CCCGF 13 lb D312CCCGF 14 lb D312CCCGF 15 lb D312CCCGF 16 lb D312CCCGF 17 lb D312CCCGF 17 lb D312CCCGF 18 lb D312CCCCGF 18 lb	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 23 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short bodies at ends of a 25.5" shaft 2 short bodies at ends of a 25.5" shaft 2 short bodies at ends of a 25.5" shaft 2 short bodies at ends of a 25.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 4 short bodies, 25.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodi	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA252CD SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2502CDNt SHA252CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA3122CDN4+2 SHA2522CDN4
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" smooth Urethane (2x4.75" wide bodies) 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) 1" flats 5 bodies 2" smooth Urethane (4x5.55" wide bodies) 2" dia. SIX body rollers 6 bodies 2" marrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 5 bodies 2" marrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 6 bodies 2" marrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats 6 bodies 2" marrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 2.5" dia. SINGLE body rolle	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 00, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 7.9 lb D2522C2C 11.5 lb D2522C2CS 4 lb D2504C2CGF 3.7 lb D2502C2C 12 lb D3122C2CG+2C 13 lb D3122C2C4+2C 13 lb D3522C2CGF 8.5 lb D2522C2CGF 8.5 lb D3122C2CGF 8.5 lb D3522C25SG 8.5 lb D2522C25SG	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 23 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 4 short bodies, 25.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 5 center bodies + 2	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2502CDNt SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA3122CDN4+2 SHA312CDN4+2 SHA3122CDN4+2 SHA312CDN4+2
6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies) 6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies) John Deere 22" 220 & 220SL WALKING & 2500, 2400, 2550, 27 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. TWO body rollers 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 3 bodies 2" smooth Urethane (2x4.75" wide bodies) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) 2" dia. SIX body rollers 6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 5 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 7 dia. SIX body rollers 6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 7 dia. SINGLE body rollers 7 wide grooved Urethane (4x5.55" inner+2x2" outer bodies) 8 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 9 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 1" flats 1 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 1" flats 1	12 lb D2719A2C4+2C 12 lb D2719A2S4+2S 200, 2750 & 2243 RIDING G 6.5 lb D2522C2CG 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 6.7 lb D2522C2CGF 7.9 lb D2522C2C 11.5 lb D2522C2S 4 lb D2504C2CGf 3.7 lb D2502C2C 12 lb D3122C2CGF 13 lb D3122C2CGF 13 lb D3122C2CGF 13 lb D3122C2CGF 14 lb D2504C2CGF 15 lb D2502C2C 16 lb D3122C2CGF 17 lb D3122C2CGF 18 lb D3122C2CGF 19 lb D3122C2CGF 19 lb D3122C2CGF 10 lb D3122C2CGF 10 lb D3122C2CGF 11 lb D3122C2CGF 12 lb D3122C2CGF 13 lb D3122C2CGF 14 lb D3122C2CGF 15 lb D2522C2CGF 16 lb D3122C2CGF 17 lb D3122C2CGF 18 lb D3122C2CGF 19 lb D3122C2CGF 10 lb D3122C2CGF 11 lb D3122C2CGF 12 lb D3122C2CGF 13 lb D3122C2CGF 14 lb D3122C2CGF 15 lb D3122C2CGF 16 lb D3122C2CGF 17 lb D312CCCGF 18 lb D312C2CGGF 18 lb D312C2CGGF 19 lb D312CCCGF 19 lb D312CCCGF 10 lb D312CCCGF 10 lb D312CCCGF 11 lb D312CCCGF 12 lb D312CCCGF 12 lb D312CCCGF 13 lb D312CCCGF 14 lb D312CCCGF 15 lb D312CCCGF 16 lb D312CCCGF 17 lb D312CCCGF 17 lb D312CCCGF 18 lb D312CCCGF 18 lb D312CCCGF 19 lb D312CCCGF 19 lb D312CCCGF 10 lb D312CCCGF 10 lb D312CCCGF 11 lb D312CCCGF 12 lb D312CCCGF 12 lb D312CCCGF 13 lb D312CCCGF 14 lb D312CCCGF 15 lb D312CCCGF 16 lb D312CCCGF 17 lb D312CCCGF 17 lb D312CCCGF 18 lb D312CCCCGF 18 lb	4 center bodies + 2 short outer bodies, 27.25" shaft 4 center bodies + 2 short outer bodies, 27.25" shaft REENSMOWERS - FRONT & BACK ROLLERS 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.45" body, 25.5" shaft 22.25" body, 25.5" shaft 23 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short twin bodies at ends of a 25.5" shaft 2 short bodies at ends of a 25.5" shaft 2 short bodies at ends of a 25.5" shaft 2 short bodies at ends of a 25.5" shaft 2 short bodies at ends of a 25.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 4 short bodies, 25.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodies, 31.5" shaft 4 center bodies + 2 short outer bodi	SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2719ADN4+2 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA252CD SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2504CDNt SHA2502CDNt SHA2502CDNt SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA3122CDN4+2 SHA2522CDN4



2 E" dia TWO hadu rallara			non strining non skidding for tight turns & ground undu	lations
2.5" dia. TWO body rollers 2 bodies 2.5" grooved Urethane (2x4.75" wide bodies) no flats	4 lb D25	504C25CGt	non-striping, non-skidding for tight turns & ground undu 2 short twin independent roller bodies, 25.5" shaft	SHA2504CDNt
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies)	4.2 lb D25	3.7.1.1.7.7.7.7.7.7.1	2 short twin independent roller bodies, 25.5" shaft	SHA2504CDNt
2.5" dia. FOUR body rollers		33132331	non-skidding for tight turns & ground undulations	
4 bodies 2.5" grooved Urethane (4x5.55" wide bodies) no flats	10.5 lb D25	522C25CG4	4 short bodies, 25.5" shaft	SHA2522CDN4
4 bodies 2.5" smooth Urethane (4x5.55" wide bodies)	10 lb D25	522C25C4	4 short bodies, 25.5" shaft	SHA2522CDN4
2.5" dia. SIX body rollers			non-skidding for tight turns & ground undulations	
6 bodies 2.5" grooved Urethane (4x5.55" inner+2x2" outer bodies)		122C25CG4+2C	4 center bodies + 2 short outer bodies, 31.5" shaft	SHA3122CDN4+2
6 bodies 2.5" smooth Urethane (4x5.55" inner+2x2" outer bodies)	14 lb D31:	122C25C4+2C	4 center bodies + 2 short outer bodies, 31.5" shaft	SHA3122CDN4+2
John Deere 260SL WALKING GREENSMOWERS - FRONT ROLLER 4 bodies 2.5" smooth Steel (4x6.5" wide bodies)	13 lb D29	02642554	4 independent roller bodies, 29.75" shaft	SHA2926CDN4
2" dia. SINGLE body rollers	13 10 023	320A2334	4 indepartualit folia soulds, 20.70 share	0117202000114
2" wide grooved Urethane no flats	7.8 lb D29	926A2CG	26.45" body, 29.75" shaft	SHA2926AD
2" wide grooved Urethane 1" flats		926A2CGF	26.45" body, 29.75" shaft	SHA2926AD
2" smooth Urethane	9.5 lb D29	926A2C	26.25" body, 29.75" shaft	SHA2926AD
2" smooth Steel heavy (1/4" wall)	12.5 lb D29	926A2S	26.25" body, 29.75" shaft	SHA2926AD
2.5" dia. SINGLE body rollers			2449446 2020 ACC 400 A	72802222222
2.5" grooved Urethane no flats	9.5 lb D29:		26.45" body, 29.75" shaft	SHA2926AD
2.5" smooth Urethane 2.5" smooth Steel	11 lb D29: 11 lb D29:		26.45" body, 29.75" shaft 26.45" body, 29.75" shaft	SHA2926AD SHA2926AD
2.5" dia. TWO body rollers	1110 029.	920A233	non-striping, non-skidding for tight turns & ground undu	
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies)	7 lb D29	904A25Ct	2 short twin bodies at ends of a 29.75° shaft	SHA2904ADNt
2.5" dia. FOUR body rollers	100%,0000	5.5-1/0/55.50.50	non-skidding for tight turns & ground undulations	
4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats	10 lb D29:	926A25CG4	4 short bodies, 29.75" shaft	SHA2926ADN4
4 bodies 2.5" smooth Urethane (4x6.5" wide bodies)	13 lb D29	926A25C4	4 short bodies, 29.75" shaft	SHA2926ADN4
2.5" dia. SIX body rollers			non-skidding for tight turns & ground undulations	
6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies)		526A25CG4+2C	4 center bodies + 2 short outer bodies, 29.75" shaft	SHA3526ADN4+2
6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies)		526A25C4+2C	4 center bodies + 2 short outer bodies, 29.75" shaft	SHA3526ADN4+2
John Deere 22" 3215 & 3225 LIGHT FAIRWAY MOWERS - FRONT & Combination roller assemblies to diminish effect of reel overla			(Sectional rollers with 4 bodies also available)	
2" wide grooved Urethane 1" flats	6.7 lb D25		22.45" body, 25.5" shaft	SHA2522CD
2" smooth Urethane	7.9 lb D25		22.25" body, 25.5" shaft	SHA2522CD
2" smooth Steel heavy (1/4" wall)	11.5 lb D25		22.25" body, 25.5" shaft	SHA2522CD
John Deere 22" 3235 LIGHT FAIRWAY MOWER - FRONT & BACK RO	LLERS (2 styles	es)	(Sectional rollers with 4 bodies also available)	
Rollers for QA-5 reels (with 1 flat on one end of the shaft):				
3" grooved Urethane no flats	9.5 lb D25		22.45" body, 25.5" shaft-1 flat	SHA2522CD
3" smooth Urethane	12 lb D25		22.45" body, 25.5" shaft-1 flat	SHA2522CD
3" smooth Steel To diminish instances of shadowing lines due to overlap of	11.5 lb D25	522035	22.25" body, 25.5" shaft-1 flat call for proper application specifics	SHA2522CD
3" grooved Urethane with 2.2" wide smooth ends		522C3CG.22C	front roller for rear mower heads-use with D2519C3C	SHA2522CD
3" smooth Urethane	11 lb D25		back roller for rear mower heads-use with D2522C3CG.22C	SHA2519CD
Rollers with 2 flats on 1 end of the shaft:	A 1 A 1 A 1 A 1 A 1 A 1 A 1 A 1 A 1 A 1	ELLOCATION TO TO		
Trollero Will E hate off I cha of the offart.				
3" grooved Urethane no flats	9.5 lb D25	522F3CG	22.45" body, 1404" shaft-2 flats on 1 end	SHA2522FD
	9.5 lb D25 11 lb D25		22.45" body, 1404" shaft-2 flats on 1 end 22.45" body, 25.5" shaft-2 flats on 1 end	SHA2522FD SHA2522FD
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel	11 lb D25 12 lb D25	522F3C	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft	
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of	11 lb D25 12 lb D25 f reels	522F3C 522F3S	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics	SHA2522FD SHA2522FD
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends	11 lb D25 12 lb D25 f reels 9.5 lb D25	522F3C 522F3S 522F3CG.22C	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C	SHA2522FD SHA2522FD SHA2522FD
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane	11 lb D25 12 lb D25 f reels 9.5 lb D25 11 lb D25	522F3C 522F3S 522F3CG.22C 519F3C	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C	SHA2522FD SHA2522FD
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends	11 lb D25 12 lb D25 f reels 9.5 lb D25 11 lb D25	522F3C 522F3S 522F3CG.22C 519F3C	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C	SHA2522FD SHA2522FD SHA2522FD
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl	11 lb D25 12 lb D25 f reels 9.5 lb D25 11 lb D25	522F3C 522F3S 522F3CG.22C 519F3C	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C	SHA2522FD SHA2522FD SHA2522FD
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft):	11 lb D25 12 lb D25 f reels 9.5 lb D25 11 lb D25	522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels)	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C	SHA2522FD SHA2522FD SHA2522FD
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats	11 lb D25. 12 lb D25. 17 reels 9.5 lb D25. 11 lb D25. UT FAIRWAY (C	522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2522FD SHA2519FD SHA252CD SHA2522CD
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats	11 lb D25. 12 lb D25. 15 reels 9.5 lb D25. 11 lb D25. UT FAIRWAY (C 6.5 lb D25. 6.7 lb D25. 6.5 lb D25.	522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2CGF	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2521FD SHA2519FD SHA252CD SHA2522CD SHA2522CD SHA2522CD
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats	11 lb D25; 12 lb D25; 12 lb D25; 11 lb D25; 11 lb D25; UT FAIRWAY (C 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 6.7 lb D25;	522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2CGF 522C2NGF	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2519FD SHA2519FD SHA252CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane	11 lb D25; 12 lb D25; 12 lb D25; 11 lb D25; 11 lb D25; UT FAIRWAY (C 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 6.7 lb D25; 7.9 lb D25;	522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2CGF 522C2NGF 522C2NGF 522C2NGF	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2519FD SHA2519FD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall)	11 lb D25; 12 lb D25; 12 lb D25; 11 lb D25; 11 lb D25; UT FAIRWAY (C 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 6.7 lb D25;	522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2CGF 522C2NGF 522C2NGF 522C2NGF	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2519FD SHA2519FD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane	11 lb D25. 12 lb D25. 12 lb D25. 11 lb D25. 11 lb D25. UT FAIRWAY (G 6.5 lb D25. 6.7 lb D25. 6.7 lb D25. 7.9 lb D25. 11.5 lb D25.	522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2CGF 522C2NGF 522C2NGF 522C2NGF	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2519FD SHA2519FD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7550/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers	11 lb D25. 12 lb D25. 12 lb D25. 15 reels 9.5 lb D25. 11 lb D25. UT FAIRWAY (G 6.5 lb D25. 6.7 lb D25. 6.7 lb D25. 7.9 lb D25. 11.5 lb D25.	522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2NG 522C2CGF 522C2NGF 522C2CGF 522C2CGF	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2521PD SHA2519FD SHA2522CD
3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" vide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies)	11 lb D25; 12 lb D25; 12 lb D25; 11 lb D25; 11 lb D25; UT FAIRWAY (C 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 7.9 lb D25; 11.5 lb D25; 12 lb D31; 12 lb D31; 13 lb D31;	522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2CGF 522C2CGF 522C2C 522C2C 122C2CG+2C 122C2CG+2C 122C2CG+2C	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG 22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.25" shaft-1 flat 22	SHA2522FD SHA2522FD SHA2521PD SHA2519FD SHA2522CD SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" vide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies)	11 lb D25; 12 lb D25; 11 lb D25; 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 7.9 lb D25; 11.5 lb D25; 12 lb D31; 12 lb D31; 13 lb D31;	522F3C 522F3S 522F3CG .22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2CNGF 522C2CNGF 522C2CS 522C2CS 122C2CG+2C	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.45" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft	SHA2522FD SHA2522FD SHA2521FD SHA2519FD SHA2522CD
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Ci Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies)	11 lb D25; 12 lb D25; 11 lb D25; 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 11.5 lb D25; 12 lb D31; 12 lb D31; 13 lb D31;	522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2NG 522C2CGF 522C2CGF 522C2CGF 522C2CGF 522C2CGF 522C2CCC 522C2CCCCCCCCCCCCCCCCCCCCCCC	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D252F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft non-skidding for tight turns & ground undulations	SHA2522FD SHA2522FD SHA2522FD SHA2519FD SHA2519FD SHA2522CD SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats	11 lb D25; 12 lb D25; 11 lb D25; 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 11.5 lb D25; 12 lb D31; 12 lb D31; 13 lb D31; 13 lb D31; 8.5 lb D25;	522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CQG 522C2VQG 522C2VQG 522C2VQGF 522C2CQF 522C2CQF 522C2CQC 522C2CQC 122C2CQCQC 122C2CQCQC 122C2CQCQC 122C2CQCQC 122C2CQCQC 122C2CQCQC	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D252F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2521PD SHA2519FD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 2 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2 dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats	11 lb D25; 12 lb D25; 11 lb D25; 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 7.9 lb D25; 11.5 lb D25; 12 lb D31; 13 lb D31; 13 lb D31; 13 lb D31; 8.5 lb D25; 8.5 lb D25;	522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2NGF 522C2CS 522C2S 122C2CG+2C 122C2CG+2C 122C2C+2C 122C2C+2C 122C2S+2S 522C2CG4	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft-1 flat 4 short bodies, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2522FD SHA2521PD SHA2519FD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 2 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats	11 lb D25; 12 lb D25; 11 lb D25; 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 11.5 lb D25; 12 lb D31; 12 lb D31; 13 lb D31; 13 lb D31; 13 lb D31; 8.5 lb D25; 8.5 lb D25; 8.5 lb D25;	522F3C 522F3C 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2CGF 522C2CGF 522C2C 122C2CH2C 122C2CH2C 122C2CH2C 122C2CH2C 122C2CH2C 122C2CH2C 122C2CH2C 122C2CH2C 122C2CH2C 122C2CH2C 122C2CH2C	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2529F3CG 22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.25" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft	SHA2522FD SHA2522FD SHA2522FD SHA2521PD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA252CD SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats	11 lb D25; 12 lb D25; 11 lb D25; 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 11.5 lb D25; 12 lb D31; 13 lb D31; 13 lb D31; 13 lb D31; 13 lb D35; 8.5 lb D25;	522F3C 522F3C 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2CGF 522C2CS 122C2CG+2C 122C2CG+2C 122C2CH4-2C 122C2C+2C 122C2C+2C 122C2C+2C 122C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CG4	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft-1 flat 4 short bodies, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2522FD SHA2521PD SHA2519FD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 2 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats	11 lb D25; 12 lb D25; 11 lb D25; 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 11.5 lb D25; 12 lb D31; 12 lb D31; 13 lb D31; 13 lb D31; 13 lb D31; 8.5 lb D25; 8.5 lb D25; 8.5 lb D25;	522F3C 522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2NG 522C2CGF 522C2C 522C2C 122C2CG+2C 122C2CG+2C 122C2C+2C 122C2CS+2S 522C2CG4 522C2CG4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.25" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft non-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA25219FD SHA2519FD SHA2519FD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" marrow grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.25" inner+2x2" outer bodies) 2 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" vide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats	11 lb D25; 12 lb D25; 11 lb D25; 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 11.5 lb D25; 12 lb D31; 12 lb D31; 13 lb D31; 13 lb D31; 13 lb D35; 8.5 lb D25; 8.6 lb D25; 8.6 lb D25; 8.7 lb D25; 8.7 lb D25; 8.7 lb D25; 8.8 lb D25;	522F3C 522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2NG 522C2CGF 522C2C 522C2C 122C2CG+2C 122C2CG+2C 122C2C+2C 122C2CS+2S 522C2CG4 522C2CG4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.45" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft anon-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2521FD SHA2519FD SHA2519FD SHA2522CD SHA2522CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2.5" dia. SINGLE body rollers 2.5" wide grooved (1" spacing) Urethane no flats	11 lb D25; 12 lb D25; 11 lb D31; 12 lb D31; 13 lb D31; 13 lb D31; 13 lb D35; 8.5 lb D25;	522F3C 522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2CGF 522C2CS 422C2CS 422C2CS+2C 422C2NG+2C 422C2NG+2C 422C2CS+2C 422C2CGF 522C2CGF 522C2CGF 522C2CGF 522C2CGF 522C2CGF 522C2CGF 522C2CGF 522C2CGF 522C2CGF 522C2CGF 522C2CGF 522C2CGF 522C2CGF 522C2CGF 522C2CGF	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D252F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft anon-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft-1 flat 5 short bodies, 25.5" shaft-1 flat 6 short bodies, 25.5" shaft-1 flat 7 short bodies, 25.5" shaft-1 flat 8 short bodies, 25.5" shaft-1 flat 9 short bodies, 25.5" shaft-1 flat 1 short bodies, 25.5" shaft-1 flat 1 short bodies, 25.5" shaft-1 flat 1 short bodies, 25.5" shaft-1 flat 2 short bodies, 25.5" shaft-1 flat 3 short bodies, 25.5" shaft-1 flat 4 short bodies, 25.5" shaft-1 flat 5 short bodies, 25.5" shaft-1 flat 7 short bodies, 25.5" shaft-1 flat 8 short bodies, 25.5" shaft-1 flat 9 short bodies, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2522FD SHA25219FD SHA2519FD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA2522CDN4 SHA252CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (42.45.55" wide bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2.5" dia. SINGLE body rollers 2.5" wide grooved (1" spacing) Urethane no flats 2.5" wide grooved (1" spacing) Urethane no flats	11 lb D25; 12 lb D25; 11 lb D25; 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 6.7 lb D25; 11.5 lb D25; 12 lb D31; 13 lb D31; 13 lb D31; 13 lb D31; 13 lb D35; 8.5 lb D25; 8.5 lb D25; 8 lb D25; 8 lb D25; 12 lb D25; 8 lb D25;	522F3C 522F3C 522F3S 522F3CG_22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2CGF 522C2C 522C2C 122C2C4+2C 122C2C4+2C 122C2C+2C 122C2C5+2S 522C2CG4 522C2CG4 522C2CG4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG 22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.25" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 4 short bodies, 25.5" shaft-1 flat 5 short bodies, 25.5" shaft-1 flat 6 short bodies, 25.5" shaft-1 flat 7 sh	SHA2522FD SHA2522FD SHA2522FD SHA25219FD SHA2519FD SHA2519FD SHA2522CD SHA2522CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA2522CDN4 SHA2522CD SHA2522CD
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2.5" dia. SINGLE body rollers 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane	11 lb D25; 12 lb D25; 11 lb D25; 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 11.5 lb D25; 12 lb D31; 13 lb D31; 13 lb D31; 13 lb D31; 13 lb D35; 8.5 lb D25; 8.5 lb D25; 8.5 lb D25; 8 lb D25; 12 lb D25; 12 lb D25; 15 lb D25; 16 lb D25; 17 lb D25; 18 lb D25; 19 lb D25; 19 lb D25; 10 D25; 11 lb D25; 11 lb D25; 12 lb D25; 12 lb D25; 13 lb D25; 14 lb D25; 15 lb D25; 16 lb D25; 17 lb D25; 18 lb D25; 18 lb D25; 18 lb D25; 19 lb D25; 19 lb D25;	522F3C 522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2NGF 522C2C 522C2C 122C2C4-2C 122C2C4-2C 122C2C+2C 122C2S+2S 522C2CG4 522C2NG4 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG6 522C2CGG6 522C2CGG6 522C2CSGG6 522C2CSGG6 522C2CSGG6 522C2CSCG	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.45" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 4 short bodies, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2522FD SHA25219FD SHA2519FD SHA2519FD SHA2522CD SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CD SHA2522CD SHA2522CD SHA2522CD
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" marrow grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2 " smooth Urethane (4x5.55" wide bodies) 5 " wide grooved Urethane (4x5.55" wide bodies) 5 " smooth Urethane (4x5.55" wide bodies) 5 " smooth Urethane (4x5.55" wide bodies) 5 " smooth Urethane (4x5.55" wide bodies) 5 " wide grooved (1/2" spacing) Urethane no flats 5 " smooth Urethane 6 " smooth U	11 lb D25; 12 lb D25; 11 lb D25; 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 11.5 lb D25; 12 lb D31; 12 lb D31; 13 lb D31; 13 lb D31; 13 lb D35; 8.5 lb D25; 9.5 lb D25;	522F3C 522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2NGF 522C2C 522C2C 122C2C4-2C 122C2C4-2C 122C2C+2C 122C2S+2S 522C2CG4 522C2NG4 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG4 522C2CGG6 522C2CGG6 522C2CGG6 522C2CSGG6 522C2CSGG6 522C2CSGG6 522C2CSCG	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.45" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.5" center body + 2 short outer bodies, 31.5" shaft 4 short bodies, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2522FD SHA25219FD SHA2519FD SHA2519FD SHA2522CD SHA2522CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA2522CDN4 SHA2522CD SHA2522CD
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" marrow grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2.5" dia. SINGLE body rollers 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1" spacing) Urethane no flats 2.5" smooth Steel To diminish instances of shadowing lines due to overlap of	11 lb D25: 12 lb D25: 11 lb D25: 6.5 lb D25: 6.7 lb D25: 6.7 lb D25: 11.5 lb D25: 12 lb D31: 13 lb D31: 13 lb D31: 13 lb D31: 13 lb D35: 8.5 lb D25: 9.5 lb D25:	522F3C 522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2NG 522C2CGF 522C2C 522C2C 122C2CG+2C 122C2CH2C 122C2CH4 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CGF4	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D252F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.45" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft anon-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.5" body, 25.5" shaft-1 flat 23.5" body, 25.5" shaft-1 flat 24.5" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2522FD SHA2519FD SHA2519FD SHA2522CD SHA2522CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CD
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Urethane (22.2.5" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2.5" dia. SINGLE body rollers 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel To diminish instances of shadowing lines due to overlap of 2.5" grooved Urethane with 2.2" wide smooth ends	11 lb D25; 12 lb D25; 11 lb D25; 11 lb D25; 11 lb D25; 11 lb D25; 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 6.7 lb D25; 11.5 lb D25; 12 lb D31; 13 lb D31; 13 lb D31; 13 lb D31; 13 lb D35; 8.5 lb D25; 8.5 lb D25; 8.5 lb D25; 12 lb D25; 12 lb D25; 12 lb D25; 13 lb D25; 14 lb D25; 15 lb D25; 16 lb D25; 17 lb D25; 18 lb D25; 19 lb D25; 19 lb D25; 10 lb D25; 11 lb D25; 12 lb D25; 12 lb D25; 14 lb D25; 15 lb D25; 16 lb D25; 17 lb D25; 18 lb D25; 19 lb D25; 11 lb D25; 11 lb D25; 12 lb D25; 15 lb D25; 16 lb D25; 17 lb D25; 18 lb D25;	522F3C 522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CGG 522C2NG 522C2NGF 522C2CGF 522C2CGF 522C2CS 122C2CG+2C 122C2C+2C 122C2C9A4 522C2CNG4 522C2CNG4 522C2CNG4 522C2CNGF4 522C2CNGF4 522C2CSAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.45" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.5" center body + 2 short outer bodies, 31.5" shaft 4 short bodies, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2522FD SHA25219FD SHA2519FD SHA2519FD SHA2522CD SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CD SHA2522CD SHA2522CD SHA2522CD
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (22.5" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2.5" dia. SINGLE body rollers 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane with 2.2" wide smooth ends 2.5" grooved Urethane with 2.2" wide smooth ends 2.5" smooth Urethane 3.5" smooth Urethane with 2.2" wide smooth ends 3" smooth Urethane	11 lb D25: 12 lb D25: 11 lb D25: 6.5 lb D25: 6.7 lb D25: 6.7 lb D25: 11.5 lb D25: 12 lb D31: 13 lb D31: 13 lb D31: 13 lb D31: 13 lb D35: 8.5 lb D25: 9.5 lb D25:	522F3C 522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CGG 522C2NG 522C2NGF 522C2CGF 522C2CGF 522C2CS 122C2CG+2C 122C2C+2C 122C2C9A4 522C2CNG4 522C2CNG4 522C2CNG4 522C2CNGF4 522C2CNGF4 522C2CSAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG 522C2SAG	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D252F3CG .22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.45" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft anon-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2522FD SHA2521PD SHA2519FD SHA2519FD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CDN4 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA252CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Urethane (22.2.5" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2.5" dia. SINGLE body rollers 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel To diminish instances of shadowing lines due to overlap of 2.5" grooved Urethane with 2.2" wide smooth ends	11 lb D25; 12 lb D25; 11 lb D25; 11 lb D25; 11 lb D25; 11 lb D25; 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 6.7 lb D25; 11.5 lb D25; 12 lb D31; 13 lb D31; 13 lb D31; 13 lb D31; 13 lb D35; 8.5 lb D25; 8.5 lb D25; 8.5 lb D25; 12 lb D25; 12 lb D25; 12 lb D25; 13 lb D25; 14 lb D25; 15 lb D25; 16 lb D25; 17 lb D25; 18 lb D25; 19 lb D25; 19 lb D25; 10 lb D25; 11 lb D25; 12 lb D25; 12 lb D25; 14 lb D25; 15 lb D25; 16 lb D25; 17 lb D25; 18 lb D25; 19 lb D25; 11 lb D25; 11 lb D25; 12 lb D25; 15 lb D25; 16 lb D25; 17 lb D25; 18 lb D25;	522F3C 522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2CGF 522C2CS 122C2CG+2C 122C2CH-2C 122C2C+2C 122C2CS+2S 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CG4 522C2CGF4 522C2CFC 522C2CFC 522C2CFC	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D252F3CG .22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.45" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft anon-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2522FD SHA2521PD SHA2519FD SHA2519FD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CDN4 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA252CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 2 bodies 2" smooth Urethane (42.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2.5" dia. SINGLE body rollers 2.5" wide grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3 "SINGLE body rollers 3 dia. SINGLE body rollers	11 lb D25: 12 lb D25: 11 lb D25: 6.5 lb D25: 6.7 lb D25: 6.7 lb D25: 11.5 lb D25: 12 lb D31: 13 lb D31: 13 lb D31: 13 lb D31: 13 lb D35: 8.5 lb D25: 8.5 lb D25: 8 lb D25: 12 lb D25: 12 lb D25: 15 lb D25: 15 lb D25: 16 lb D25: 17 lb D25: 18 lb D25: 19 lb D25: 19 lb D25: 10 lb D25: 11 lb D25: 11 lb D25: 12 lb D25: 12 lb D25: 15 lb D25: 16 freels 15 lb D25: 16 lb D25: 17 lb D25: 18 lb D25:	522F3C 522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2NGF 522C2CGF 522C2C 122C2CG+2C 122C2CH-2C 122C2C+2C 122C2CS+2S 522C2CG4 522C2CGF4 522C2CGG-2CCG 522C2SCG-2CCCG-2CCC 519C2SC	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG 22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.25" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft anon-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 2	SHA2522FD SHA2522FD SHA2522FD SHA25219FD SHA2519FD SHA2519FD SHA2522CD SHA2522CDN4 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CD SHA2519CD
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" vide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2.5" dia. SINGLE body rollers 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel To diminish instances of shadowing lines due to overlap of 2.5" grooved Urethane 3" dia. SINGLE body rollers 3" grooved Urethane 3" dia. SINGLE body rollers 3" grooved Urethane 3" dia. SINGLE body rollers 3" grooved Urethane 3" dia. SINGLE body rollers	11 lb D25; 12 lb D25; 11 lb D25; 6.5 lb D25; 6.7 lb D25; 6.7 lb D25; 11.5 lb D25; 12 lb D31; 13 lb D25; 8.5 lb D25; 12 lb D25; 12 lb D25; 15 lb D25; 16 lb D25; 17 lb D25; 18 lb D25; 19 lb D25; 11 lb D25; 11 lb D25; 12 lb D25; 12 lb D25; 15 lb D25; 16 lb D25; 17 lb D25; 18 lb D25; 19 lb D25; 11 lb D25; 11 lb D25; 12 lb D25; 12 lb D25; 12 lb D25; 13 lb D25; 14 lb D25; 15 lb D25; 16 lb D25; 17 lb D25; 18 lb D25; 19 lb D25; 19 lb D25; 11 lb D25; 12 lb D25; 11 lb D25;	522F3C 522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2NG 522C2CGF 522C2CS 122C2CG+2C 122C2CG+2C 122C2CG+2C 122C2CGF4 522C2NG4 522C2CGF4 522C2NG4 522C2CGF4 522C2CGG 522C2CGG 522C2CGC 522C2SCG 522C2SCG 522C2SCG 522C3CG 522C3CG	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D252F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.45" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft anon-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.5" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2522FD SHA2519FD SHA2519FD SHA2519FD SHA2519FD SHA2522CD SHA2522CDN4 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3.5" smoo	11 lb D25: 12 lb D25: 11 lb D25: 6.5 lb D25: 6.7 lb D25: 6.7 lb D25: 6.7 lb D25: 11.5 lb D25: 12 lb D31: 13 lb D31: 13 lb D31: 13 lb D31: 13 lb D25: 8.5 lb D25: 8.5 lb D25: 8.5 lb D25: 8.5 lb D25: 9.5 lb D25: 9.5 lb D25: 9.5 lb D25: 9.5 lb D25: 12 lb D25: 14 lb D25: 15 reels	522F3C 522F3C 522F3S 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2CGF 522C2CS 422C2CG+2C 422C2NG+2C 422C2NG+2C 422C2NG+2C 422C2CG4 522C2CG4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CSCG 522C2SA 522C2SCG 522C2SCG 522C2SCG 522C2SCG 522C2SCG 522C2SCG 522C2SCG 522C2SCG 522C2SCG 522C2SCG 522C2SCG 522C2SCG 522C2SCG 522C2SCG 522C2SCG 522C2SCG 522C3CG 522C3CG 522C3CG 522C3CG 522C3CG 522C3CG 522C3CG 522C3CG 522C3CG 522C3CG 522C3CG 522C3CG	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D2522F3CG 22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.25" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft 22.55" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" shaft-1 flat 4 short bodies, 25.5" shaft-1 flat 4 short bodies, 25.5" shaft-1 flat 4 short bodies, 25.5" shaft-1 flat 22.45" body, 25.5" shaf	SHA2522FD SHA2522FD SHA2522FD SHA2521FD SHA2519FD SHA2519FD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA2522CD SHA252CD SHA252CD SHA252CDN4 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA3122CDN+2 SHA252CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CD SHA252CD
3" grooved Urethane no flats 3" smooth Steel To diminish instances of shadowing lines due to overlap of 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane John Deere 22" 7500/ 8500 & 6700/7700/ 8700 PRECISION CUT & E-Cl Rollers for QA-5 reels (with 1 flat on 1 end of the shaft): 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 2" narrow grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" dia. THREE body rollers 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 4 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2" vide grooved Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 1" flats 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 2.5" dia. SINGLE body rollers 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel To diminish instances of shadowing lines due to overlap of 2.5" grooved Urethane 3" dia. SINGLE body rollers 3" grooved Urethane 3" dia. SINGLE body rollers 3" grooved Urethane 3" dia. SINGLE body rollers 3" grooved Urethane 3" dia. SINGLE body rollers	11 lb D25: 12 lb D25: 11 lb D25: 6.5 lb D25: 6.7 lb D25: 6.7 lb D25: 6.7 lb D25: 11.5 lb D25: 12 lb D31: 13 lb D31: 13 lb D31: 13 lb D31: 13 lb D25: 8.5 lb D25: 8.5 lb D25: 8.5 lb D25: 8.5 lb D25: 9.5 lb D25: 9.5 lb D25: 9.5 lb D25: 9.5 lb D25: 12 lb D25: 14 lb D25: 15 reels	522F3C 522F3C 522F3CG.22C 519F3C QA5 & QA7 reels) 522C2CG 522C2NG 522C2NGF 522C2CS 122C2CG+2C 122C2CH-2C 122C2CH-2C 122C2C+2C 122C2CS+2S 522C2CG4 522C2CG4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CGF4 522C2CSG-2CCC 522C2SNG 522C2SNG 522C2SNG 522C2SNG 522C2SCG-22C 519C2SC	22.45" body, 25.5" shaft-2 flats on 1 end 2 flats on 1 end of shaft call for proper application specifics front roller for rear mower heads-use with D2519F3C back roller for rear mower heads-use with D252F3CG.22C (Sectional rollers with 4 bodies also available) 22.45" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.25" body, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.45" center body + 2 short outer bodies, 31.5" shaft 22.45" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft 22.25" center body + 2 short outer bodies, 31.5" shaft anon-skidding for tight turns & ground undulations 4 short bodies, 25.5" shaft-1 flat 22.45" body, 25.5" shaft-1 flat 22.5" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD SHA2522FD SHA2521FD SHA2519FD SHA2519FD SHA2519FD SHA2522CD SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CDN4 SHA2522CD SHA252CD SHA252CD SHA252CD SHA2522CD



Roll	ers for QA-7 reels (with 2 flats on 1 end of the shaft):			
	2" dia. SINGLE body rollers		4 STHERM TO VIOLETANT WITH A SECURIT	999999777777
	2" wide grooved Urethane no flats	6.5 lb D2522F2CG	22,45" body, 25.5" shaft-2 flats	SHA2522FD
	2" narrow grooved Urethane no flats	6.7 lb D2522F2NG	22.45" body, 25.5" shaft-2 flats	SHA2522FD SHA2522FD
	2" wide grooved Urethane 1" flats	6.5 lb D2522F2CGF 6.7 lb D2522F2NGF	22.45" body, 25.5" shaft-2 flats 22.45" body, 25.5" shaft-2 flats	SHA2522FD SHA2522FD
	2" narrow grooved Urethane 1" flats 2" smooth Urethane	7.9 lb D2522F2NGF	22.25" body, 25.5" shaft-2 flats	SHA2522FD
	2" smooth Steel heavy (1/4" wall)	11.5 lb D2522F2S	22.25" body, 25.5" shaft-2 flats	SHA2522FD
	2" dia. THREE body rollers	11.0 10 020221 20	non-skidding for tight turns & ground undulations	
3 bodies	2" wide grooved Urethane (22.45" inner+2x2" outer bodies)	12 lb D3122F2CG+2C	22.45" center body + 2 short outer bodies, 31.5" shaft w/ 2 flats	SHA3122FDN+2
	2" narrow grooved Urethane (22.45" inner+2x2" outer bodies)	12 lb D3122F2NG+2C	22.45" center body + 2 short outer bodies, 31.5" shaft w/ 2 flats	SHA3122FDN+2
	2" smooth Urethane (22.45" inner+2x2" outer bodies)	13 lb D3122F2C+2C	22.25" center body + 2 short outer bodies, 31.5" shaft w/ 2 flats	SHA3122FDN+2
3 bodies	2" smooth Steel heavy (22.25" inner+2x2" outer bodies)	13 lb D3122F2S+2S	22.25" center body + 2 short outer bodies, 31.5" shaft w/ 2 flats	SHA3122FDN+2
	2" dia. FOUR body rollers		non-skidding for tight turns & ground undulations	
4 bodies	2" wide grooved Urethane (4x5.55" wide bodies) no flats	8.5 lb D2522F2CG4	4 short bodies, 25.5" shaft-2 flats	SHA2522FDN4
	2" narrow grooved Urethane (4x5.55" wide bodies) no flats	8.5 lb D2522F2NG4	4 short bodies, 25.5" shaft-2 flats	SHA2522FDN4
4 bodies	2" wide grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb D2522F2CGF4	4 short bodies, 25.5" shaft w/ 2 flats	SHA2522FDN4
	2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb D2522F2NGF4	4 short bodies, 25.5" shaft w/ 2 flats	SHA2522FDN4
	2" smooth Urethane (4x5.55" wide bodies)	8 lb D2522F2C4	4 short bodies, 25.5" shaft w/ 2 flats	SHA2522FDN4
4 bodies	2" smooth steel heavy (4x5.55" wide bodies)	12 lb D2522F2S4	4 short bodies, 25.5" shaft w/ 2 flats	SHA2522FDN4
	2.5" dia. SINGLE body rollers	9 E IL D252252500	non-skidding for tight turns & ground undulations	SHA2522FD
	2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats	8.5 lb D2522F25CG 8.5 lb D2522F25NG	22.45" body, 25.5" shaft w/ 2 flats 22.45" body, 25.5" shaft-1 flat	SHA2522FD SHA2522FD
	2.5" smooth Urethane	9.5 lb D2522F25NG	22.45" body, 25.5" shaft w/ 2 flats	SHA2522FD SHA2522FD
	2.5" smooth Steel	9.2 lb D2522F25S	22.25" body, 25.5" shaft w/ 2 flats	SHA2522FD
	To diminish instances of shadowing lines due to overlap		call for proper application specifics	OT PLEASE IS
	2.5" grooved Urethane with 2.2" wide smooth ends	8.5 lb D2522F25CG.22C	front roller for rear mower heads-use with D2519F25C	SHA2522FD
	2.5" smooth Urethane	9.5 lb D2519F25C	back roller for rear mower heads-use with D2522F25CG.22C	SHA2519FD
	3" dia. SINGLE body rollers	2.0 10 220 31 200		
	3" grooved Urethane no flats	9.5 lb D2522F3CG	22.45" body, 25.5" shaft w/ 2 flats	SHA2522FD
	3" smooth Urethane	12 lb D2522F3C	22.45" body, 25.5" shaft w/ 2 flats	SHA2522FD
	3" smooth Steel	11.5 lb D2522F3S	22.25" body, 25.5" shaft w/ 2 flats	SHA2522FD
	To diminish instances of shadowing lines due to overlap	of reels	call for proper application specifics	
	3" grooved Urethane with 2.2" wide smooth ends	9.5 lb D2522F3CG.22C	front roller for rear mower heads-use with D2519F3C	SHA2522FD
	3" smooth Urethane	11 lb D2519F3C	back roller for rear mower heads-use with D2522F3CG.22C	SHA2519FD
John	Deere 18" 8000A & 6080A PRECISION CUT & E-CUT FAIRWAY	- FRONT & BACK ROLLERS		
	2" dia. SINGLE body rollers 2" smooth Urethane	7.5 lb D2218A2C	18.0" body, 22" shaft	SHA2218AD
	2" smooth Steel heavy (1/4" wall)	10.5 lb D2218A2S	18.0" body, 22" shaft	SHA2218AD
	2" smooth Steel heavy (1/4" wall)	9 lb D2216A2S	16.0" body, 22" shaft	SHA2218AD
	2.5" dia. SINGLE body rollers	0 10 02210/120	Control to the Control of the Contro	
	2.5" grooved Urethane no flats	6.7 lb D2218A25CG	18.2" body, 22" shaft	SHA2218AD
	2.5" smooth Urethane	7.5 lb D2218A25C	18.2" body, 22" shaft	SHA2218AD
	2.5" smooth Urethane 2.5" smooth Steel	7.5 lb D2218A25C 9.2 lb D2218A25S	18.2" body, 22" shaft 18.0" body, 22" shaft	SHA2218AD SHA2218AD
new	2.5" smooth Steel			
new	2.5" smooth Steel 3" dia. SINGLE body rollers	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C	18.0" body, 22" shaft	SHA2218AD SHA2218CD SHA2218CD
new	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft	SHA2218AD SHA2218CD
new	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlaped	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft call for proper application specifics	SHA2218AD SHA2218CD SHA2218CD SHA2218CD
new	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlape 2.5" grooved Urethane with 2.2" wide smooth ends	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C	SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3
new	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the shadowing lines due to overlap overlap of the shadowing lines due to overlap	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2218A25CG.22C	SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD
new	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the shadowing lines due to overlap overlap of the shadowing lines due to overlap overlap of the shadowing lines due to overlap	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2218A3CG.22C	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A3C	SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD
	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlape 2.5" grooved Urethane with 2.2" wide smooth ends 2.5" smooth Urethane 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2218A3CG.22C 7 lb D2215A3C	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2218A25CG.22C front roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2215A3C	SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2218AD SHA2215AD
	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlaped 2.5" grooved Urethane with 2.2" wide smooth ends 2.5" smooth Urethane 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane Deere 26" 8900A, 7200, 2653 +A/B FAIRWAY - FRONT & BAC	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2218A3CG.22C 7 lb D2215A3C	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A3C	SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD
	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlape 2.5" grooved Urethane with 2.2" wide smooth ends 2.5" smooth Urethane 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2218A3CG.22C 7 lb D2215A3C	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2218A25CG.22C front roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2215A3C	SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD
	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the smooth Urethane with 2.2" wide smooth ends 2.5" grooved Urethane with 2.2" wide smooth ends 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane Deere 26" 8900A, 7200, 2653 +A/B FAIRWAY - FRONT & BACC 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2218A3CG.22C 7 lb D2215A3C KROLLERS (QA-7 reels)	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft 18.25" body, 22" shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2218A3CG.22C (2.5" diameter also availal 26.45" body, 29.75" shaft-2 flats on 1 end 26.45" body, 29.75" shaft-2 flats on 1 end	SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD
	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the shadowin	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2218A3CG.22C front roller for rear mower heads-use with D2218A3CG.22C (2.5" diameter also availal 26.45" body, 29.75" shaft-2 flats on 1 end	SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2215AD
John	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the shadowin	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG,22C 7 lb D2215A25C 6.8 lb D2218A3CG,22C 7 lb D2215A3C K ROLLERS (QA-7 reels) 11.1 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3S	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft 18.25" body, 22" shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2218A25CG.22C front roller for rear mower heads-use with D2218A3CG acc cache roller for rear mower heads-use with D2218A3CG acc (2.5" diameter also availal 26.45" body, 29.75" shaft-2 flats on 1 end 26.25" body, 29.75" shaft-2 flats on 1 end	SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2215AD
John 2 bodier	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlape 2.5" grooved Urethane with 2.2" wide smooth ends 2.5" smooth Urethane 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane Deere 26" 8900A, 7200, 2653 +A/B FAIRWAY - FRONT & BAC 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane (2x4" wide bodies)	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG,22C 7 lb D2215A25C 6.8 lb D2218A3CG,22C 7 lb D2215A3C K ROLLERS (QA-7 reels) 11.1 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3S 6 lb D2904F3Ct	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft 18.25" body, 22" shaft 18.25" body, 22" shaft 18.25" body, 22" shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2218A25CG.22C front roller for rear mower heads-use with D2218A3CG back roller for rear mower heads-use with D2218A3CG.22C (2.5" diameter also availal 26.45" body, 29.75" shaft-2 flats on 1 end 26.25" body, 29.75" shaft-2 flats on 1 end non-striping, non-skidding for tight turns & ground und 2 short twin bodies at ends of a 29.75" shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2926FD SHA2926FD SHA2926FD
John 2 bodier	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlape 2.5" grooved Urethane with 2.2" wide smooth ends 2.5" smooth Urethane 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane Deere 26" 8900A, 7200, 2653 +A/B FAIRWAY - FRONT & BAC 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane (2x4" wide bodies) 3" smooth Urethane (2x5.2" wide bodies)	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG,22C 7 lb D2215A25C 6.8 lb D2218A3CG,22C 7 lb D2215A3C K ROLLERS (QA-7 reels) 11.1 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3S	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A25CG.22C front roller for rear mower heads-use with D2215A3CG.22C front roller for rear mower heads-use with D2218A2GG.22C (2.5" diameter also availal 26.45" body, 29.75" shaft-2 flats on 1 end 26.45" body, 29.75" shaft-2 flats on 1 end 26.25" body, 29.75" shaft-2 flats on 1 end 26.25" body, 29.75" shaft-2 flats on 1 end 27.50" available turns a ground und 28.50" body 29.75" shaft-27.50" shaft-27.50 flats on 1 end 29.75" shaft-27.50" shaft-27.50" shaft-27.50 flats on 1 end 29.75" shaft-27.50" shaft-27.50" shaft-27.50 flats on 1 end 29.75" shaft-27.50" sha	SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2215AD
John 2 bodies 2 bodies	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the shadow	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2215A25C 6.8 lb D2215A3CG.22C 7 lb D2215A3CG.22C T lb D2215A3C K ROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 6.5 lb D2904F3Ct 6.5 lb D2905F3Ct	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft 18.25" body, 22" shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2218A3CG.22C front roller for rear mower heads-use with D2218A3CG.22C (2.5" diameter also availal 26.45" body, 29.75" shaft-2 flats on 1 end 26.25" body, 29.75" shaft-2 flats on 1 end 26.25" body, 29.75" shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75" shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75" shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75" shaft-2 flats on 1 end non-skidding for tight turns & ground undulations	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2904FD Ulations SHA2904FDNt
John 2 bodies 2 bodies 4 bodies	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the steel of the shadowing lines due to overlap ov	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG,22C 7 lb D2215A25C 6.8 lb D2218A3CG,22C 7 lb D2215A3C K ROLLERS (QA-7 reels) 11.1 lb D2926F3C 13.5 lb D2926F3C	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft 18.25" body, 22" shaft 18.25" body, 22" shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2218A25CG.22C front roller for rear mower heads-use with D2218A3CG.22C (2.5" diameter also availal 26.45" body, 29.75" shaft-2 flats on 1 end 26.45" body, 29.75" shaft-2 flats on 1 end 26.25" body, 29.75" shaft-2 flats on 1 end 28.25" body, 29.75" shaft-2 flats on 1 end 29.55" shaft-2 flats on 1 end 29.55" shaft-2 flats on 1 end 29.55" shaft-2 flats on 1 end 29.75" shaft-2 flats on 1 end 30.75" shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2215AD ble) SHA2926FD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2926FDN4
John 2 bodie: 2 bodie: 4 bodie: 4 bodie: 4 bodie:	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the steel of the shadowing lines due to overlap ov	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG,22C 7 lb D2215A25C 6.8 lb D2218A3CG,22C 7 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2905F3Ct 6.5 lb D2905F3Ct 12.5 lb D2926F3CG4 13.5 lb D2926F3CG4	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft 18.25" body, 22" shaft 18.25" body, 22" shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2218A3CG.22C (2.5" diarmeter also availal 26.45" body, 29.75" shaft-2 flats on 1 end 26.45" body, 29.75" shaft-2 flats on 1 end 26.25" body, 29.75" shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75" shaft-2 flats on 1 end non-skidding for tight turns & ground undulations 4 short bodies, 29.75" shaft-2 flats on 1 end 4 short bodies, 29.75" shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA2926FDN4
John 2 bodie: 2 bodie: 4 bodie: 4 bodie: 4 bodie:	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the shadowing lines and shadowing lines are shadowing lines and shadowing lines due to overlap of the shadowing lines due to overlap of the shadowing lines are shadowing lines due to overlap of the shadowing lines due to overla	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG,22C 7 lb D2215A25C 6.8 lb D2218A3CG,22C 7 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2905F3Ct 6.5 lb D2905F3Ct 12.5 lb D2926F3CG4 13.5 lb D2926F3CG4	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft 18.25" body, 22" shaft 18.25" body, 22" shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2218A25CG.22C front roller for rear mower heads-use with D2218A3CG.22C (2.5" diameter also availal 26.45" body, 29.75" shaft-2 flats on 1 end 26.45" body, 29.75" shaft-2 flats on 1 end 26.25" body, 29.75" shaft-2 flats on 1 end 28.25" body, 29.75" shaft-2 flats on 1 end 29.55" shaft-2 flats on 1 end 29.55" shaft-2 flats on 1 end 29.55" shaft-2 flats on 1 end 29.75" shaft-2 flats on 1 end 30.75" shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA2926FDN4
John 2 bodie: 2 bodie: 4 bodie: 4 bodie: 4 bodie:	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the steel of the shadowing lines due to overlap ov	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG,22C 7 lb D2215A25C 6.8 lb D2218A3CG,22C 7 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2905F3Ct 6.5 lb D2905F3Ct 12.5 lb D2926F3CG4 13.5 lb D2926F3CG4	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft 18.25" body, 22" shaft 18.25" body, 22" shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2218A3CG.22C (2.5" diarmeter also availal 26.45" body, 29.75" shaft-2 flats on 1 end 26.45" body, 29.75" shaft-2 flats on 1 end 26.25" body, 29.75" shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75" shaft-2 flats on 1 end non-skidding for tight turns & ground undulations 4 short bodies, 29.75" shaft-2 flats on 1 end 4 short bodies, 29.75" shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA2926FDN4
John 2 bodie: 2 bodie: 4 bodie: 4 bodie: 4 bodie:	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlape of the steel of the shadowing lines due to overlape of the shadowing lines due to overlape of the shadowing	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2215A3C K ROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 4.5 lb D2905F3Ct 12.5 lb D2926F3C4 K ROLLERS (QA-7 reels)	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A25C front roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2218A25CG.22C (2.5" diameter also availal 26.45° body, 29.75° shaft-2 flats on 1 end 26.45° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end non-skidding for tight turns & ground undulations 4 short bodies, 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end (2.5" diameter also availal	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA2926FDN4
John 2 bodie: 2 bodie: 4 bodie: 4 bodie: 4 bodie:	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlape of the steel of the shadowing lines due to overlape of the shadowing lines due to overlape of the s	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 4.5 lb D2926F3C 4.5 lb D2926F3C 4.7 lb D2926F3CG	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2218A3CG.22C (2.5" diameter also availal 26.45" body, 29.75" shaft-2 flats on 1 end 26.45" body, 29.75" shaft-2 flats on 1 end 28.25" body, 29.75" shaft-2 flats on 1 end 29.55" body, 29.75" shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75" shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75" shaft-2 flats on 1 end 4 short bodies, 29.75" shaft-2 flats on 1 end 4 short bodies, 29.75" shaft-2 flats on 1 end 4 short bodies, 29.75" shaft-2 flats on 1 end 29.45" body, 33.5" shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2904FDNd SHA2926FDNd SHA2926FDNd SHA2926FDNd SHA2926FDNd SHA2926FDNd SHA2926FDNd SHA2926FDNd SHA2926FDNd
John 2 bodie: 2 bodie: 4 bodie: 4 bodie: John	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the shadowing lines due	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3S 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG,22C 7 lb D2215A25C 6.8 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2905F3Ct 12.5 lb D2905F3Ct 12.5 lb D2926F3C4 KROLLERS (QA-7 reels) 11.1 lb D3329F3CG 13.5 lb D3329F3C 13.5 lb D3329F3C 13.5 lb D3329F3C	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft 18.25° body, 22° shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2218A25CG.22C front roller for rear mower heads-use with D2218A3CG.22C (2.5" diameter also availal 26.45° body, 29.75° shaft-2 flats on 1 end 26.45° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end non-skidding for tight turns & ground undulations 4 short bodies, 29.75° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.25° body, 33.5° shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218AD SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA3329FD SHA3329FD SHA3329FD SHA3329FD
John 2 bodiet 2 bodiet 4 bodiet John 5 bodiet	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the standard of the shadowing lines due to overlap of the standard of the shadowing lines due to overlap of the shadowing line	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG,22C 7 lb D2215A25C 6.8 lb D2218A3CG,22C 7 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2905F3Ct 12.5 lb D2905F3Ct 12.5 lb D2905F3Ct 13.5 lb D2926F3C4 KROLLERS (QA-7 reels) 11.1 lb D3329F3CG 13.5 lb D3329F3C 13.5 lb D3329F3C 13.5 lb D3329F3CG5	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft 18.25° body, 22° shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2218A25CG.22C front roller for rear mower heads-use with D2218A3CG.22C (2.5° diarmeter also availal 26.45° body, 29.75° shaft-2 flats on 1 end 26.45° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.25° body, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 29.5° body, 33.5° shaft-2 flats on 1 end 29.5° body, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218AD SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD Ulations SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA3329FD SHA3329FD SHA3329FD SHA3329FD
John 2 bodiet 2 bodiet 4 bodiet 4 bodiet John 5 bodiet 5 bodiet	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlape of the steel of the shadowing lines due to overlape of the steel of the shadowing lines due to overlape of the shadowing lines due to overlape of the shadowing lines of the shadowing lines due to overlape of the shadowing	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3CG 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 4.5 lb D3329F3C 4.5 lb D3329F3C 4.5 lb D3329F3C 5.5 lb D3329F3C 5.5 lb D3329F3C5 6.6 lb D3329F3C5	18.0" body, 22" shaft 18.45" body, 22" shaft 18.45" body, 22" shaft 18.25" body, 22" shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A25C front roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2216A3CG.22C (2.5" diameter also availal 26.45" body, 29.75" shaft-2 flats on 1 end 26.45" body, 29.75" shaft-2 flats on 1 end 26.25" body, 29.75" shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75" shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75" shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75" shaft-2 flats on 1 end 4 short bodies, 29.75" shaft-2 flats on 1 end 4 short bodies, 29.75" shaft-2 flats on 1 end 29.45" body, 33.5" shaft-2 flats on 1 end 29.45" body, 33.5" shaft-2 flats on 1 end 29.55" body, 33.5" shaft-2 flats on 1 end 29.25" body, 33.5" shaft-2 flats on 1 end 29.55" body, 33.5" shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218AD SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA3329FD SHA3329FD SHA3329FD SHA3329FD
John 2 bodiet 2 bodiet 4 bodiet 4 bodiet John 5 bodiet 5 bodiet	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlape of the steel of the shadowing lines due to overlape of the shadowing lines of the shadowing lines due to overlape of the	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3CG 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 4.5 lb D3329F3C 4.5 lb D3329F3C 4.5 lb D3329F3C 5.5 lb D3329F3C 5.5 lb D3329F3C5 6.6 lb D3329F3C5	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft 18.25° body, 22° shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2218A25CG.22C front roller for rear mower heads-use with D2218A3CG.22C (2.5° diarmeter also availal 26.45° body, 29.75° shaft-2 flats on 1 end 26.45° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.25° body, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 29.5° body, 33.5° shaft-2 flats on 1 end 29.5° body, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218AD SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD Ulations SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA3329FD SHA3329FD SHA3329FD SHA3329FD
John 2 bodiet 2 bodiet 4 bodiet 4 bodiet John 5 bodiet 5 bodiet	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the shadowing lines due	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218CA3C 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2215A25C 6.8 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 11.1 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3CG 13.5 lb D2926F3CG 13.5 lb D2926F3CG 13.5 lb D2926F3CG 13.5 lb D3329F3CG 13.5 lb D3329F3C 13.5 lb D3329F3C5 PTO GANG (2 styles)	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft 2all for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2218A3CG.22C (2.5" diameter also availal 26.45° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA3329FD SHA3329FD SHA3329FD SHA3329FD SHA3329FDN5 SHA3329FDN5
John 2 bodiet 2 bodiet 4 bodiet 4 bodiet John 5 bodiet 5 bodiet	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the shadowing lines due	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3CG 7.5 lb D2218C3S of reels 6.8 lb D2218A25CG,22C 7 lb D2215A25C 6.8 lb D2218A3CG,22C 7 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C4 KROLLERS (QA-7 reels) 11.1 lb D3329F3CG 13.5 lb D3329F3CG 13.5 lb D3329F3C 13.5 lb D3329F3C5 PTO GANG (2 styles) 13.5 lb D3229F3CG	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft 2all for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2218A3CG.22C (2.5° diameter also availal 26.45° body, 29.75° shaft-2 flats on 1 end 26.45° body, 29.75° shaft-2 flats on 1 end 28.25° body, 29.75° shaft-2 flats on 1 end 29.55° thaft-2 flats on 1 end 29.55° thaft-2 flats on 1 end 4 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end (2.5° diameter also availal 29.45° body, 33.5° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.25° body, 33.5° shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218AD SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA329FD SHA3329FD SHA3329FD SHA3329FD SHA3329FDN5 SHA3229FD
John 2 bodiet 2 bodiet 4 bodiet 4 bodiet John 5 bodiet 5 bodiet	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the shadowing lines due	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3S 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2215A3C C7 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C4 KROLLERS (QA-7 reels) 11.1 lb D3329F3CG 13.5 lb D3329F3C 13.5 lb D3329F3C 13.5 lb D3329F3C 13.5 lb D3329F3C5 14 lb D3329F3C5 PTO GANG (2 styles) 13.5 lb D3229F3CG 15 lb D3229F3CG	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft 2all for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2218A3CG.22C (2.5" diameter also availal 26.45° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA3329FD SHA3329FD SHA3329FD SHA3329FD SHA3329FDN5 SHA3329FDN5
John 2 bodiet 2 bodiet 4 bodiet 4 bodiet John 5 bodiet 5 bodiet	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlape of the steel of the shadowing lines due to overlape of the steel of the shadowing lines due to overlape of the shadowing	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3CG 7.5 lb D2218C3S of reels 6.8 lb D2218A25CG,22C 7 lb D2215A25C 6.8 lb D2218A3CG,22C 7 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C4 KROLLERS (QA-7 reels) 11.1 lb D3329F3CG 13.5 lb D3329F3CG 13.5 lb D3329F3C 13.5 lb D3329F3C5 PTO GANG (2 styles) 13.5 lb D3229F3CG	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft 2all for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2218A3CG.22C (2.5" diameter also availal 26.45° body, 29.75° shaft-2 flats on 1 end 26.45° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end non-skidding for tight turns & ground undulations 4 short bodies, 29.75° shaft-2 flats on 1 end (2.5" diameter also availal 29.45° body, 33.5° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end con-skidding for tight turns & ground undulations 5 short bodies, 33.5° shaft-2 flats on 1 end con-skidding for tight turns & ground undulations 5 short bodies, 33.5° shaft-2 flats on 1 end call to confirm roller options	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218AD SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA329FD SHA3329FD SHA3329FD SHA3329FD SHA3329FD SHA3229FD SHA3229FD SHA3229FD SHA3229FD
John 2 bodiet 2 bodiet 4 bodiet 4 bodiet John 5 bodiet 5 bodiet	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the shadowing lines due	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3CG 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 43.5 lb D2926F3C 13.5 lb D3329F3C 13.5 lb D3329F3C5 14 lb D3329F3C5 PTO GANG (2 styles) 13.5 lb D3229F3C 15 lb D3229F3C	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A25C front roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2216A25C g.22C front roller for rear mower heads-use with D2216A25C g.22C (2.5" diameter also availal 26.45° body, 29.75° shaft-2 flats on 1 end 26.45° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end non-skidding for tight turns & ground undulations 4 short bodies, 29.75° shaft-2 flats on 1 end (2.5" diameter also availal 29.45° body, 33.5° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.25° body, 33.5° shaft-2 flats on 1 end 29.25° body, 33.5° shaft-2 flats on 1 end 5 short bodies, 33.5° shaft-2 flats on 1 end 29.45° body, 32° shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA2926FDN4 SHA329FD SHA3329FD SHA3329FD SHA3329FD SHA3329FD SHA3329FD SHA3229FD
John 2 bodiet 2 bodiet 4 bodiet 4 bodiet John 5 bodiet 5 bodiet	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlape of the steel of	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3CG 7.5 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2215A25C 6.8 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 4.5 lb D2926F3C 4.5 lb D2926F3C 4.5 lb D2926F3CG 13.5 lb D2926F3CG 13.5 lb D2926F3CG 13.5 lb D2926F3CG 13.5 lb D3329F3C 13.5 lb D3229F3C 14 lb D3329F3C 15 lb D3229F3C	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft call for proper application specifics front roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2216A25CG.22C front roller for rear mower heads-use with D2216A3CG.22C (2.5" diameter also availal 26.45° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 2 sbort twin bodies at ends of a 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.25° body, 33.5° shaft-2 flats on 1 end 29.25° body, 33.5° shaft-2 flats on 1 end 29.45° body, 32° shaft-2 flats on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2904FDNt SHA2904FDNb SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN5 SHA3329FD SHA3329FD SHA3329FD SHA3229FD SHA3229FD
John 2 bodiet 2 bodiet 4 bodiet 4 bodiet John 5 bodiet 5 bodiet	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the state of smooth ends 2.5" grooved Urethane with 2.2" wide smooth ends 2.5" smooth Urethane 3" grooved Urethane with 2.2" wide smooth ends 3" smooth Urethane Deere 26" 8900A, 7200, 2653 +A/B FAIRWAY - FRONT & BACCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3CG 7.5 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2215A25C 6.8 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 43.5 lb D2926F3C4 KROLLERS (QA-7 reels) 11.1 lb D3329F3C 13.5 lb D3229F3C 15 lb D3229F3C	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft 28.5° body, 22° shaft 28.5° body, 22° shaft 28.6° body, 22° shaft 29.6° body, 22° shaft 29.6° body, 22° shaft 29.6° body, 29.75° shaft-2 flats on 1 end 29.45° body, 29.75° shaft-2 flats on 1 end 20.5° body, 30.5° shaft-2 flats on 1 end 20.5° body, 33.5° shaft-2 flats on 1 end 20.5° body, 32° shaft-1 flat on 1 end 20.5° body, 32° shaft-1 flat on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2926FDN4 SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA3329FD SHA3329FD SHA3329FD SHA3329FD SHA3229FD SHA3229FD SHA3229FD SHA3229FD SHA3229FD SHA3229FD SHA3229AD SHA3229AD
John 2 bodie: 2 bodie: 4 bodie: 4 bodie: 5 bodie: 5 bodie: John	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the shadowing lines due	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3CG 7.5 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2215A25C 6.8 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 43.5 lb D2926F3C4 KROLLERS (QA-7 reels) 11.1 lb D3329F3C 13.5 lb D3229F3C 15 lb D3229F3C	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft 28.25° controller for rear mower heads-use with D2215A25C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2215A3C back roller for rear mower heads-use with D2218A3CG.22C (2.5° diarmeter also availal 26.45° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 26.25° body, 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 2 short twin bodies at ends of a 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end 4 short bodies, 29.75° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.45° body, 32° shaft-1 flat on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218ADN3 SHA2215AD SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2926FD SHA2926FDN4 SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA3329FD SHA3329FD SHA3329FD SHA3329FD SHA3229FD SHA3229FD SHA3229FD SHA3229FD SHA3229FD SHA3229FD SHA3229AD SHA3229AD
John 2 bodiet 2 bodiet 4 bodiet 4 bodiet 5 bodiet 5 bodiet John	2.5" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel To diminish instances of shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the steel of the shadowing lines due to overlap of the shadowing lines due	9.2 lb D2218A25S 6.6 lb D2218C3CG 7.5 lb D2218C3CG 7.5 lb D2218C3S 9.2 lb D2218C3S of reels 6.8 lb D2218A25CG.22C 7 lb D2215A25C 6.8 lb D2218A3CG.22C 7 lb D2215A3C KROLLERS (QA-7 reels) 11.1 lb D2926F3CG 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C 13.5 lb D2926F3C4 KROLLERS (QA-7 reels) 11.1 lb D3329F3CG 13.5 lb D3329F3CG 13.5 lb D3329F3C 13.5 lb D3229F3C 15 lb D3229A3C 15 lb D3229A3C 15 lb D3229A3C	18.0° body, 22° shaft 18.45° body, 22° shaft 18.45° body, 22° shaft 18.25° body, 22° shaft 28.25° body, 29.75° shaft-2 flats on 1 end 28.45° body, 29.75° shaft-2 flats on 1 end 28.25° body, 29.75° shaft-2 flats on 1 end 29.45° body, 33.5° shaft-2 flats on 1 end 29.45° body, 32° shaft-1 flat on 1 end 29.25° body, 32° shaft-1 flat on 1 end	SHA2218AD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218CD SHA2218AD SHA2215AD SHA2215AD SHA2215AD SHA2926FD SHA2926FD SHA2904FDNt SHA2904FDNt SHA2904FDNt SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA2926FDN4 SHA329FD SHA3329FD SHA3329FD SHA3329FD SHA3229FD SHA3229FD SHA3229PD SHA3229PD SHA3229AD SHA3229AD SHA3229AD SHA3229AD



John Deere 30" FAIRWAY (305, 303, 756 & 856) - ALL ROLLER		call to confirm roller options	
3" grooved Urethane no flats	13.5 lb D3229X3CG	29.45" body, 32.25" shaft5" dia. ends	SHA3229XD
3" smooth Urethane	15 lb D3229X3C	29.45" body, 32.25" shaft5" dia. ends	SHA3229XD
3" smooth Steel	15 lb D3229X3S	29.25" body, 32.25" shaft5" dia. ends	SHA3229XD
3" grooved Urethane no flats	13.5 lb D3029W3CG	29.45" body, 30" shaft-5/8" dia. ends & 7/16" taps	SHA3029WD
3" smooth Urethane	15 lb D3029W3C	29.45" body, 30" shaft-5/8" dia. ends & 7/16" taps	SHA3029WD
3" smooth Steel	15 lb D3029W3S	29.25" body, 30" shaft-5/8" dia. ends & 7/16" taps	SHA3029WD
ohn Deere ROTARY 22" 2653 WITH NUNS DECK - BACK ROLL			
3" smooth Urethane	11 lb D2522C3C	22.45" body, 25.5" shaft	SHA2522CD
3" smooth Steel	12 lb D2522C3S	22.25" body, 25.5" shaft	SHA2522CD
3.5" smooth Urethane	13.5 lb D2522C7C	22.45" body, 25.5" shaft	SHA2522CD
hn Deere ROTARY 30" 2653 WITH NUNS DECK - BACK ROLL	ER		
3" smooth Urethane	15 lb D3229N3C	22.45" body, 32" shaft	SHA3229ND
3" smooth Steel	15 lb D3229N3S	22.25" body, 32" shaft	SHA3229ND
3.5" smooth Urethane	18 lb D3229N7C	22.45" body, 32" shaft	SHA3229ND
hn Deere ROTARY DECK 8800 & 3245C - FRONT ROLLER (W	th two independent rolling 4" wide ro	oller bodies)	
odies 5" grooved Urethane (2x5.2" wide bodies) no flats	8 lb D2305A5CGt	2 short twin bodies at ends of 23" shaft-3 grooves per body	SHA2305ADNt
odies 5" smooth Urethane (2x4" wide bodies)	9.3 lb D2304A5Ct	2 short twin bodies at ends of 23" shaft	SHA2304ADNt
hn Deere ROTARY DECK 8800 & 3245C & 1565 - BACK ROLL	R (choose from multiple styles to m	atch your needs)	
3" dia. SINGLE body rollers			
3" grooved Urethane no flats	9.5 lb D2319B3CG	19.45" body, 23" shaft	SHA2319BD
3" smooth Urethane	11 lb D2319B3C	19.45" body, 23" shaft	SHA2319BD
3" smooth Steel	12 lb D2319B3S	19.25" body, 23" shaft	SHA2319BD
3" smooth Urethane	11.5 lb D2419B3C	19.45" body, 24" shaft	SHA2419BD
3" smooth Steel	11 lb D2419B3S	19.25" body, 24" shaft	SHA2419BD
3" smooth Urethane	12 lb D2522T3C	22.45" body, 25.87" shaft	SHA2522TD
3" smooth Steel	11.5 lb D2522T3C	22.25" body, 25.87" shaft	SHA2522TD
9 ign 5 i i 5 i 5 i 5 i 5 i 7 i 5 i 7 i 7 i 7	9.5 lb D2622A3CG		SHA2622AD
3" grooved Urethane no flats		22.45" body, 26.75" shaft	SHA2622AD
3" smooth Urethane	12 lb D2622A3C	22.45" body, 26.75" shaft	
3" smooth Steel	11.5 lb D2622A3S	22.25" body, 26.75" shaft	SHA2622AD
3" dia. TWO body rollers	0 W D0005D0000	non-striping, non-skidding for tight turns & ground u	
odies 3" grooved Urethane (2x5.2" wide bodies) no flats	8 lb D2305B3CGt	2 short twin bodies at ends of a 23" shaft	SHA2305BDNt
odies 3" smooth Urethane (2x4" wide bodies)	8 lb D2304B3Ct	2 short twin bodies at ends of a 23" shaft	SHA2304BDNt
odies 3" smooth Steel (2x4" wide bodies)	10 lb D2304B3St	2 short twin bodies at ends of a 23" shaft	SHA2304BDNt
3" dia. THREE body rollers		non-skidding for tight turns & ground undulations	
odies 3" grooved Urethane (3x5.2" wide bodies) no flats	11 lb D2319B3CG3	3 short bodies, 23" shaft	SHA2319BDN3
odies 3" smooth Urethane (3x5.2" wide bodies)	11 lb D2319B3C3	3 short bodies, 23" shaft	SHA2319BDN3
3.5" dia. SINGLE body rollers			
3.5" smooth Urethane	13.5 lb D2319B7C	19.45" body, 23" shaft	SHA2319BD
3.5" smooth Urethane	13.5 lb D2419B7C	19.45" body, 24" shaft	SHA2419BD
3.5" smooth Urethane	13.5 lb D2522T7C	22.45" body, 25.87" shaft	SHA2522TD
3.5" smooth Urethane	13.5 lb D2622A7C	22.45" body, 26.75" shaft	SHA2622AD
4" dia. SINGLE body rollers			
4" smooth Steel	20 lb D2319B4S	19.25" body, 23" shaft	SHA2319BD
4" smooth Steel	20 lb D2419B4S	19.25" body, 24" shaft	SHA2419BD
4" smooth Steel	20 lb D2522T4S	22.25" body, 25.87" shaft	SHA2522TD
4" smooth Steel	20 lb D2622A4S	22.25" body, 26.75" shaft	SHA2622AD
hn Deere ROTARY DECK 9009A & 7400A (2016 & newer) 27"			
odies 5" grooved Urethane (2x5.2" wide bodies)	12 lb D2905C5CGt	2 short twin bodies at ends of 29" shaft-3 grooves per body	SHA2905CDNt
odies 5" grooved Orethane (2x5.2" wide bodies)	13 lb D2905C5CGt	2 short twin bodies at ends of 29 shart-3 grooves per body 2 short twin bodies at ends of 29" shaft	SHA2905CDNt
		a short twill bodies at emas of 29. Shall	SHAZƏUDÜDINI
hn Deere ROTARY DECK 9009A & 7400A (2016 & newer) 27" (MI - BACK ROLLER		
3" dia. SINGLE body rollers	44 lb D0000000	20 45" hada 20" abati	CHIANNACA
3" grooved Urethane no flats	11 lb D2926C3CG	26.45" body, 29" shaft	SHA2926CD
3" smooth Urethane	12.5 lb D2926C3C	26.45" body, 29" shaft	SHA2926CD
3" smooth Steel	12.5 lb D2926C3S	26.25" body, 29" shaft	SHA2926CD
3" smooth Urethane	12.5 lb D2919C3C	19.45" body, 29" shaft	SHA2919CD
3" dia. TWO body rollers		non-striping, non-skidding for tight turns & ground u	
odies 3" grooved Urethane (2x5.2" wide bodies) no flats	10 lb D2905C3CGt	2 short twin bodies at ends of a 29" shaft	SHA2905CDN
odies 3" smooth Urethane (2x4" wide bodies)	10 lb D2904C3Ct	2 short twin bodies at ends of a 29" shaft	SHA2904CDN
odies 3" smooth Steel (2x4" wide bodies)	11 lb D2904C3St	2 short twin bodies at ends of a 29" shaft	SHA2904CDN
		non-skidding for tight turns & ground undulations	
3" dia. FOUR body rollers			
3" dia. FOUR body rollers	12 lb D2926C3CG4	4 short bodies, 29" shaft	SHA2926CDN
3" dia. FOUR body rollers odies 3" grooved Urethane (4x5.2" wide bodies) no flats	12 lb D2926C3CG4 12 lb D2926C3C4	4 short bodies, 29" shaft 4 short bodies, 29" shaft	
3" dia. FOUR body rollers odies 3" grooved Urethane (4x5.2" wide bodies) no flats odies 3" smooth Urethane (4x5.2" wide bodies)	12 lb D2926C3C4		
3" dia. FOUR body rollers odies 3" grooved Urethane (4x5.2" wide bodies) no flats odies 3" smooth Urethane (4x5.2" wide bodies) hn Deere ROTARY 7400 (pre-2016) DECK 27" cut - FRONT CA	12 lb D2926C3C4 STER	4 short bodies, 29" shaft.	SHA2926CDN
3" dia. FOUR body rollers odies 3" grooved Urethane (4x5.2" wide bodies) no flats odies 3" smooth Urethane (4x5.2" wide bodies) ohn Deere ROTARY 7400 (pre-2016) DECK 27" cut - FRONT CA 5" grooved Urethane (4" wide body)	12 lb D2926C3C4 STER 5 lb D0404G5CG2	4 short bodies, 29" shaft Shaft includes sleeves & bolts for mounting to fork	SHA2926CDN4 SHA0404GD
3" dia. FOUR body rollers odies 3" grooved Urethane (4x5.2" wide bodies) no flats odies 3" smooth Urethane (4x5.2" wide bodies) on Deere ROTARY 7400 (pre-2016) DECK 27" cut - FRONT CA 5" grooved Urethane (4" wide body) 5" smooth Urethane (4" wide body)	12 lb D2926C3C4 STER 5 lb D0404G5CG2 5 lb D0404G5C	4 short bodies, 29" shaft.	SHA2926CDN4
3" dia. FOUR body rollers odies 3" grooved Urethane (4x5.2" wide bodies) no flats odies 3" smooth Urethane (4x5.2" wide bodies) hn Deere ROTARY 7400 (pre-2016) DECK 27" cut - FRONT CA 5" grooved Urethane (4" wide body) 5" smooth Urethane (4" wide body) hn Deere ROTARY 7400 (pre-2016) DECK 27" cut - BACK ROL	12 lb D2926C3C4 STER 5 lb D0404G5CG2 5 lb D0404G5C LER	4 short bodies, 29" shaft Shaft includes sleeves & bolts for mounting to fork Shaft includes sleeves & bolts for mounting to fork	SHA0404GD SHA0404GD
3" dia. FOUR body rollers bodies 3" grooved Urethane (4x5.2" wide bodies) no flats bodies 3" smooth Urethane (4x5.2" wide bodies) bohn Deere ROTARY 7400 (pre-2016) DECK 27" cut - FRONT CA 5" grooved Urethane (4" wide body)	12 lb D2926C3C4 STER 5 lb D0404G5CG2 5 lb D0404G5C	4 short bodies, 29" shaft Shaft includes sleeves & bolts for mounting to fork	



for TORO mowers GREENSMOWERS - FRONT ROLLER: series 1000, 3, 300, 3000, 3050, 3100, 3150 (with 3/8" tap in shaft ends for ball stud) (Except TriFlex series without ball stud for basket yoke as follows: 3200, 3250, 3300, 3320, 3400, 3420 & FLEX 21) 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 6.5 lb T2522S2CG 22.45" body, 25.75" shaft-3/8" taps SHA2522ST 2" narrow grooved Urethane no flats 6.7 lb T2522S2NG 22.45" body, 25.75" shaft-3/8" taps SHA2522ST 2" wide grooved Urethane 1" flats 6.5 lb T2522S2CGF 22.45" body, 25.75" shaft-3/8" taps SHA2522ST 2" narrow grooved Urethane 1" flats 22.45" body, 25.75" shaft-3/8" taps SHA2522ST 6.7 lb T2522S2NGF 8 lb T2522S2C 22.25" body, 25.75" shaft-3/8" taps SHA2522ST 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 11.5 lb T2522S2S 22.25" body, 25.75" shaft-3/8" taps SHA2522ST 2" dia. TWO body rollers non-striping, non-skidding for tight turns & ground undulations SHA2504STNt 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 4 lb T2504S2CGt 2 short twin bodies at ends of a 25.75" shaft-3/8" taps 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 4 lb T2504S2NGt 2 short twin bodies at ends of a 25.75" shaft-3/8" taps SHA2504STNt 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 4 lb T2504S2CGFt 2 short twin bodies at ends of a 25.75" shaft-3/8" taps SHA2504STNt 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 4 lb T2504S2NGFt 2 short twin bodies at ends of a 25.75" shaft-3/8" taps SHA2504STNt 2 bodies 2" smooth Urethane (2x2" wide bodies) 4.2 lb T2502S2Ct 2 short twin bodies at ends of a 25.75" shaft-3/8" taps SHA2502STNt 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 4 lb T2504S2Ct SHA2504STNt 2 short twin bodies at ends of a 25.75" shaft-3/8" taps 2" dia. THREE body rollers non-skidding for tight turns & ground undulations 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 12 lb T3122S2CG+2C 22.45" center body +2 short outer bodies, 31.75" shaft-3/8" taps SHA3122STN+2 22.45" center body +2 short outer bodies, 31.75" shaft-3/8" taps SHA3122STN+2 3 bodies 2" narrow grooved Urethane (22.45" inner+2x2" outer bodies) 12 lb T3122S2NG+2C 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 13 lb T3122S2C+2C 22.25" center body +2 short outer bodies, 31.75" shaft-3/8" taps SHA3122STN+2 3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 22.25" center body +2 short outer bodies, 31.75" shaft-3/8" taps SHA3122STN+2 13 lb T3122S2S+2S 2" dia. FOUR body rollers non-skidding for tight turns & ground undulations 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 8.5 lb T2522S2CG4 SHA2522STN4 4 short bodies, 25.75" shaft-3/8" taps 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 4 short bodies, 25.75" shaft-3/8" taps 8.5 lb T2522S2NG4 SHA2522STN4 SHA2522STN4 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 8.5 lb T2522S2CGF4 4 short bodies, 25.75" shaft-3/8" taps 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 8.5 lb T2522S2NGF4 4 short bodies, 25,75" shaft-3/8" taps SHA2522STN4 4 bodies 2" smooth Urethane (4x5.55" wide bodies) 8.5 lb T2522S2C4 4 short bodies, 25.75" shaft-3/8" taps SHA2522STN4 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) 12 lb T2522S2S4 4 short bodies, 25.75" shaft-3/8" taps SHA2522STN4 2" dia. SIX body rollers non-skidding for tight turns & ground undulations 6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies) 13 lb T3122S2CG4+2C 4 center bodies + 2 short outer bodies, 31.75" shaft SHA3122STN4+2 6 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 13 lb T3122S2NG4+2C 4 center bodies + 2 short outer bodies, 31.75" shaft SHA3122STN4+2 6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats 13 lb T3122S2CGF4+2C 4 center bodies + 2 short outer bodies, 31.75" shaft SHA3122STN4+2 6 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats 13 lb T3122S2NGF4+2C 4 center bodies + 2 short outer bodies, 31.75" shaft SHA3122STN4+2 6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 13 lb T3122S2C4+2C 4 center bodies + 2 short outer bodies, 31.75" shaft SHA3122STN4+2 6 bodies 2" smooth Steel heavy (4x5.55" inner+2x2" outer bodies) 13 lb T3122S2S4+2C 4 center bodies + 2 short outer bodies, 31.75" shaft SHA3122STN4+2 2.5" dia. SINGLE body rollers 9 lb T2522S25CG SHA2522ST 2.5" wide grooved (1" spacing) Urethane no flats 22.45" body, 25.75" shaft-3/8" taps 22.45" body, 25.75" shaft-3/8" taps 2.5" narrow grooved (1" spacing) Urethane no flats 9 lb T2522S25NG SHA2522ST 2.5" smooth Urethane 9.5 lb T2522S25C 22.45" body, 25.75" shaft-3/8" taps SHA2522ST 2.5" smooth Steel 10 lb T2522S25S 22.25" body, 25.75" shaft-3/8" taps SHA2522ST non-striping, non-skidding for tight turns & ground undulations 2.5" dia. TWO body rollers 2 bodies 2.5" grooved Urethane (2x4.75" wide bodies) no flats 4 lb T2504S25CGt 2 short twin bodies at ends of a 25.75" shaft-3/8" taps SHA2504STNt 2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 4.2 lb T2504S25Ct 2 short twin bodies at ends of a 25.75" shaft-3/8" taps SHA2504STNt 2.5" dia. FOUR body rollers non-skidding for tight turns & ground undulations 4 bodies 2.5" grooved Urethane (4x5.55" wide bodies) no flats SHA2522STN4 10 lb T2522S25CG4 4 short bodies, 25.75" shaft-3/8" taps 4 bodies 2.5" smooth Urethane (4x5.55" wide bodies) 13 lb T2522S25C4 4 short bodies, 25.75" shaft-3/8" taps SHA2522STN4 SHA2522STN4 4 bodies 2.5" smooth Steel (4x5.55" wide bodies) 13 lb T2522S25S4 4 independent roller bodies @22.3" oal, shaft 2.5" dia. SIX body rollers non-skidding for tight turns & ground undulations SHA3122STN4+2 6 bodies 2.5" grooved Urethane (4x5.55" inner+2x2" outer bodies) 4 center bodies +2 short outer bodies, 31.75" shaft-38" taps 14 lb D3122C25CG4+2C 6 bodies 2.5" smooth Urethane (4x5.55" inner+2x2" outer bodies) 14 lb D3122C25C4+2C 4 center bodies +2 short outer bodies, 31.75" shaft-38" taps SHA3122STN4+2 Toro 22" GREENSMOWERS - BACK ROLLER: series 3, 300, 3000, 3050, 3100, 3150 (Except TriFlex series as follows: 3200, 3250, 3300, 3320, 3400, 3420 & FLEX 21) 2" dia. SINGLE body rollers 2" wide grooved Urethane no flats 6.5 lb T2522A2CG 22.45" body, 25.875" shaft SHA2522AT 2" narrow grooved Urethane no flats 6.7 lb T2522A2NG 22.45" body, 25.875" shaft SHA2522AT 2" wide grooved Urethane 1" flats 6.5 lb T2522A2CGF 22.45" body, 25.875" shaft SHA2522AT 2" narrow grooved Urethane 1" flats 6.7 lb T2522A2NGF 22.45" body, 25.875" shaft SHA2522AT 2" smooth Urethane 8 lb T2522A2C 22.25" body, 25.875" shaft SHA2522AT 22.25" body, 25.875" shaft 2" smooth Steel heavy (1/4" wall) 11.5 lb T2522A2S SHA2522AT 2" dia. TWO body rollers non-striping, non-skidding for tight turns & ground undulations 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats 4 lb T2504A2CGt 2 short twin bodies at ends of a 25.875" shaft SHA2522ATNt 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats 4 lb T2504A2NGt 2 short twin bodies at ends of a 25.875" shaft SHA2522ATNt 2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 4 lb T2504A2CGFt 2 short twin bodies at ends of a 25.875" shaft SHA2522ATNt SHA2522ATNt 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 4 lb T2504A2NGFt 2 short twin bodies at ends of a 25.875" shaft 2 bodies 2" smooth Urethane (2x2" wide bodies) 4 lb T2502A2Ct 2 short twin bodies at ends of a 25.875" shaft SHA2522ATNt 2 bodies 2" smooth Urethane (2x4.75" wide bodies) 4.2 lb T2504A2Ct 2 short twin bodies at ends of a 25.875" shaft SHA2522ATNt 2" dia. THREE body rollers non-skidding for tight turns & ground undulations 3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies) 12 lb T3122A2CG+2C 22.45" center body + 2 short outer bodies, 31.875" shaft SHA3122ATN+2 3 bodies 2" narrow grooved Urethane (22.45" inner+2x2" outer bodies) 12 lb T3122A2NG+2C 22.45" center body + 2 short outer bodies, 31.875" shaft SHA3122ATN+2 3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies) 13 lb T3122A2C+2C 22.25" center body + 2 short outer bodies, 31.875" shaft SHA3122ATN+2 3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies) 13 lb T3122A2S+2S 22.25" center body + 2 short outer bodies, 31.875" shaft SHA3122ATN+2 2" dia. FOUR body rollers non-skidding for tight turns & ground undulations SHA2522ATN4 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats 8.5 lb T2522A2CG4 4 short bodies, 24.25" shaft-7/16" taps 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats 8.5 lb T2522A2NG4 4 short bodies, 24.25" shaft-7/16" taps SHA2522ATN4 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats 8.5 lb T2522A2CGF4 4 short bodies, 24.25" shaft-7/16" taps SHA2522ATN4 SHA2522ATN4 4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats 8.5 lb T2522A2NGF4 4 short bodies, 24.25" shaft-7/16" taps 4 bodies 2" smooth Urethane (4x5.55" wide bodies) SHA2522ATN4 4 short bodies, 24.25" shaft-7/16" taps 8.5 lb T2522A2C4 4 bodies 2" smooth Steel heavy (4x5.55" wide bodies) 4 short bodies, 24,25" shaft-7/16" taps SHA2522ATN4 12 lb T2522A2S4 2" dia. SIX body rollers non-skidding for tight turns & ground undulations 6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies) 13 lb T3122A2CG4+2C 4 center bodies + 2 short outer bodies, 30:25" shaft-7/16" taps SHA3122ATN4+2 6 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 13 lb T3122A2NG4+2C 4 center bodies + 2 short outer bodies, 30,25" shaft-7/16" taps SHA3122ATN4+2 6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats 13 lb T3122A2CGF4+2C 4 center bodies + 2 short outer bodies, 30,25" shaft-7/16" taps SHA3122ATN4+2 6 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats 13 lb T3122A2NGF4+2C 4 center bodies + 2 short outer bodies, 30.25" shaft-7/16" taps SHA3122ATN4+2 6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies) 13 lb T3122A2C4+2C 4 center bodies + 2 short outer bodies, 30,25" shaft-7/16" taps SHA3122ATN4+2

SHA3122ATN4+2

4 center bodies + 2 short outer bodies, 30.25" shaft-7/16" taps

13 lb T3122A2S4+2C

6 bodies 2" smooth Steel heavy (4x5.55" inner+2x2" outer bodies)



2 F" die SINGI E bedy rollers	(0) 54		INTERNATIONAL		
2.5" wide grooved (1" spacing) Urethane no flats	9 lb	т	2522A25CG	22.45" body, 25.87" shaft	SHA2522AT
2.5" narrow grooved (1" spacing) Urethane no flats			2522A25NG	22.45" body, 25.87" shaft	SHA2522AT
2.5" smooth Urethane	9.5 lb	T	2522A25C	22.45" body, 25.87" shaft	SHA2522AT
2.5" smooth Steel	10 lb	T	2522A25S	22.25" body, 25.87" shaft	SHA2522AT
2.5" dia. Four body rollers				non-skidding for tight turns & ground undulations	120002001201
4 bodies 2.5" grooved Urethane (4x5.55" wide bodies) no flats	2000000		2522A25CG4	4 short bodies, 25.875" shaft	SHA2522ATN4 SHA2522ATN4
4 bodies 2.5" smooth Urethane (4x5.55" wide bodies) 4 bodies 2.5" smooth Steel (4x5.55" wide bodies)			2522A25C4 2522A25S4	4 short bodies, 25.875" shaft 4 short bodies, 25.875" shaft	SHA2522ATN4 SHA2522ATN4
Toro 22" GREENSMOWERS - BASKET (Yoke) ROLLERS: series 3, 300, 3				(fully assembled with body + shaft + bearings + s	
(Except TriFlex series as follows: 3200, 3250, 3300, 3320, 3400, 34				(rany assembled min soup a share a searings a s	cu.5)
3" grooved Urethane no flats			2520H3CG	20.45" body, 25.063" shaft-3/8" taps	SHA2520HT
3" smooth Urethane			2520H3C	20.45" body, 25.063" shaft-3/8" taps	SHA2520HT
3" smooth Steel			2520H3S	20.45" body, 25.063" shaft-3/8" taps	SHA2520HT
3.5" smooth Urethane			2520H7C	20.45" body, 25.063" shaft-3/8" taps	SHA2520HT
2 bodies 3" smooth Urethane (2x4" wide bodies) Toro 21/22" FLEX & TRIFLEX models 21, 2100, 2120, 1021 & e1021 + 320			2504H3CT	2 short twin bodies at ends of a 25.063" shaft-3/8" taps	SHA2520HTNt
(these rollers do not accommodate yoke ball studs. They have so					art # to "S")
2" dia. SINGLE body rollers					
2" wide grooved Urethane no flats			2522A2CG	22.45" body, 25.875" shaft	SHA2522AT
2" narrow grooved Urethane no flats			2522A2NG	22.45" body, 25.875" shaft	SHA2522AT
2" wide grooved Urethane 1" flats 2" narrow grooved Urethane 1" flats			2522A2CGF 2522A2NGF	22.45" body, 25.875" shaft 22.45" body, 25.875" shaft	SHA2522AT SHA2522AT
2" smooth Urethane			2522A2NG1	22.25" body, 25.875" shaft	SHA2522AT
2" smooth Steel heavy (1/4" wall)			2522A2S	22.25" body, 25.875" shaft	SHA2522AT
2" dia. TWO body rollers				non-striping, non-skidding for tight turns & ground undula	itions
2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats			2504A2CGt	2 short twin bodies at ends of a 25.875" shaft	SHA2522ATNt
2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats			2504A2NGt	2 short twin bodies at ends of a 25.875" shaft	SHA2522ATNt
2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats			2504A2CGFt 2504A2NGFt	2 short twin bodies at ends of a 25.875" shaft 2 short twin bodies at ends of a 25.875" shaft	SHA2522ATNt SHA2522ATNt
2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" smooth Urethane (2x2" wide bodies)			2504A2NGFt 2502A2Ct	2 short twin bodies at ends of a 25.875" shaft 2 short twin bodies at ends of a 25.875" shaft	SHA2522ATNt
2 bodies 2" smooth Urethane (2x4.75" wide bodies)			2504A2Ct	2 short twin bodies at ends of a 25.875" shaft	SHA2522ATNt
2" dia. THREE body rollers	155.75	20.3		non-skidding for tight turns & ground undulations	
3 bodies 2" wide grooved Urethane (22.45" inner+2x2" outer bodies)	12 lb	T	3122A2CG+2C	22.45" center body + 2 short outer bodies, 31.875" shaft	SHA3122ATN+2
3 bodies 2" narrow grooved Urethane (22.45" inner+2x2" outer bodies)			3122A2NG+2C	22.45" center body + 2 short outer bodies, 31.875" shaft	SHA3122ATN+2
3 bodies 2" smooth Urethane (22.45" inner+2x2" outer bodies)			3122A2C+2C	22.25" center body + 2 short outer bodies, 31.875" shaft	SHA3122ATN+2
3 bodies 2" smooth Steel heavy (22.25" inner+2x2" outer bodies)	13 lb	0 1	3122A2S+2S	22.25" center body + 2 short outer bodies, 31.875" shaft	SHA3122ATN+2
2" dia. FOUR body rollers 4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) no flats	8 5 lb	٠ т	2522A2CG4	non-skidding for tight turns & ground undulations 4 short bodies, 25.875" shaft	SHA2522ATN4
4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) no flats			2522A2OG4	4 short bodies, 25.875" shaft	SHA2522ATN4
4 bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats			2522A2CGF4	4 short bodies, 25.875" shaft	SHA2522ATN4
4 bodies 2" narrow grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb	T	2522A2NGF4	4 short bodies, 25.875" shaft	SHA2522ATN4
4 bodies 2" smooth Urethane (4x5.55" wide bodies)	8.5 lb	T	2522A2C4	4 short bodies, 25.875" shaft	SHA2522ATN4
4 bodies 2" smooth Steel heavy (4x5.55" wide bodies)	12 lb	T	2522A2S4	4 short bodies, 25.875" shaft	SHA2522ATN4
2" dia. SIX body rollers	40 11	· T	2040040004.00	non-skidding for tight turns & ground undulations	0111040047044
6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies) 6 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies)			3122A2CG4+2C 3122A2NG4+2C	4 center bodies + 2 short outer bodies, 31.875" shaft 4 center bodies + 2 short outer bodies, 31.875" shaft	SHA3122ATN4+2 SHA3122ATN4+2
6 bodies 2" wide grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats			3122A2NG4+2C 3122A2CGF4+2C	4 center bodies + 2 short outer bodies, 31.875" shaft	SHA3122ATN4+2
6 bodies 2" narrow grooved Urethane (4x5.55" inner+2x2" outer bodies) 1" flats			3122A2NGF4+2C	4 center bodies + 2 short outer bodies, 31.875" shaft	SHA3122ATN4+2
6 bodies 2" smooth Urethane (4x5.55" inner+2x2" outer bodies)			3122A2C4+2C	4 center bodies + 2 short outer bodies, 31.875" shaft	SHA3122ATN4+2
6 bodies 2" smooth Steel heavy (4x5.55" inner+2x2" outer bodies)	13 lb	T	3122A2S4+2C	4 center bodies + 2 short outer bodies, 31.875" shaft	SHA3122ATN4+2
2.5" dia. SINGLE body rollers	200			DENIED PROVIDE CONCESSION	PERFECCION
2.5" wide grooved (1" spacing) Urethane no flats			2522A25CG	22.45" body, 25.875" shaft	SHA2522AT
2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane			2522A25NG 2522A25C	22.45" body, 25.875" shaft 22.45" body, 25.875" shaft	SHA2522AT SHA2522AT
2.5" smooth Steel			2522A25S	22.25" body, 25.875" shaft	SHA2522AT
2.5" dia. TWO body rollers		504.5	10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	non-striping, non-skidding for tight turns & ground undula	itions
2 bodies 2.5" grooved Urethane (2x4.75" wide bodies) no flats	4 lb	T	2504A25CGt	2 short twin bodies at ends of a 25.75" shaft	SHA2504ATNt
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies)	4.2 lb	T	2504A25Ct	2 short twin bodies at ends of a 25.75" shaft	SHA2504ATNt
2.5" dia. Four body rollers	40.0		2522425004	non-skidding for tight turns & ground undulations	CHARCONATA
4 bodies 2.5" grooved Urethane (4x5.55" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x5.55" wide bodies)			2522A25CG4 2522A25C4	4 short bodies, 25.875" shaft 4 short bodies, 25.875" shaft	SHA2522ATN4 SHA2522ATN4
2.5" dia. SIX body rollers	10 10	, 1	LULLINGUUT	non-skidding for tight turns & ground undulations	SIDESEE IN
6 bodies 2.5" grooved Urethane (4x5.55" inner+2x2" outer bodies)	14 lb	т	3122A25CG4+2C	4 center body + 2 short outer bodies, 31.875" shaft	SHA3122ATN4+2
6 bodies 2.5" smooth Urethane (4x5.55" inner+2x2" outer bodies)	14 lb	T	3122A25C4+2C	4 center body + 2 short outer bodies, 31.875" shaft	SHA3122ATN4+2
Toro GREENSMOWER FLEX models 18, 1800, 1820 & 1018 - FRONT & BA	ACK R	OL	LERS (if groomer kit requ	ires tap in ends of shaft, change "C" in part # to "S	")
2" dia. SINGLE body rollers			122 12 12 12 12 12 12 12 12 12 12 12 12	CONTROL SIA DVI C	PERSONAL PROPERTY.
2" wide grooved Urethane no flats			2319C2CG	19.45" body, 23" shaft w/o taps	SHA2319CT SHA2319CT
2" narrow grooved Urethane no flats 2" wide grooved Urethane 1" flats			2319C2NG 2319C2CGF	19.45" body, 23" shaft w/o taps 19.45" body, 23" shaft w/o taps	SHA2319CT
2" narrow grooved Urethane 1" flats			2319C2NGF	19.45" body, 23" shaft w/o taps	SHA2319CT
2" smooth Urethane			2319C2C	19.25" body, 23" shaft w/o taps	SHA2319CT
2" smooth Steel heavy (1/4" wall)			2319C2S	19.25" body, 23" shaft w/o taps	SHA2319CT
2" dia. TWO body rollers				non-striping, non-skidding for tight turns & ground undula	
2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) no flats			2304C2CGt	2 short twin bodies at ends of a 23" shaft	SHA2304CTNt
2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) no flats			2304C2NGt	2 short twin bodies at ends of a 23" shaft	SHA2304CTNt
2 bodies 2" wide grooved Urethane (2x4.75" wide bodies) 1" flats 2 bodies 2" narrow grooved Urethane (2x4.75" wide bodies) 1" flats			2304C2CGFt 2304C2NGFt	2 short twin bodies at ends of a 23" shaft 2 short twin bodies at ends of a 23" shaft	SHA2304CTNt SHA2304CTNt
2 bodies 2" smooth Urethane (2x2" wide bodies) 1 mats			2302C2Ct	2 short twin bodies at ends of a 23" shaft 2 short twin bodies at ends of a 23" shaft	SHA2302CTNt
2 bodies 2" smooth Urethane (2x4.75" wide bodies)			2304C2Ct	2 short twin bodies at ends of a 23" shaft	SHA2304CTNt
2" dia. THREE body rollers	2000		1.7 STW (1007 - 1007 (1000) - 10 3 TOW	non-skidding for tight turns & ground undulations	
3 bodies 2" wide grooved Urethane (19.45" inner+2x2" outer bodies)			2919C2CG+2C	19.45" center body + 2 short outer bodies, 29" shaft	SHA2919CTN+2
3 bodies 2" narrow grooved Urethane (19.45" inner+2x2" outer bodies)			2919C2NG+2C	19.45" center body + 2 short outer bodies, 29" shaft	SHA2919CTN+2
3 bodies 2" smooth Urethane (19.45" inner+2x2" outer bodies)	13 lb) [2919C2C+2C	19.25" center body + 2 short outer bodies, 29" shaft	SHA2919CTN+2



2" dia. FOUR body rollers	0.5 lb T224002004	non-skidding for tight turns & ground undulations	CUADDIOCTUA
4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats 4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) no flats	8.5 lb T2319C2CG4 8.5 lb T2319C2NG4	4 short bodies, 23" shaft 4 short bodies, 23" shaft	SHA2319CTN4 SHA2319CTN4
4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) 1" flats	8.5 lb T2319C2CGF4	4 short bodies, 23" shaft	SHA2319CTN4
4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats	8.5 lb T2319C2NGF4	4 short bodies, 23" shaft	SHA2319CTN4
4 bodies 2" smooth Urethane (4x4.75" wide bodies)	8.5 lb T2319C2C4	4 short bodies, 23" shaft	SHA2319CTN4
4 bodies 2" smooth Steel heavy (4x4.75" wide bodies)	12 lb T2319C2S4	4 short bodies, 23" shaft	SHA2319CTN4
2" dia. SIX body rollers		non-skidding for tight turns & ground undulations	
6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) no flats	13 lb T2919C2CG4+2C	4 center bodies + 2 short outer bodies, 29" shaft	SHA2919CTN4+2
6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies)	13 lb T2919C2NG4+2C	4 center bodies + 2 short outer bodies, 29" shaft	SHA2919CTN4+2
6 bodies 2" wide grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats	13 lb T2919C2CGF4+2C 13 lb T2919C2NGF4+2C	4 center bodies + 2 short outer bodies, 29" shaft 4 center bodies + 2 short outer bodies, 29" shaft	SHA2919CTN4+2 SHA2919CTN4+2
6 bodies 2" narrow grooved Urethane (4x4.75" inner+2x2" outer bodies) 1" flats 6 bodies 2" smooth Urethane (4x4.75" inner+2x2" outer bodies)	12 lb T2919C2NGF4+2C	4 center bodies + 2 short outer bodies, 29" shaft 4 center bodies + 2 short outer bodies, 29" shaft	SHA2919CTN4+2
6 bodies 2" smooth Steel heavy (4x4.75" inner+2x2" outer bodies)	12 lb T2919C2S4+2C	4 center bodies + 2 short outer bodies, 29" shaft	SHA2919CTN4+2
Toro GM800 18" GREENSMOWER - FRONT & BACK ROLLERS	1212 120100201120		
2" dia. SINGLE body rollers			
2" wide grooved Urethane no flats	6.5 lb T2219S2CG	19.45" body, 22.75" shaft w/o taps	SHA2219ST
2" narrow grooved Urethane no flats	6.7 lb T2219S2NG	19.45" body, 22.75" shaft w/o taps	SHA2219ST
2" wide grooved Urethane 1" flats	6.5 lb T2219S2CGF	19.45" body, 22.75" shaft w/o taps	SHA2219ST
2" narrow grooved Urethane 1" flats	6.7 lb T2219S2NGF	19.45" body, 22.75" shaft w/o taps	SHA2219ST
2" smooth Urethane 2" smooth Steel heavy (1/4" wall)	7.5 lb T2219S2C 10.5 lb T2219S2S	19.25" body, 22.75" shaft w/o taps 19.25" body, 22.75" shaft w/o taps	SHA2219ST SHA2219ST
2" dia. FOUR body rollers	10.5 lb 12219828	non-skidding for tight turns & ground undulations	3HA221931
4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) no flats	8.5 lb T2219S2CG4	4 short bodies, 22.75" shaft	SHA2219STN4
4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) no flats	8.5 lb T2219S2NG4	4 short bodies, 22.75" shaft	SHA2219STN4
4 bodies 2" wide grooved Urethane (4x4.75" wide bodies) 1" flats	8.5 lb T2219S2CGF4	4 short bodies, 22.75" shaft	SHA2219STN4
4 bodies 2" narrow grooved Urethane (4x4.75" wide bodies) 1" flats	8.5 lb T2219S2NGF4	4 short bodies, 22.75" shaft	SHA2219STN4
4 bodies 2" smooth Urethane (4x4.75" wide bodies)	8.5 lb T2219S2C4	4 short bodies, 22.75" shaft	SHA2219STN4
4 bodies 2" smooth Steel heavy (4x4.75" wide bodies)	12 lb T2219S2S4	4 short bodies, 22.75" shaft	SHA2219STN4
Toro GM1600 26" GREENSMOWER - FRONT & BACK ROLLERS			
2" dia. SINGLE body rollers	7.9 lb T24074000	07 451 hard 241 hard	CUADADTAT
2" wide grooved Urethane no flats 2" wide grooved Urethane 1" flats	7.8 lb T3127A2CG 7.8 lb T3127A2CGF	27.45" body, 31" shaft 27.45" body, 31" shaft	SHA3127AT SHA3127AT
2" smooth Urethane	11 lb T3127A2C	27.25" body, 31" shaft	SHA3127AT
2" smooth Steel heavy (1/4" wall)	13.5 lb T3127A2S	27.25" body, 31" shaft	SHA3127AT
2.5" dia. SINGLE body rollers			
2.5" grooved Urethane no flats	9.5 lb T3127A25CG	27,45" body, 31" shaft	SHA3127AT
2.5" smooth Urethane	11 lb T3127A25C	27.45" body, 31" shaft	SHA3127AT
2.5" smooth Steel	11 lb T3127A25S	27.25" body, 31" shaft	SHA3127AT
2.5" dia. TWO body rollers		non striping non skidding for tight turns 2 ground unduly	ations
		non-striping, non-skidding for tight turns & ground undula	
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies)	7 lb T3104A25Ct	2 short twin bodies at ends of a 31" shaft	SHA3104ATNt
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers		2 short twin bodies at ends of a 31° shaft non-skidding for tight turns & ground undulations	SHA3104ATNt
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats	10 lb T3127A25CG4	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft	SHA3104ATNt SHA3127ATN4
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies)		2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft	SHA3104ATNt
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers	10 lb T3127A25CG4 13 lb T3127A25C4	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft	SHA3104ATNt SHA3127ATN4
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies)	10 lb T3127A25CG4	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations	SHA3104ATNt SHA3127ATN4 SHA3127ATN4
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies)	10 lb T3127A25CG4 13 lb T3127A25C4 10 lb T3727A25CG4+2C	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 37" shaft	SHA3104ATNt SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) Toro 5100D, 5300D & 223D FAIRWAY MOWERS - FRONT ROLLER Combination roller assemblies to diminish effect of reel overlaps	10 lb T3127A25CG4 13 lb T3127A25C4 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft (Sectional rollers with 4 bodies also available)	SHA3107ATN1 SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2 SHA3727ATN4+2
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) Toro 5100D, 5300D & 223D FAIRWAY MOWERS - FRONT ROLLER Combination roller assemblies to diminish effect of reel overlap s 2.5" wide grooved (1" spacing) Urethane no flats	10 lb T3127A25CG4 13 lb T3127A25C4 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available 9 lb T2522A25CG	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft (Sectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft	SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) Toro 5100D, 5300D & 223D FAIRWAY MOWERS - FRONT ROLLER Combination roller assemblies to diminish effect of reel overlap s 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats	10 lb T3127A25CG4 13 lb T3127A25C4 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available 9 lb T2522A25CG 9 lb T2522A25NG	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 10 short bodies, 31" shaft 11 short bodies, 31" shaft 12 short bodies, 37" shaft 13 center bodies + 2 short outer bodies, 37" shaft 14 center bodies + 2 short outer bodies, 37" shaft 15 cectional rollers with 4 bodies also available) 16 22.45" body, 25.87" shaft 17 shaft 18 short bodies also available)	SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) Toro 5100D, 5300D & 223D FAIRWAY MOWERS - FRONT ROLLER Combination roller assemblies to diminish effect of reel overlap s 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane	10 lb T3127A25CG4 13 lb T3127A25C4 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available 9 lb T2522A25CG 9 lb T2522A25NG 9.5 lb T2522A25C	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft (Sectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft	SHA3127ATN4 SHA3127ATN4 SHA3127ATN4+2 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) Toro 5100D, 5300D & 223D FAIRWAY MOWERS - FRONT ROLLER Combination roller assemblies to diminish effect of reel overlap s 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane	10 lb T3127A25CG4 13 lb T3127A25C4 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available- 9 lb T2522A25CG 9 lb T2522A25NG 9.5 lb T2522A25C 10 lb T2522A25S	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft (Sectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.25" body, 25.87" shaft	SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 combination roller assemblies to diminish effect of reel overlap so 2.5" wide grooved (1" spacing) Urethane no flats 9 combination roller assemblies to diminish effect of reel overlap so 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlap so 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlap so 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlap so 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlap so 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlap so 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlap so 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlap so 2.5" wide grooved (1" spacing) Urethane no flats 9 combination roller assemblies to diminish effect of reel overlap so 2.5" wide grooved (1" spacing) Urethane no flats 9 combination roller assemblies to diminish effect of reel overlap so 2.5" wide grooved (1" spacing) Urethane no flats 9 combination roller assemblies to diminish effect of reel overlap so 2.5" wide grooved (1" spacing) Urethane no flats 9 combination roller assemblies to diminish effect of reel overlap so 2.5" wide grooved (1" spacing) Urethane no flats 9 combination roller assemblies to diminish effect of reel overlap so 2.5" wide flower assemblies to diminish effect of reel overlap so 2.5" wide flower assem	10 lb T3127A25CG4 13 lb T3127A25CG4 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available 9 lb T2522A25CG 9 lb T2522A25NG 9.5 lb T2522A25C 10 lb T2522A25S diameter also available)	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft (Sectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft	SHA3127ATN4 SHA3127ATN4 SHA3127ATN4+2 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) Toro 5100D, 5300D & 223D FAIRWAY MOWERS - FRONT ROLLER Combination roller assemblies to diminish effect of reel overlap s 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane	10 lb T3127A25CG4 13 lb T3127A25C4 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available- 9 lb T2522A25CG 9 lb T2522A25NG 9.5 lb T2522A25C 10 lb T2522A25S	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 5 (Sectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft (Sectional rollers with 4 bodies also available)	SHA3107ATN1 SHA3127ATN4 SHA3127ATN4+2 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodie	10 lb T3127A25CG4 13 lb T3127A25CG4 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available 9 lb T2522A25CG 9 lb T2522A25NG 9.5 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2CGF	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft (Sectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft	SHA3107ATN1 SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" wide grooved (1" spacing) Urethane no flats 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel 7 bodies 2.5" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 7 bodies 2.5" bo	10 lb T3127A25CG4 13 lb T3127A25CG4 10 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available. 9 lb T2522A25CG 9 lb T2522A25NG 9.5 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2CGF 7.5 lb T2319A2C 10.5 lb T2319A2S SAIRWAY MOWERS - FRONT	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft (Sectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft	SHA3107ATN1 SHA3127ATN4 SHA3127ATN4+2 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 combination roller assemblies to diminish effect of reel overlap of 2.5" wide grooved (1" spacing) Urethane no flats 9 combination toller assemblies to diminish effect of reel overlap of 2.5" smooth Urethane 9 combination toller assemblies to diminish effect of reel overlap of 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlap of 2.5" combination roller assemblies to diminish effect of reel overlap of 2.5" combination roller assemblies to diminish effect of reel overlap of 2.5" combination roller assemblies to diminish effect of reel overlap of 2.5" combination roller assemblies to diminish effect of reel overlap of 2.5" combination roller assemblies to diminish effect of 2.5"	10 lb T3127A25CG4 13 lb T3127A25CG4 10 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available. 9 lb T2522A25CG 9 lb T2522A25NG 9.5 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2CGF 7.5 lb T2319A2C 10.5 lb T2319A2S SAIRWAY MOWERS - FRONT	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies, 28.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.25" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft	SHA3107ATN1 SHA3127ATN4 SHA3127ATN4+2 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) Toro 5100D, 5300D & 223D FAIRWAY MOWERS - FRONT ROLLER Combination roller assemblies to diminish effect of reel overlap so 2.5" wide grooved (1" spacing) Urethane no flats 2.5" marrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel Toro 5100D, 5300D & 223D FAIRWAY MOWERS - BACK ROLLER (2.5" 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) Toro 3550D, 3555D, 3575D, 5200D, 5210D, 5400D, 5410D, 5510D, 5610D F Combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers	10 lb T3127A25CG4 13 lb T3127A25CG4 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available 9 lb T2522A25CG 9 lb T2522A25C 10 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2CGF 7.5 lb T2319A2C 10.5 lb T2319A2S SAIRWAY MOWERS - FRONT shadowing are available	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 5 (Sectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft (Sectional rollers with 4 bodies also available) (Sectional rollers with 4 bodies also available)	SHA3104ATN1 SHA3127ATN4 SHA3127ATN4+2 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 combination roller assemblies to diminish effect of reel overlap so 2.5" wide grooved (1" spacing) Urethane no flats 9 2.5" smooth Urethane 9 2.5" smooth Urethane 9 2.5" smooth Steel 9 Toro 5100D, 5300D & 223D FAIRWAY MOWERS - BACK ROLLER (2.5" 2" wide grooved Urethane 1" flats 9 2" smooth Urethane 9 2" smooth Steel heavy (1/4" wall) 9 Toro 3550D, 3555D, 3575D, 5200D, 5210D, 5400D, 5410D, 5510D, 5610D FC Combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 2" dia. SINGLE body rollers 9 2.5" grooved Urethane no flats	10 lb T3127A25CG4 13 lb T3127A25CG4 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available 9 lb T2522A25CG 9 lb T2522A25NG 9.5 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2CGF 7.5 lb T2319A2C 10.5 lb T2319A2S SAIRWAY MOWERS - FRONT Shadowing are available 8 lb T2319T25CG	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 2 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 2 2.45" body, 25.87" shaft 2 2.45" body, 25.87" shaft 2 2.45" body, 25.87" shaft 2 2.25" body, 25.87" shaft 3 2.25" body, 23" shaft 3 19.25" body, 23" shaft 3 19.25" body, 23" shaft 4 bodies also available) 19.45" body, 23" shaft 4 bodies also available) 19.45" body, 23" shaft	SHA3104ATN1 SHA3127ATN4 SHA3127ATN4+2 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 combination roller assemblies to diminish effect of reel overlaps 2.5" wide grooved (1" spacing) Urethane no flats 9 combination roller assemblies to diminish effect of reel overlaps 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlaps 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlaps 2.5" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlaps 2.5" grooved Urethane no flats 9 combination roller assemblies to diminish effect of reel overlaps 2.5" grooved Urethane no flats 9 combination roller assemblies to diminish effect of reel overlaps 2.5" grooved Urethane no flats 9 combination roller assemblies to diminish effect of reel overlaps 2.5" grooved Urethane no flats 9 combination roller assemblies to diminish effect of reel overlaps 2.5" grooved Urethane no flats	10 lb T3127A25CG4 13 lb T3127A25CG4 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available 9 lb T2522A25CG 9 lb T2522A25NG 9.5 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2CGF 7.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319A2S sAIRWAY MOWERS - FRONT shadowing are available 8 lb T2319T25CG 9 lb T2319T25C	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 2 center bodies + 2 short outer bodies, 37" shaft 2 cettonal rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft (Sectional rollers with 4 bodies also available)	SHA3104ATN1 SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 1 cro 5100D, 5300D & 223D FAIRWAY MOWERS - FRONT ROLLER 1 combination roller assemblies to diminish effect of reel overlaps of the state of the sta	10 lb T3127A25CG4 13 lb T3127A25CG4 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available 9 lb T2522A25CG 9 lb T2522A25NG 9.5 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2CGF 7.5 lb T2319A2C 10.5 lb T2319A2S SAIRWAY MOWERS - FRONT Shadowing are available 8 lb T2319T25CG	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 2 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 2 2.45" body, 25.87" shaft 2 2.45" body, 25.87" shaft 2 2.45" body, 25.87" shaft 2 2.25" body, 25.87" shaft 3 2.25" body, 23" shaft 3 19.25" body, 23" shaft 3 19.25" body, 23" shaft 4 bodies also available) 19.45" body, 23" shaft 4 bodies also available) 19.45" body, 23" shaft	SHA3104ATN1 SHA3127ATN4 SHA3127ATN4+2 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 combination roller assemblies to diminish effect of reel overlaps 2.5" wide grooved (1" spacing) Urethane no flats 9 combination roller assemblies to diminish effect of reel overlaps 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlaps 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlaps 2.5" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlaps 2.5" grooved Urethane no flats 9 combination roller assemblies to diminish effect of reel overlaps 2.5" grooved Urethane no flats 9 combination roller assemblies to diminish effect of reel overlaps 2.5" grooved Urethane no flats 9 combination roller assemblies to diminish effect of reel overlaps 2.5" grooved Urethane no flats 9 combination roller assemblies to diminish effect of reel overlaps 2.5" grooved Urethane no flats	10 lb T3127A25CG4 13 lb T3127A25CG4 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available 9 lb T2522A25CG 9 lb T2522A25NG 9.5 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2CGF 7.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319A2S sAIRWAY MOWERS - FRONT shadowing are available 8 lb T2319T25CG 9 lb T2319T25C	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 2 center bodies + 2 short outer bodies, 37" shaft 2 cettonal rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft (Sectional rollers with 4 bodies also available)	SHA3104ATN1 SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 1 cro 5100D, 5300D & 223D FAIRWAY MOWERS - FRONT ROLLER 1 combination roller assemblies to diminish effect of reel overlaps of the state of the sta	10 lb T3127A25CG4 13 lb T3127A25CG4 10 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C shadowing are available. 9 lb T2522A25CG 9 lb T2522A25CG 10 lb T2522A25C 10 lb T2522A25C 10 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2CGF 7.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319A2C SAIRWAY MOWERS - FRONT shadowing are available 8 lb T2319T25CG 9 lb T2319T25C	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft non-skidding for tight turns & ground undulations 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft (Sectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft	SHA3104ATNI SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2519AT SHA2319AT SHA2319AT SHA2319TT SHA2319TT SHA2319TT SHA2319TT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 combination roller assemblies to diminish effect of reel overlap of 2.5" wide grooved (1" spacing) Urethane no flats 9 combination toller assemblies to diminish effect of reel overlap of 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlap of 2" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlap of 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap of 3" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap of 3" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap of 3" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap of 3" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap of 3" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap of 3" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap of 3" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap of 3" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap of 3" dia. SINGLE body rollers	10 lb T3127A25CG4 13 lb T3127A25CG4 13 lb T3127A25C4 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C Shadowing are available 9 lb T2522A25CG 9 lb T2522A25CG 10 lb T2522A25C 10 lb T2522A25C 10 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2CGF 7.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319A2C shadowing are available 8 lb T2319T25CG 9 lb T2319T25C 9 lb T2319T25S	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 2 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 2 2.45" body, 25.87" shaft 2 2.45" body, 25.87" shaft 2 2.45" body, 25.87" shaft 2 2.5" body, 25.87" shaft 2 2.5" body, 25.87" shaft 1 9.25" body, 23" shaft 1 9.25" body, 23" shaft 1 9.25" body, 23" shaft 1 9.45" body, 23" shaft 1 9.25" body, 23" shaft	SHA3104ATNI SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT SHA2319AT SHA2319TT SHA2319TT SHA2319TT SHA2319TT SHA2319TT SHA2319TT SHA2319TT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 1 bodies 2.5" smooth Urethane roller assemblies to diminish effect of reel overlap society of the second of the sec	10 lb T3127A25CG4 13 lb T3127A25CG4 10 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available 9 lb T2522A25CG 9 lb T2522A25CG 10 lb T2522A25S diameter also available) 6.5 lb T2319A2CGF 7.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319A2S SAIRWAY MOWERS - FRONT shadowing are available 8 lb T2319T25CG 9 lb T2319T25C 9 lb T2319T25S 9.5 lb T2722A3CG 11.5 lb T2722A3C 11.5 lb T2722A3C 11.5 lb T2722A3C	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 5 cectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft 19.25" body, 23" shaft 19.45" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 27" shaft 22.45" body, 27" shaft 22.55" body, 27" shaft	SHA3104ATNI SHA3127ATN4 SHA3127ATN4 SHA3127ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT SHA2319TT SHA2319TT SHA2319TT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 1 combination roller assemblies to diminish effect of reel overlaps of the state of	10 lb T3127A25CG4 13 lb T3127A25CG4 10 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C shadowing are available. 9 lb T2522A25CG 9 lb T2522A25NG 9.5 lb T2522A25NG 9.5 lb T2522A25S diameter also available) 6.5 lb T2319A2CGF 7.5 lb T2319A2CG 10.5 lb T2319A2CS 6AIRWAY MOWERS - FRONT shadowing are available 8 lb T2319T25CG 9 lb T2319T25C 9 lb T2319T25S 9.5 lb T2722A3CG 11.5 lb T2722A3CG 11.5 lb T2722A3CG 12 lb T2722A3CG	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 5 cectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.25" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 27" shaft 22.45" body, 27" shaft 22.45" body, 27" shaft 24.45" body, 27" shaft	SHA3104ATNI SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA25219AT SHA2319AT SHA2319AT SHA2319TT SHA2319TT SHA2319TT SHA2319TT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane flet of reel overlaps 2.5" wide grooved (1" spacing) Urethane no flats 9 2.5" wide grooved (1" spacing) Urethane no flats 9 2.5" smooth Urethane 9 2.5" smooth Urethane 9 2.5" smooth Urethane 9 2" wide grooved Urethane 1" flats 9 2" smooth Urethane 9 2" smooth Steel heavy (1/4" wall) 9 Toro 3550D, 3555D, 3575D, 5200D, 5210D, 5400D, 5410D, 5510D, 5610D floor Combination roller assemblies to diminish effect of reel overlaps 2.5" grooved Urethane no flats 9 2.5" smooth Urethane 9 2.5" smooth Urethane 9 3" grooved Urethane no flats 9 3" grooved Urethane no flats 9 3" grooved Urethane no flats 9 3" grooved Urethane 9 3" smooth Urethane 9 3" smooth Urethane 9 3" grooved Urethane no flats 9 3" grooved Urethane no flats 9 3" grooved Urethane no flats 9 3" grooved Urethane 9 3" smooth Urethane	10 lb T3127A25CG4 13 lb T3127A25CG4 13 lb T3727A25CG4+2C 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C Shadowing are available 9 lb T2522A25CG 9 lb T2522A25CG 10 lb T2522A25C 10 lb T2522A25C 10 lb T2522A25C 10 lb T2319A2CGF 7.5 lb T2319A2CGF 7.5 lb T2319A2CS SAIRWAY MOWERS - FRONT Shadowing are available 8 lb T2319T25CG 9 lb T2319T25C 9 lb T2319T25C 9 lb T2319T25S 9.5 lb T2722A3CG 12 lb T2722A3C 11.5 lb T2722A3C 11.5 lb T2724A3C 11.5 lb T2724A3C 11.5 lb T2724A3C	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 5 cectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft 19.45" body, 23" shaft 19.45" body, 23" shaft 19.45" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 27" shaft 22.45" body, 27" shaft 24.45" body, 27" shaft 24.45" body, 27" shaft 24.45" body, 27" shaft 24.5" body, 27" shaft	SHA3104ATNI SHA3127ATN4 SHA3127ATN4 SHA3127ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT SHA2319TT SHA2319TT SHA2319TT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 combination roller assemblies to diminish effect of reel overlap so 2.5" wide grooved (1" spacing) Urethane no flats 9 combination Urethane 9 combination Supposed (1/2" spacing) Urethane no flats 9 combination roller assemblies to diminish effect of reel overlap so 2" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to dimini	10 lb T3127A25CG4 13 lb T3127A25CG4 13 lb T3727A25CG4+2C 10 lb T3727A25CG4+2C 13 lb T3727A25C4+2C Shadowing are available 9 lb T2522A25CG 9 lb T2522A25CG 10 lb T2522A25C 10 lb T2522A25C 10 lb T2522A25C 10 lb T2319A2CGF 7.5 lb T2319A2CGF 7.5 lb T2319A2CS SAIRWAY MOWERS - FRONT Shadowing are available 8 lb T2319T25CG 9 lb T2319T25C 9 lb T2319T25C 9 lb T2319T25S 9.5 lb T2722A3CG 12 lb T2722A3C 11.5 lb T2722A3C 11.5 lb T2724A3C 11.5 lb T2724A3C 11.5 lb T2724A3C	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 5 cectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.25" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 27" shaft 22.45" body, 27" shaft 22.45" body, 27" shaft 24.45" body, 27" shaft	SHA3104ATNI SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA25219AT SHA2319AT SHA2319AT SHA2319TT SHA2319TT SHA2319TT SHA2319TT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" inher bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 combination roller assemblies to diminish effect of reel overlap so 2.5" wide grooved (1" spacing) Urethane no flats 9 combination toller assemblies to diminish effect of reel overlap so 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers	10 lb T3127A25CG4 13 lb T3127A25CG4 13 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C Shadowing are available. 9 lb T2522A25CG 9 lb T2522A25C 10 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319CCG 9 lb T2319T25CG 9 lb T2319T25C 9 lb T2319T25C 9 lb T2319T25S 9.5 lb T2722A3C 11.5 lb T2722A3C 11.5 lb T2722A3C 12 lb T272A43C 11.5 lb T272A3C	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.5" body, 25.87" shaft 22.5" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft 22.45" body, 27" shaft 24.45" body, 27" shaft 24.25" body, 27" shaft	SHA3104ATNI SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT SHA2319TT SHA2319TT SHA2319TT SHA2319TT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Roller assemblies to diminish effect of reel overlap social diminish effect o	10 lb T3127A25CG4 13 lb T3127A25CG4 13 lb T3727A25CG4+2C 13 lb T3727A25CG 9 lb T2522A25CG 9 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319A2S AIRWAY MOWERS - FRONT shadowing are available 8 lb T2319T25CG 9 lb T2319T25C 9 lb T2319T25C 9 lb T2319T25S 9.5 lb T2722A3C 11.5 lb T2722A3C 11.5 lb T2724A3C 11.5 lb T2319A2CGF	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 5 cectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft 19.45" body, 23" shaft 19.45" body, 23" shaft 19.45" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 27" shaft 22.45" body, 27" shaft 24.45" body, 27" shaft 24.45" body, 27" shaft 24.45" body, 27" shaft 24.5" body, 27" shaft	SHA3104ATNI SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA25219AT SHA2319AT SHA2319AT SHA2319TT SHA2319TT SHA2319TT SHA2319TT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" inher bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 9 combination roller assemblies to diminish effect of reel overlap so 2.5" wide grooved (1" spacing) Urethane no flats 9 combination toller assemblies to diminish effect of reel overlap so 2.5" smooth Urethane 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 10 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers	10 lb T3127A25CG4 13 lb T3127A25CG4 13 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C Shadowing are available. 9 lb T2522A25CG 9 lb T2522A25C 10 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319CCG 9 lb T2319T25CG 9 lb T2319T25C 9 lb T2319T25C 9 lb T2319T25S 9.5 lb T2722A3C 11.5 lb T2722A3C 11.5 lb T2722A3C 12 lb T272A43C 11.5 lb T272A3C	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.45" body, 23" shaft 19.25" body, 23" shaft 22.45" body, 23" shaft 22.45" body, 27" shaft 22.45" body, 27" shaft 24.45" body, 27" shaft 24.45" body, 27" shaft 24.45" body, 27" shaft 24.55" body, 27" shaft	SHA3104ATNI SHA3127ATN4 SHA3127ATN4 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT SHA2319TT SHA2319TT SHA2319TT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane roller assemblies to diminish effect of reel overlap so 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 8 body rollers 8 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 8 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 combination roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 condition roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 condition roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 condition roller assemblies to diminish effect of reel overlap so 2" dia. SINGLE body rollers 9 condition roller diane no flats 1 condition roller diane no flats 2 condition roller diane no flats 3 condition roller	10 lb T3127A25CG4 13 lb T3127A25CG4 13 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C 13 lb T3727A25C4+2C Shadowing are available 9 lb T2522A25CG 9 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2CGF 7.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319A2S SAIRWAY MOWERS - FRONT Shadowing are available 8 lb T2319T25CG 9 lb T2319T25C 9 lb T2319T25S 9.5 lb T2722A3CG 12 lb T2722A3C 11.5 lb T2722A3C 11.5 lb T2724A3C 11.5 lb T2724A3C 11.5 lb T2724A3C 11.5 lb T2724A3S SAIRWAY MOWERS - BACK 6.5 lb T2319A2CGF 7.5 lb T2319A2CGF 7.5 lb T2319A2CGF 7.5 lb T2319A2CGF 7.5 lb T2319A2C	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 5 cectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.25" body, 25.87" shaft 22.25" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft 19.45" body, 23" shaft 19.45" body, 23" shaft 19.45" body, 23" shaft 19.45" body, 27" shaft 22.45" body, 27" shaft 24.45" body, 27" shaft 24.55" body, 27" shaft	SHA3104ATNI SHA3127ATN4 SHA3127ATN4 SHA3127ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT SHA2319TT SHA2319TT SHA2319TT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" inde bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane for flats 2.5" wide grooved (1" spacing) Urethane no flats 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2" smooth Steel heavy (1/4" wall) 9 bodies 2.5" grooved Urethane no flats 2.5" grooved Urethane no flats 2.5" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" grooved Urethane 1" flats 2" dia. SINGLE body rollers 2" dia. SINGLE body rollers 2" wide grooved Urethane 1" flats 2" dia. SINGLE body rollers 2" wide grooved Urethane 1" flats 2" smooth Urethane	10 lb T3127A25CG4 13 lb T3127A25CG4 13 lb T3727A25CG4+2C 10 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C shadowing are available. 9 lb T2522A25CG 9 lb T2522A25C 10 lb T2319A2CGF 7.5 lb T2319A2C 10.5 lb T2319A2C 9 lb T2319T25CG 9 lb T2319T25CG 9 lb T2319T25C 9 lb T2319T25C 11.5 lb T2722A3C 11.5 lb T2722A3C 11.5 lb T2722A3C 11.5 lb T2722A3C 11.5 lb T2724A3C 11.5 lb T2734A3C 11.5 lb T2319A2CGF 7.5 lb T2319A2C 10.5 lb T2319A2C	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 5 cectional rollers with 4 bodies also available) 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft 19.45" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 27" shaft 22.45" body, 27" shaft 22.45" body, 27" shaft 24.45" body, 27" shaft 24.45" body, 27" shaft 24.45" body, 27" shaft 24.45" body, 27" shaft 24.55" body, 27" shaft 25.55" body, 27" shaft 26.55" body, 27" shaft 27.55" body, 27" shaft 28.55" body, 23" shaft 28.55" body, 23" shaft 28.55" body, 23" shaft	SHA3104ATNI SHA3127ATN4 SHA3127ATN4 SHA3127ATN4+2 SHA3727ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT SHA2319TT SHA2319TT SHA2319TT SHA2722AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT SHA2319AT SHA2319AT SHA2319AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) 2.6" dia. SIN body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane assemblies to diminish effect of reel overlap section and section are section as a section of the section and section and section are section as a section and section a	10 lb T3127A25CG4 13 lb T3127A25CG4 13 lb T3127A25CG4 10 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C 15 lb T2522A25CG 9 lb T2522A25C 10 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319A2S 2AIRWAY MOWERS - FRONT 3 lb T2319T25CG 9 lb T2319T25C 9 lb T2319T25C 9 lb T2319T25S 9.5 lb T2722A3C 11.5 lb T2722A3C 11.5 lb T2722A3C 11.5 lb T2724A3C 11.5 lb T2724A3C 11.5 lb T2724A3C 12 lb T2724A3C 11.5 lb T2724A3C 12 lb T2724A3C 11.5 lb T27519A2C 10.5 lb T2519A2C 10.5 lb T2519A2C 10.5 lb T2519A2S	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft 22.45" body, 25.87" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 23" shaft 19.25" body, 27" shaft 22.45" body, 27" shaft 22.45" body, 27" shaft 22.45" body, 27" shaft 24.45" body, 27" shaft 24.45" body, 27" shaft 24.45" body, 27" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 27" shaft (Sectional rollers with 4 bodies also available) 19.45" body, 27" shaft (Sectional rollers with 4 bodies also available)	SHA3104ATNI SHA3127ATN4 SHA3127ATN4 SHA3127ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319TT SHA2319TT SHA2319TT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT SHA2719AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT SHA2519AT SHA2519AT SHA2519AT SHA2519AT SHA2519AT
2 bodies 2.5" smooth Urethane (2x4.75" wide bodies) 2.5" dia. FOUR body rollers 4 bodies 2.5" grooved Urethane (4x6.5" wide bodies) no flats 4 bodies 2.5" smooth Urethane (4x6.5" wide bodies) 2.5" dia. SIX body rollers 6 bodies 2.5" grooved Urethane (4x6.5" inner+2x2" outer bodies) 6 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 7 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane (4x6.5" inner+2x2" outer bodies) 8 bodies 2.5" smooth Urethane roller assemblies to diminish effect of reel overlap so 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 9 bodies 2.5" grooved Urethane no flats 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3." dia. SINGLE body rollers 3." grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 7 oro 3550D, 3555D, 3575D, 5200D, 5210D, 5400D, 5410D, 5510D, 5610D for 2" dia. SINGLE body rollers 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2" wide grooved Urethane 1" flats 2" smooth Urethane	10 lb T3127A25CG4 13 lb T3127A25CG4 13 lb T3127A25C4 10 lb T3727A25CG4+2C 13 lb T3727A25CG4+2C 13 lb T3727A25C4+2C shadowing are available 9 lb T2522A25CG 9 lb T2522A25C 10 lb T2522A25C 10 lb T2522A25C 10 lb T2522A25S diameter also available) 6.5 lb T2319A2CGF 7.5 lb T2319A2C 10.5 lb T2319A2C 10.5 lb T2319T25CG 9 lb T2319T25CG 9 lb T2319T25C 9 lb T2319T25C 9 lb T2722A3C 11.5 lb T2724A3C 11.5 lb T2519A2CGF 7.5 lb T2319A2CGF 7.5 lb T2319A2CGF 7.5 lb T2519A2CGF 7.5 lb T2519A2CGF 7.5 lb T2519A2CGF 7.5 lb T2519A2CGF	2 short twin bodies at ends of a 31" shaft non-skidding for tight turns & ground undulations 4 short bodies, 31" shaft 4 short bodies, 31" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 2 center bodies + 2 short outer bodies, 37" shaft 4 center bodies + 2 short outer bodies, 37" shaft 2 2.45" body, 25.87" shaft 2 2.45" body, 25.87" shaft 2 2.45" body, 25.87" shaft 2 2.5" body, 25.87" shaft 2 2.5" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft 19.25" body, 23" shaft 19.45" body, 23" shaft 19.45" body, 23" shaft 19.45" body, 23" shaft 2 2.45" body, 27" shaft 2 2.5" body, 27" shaft 3 2.5" body, 25" shaft	SHA3104ATNI SHA3127ATN4 SHA3127ATN4 SHA3127ATN4+2 SHA3727ATN4+2 SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2522AT SHA2319AT SHA2319AT SHA2319TT SHA2319TT SHA2319TT SHA2319TT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2722AT SHA2724AT SHA2724AT SHA2724AT SHA2724AT SHA27319AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT SHA2319AT SHA2519AT SHA2519AT



	- INTERNATION		
2.5" dia. SINGLE body rollers			
2.5" grooved Urethane no flats	8 lb T2319A25CG	19.45" body, 23" shaft	SHA2319AT
2.5" smooth Urethane	9 lb T2319A25C	19.45" body, 23" shaft	SHA2319AT
2.5" smooth Steel	9 lb T2319A25S	19.25" body, 23" shaft	SHA2319AT
2.5" grooved Urethane no flats	8 lb T2519A25CG	19.45" body, 25" shaft	SHA2519AT
2.5" smooth Urethane	9 lb T2519A25C	19.45" body, 25" shaft	SHA2519AT
2.5" smooth Steel	9 lb T2519A25S	19.25" body, 25" shaft	SHA2519AT
2.5" grooved Urethane no flats	8.5 lb T2321A25CG	21.45" body, 23.75" shaft	SHA2321AT
2.5" smooth Urethane	9.5 lb T2321A25C	21.45" body, 23.75" shaft	SHA2321AT
2.5" smooth Steel	9.2 lb T2321A25S	21.25" body, 23.75" shaft	SHA2321AT
2.5" grooved Urethane no flats	8.5 lb T2521C25CG	21.45" body, 25.5" shaft	SHA2521CT
2.5" smooth Urethane	9.5 lb T2521C25C	21.45" body, 25.5" shaft	SHA2521CT
2.5" smooth Steel	10 lb T2521C25S	21.25" body, 25.5" shaft	SHA2521CT
2.5" grooved Urethane no flats	8.5 lb T2522C25CG	22.45" body, 25.5" shaft	SHA2522CT
2.5" smooth Urethane	9.5 lb T2522C25C	22.45" body, 25.5" shaft	SHA2522CT
2.5" smooth Steel	10 lb T2522C25S	22.25" body, 25.5" shaft	SHA2522CT
3" dia. SINGLE body rollers			
3" grooved Urethane no flats	9 lb T2319T3CG	19.45" body, 23" shaft	SHA2319TT
3" smooth Urethane	11 lb T2319T3C	19.45" body, 23" shaft	SHA2319TT
3" smooth Steel	11 lb T2319T3S	19.25" body, 23" shaft	SHA2319TT
3" grooved Urethane no flats	9 lb T2519A3CG	19.45" body, 25" shaft	SHA2519AT
3" smooth Urethane	11 lb T2519A3C	19.45" body, 25" shaft	SHA2519AT
3" smooth Steel	11 lb T2519A3S	19.25" body, 25" shaft	SHA2519AT
3" grooved Urethane no flats	9.5 lb T2522C3CG	22.45" body, 25.5" shaft	SHA2522CT
3" smooth Urethane	12 lb T2522C3C	22.45" body, 25.5" shaft	SHA2522CT
3" smooth Steel	11.5 lb T2522C3S	22.25" body, 25.5" shaft	SHA2522CT
o 5500D, 6500D & 6700D FAIRWAY MOWERS - FRONT & BA		(Sectional rollers with 4 bodies also available)	
2.5" dia. SINGLE body rollers		, and the state of	
2.5" grooved Urethane no flats	8 lb T2419A25CG	19.45" body, 24.5" shaft	SHA2419AT
2.5" smooth Urethane	9 lb T2419A25C	19.45" body, 24.5" shaft	SHA2419AT
2.5" smooth Steel	9 lb T2419A25S	19.25" body, 24.5" shaft	SHA2419AT
2.5" grooved Urethane no flats	8.5 lb T2421A25CG	21.45" body, 24.5" shaft	SHA2421AT
2.5" smooth Urethane	9.5 lb T2421A25C	21.45" body, 24.5" shaft	SHA2421AT
2.5" smooth Steel	10 lb T2421A25S	21.25" body, 24.5" shaft	SHA2421AT
2.5" grooved Urethane no flats	9 lb T2422A25CG	22.45" body, 24.5" shaft	SHA2422AT
[PROCESTATE PROCESTATE PROC	9.5 lb T2422A25CG	22.45" body, 24.5" shaft	SHA2422AT
2.5" smooth Urethane			
2.5" smooth Steel	10 lb T2422A25S	22.25" body, 24.5" shaft	SHA2422AT
2.5" grooved Urethane no flats	8 lb T2519A25CG	19.45" body, 25" shaft	SHA2519AT
2.5" smooth Urethane	9 lb T2519A25C	19.45" body, 25" shaft	SHA2519AT
2.5" smooth Steel	9 lb T2519A25S	19.25" body, 25" shaft	SHA2519AT
2.5" wide grooved (1" spacing) Urethane no flats	9 lb T2522A25CG	22.45" body, 25.87" shaft	SHA2522AT
2.5" narrow grooved (1/2" spacing) Urethane no flats	9 lb T2522A25NG	22.45" body, 25.87" shaft	SHA2522AT
2.5" smooth Urethane	9.5 lb T2522A25C	22.45" body, 25.87" shaft	SHA2522AT
2.5" smooth Steel	10 lb T2522A25S	22.25" body, 25.87" shaft	SHA2522AT
To diminish instances of shadowing lines due to overl	ap of reels	call for proper application specifics	
2.5" grooved Urethane with 2" wide smooth ends	9.5 lb T2522A25CG.22C	front roller for rear mower heads-use with T2519A25C	SHA2522AT
2.5" smooth Urethane	11 lb T2519A25C	back roller for rear mower heads-use with T2522A25CG.22C	SHA2519AT
(please confirm diameter of body and length of shaft require	red to fit BACK ROLLER)		
3" dia. SINGLE body rollers			
3" grooved Urethane no flats	9.5 lb T2522A3CG	22.45" body, 25.87" shaft	SHA2522AT
3" smooth Urethane	12 lb T2522A3C	22.45" body, 25.87" shaft	SHA2522AT
3" smooth Steel	11.5 lb T2522A3S	22,25" body, 25.87" shaft	SHA2522AT
3" grooved Urethane no flats	9.5 lb T2722A3CG	22.45" body, 27" shaft	SHA2722AT
3" smooth Urethane	12 lb T2722A3C	22.45" body, 27" shaft	SHA2722AT
3" smooth Steel	11.5 lb T2722A3S	22.25" body, 27" shaft	SHA2722AT
3" grooved Urethane no flats	9.5 lb T2724A3CG	24.45" body, 27" shaft	SHA2724AT
3" smooth Urethane	12 lb T2724A3C	24.45" body, 27" shaft	SHA2724AT
3" smooth Steel			O. I. LET E TOTAL
3 SHOOTH Steel			SHADTOAAT
To diminish instances of shadowing lines due to over	11.5 lb T2724A3S	24.25" body, 27" shaft	SHA2724AT
To diminish instances of shadowing lines due to overl	ap of reels	call for proper application specifics	
3" grooved Urethane with 2" wide smooth ends	ap of reels 9.5 lb T2722A3CG.22C	call for proper application specifics front roller for rear mower heads-use with T2719A3C	SHA2722AT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C	call for proper application specifics	
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft require	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER)	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C	SHA2722AT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) eel overlap shadowing are available	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics	SHA2722AT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r o SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D 8	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) eel overlap shadowing are available	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C	SHA2722AT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r o SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D 8 2.5" dia. SINGLE body rollers	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) eel overlap shadowing are available 216 - FRONT & BACK ROLLERS	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available)	SHA2722AT SHA2719AT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r o SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D 8 2.5" dia. SINGLE body rollers 2.5" grooved Urethane no flats	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) eel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft	SHA2722AT SHA2719AT SHA3026DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r o SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D 8 2.5" dia. SINGLE body rollers 2.5" grooved Urethane no flats 2.5" smooth Urethane	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) reel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r o SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D 8 2.5" dia. SINGLE body rollers 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) eel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25S	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 26.25" body, 30" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3026DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r o SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D & 2.5" dia. SINGLE body rollers 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 2.5" grooved Urethane no flats	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) eel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25S 10.3 lb T3227D25CG	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 26.25" body, 30" shaft 27.45" body, 32" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3026DT SHA3227DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r to SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D 8 2.5" dia. SINGLE body rollers 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 2.5" grooved Urethane no flats 2.5" smooth Urethane	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) eel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25S	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 26.25" body, 30" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3026DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r o SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D 8 2.5" dia. SINGLE body rollers 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 2.5" grooved Urethane no flats 2.5" smooth Urethane 3" dia. SINGLE body rollers	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) eel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25C 10.3 lb T3227D25CG 11 lb T3227D25C	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA322TDT SHA322TDT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of ro SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D 8 2.5" dia. SINGLE body rollers 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 2.5" grooved Urethane no flats 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) reel overlap shadowing are available 1216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25C 11 lb T3227D25CG 11 lb T3227D25C 12.5 lb T3026D3CG	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 30" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3227DT SHA3227DT SHA3026DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r o SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D 8 2.5" dia. SINGLE body rollers 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane no flats 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" grooved Urethane no flats	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) reel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25C 10.3 lb T3227D25CG 11 lb T3227D25CC 12.5 lb T3026D3CG 13 lb T3026D3C	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 26.45" body, 30" shaft 26.45" body, 30" shaft 26.45" body, 30" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3227DT SHA3227DT SHA3026DT SHA3026DT SHA3026DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of ro SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D 8 2.5" dia. SINGLE body rollers 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 2.5" grooved Urethane no flats 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) reel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25S 10.3 lb T3227D25CG 11 lb T3227D25CC 12.5 lb T3026D3CG 13 lb T3026D3C 13 lb T3026D3C 13 lb T3026D3S	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 30" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3227DT SHA3227DT SHA3026DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r o SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D 8 2.5" dia. SINGLE body rollers 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane no flats 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" grooved Urethane no flats	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) reel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25C 10.3 lb T3227D25CG 11 lb T3227D25CC 12.5 lb T3026D3CG 13 lb T3026D3C	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 26.45" body, 30" shaft 26.45" body, 30" shaft 26.45" body, 30" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3227DT SHA3227DT SHA3026DT SHA3026DT SHA3026DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r to SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D 8 2.5" dia. SINGLE body rollers 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3.5" grooved Urethane no flats 3" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) reel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25S 10.3 lb T3227D25CG 11 lb T3227D25CC 12.5 lb T3026D3CG 13 lb T3026D3C 13 lb T3026D3C 13 lb T3026D3S	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 26.45" body, 30" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3227DT SHA3227DT SHA3026DT SHA3026DT SHA3026DT SHA3026DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r o SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D 8 2.5" dia. SINGLE body rollers 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" grooved Urethane no flats 3" smooth Urethane	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) reel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25S 10.3 lb T3227D25CG 11 lb T3227D25C 12.5 lb T3026D3CG 13 lb T3026D3C 13 lb T3026D3S 12.8 lb T3227D3CG	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 28.45" body, 30" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3227DT SHA3026DT SHA3026DT SHA3026DT SHA3026DT SHA3026DT SHA3026DT SHA3026DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r o SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D 8 2.5" dia. SINGLE body rollers 2.5" smooth Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" grooved Urethane 3" smooth Urethane	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) reel overlap shadowing are available 1216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25C 11.5 lb T3026D25C 11 lb T3227D25C 12.5 lb T3026D3CG 13 lb T3026D3C 13.3 lb T3227D3C 13.3 lb T3227D3C 13.3 lb T3227D3C	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 30" shaft 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.25" body, 32" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3227DT SHA3026DT SHA3026DT SHA3026DT SHA3026DT SHA3026DT SHA3026DT SHA3025DT SHA3027DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of roo SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D & 2.5" dia. SINGLE body rollers 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane no flats 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" smooth Urethane 3" smooth Steel 3" smooth Urethane 3" smooth Steel	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) reel overlap shadowing are available 1216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25C 11.5 lb T3026D25C 11 lb T3227D25C 12.5 lb T3026D3CG 13 lb T3026D3C 13.3 lb T3227D3C 13.3 lb T3227D3C 13.3 lb T3227D3C	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 30" shaft 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.25" body, 32" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3227DT SHA3026DT SHA3026DT SHA3026DT SHA3026DT SHA3026DT SHA3026DT SHA3025DT SHA3027DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of ro SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D & 2.5" dia. SINGLE body rollers 2.5" smooth Urethane no flats 2.5" smooth Steel 2.5" grooved Urethane no flats 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 5" SIDEWINDER 32" REEL MOWERS: 3100D & 2600D & 2300 3" grooved Urethane no flats	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) reel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25C 11.5 lb T3026D25C 11 lb T3227D25CC 12.5 lb T3026D3CG 13 lb T3026D3C 14 lb T3026D3C 15 lb T3026D3C 16 lb T3026D3C 17 lb T3026D3C 17 lb T3026D3C 18 lb T3026D3C 18 lb T3026D3C 19 lb T3026D3C 10 lb T3026D3C 11 lb T3026D3C 11 lb T3026D3C 12 lb T3026D3C 13 lb T3026D3C 13 lb T3026D3C 13 lb T3026D3C 14 lb T3026D3C 15 lb T3026D3C 16 lb T3026D3C 17 lb T3026D3C 17 lb T3026D3C 18 lb T3026D3C 18 lb T3026D3C 19 lb T3026D3C 19 lb T3026D3C 10 lb T3026D3C 10 lb T3026D3C 11	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 26.25" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 28.25" body, 30" shaft 29.25" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.25" body, 32" shaft 37.45" body, 32" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3227DT SHA3026DT SHA3026DT SHA3026DT SHA3026DT SHA3027DT SHA3027DT SHA3227DT SHA3227DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r o SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D & 2.5" dia. SINGLE body rollers 2.5" smooth Urethane 2.5" smooth Steel 2.5" grooved Urethane no flats 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel O SIDEWINDER 32" REEL MOWERS: 3100D & 2600D & 2300 3" grooved Urethane no flats 3" smooth Steel	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) reel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25C 11.5 lb T3026D25C 11 lb T3227D25CC 12.5 lb T3026D3CG 13 lb T3026D3C 13 lb T3026D3C 13 lb T3026D3S 12.8 lb T3026D3S 12.8 lb T3027D3CG 13.3 lb T30227D3CG 13.3 lb T30227D3C 13.3 lb T30227D3C 13.3 lb T30227D3C 13.3 lb T30227D3C 13.4 lb T3026D3C 13.5 lb T30227D3C 13.6 lb T30227D3C 13.7 lb T30227D3C 13.8 lb T30227D3C 13.8 lb T30227D3C 13.9 lb T3024D3C 13.9 lb T3024D3C 13.9 lb T3024D3C 13.1 lb T3024D3C 13.1 lb T3024D3C 13.3 lb T304D3C 13.3 lb T304	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 26.45" body, 32" shaft 27.45" body, 30" shaft 28.45" body, 30" shaft 28.45" body, 30" shaft 29.45" body, 30" shaft 27.45" body, 32" shaft 37.45" body, 32" shaft 37.45" body, 32" shaft 37.45" body, 34" shaft body and shaft to match your requirements) 31.45" body, 34.5" shaft 31.25" body, 34.5" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3227DT SHA3227DT SHA3026DT SHA3026DT SHA3026DT SHA3027DT SHA3027DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r o SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D & 2.5" dia. SINGLE body rollers 2.5" smooth Urethane 2.5" smooth Steel 2.5" grooved Urethane no flats 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 3" grooved Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) eel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25C 11 lb T3227D25CC 12.5 lb T3026D3CG 13 lb T3026D3C 13 lb T3026D3C 13 lb T3026D3C 13 lb T3026D3S 12.8 lb T3227D3CG 13.3 lb T3227D3CG 13.3 lb T3227D3C 13.3 lb T3227D3C 13.3 lb T3227D3C 13.1 lb T3431U3CG 15 lb T3431U3CG 15 lb T3431U3CG	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 37.45" body, 32" shaft 37.45" body, 34.5" shaft 31.25" body, 34.5" shaft 31.25" body, 34.5" shaft 31.25" body, 36" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3027DT SHA3026DT SHA3026DT SHA3026DT SHA3026DT SHA3027DT SHA3027DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D & 2.5" dia. SINGLE body rollers 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" grooved Urethane no flats 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) eel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25C 11.5 lb T3026D25C 11 lb T3227D25C 12.5 lb T3026D3CG 13 lb T3026D3C 15 lb T3431U3CG 15 lb T3431U3CG 15 lb T3431U3CG 15 lb T3632U3CG 15 lb T3632U3CG 15 lb T3632U3CS	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 30" shaft 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 37.45" body, 32" shaft 37.45" body, 32" shaft 37.45" body, 34" shaft 37.55" body, 34.5" shaft 37.45" body, 36" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3027DT SHA3027DT SHA3026DT SHA3026DT SHA3026DT SHA3027DT SHA3027DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r o SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D & 2.5" dia. SINGLE body rollers 2.5" smooth Urethane 2.5" smooth Steel 2.5" grooved Urethane no flats 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Steel 5" SIDEWINDER 32" REEL MOWERS: 3100D & 2600D & 2300 3" grooved Urethane no flats 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) seel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25C 11.5 lb T3026D25C 11 lb T3227D25CG 11 lb T3227D25CG 12.5 lb T3026D3C 13 lb T3026D3C 13.3 lb T3026D3C 13.3 lb T3027D3C 13.3 lb T3227D3C 13.5 lb T3431U3CG 15 lb T3431U3CG 15 lb T3431U3S 14 lb T3632U3CG 15 lb T3632U3S 12.5 lb T3431U25S	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 37.45" body, 32" shaft 37.45" body, 34.5" shaft 31.25" body, 34.5" shaft 31.25" body, 34.5" shaft 31.25" body, 36" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3027DT SHA3026DT SHA3026DT SHA3026DT SHA3026DT SHA3027DT SHA3027DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D & 2.5" dia. SINGLE body rollers 2.5" smooth Urethane 2.5" smooth Steel 2.5" smooth Urethane no flats 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 5" smooth Steel 5" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 5" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 2.5" smooth Steel 2.5" smooth Steel	9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) red to fit BACK ROLLER) red overlap shadowing are available red 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25S 10.3 lb T3227D25CG 11 lb T3227D25C 12.5 lb T3026D3CG 13 lb T3026D3C 13 lb T3026D3C 13 lb T3026D3C 13 lb T3026D3C 13 lb T3027D3CG 13.3 lb T3227D3CG 13.3 lb T3227D3C 13.5 lb T3431U3CG 15 lb T3431U3S 14 lb T3632U3S 12.5 lb T3431U25S	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 37.45" body, 32" shaft 37.45" body, 32" shaft 37.25" body, 36" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3227DT SHA3227DT SHA3026DT SHA3026DT SHA3026DT SHA3027DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3431UT SHA3632UT SHA3632UT SHA3431UT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D & 2.5" dia. SINGLE body rollers 2.5" smooth Urethane no flats 2.5" smooth Steel 2.5" grooved Urethane no flats 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 0 SIDEWINDER 32" REEL MOWERS: 3100D & 2600D & 2300 3" grooved Urethane no flats 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 2.5" smooth Steel 2.5" smooth Steel 2.5" smooth Steel 3" grooved Urethane no flats 3" smooth Steel	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) reel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25C 11.5 lb T3026D25C 11 lb T3227D25CC 12.5 lb T3026D3C 13 lb T3027D3CG 13.3 lb T3227D3CG 13.3 lb T3227D3CG 13.3 lb T3227D3C 13.3 lb T3227D3C 13.3 lb T3227D3C 13.3 lb T3227D3C 15 lb T3421U3CG 15 lb T3431U3CG 15 lb T3632U3CG 15 lb T3632U3S 12.5 lb T3431U25S 10 - BACK ROLLER 15 lb T3429U3C	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 26.45" body, 30" shaft 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 37.45" body, 34" shaft 37.45" body, 34.5" shaft 31.25" body, 36" shaft 32.25" body, 36" shaft 32.25" body, 36" shaft 31.25" body, 34.5" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3227DT SHA3227DT SHA3026DT SHA3026DT SHA3026DT SHA3027DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3231UT SHA3431UT SHA3632UT SHA3431UT SHA3431UT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D & 2.5" dia. SINGLE body rollers 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 2.5" smooth Urethane 3" smooth Steel 5" SIDEWINDER 32" REEL MOWERS: 3100D & 2600D & 2300 3" grooved Urethane no flats 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 5" SIDEWINDER 32" REEL MOWERS: 3100D & 2600D & 2300 3" grooved Urethane no flats 3" smooth Steel 5" SIDEWINDER 32" REEL MOWERS: 3100D & 2600D & 2300 3" smooth Steel 5" SIDEWINDER 32" REEL MOWERS: 3100D & 2600D & 2300 3" smooth Urethane 3" smooth Urethane	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) eel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25CS 10.3 lb T3227D25CG 11 lb T3227D25CC 12.5 lb T3026D3CG 13 lb T3026D3C 13 lb T3026D3C 13 lb T3026D3C 13 lb T3026D3C 13 lb T30227D3C 13.3 lb T3227D3C 13.1 lb T3026D3C 15 lb T3431U3S 14 lb T3632U3CG 15 lb T3431U25S 12.5 lb T3431U25S 12.5 lb T3431U25S 13.5 lb T3429U3C 14.5 lb T3429U3C 14.5 lb T3429U3C	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 28.45" body, 30" shaft 28.45" body, 32" shaft 28.45" body, 32" shaft 28.45" body, 32" shaft 28.45" body, 32" shaft 28.45" body, 34" shaft 38.45" body, 34.5" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3227DT SHA3227DT SHA3026DT SHA3026DT SHA3026DT SHA3027DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3431UT SHA3431UT SHA3431UT SHA3431UT SHA3431UT SHA3431UT
3" grooved Urethane with 2" wide smooth ends 3" smooth Urethane (please confirm diameter of body and length of shaft requir 2.5" Combination roller assemblies to diminish effect of r SIDEWINDER 27" REEL MOWERS: 2000D, 2300D, 3100D & 2.5" dia. SINGLE body rollers 2.5" smooth Urethane no flats 2.5" smooth Steel 2.5" grooved Urethane no flats 2.5" smooth Urethane 3" dia. SINGLE body rollers 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 0 SIDEWINDER 32" REEL MOWERS: 3100D & 2600D & 2300 3" grooved Urethane no flats 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 2.5" smooth Steel 2.5" smooth Steel 2.5" smooth Steel 3" grooved Urethane no flats 3" smooth Steel	ap of reels 9.5 lb T2722A3CG.22C 11 lb T2719A3C red to fit BACK ROLLER) reel overlap shadowing are available 216 - FRONT & BACK ROLLERS 10 lb T3026D25CG 11 lb T3026D25C 11.5 lb T3026D25C 11.5 lb T3026D25C 11 lb T3227D25CC 12.5 lb T3026D3C 13 lb T3027D3CG 13.3 lb T3227D3CG 13.3 lb T3227D3CG 13.3 lb T3227D3C 13.3 lb T3227D3C 13.3 lb T3227D3C 13.3 lb T3227D3C 15 lb T3421U3CG 15 lb T3431U3CG 15 lb T3632U3CG 15 lb T3632U3S 12.5 lb T3431U25S 10 - BACK ROLLER 15 lb T3429U3C	call for proper application specifics front roller for rear mower heads-use with T2719A3C back roller for rear mower heads-use with T2722A3CG.22C call for proper application specifics (Sectional rollers with 4 bodies also available) 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 26.45" body, 30" shaft 26.45" body, 30" shaft 26.45" body, 30" shaft 27.45" body, 30" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 27.45" body, 32" shaft 37.45" body, 34" shaft 37.45" body, 34.5" shaft 31.25" body, 36" shaft 32.25" body, 36" shaft 32.25" body, 36" shaft 31.25" body, 34.5" shaft	SHA2722AT SHA2719AT SHA3026DT SHA3026DT SHA3026DT SHA3227DT SHA3227DT SHA3026DT SHA3026DT SHA3026DT SHA3027DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3227DT SHA3231UT SHA3431UT SHA3632UT SHA3431UT SHA3431UT

SHA3429UT 5/16/24 Page 13



Toro REEL MOWERS: 4500D, 4300D, 4000D, 3500D, 450D, 335D	& 350D - FRONT ROLLER		
3" grooved Urethane no flats	14.5 lb T3732K3CG	32.45" body, 37" shaft-9/16" dia. ends	SHA3732KT
3" smooth Steel	16 lb T3732K3S	32.25" body, 37" shaft-9/16" dia. ends	SHA3732KT
3" grooved Urethane no flats	13.5 lb T3229T3CG	29.45" body, 32" shaft	SHA3229TT
3" smooth Urethane	15 lb T3229T3C	29.45" body, 32" shaft	SHA3229TT
3" smooth Steel	15 lb T3229T3S	29.25" body, 32" shaft	SHA3229TT
Toro REEL MOWERS: 4500D, 4000D, 3500D, 450D, 335D, & 350			
3" smooth Urethane	15 lb T3429K3C	29.45" body, 34" shaft	SHA3429KT
3" smooth Steel	15 lb T3429K3S	29.25" body, 34" shaft	SHA3429KT
3.5" smooth Urethane	18 lb T3429K7C	29.45" body, 34" shaft	SHA3429KT
4" smooth Urethane	30 lb T3429K4C	29.45" body, 34" shaft	SHA3429KT
4" smooth Steel	29 lb T3429K4S	29.25" body, 34" shaft	SHA3429KT
Toro REEL MOWERS: SPARTAN FAIRWAY, REELMASTER GAN		24 C 1 C 1 C 1 C 1 C 1 C 1 C 1 C 1 C 1 C	
3" smooth Urethane	14 lb T3227J3C	27.45" body, 32.5" shaft	SHA3227JT
3" smooth Steel	13.5 lb T3227J3S	27.25" body, 32.5" shaft	SHA3227JT
3.5" smooth Urethane	17 lb T3227J7C	27.45" body, 32.5" shaft	SHA3227JT
4" smooth Steel	27 lb T3227J4S	27.25" body, 32.5" shaft	SHA3227JT
Toro ROTARY DECK 4500D, 4700D, 3500D & 3505D - FRONT RO		A CONTRACT OF THE PROPERTY OF	
5" grooved Urethane w/ bearings/seals	5 lb T0505G5CG3	Shaft with mounting hardware included; doesn't use OEM 5/8" bolt	SHA0505GT
5" smooth Urethane (5.2" wide body)	5 lb T0505G5C	Shaft with mounting hardware included; doesn't use OEM 5/8" bolt	SHA0505GT
Toro ROTARY DECK 4500D, 4700D, 3500D & 3505D - BACK RO			
3" dia. SINGLE body rollers			
3" grooved Urethane no flats	13.5 lb T3329A3CG	29.45" body, 33" shaft	SHA3329AT
3" smooth Urethane	15 lb T3329A3C	29.45" body, 33" shaft	SHA3329AT
3" smooth Steel	15 lb T3329A3S	29.25" body, 33" shaft	SHA3329AT
3.5" smooth Urethane	18 lb T3329A7C	29.45" body, 33" shaft	SHA3329AT
3" dia. TWO body rollers	10 10 10023770	non-striping, non-skidding for tight turns & ground und	
2 bodies 3" grooved Urethane (2x5.2" wide bodies) no flats	10.5 lb T3305A3CGt	2 short twin bodies at ends of a 33" shaft	SHA3305ATNt
2 bodies 3" smooth Urethane (2x4" wide bodies)	11 lb T3304A3Ct	2 short twin bodies at ends of a 33" shaft	SHA3305ATNt
2 bodies 3" smooth Steel (2x4" wide bodies)	12 lb T3304A3St	2 short twin bodies at ends of a 33" shaft	SHA3305ATNt
사용하게 보통하게 되었는데 보통하게 보통하게 되었다. 보통하게 보통하게 되었다면 보통하게 되었다면 보통하게 되었다면 보통하게 되었다면 보통하게 되었다면 보통하게 되었다면 보통하게 보통하게 되었다면 보통하게 보통하게 되었다면 보면 보통하게 되었다면 보니요. 되었다면 보통하게 되었다면 보통하게 되었다면 보통하게 되었다면 보통하게 되었다면 보니요. 되었다면 보통하게 되었다면 보니요. 되었다면 보통하게 되었다면 보니요. 되었다면 보통하게 되었다면 보니요. 되었	12 ID 13304A3St	non-skidding for tight turns & ground undulations	SHASSOSATINE
3" dia. FIVE body rollers	12 F IL T222042CCF		CUARRONATAIS
5 bodies 3" grooved Urethane (5x5.2" wide bodies) no flats	13.5 lb T3329A3CG5	5 short bodies, 33" shaft 5 short bodies, 33" shaft	SHA3329ATN5 SHA3329ATN5
5 bodies 3" smooth Urethane (5x5.2" wide bodies)	14 lb T3329A3C5		SHA3329A1N5
Toro ROTARY DECK 4300D - FRONT ROLLER (with extended sl			CULTOSOS
5" grooved Urethane w/ bearings/seals	5 lb T0705G5CG3	Shaft with mounting hardware included; doesn't use OEM 5/8" bolt	SHA0705GT
5" smooth Urethane (5.2" wide body)	5.5 lb T0705G5C	Shaft with mounting hardware included; doesn't use OEM 5/8" bolt	SHA0705GT
Toro ROTARY DECK 4300D - BACK ROLLER (3.5" dia. rollers n	nay be available-please call)		
3" dia. SINGLE body rollers		No and also present to appropriate in	
3" grooved Urethane no flats	11 lb T2824K3CG	24.45" body, 28" shaft	SHA2824KT
3" smooth Urethane	12 lb T2824K3C	24.45" body, 28" shaft	SHA2824KT
3" smooth Steel	11 lb T2824K3S	24.25" body, 28" shaft	SHA2824KT
3" dia. TWO body rollers		non-striping, non-skidding for tight turns & ground und	
bodies 3" grooved Urethane (2x5.2" wide bodies) no flats	10.5 lb T2805K3CGt	2 short twin bodies at ends of a 28" shaft	SHA2805KTNt
bodies 3" smooth Urethane (2x4" wide bodies)	11 lb T2804K3Ct	2 short twin bodies at ends of a 28" shaft	SHA2804KTNt
2 bodies 3" smooth Steel (2x4" wide bodies)	12 lb T2804K3St	2 short twin bodies at ends of a 28" shaft	SHA2804KTNt
3" dia. FOUR body rollers		non-skidding for tight turns & ground undulations	
4 bodies 3" grooved Urethane (4x5.2" wide bodies) no flats	12.5 lb T2824K3CG4	4 short bodies, 28" shaft	SHA2824KTN4
4 bodies 3" smooth Urethane (4x5.2" wide bodies)	13.5 lb T2824K3C4	4 short bodies, 28" shaft	SHA2824KTN4
Toro 22" VERTICUT heads (Call to confirm dimensions of your	roller)	(Sectional rollers with 4 bodies also available)	
2" smooth Steel heavy (1/4" wall)	10 lb T2419A2S	19.25" body, 24" shaft	SHA2419AT
2" smooth Steel heavy (1/4" wall)	10.5 lb T2321A2S	21.25" body, 23" shaft	SHA2321AT



for RANSOMES mowers

for RANSOMES mowers ANSOMES ALL 22" GREENSPLEX & E-PLEX & 160 - FRONT RE	OLLER		
2" dia. SINGLE body rollers			
2" wide grooved Urethane no flats	6.5 lb R2522A2CG	22.45" body, 25.875" shaft	SHA2522AJ
2" narrow grooved Urethane no flats	6.7 lb R2522A2NG	22.45" body, 25.875" shaft	SHA2522AJ
2" wide grooved Urethane 1" flats	6.5 lb R2522A2CGF	22.45" body, 25.875" shaft	SHA2522AJ
2" narrow grooved Urethane 1" flats	6.7 lb R2522A2NGF	22.45" body, 25.875" shaft	SHA2522AJ
2" smooth Urethane	8 lb R2522A2C	22.25" body, 25.875" shaft	SHA2522AJ
2" smooth Steel heavy (1/4" wall)	11.5 lb R2522A2S	22.25" body, 25.875" shaft	SHA2522AJ
2" dia. FOUR body rollers			
bodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb R2522A2CGF4	4 short bodies, 25.875" shaft	SHA2522AJN4
bodies 2" smooth Urethane (4x5.55" wide bodies)	8.5 lb R2522A2C4	4 short bodies, 25.875" shaft	SHA2522AJN4
bodies 2" smooth Steel heavy (4x5.55" wide bodies)	12 lb R2522A2S4	4 short bodies, 25.875" shaft	SHA2522AJN4
2.5" dia. SINGLE body rollers			
2.5" wide grooved (1" spacing) Urethane no flats	9 lb R2522A25CG	22.45" body, 25.875" shaft	SHA2522AJ
2.5" narrow grooved (1/2" spacing) Urethane no flats	9 lb R2522A25NG	22.45" body, 25.875" shaft	SHA2522AJ
2.5" smooth Urethane	9.5 lb R2522A25C	22.25" body, 25.875" shaft	SHA2522AJ
2.5" smooth Steel	10 lb R2522A25S	22.25" body, 25.875" shaft	SHA2522AJ
2.5" dia. FOUR body rollers	10 ID 112322A230	non-skidding for tight turns & ground undulations	
	10 E IL D2522425004	4 short bodies, 25.875" shaft	SHA2522AJN4
podies 2.5" grooved Urethane (4x5.55" wide bodies) no flats	10.5 lb R2522A25CG4		
odies 2.5" smooth Urethane (4x5.55" wide bodies)	8.5 lb R2522A25C4	4 short bodies, 25.875" shaft	SHA2522AJN4
odies 2.5" smooth Steel (4x5.55" wide bodies)	12 lb R2522A25S4	4 short bodies, 25.875" shaft	SHA2522AJN4
ANSOMES 300 & 500 GREENSMOWERS - BACK ROLLER			
2" dia. SINGLE body rollers			
2" wide grooved Urethane 1" flats	6.5 lb R2422S2CGF	22.45" body , 24.25" shaft-3/8" taps	SHA2422SJ
2" smooth Urethane	8 lb R2422S2C	22.25" body , 24.25" shaft-3/8" taps	SHA2422SJ
2" smooth Steel heavy (1/4" wall)	11.5 lb R2422S2S	22.25" body , 24.25" shaft-3/8" taps	SHA2422SJ
2" wide grooved Urethane 1" flats	6.5 lb R2422G2CGF	22.45" body , 24.25" shaft-7/16" taps	SHA2422GJ
2" smooth Urethane	8 lb R2422G2C	22.25" body , 24.25" shaft-7/16" taps	SHA2422GJ
2" smooth Steel heavy (1/4" wall)	11.5 lb R2422G2S	22.25" body , 24.25" shaft-7/16" taps	SHA2422GJ
2" dia. FOUR body rollers	THO IS THE TEE SES	non-skidding for tight turns & ground undulations	
poodies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb R2422S2CGF4	4 bodies @22.3" oal, shaft-3/8" taps	SHA2422SJN4
단어 있어요요요. 그리면 아프리아 (국) 이 아이 아이 아이를 하지만 하지만 하다고 있다면 아이를 하는데 아이를 하지만 하지만 하는데 하는데 아이트 (H) 아이트 (H) 아이트 (H) 아이트 (H)		4 short bodies, 24.25" shaft	SHA2422SJN4
podies 2" smooth Urethane (4x5.55" wide bodies)	8.5 lb R2422S2C4		
odies 2" smooth Steel heavy (4x5.55" wide bodies)	12 lb R2422S2S4	4 short bodies, 24.25" shaft	SHA2422SJN4
odies 2" wide grooved Urethane (4x5.55" wide bodies) 1" flats	8.5 lb R2422G2CGF4	4 short bodies, 24.25" shaft	SHA2422GJN4
odies 2" smooth Urethane (4x5.55" wide bodies)	8.5 lb R2422G2C4	4 short bodies, 24.25" shaft	SHA2422GJN4
odies 2" smooth Steel heavy (4x5.55" wide bodies)	12 lb R2422G2S4	4 short bodies, 24.25" shaft	SHA2422GJN4
ANSOMES MOTOR 180D, 180 TRIPLEX & TRIPLE 18 - ALL ROL	LERS		
2.5" grooved Urethane no flats	9 lb R2826G25CG	7/16" taps in shaft ends	SHA2826GR
2.5" smooth Urethane	11.5 lb R2826G25C	7/16" taps in shaft ends	SHA2826GR
2.5" smooth Steel	12 lb R2826G25S	26.25" body, 7/16" taps	SHA2826GR
ANSOMES 250 LIGHTWEIGHT FAIRWAY - 33 HP/ 6" DIA. REELS	- ALL ROLLERS		
3" grooved Urethane no flats	13 lb R2722R3CG	22.45" body, 27" shaft	SHA2722RR
3" smooth Urethane	15 lb R2722R3C	22.45" body, 27" shaft	SHA2722RR
3" smooth Steel	15 lb R2722R3S	22.45" body, 27" shaft	SHA2722RR
ANSOMES 250 LIGHTWEIGHT FAIRWAY - 28 HP/ 2WD REELS - I			
3" grooved Urethane no flats	13 lb R2622A3CG	22.45" body, 26" shaft	SHA2622AR
3" smooth Urethane	15 lb R2622A3C	22.45" body, 26" shaft	SHA2622AR
3" smooth Steel	15 lb R2622A3S		SHA2622AR
		22.45" body, 26" shaft	SHAZOZZAR
ANSOMES 250 LIGHTWEIGHT FAIRWAY - 23 HP/ 5" DIA. REELS		Construction and Construction	
3" grooved Urethane no flats	13 lb R2722A3CG	22.45" body, 27.5" shaft	SHA2722AR
3" smooth Urethane	15 lb R2722A3C	22.45" body, 27" shaft	SHA2722AR
3" smooth Steel	15 lb R2722A3S	22.45" body, 27.5" shaft	SHA2722AR
ANSOMES 250 LIGHTWEIGHT FAIRWAY - 23 HP/ 5" DIA. REELS	- BACK ROLLER		
2.5" grooved Urethane no flats	9 lb R2421S25CG	3/8" taps in shaft ends	SHA2421SJ
2.5" smooth Urethane	9.5 lb R2421S25C	3/8" taps in shaft ends	SHA2421SJ
2.5" smooth Steel	10 lb R2421S25S	21.25" body, 3/8" taps	SHA2421SJ
2.5" grooved Urethane no flats	9 lb R2421G25CG	7/16" taps in shaft ends	SHA2421GJ
2.5" smooth Urethane	8 lb R2421G25C	7/16" taps in shaft ends	SHA2421GJ
2.5" smooth Steel	12 lb R2421G25S	21.25" body, 7/16" taps	SHA2421GJ
ANSOMES 26" FAIRWAY 300, 305, 405 & 26" T-PLEX 185D - AL			011112121
	13 lb R3026T3CG	26.45" body, 30" shaft	SHA3026TR
3" grooved Urethane no flats	15 lb R3026T3C	TO STATE OF THE ST	SHA3026TR
	15 ID R3U2613G	26.45" body, 30" shaft	
3" smooth Urethane			
3" smooth Steel	15 lb R3026T3S	26.45" body, 30.5" shaft	SHA3026TR
3" smooth Steel ANSOMES 30" T-PLEX 185D - ALL ROLLERS	15 lb R3026T3S		
3" smooth Steel ANSOMES 30" T-PLEX 185D - ALL ROLLERS 3" grooved Urethane no flats	15 lb R3026T3S 13 lb R3429T3CG	29.45" body, 34.5" shaft	SHA3429TR
3" smooth Steel NSOMES 30" T-PLEX 185D - ALL ROLLERS	15 lb R3026T3S		
3" smooth Steel ANSOMES 30" T-PLEX 185D - ALL ROLLERS 3" grooved Urethane no flats	15 lb R3026T3S 13 lb R3429T3CG	29.45" body, 34.5" shaft	SHA3429TR
3" smooth Steel ANSOMES 30" T-PLEX 185D - ALL ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel	15 lb R3026T3S 13 lb R3429T3CG 15 lb R3429T3C 15 lb R3429T3S	29.45" body, 34.5" shaft 29.45" body, 34" shaft	SHA3429TR SHA3429TR
3" smooth Steel ANSOMES 30" T-PLEX 185D - ALL ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel	15 lb R3026T3S 13 lb R3429T3CG 15 lb R3429T3C 15 lb R3429T3S	29.45" body, 34.5" shaft 29.45" body, 34" shaft	SHA3429TR SHA3429TR
3" smooth Steel NSOMES 30" T-PLEX 185D - ALL ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel NSOMES 350D, 213D, 465, 5/3 MOTOR, 5 MOUNTED, 5/7 & 34/1 2.5" grooved Urethane no flats	15 lb R3026T3S 13 lb R3429T3CG 15 lb R3429T3C 15 lb R3429T3S 0 (27" REEL) - ALL ROLLERS 9 lb R3127G25CG	29.45" body, 34.5" shaft 29.45" body, 34" shaft 29.25" body, 34.5" shaft 27.45" body, 31.62" shaft-7/16" taps	SHA3429TR SHA3429TR SHA3429TR SHA3127GR
3" smooth Steel ANSOMES 30" T-PLEX 185D - ALL ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel ANSOMES 350D, 213D, 465, 5/3 MOTOR, 5 MOUNTED, 5/7 & 34/2.5" grooved Urethane no flats 2.5" smooth Urethane	15 lb R3026T3S 13 lb R3429T3CG 15 lb R3429T3C 15 lb R3429T3S 0 (27" REEL) - ALL ROLLERS 9 lb R3127G25CG 11.2 lb R3127G25C	29.45" body, 34.5" shaft 29.45" body, 34.5" shaft 29.25" body, 34.5" shaft 27.45" body, 31.62" shaft-7/16" taps 27.45" body, 31.62" shaft-7/16" taps	SHA3429TR SHA3429TR SHA3429TR SHA3127GR SHA3127GR
3" smooth Steel ANSOMES 30" T-PLEX 185D - ALL ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel ANSOMES 350D, 213D, 465, 5/3 MOTOR, 5 MOUNTED, 5/7 & 34/2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel	15 lb R3026T3S 13 lb R3429T3CG 15 lb R3429T3C 15 lb R3429T3S 0 (27" REEL) - ALL ROLLERS 9 lb R3127G25CG 11.2 lb R3127G25C 12 lb R3127G25S	29.45" body, 34.5" shaft 29.45" body, 34.5" shaft 29.25" body, 34.5" shaft 27.45" body, 31.62" shaft-7/16" taps 27.45" body, 31.62" shaft-7/16" taps 27.25" body, 31.62" shaft-7/16" taps	SHA3429TR SHA3429TR SHA3429TR SHA3127GR SHA3127GR SHA3127GR
3" smooth Steel ANSOMES 30" T-PLEX 185D - ALL ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel ANSOMES 350D, 213D, 465, 5/3 MOTOR, 5 MOUNTED, 5/7 & 34/2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 3" grooved Urethane no flats	15 lb R3026T3S 13 lb R3429T3CG 15 lb R3429T3C 15 lb R3429T3C 15 lb R3429T3S 0 (27" REEL) - ALL ROLLERS 9 lb R3127G25CG 11.2 lb R3127G25C 12 lb R3127G25S 12.4 lb R3529A3CG	29.45" body, 34.5" shaft 29.45" body, 34.5" shaft 29.25" body, 34.5" shaft 27.45" body, 31.62" shaft-7/16" taps 27.45" body, 31.62" shaft-7/16" taps 27.25" body, 31.62" shaft-7/16" taps 29.45" body, 35" shaft	SHA3429TR SHA3429TR SHA3429TR SHA3127GR SHA3127GR SHA3127GR SHA3127GR SHA3529AR
3" smooth Steel ANSOMES 30" T-PLEX 185D - ALL ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel ANSOMES 350D, 213D, 465, 5/3 MOTOR, 5 MOUNTED, 5/7 & 34/ 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 3" grooved Urethane no flats 3" smooth Urethane	15 lb R3026T3S 13 lb R3429T3CG 15 lb R3429T3C 15 lb R3429T3C 15 lb R3429T3S 0 (27" REEL) - ALL ROLLERS 9 lb R3127G25CG 11.2 lb R3127G25C 12 lb R3127G25S 12.4 lb R3529A3CG 15 lb R3529A3C	29.45" body, 34.5" shaft 29.45" body, 34.5" shaft 29.25" body, 34.5" shaft 27.45" body, 31.62" shaft-7/16" taps 27.45" body, 31.62" shaft-7/16" taps 27.25" body, 31.62" shaft-7/16" taps 29.45" body, 35" shaft 29.45" body, 35" shaft	SHA3429TR SHA3429TR SHA3429TR SHA3127GR SHA3127GR SHA3127GR SHA3127GR SHA3529AR SHA3529AR
3" smooth Steel ANSOMES 30" T-PLEX 185D - ALL ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel ANSOMES 350D, 213D, 465, 5/3 MOTOR, 5 MOUNTED, 5/7 & 34/ 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Steel	15 lb R3026T3S 13 lb R3429T3CG 15 lb R3429T3C 15 lb R3429T3C 15 lb R3429T3S 0 (27" REEL) - ALL ROLLERS 9 lb R3127G25CG 11.2 lb R3127G25C 12 lb R3127G25S 12.4 lb R3529A3CG	29.45" body, 34.5" shaft 29.45" body, 34.5" shaft 29.25" body, 34.5" shaft 27.45" body, 31.62" shaft-7/16" taps 27.45" body, 31.62" shaft-7/16" taps 27.25" body, 31.62" shaft-7/16" taps 29.45" body, 35" shaft	SHA3429TR SHA3429TR SHA3429TR SHA3127GR SHA3127GR SHA3127GR SHA3127GR SHA3529AR
3" smooth Steel NSOMES 30" T-PLEX 185D - ALL ROLLERS 3" grooved Urethane no flats 3" smooth Steel NSOMES 350D, 213D, 465, 5/3 MOTOR, 5 MOUNTED, 5/7 & 34/2 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Steel NSOMES ROTARY AR-250, AR-2500 DECK - BACK ROLLER	15 lb R3026T3S 13 lb R3429T3CG 15 lb R3429T3C 15 lb R3429T3S 0 (27" REEL) - ALL ROLLERS 9 lb R3127G25CG 11.2 lb R3127G25C 12 lb R3127G25S 12.4 lb R3529A3CG 15 lb R3529A3C	29.45" body, 34.5" shaft 29.45" body, 34.5" shaft 29.25" body, 34.5" shaft 27.45" body, 31.62" shaft-7/16" taps 27.45" body, 31.62" shaft-7/16" taps 27.25" body, 31.62" shaft-7/16" taps 29.45" body, 35" shaft 29.45" body, 35" shaft 29.25" body, 35" shaft	SHA3429TR SHA3429TR SHA3127GR SHA3127GR SHA3127GR SHA3127GR SHA3529AR SHA3529AR SHA3529AR
3" smooth Steel ANSOMES 30" T-PLEX 185D - ALL ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel ANSOMES 350D, 213D, 465, 5/3 MOTOR, 5 MOUNTED, 5/7 & 34/ 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 3" grooved Urethane no flats 3" grooved Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Steel ANSOMES ROTARY AR-250, AR-2500 DECK - BACK ROLLER 3.5" smooth Urethane	15 lb R3026T3S 13 lb R3429T3CG 15 lb R3429T3C 15 lb R3429T3S 0 (27" REEL) - ALL ROLLERS 9 lb R3127G25CG 11.2 lb R3127G25C 12 lb R3127G25S 12.4 lb R3529A3C 15 lb R3529A3S 27 lb R2722X7C	29.45" body, 34.5" shaft 29.45" body, 34.5" shaft 29.25" body, 34.5" shaft 29.25" body, 31.62" shaft-7/16" taps 27.45" body, 31.62" shaft-7/16" taps 27.25" body, 31.62" shaft-7/16" taps 29.45" body, 35" shaft 29.45" body, 35" shaft 29.25" body, 35" shaft 29.25" body, 27.25" shaft-1/2" dia. ends	SHA3429TR SHA3429TR SHA3429TR SHA3127GR SHA3127GR SHA3127GR SHA3529AR SHA3529AR SHA3529AR SHA3529AR
3" smooth Steel ANSOMES 30" T-PLEX 185D - ALL ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel ANSOMES 350D, 213D, 465, 5/3 MOTOR, 5 MOUNTED, 5/7 & 34/ 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Steel ANSOMES ROTARY AR-250, AR-2500 DECK - BACK ROLLER	15 lb R3026T3S 13 lb R3429T3CG 15 lb R3429T3C 15 lb R3429T3S 0 (27" REEL) - ALL ROLLERS 9 lb R3127G25CG 11.2 lb R3127G25C 12 lb R3127G25S 12.4 lb R3529A3CG 15 lb R3529A3C	29.45" body, 34.5" shaft 29.45" body, 34.5" shaft 29.25" body, 34.5" shaft 27.45" body, 31.62" shaft-7/16" taps 27.45" body, 31.62" shaft-7/16" taps 27.25" body, 31.62" shaft-7/16" taps 29.45" body, 35" shaft 29.45" body, 35" shaft 29.25" body, 35" shaft	SHA3429TR SHA3429TR SHA3429TR SHA3127GR SHA3127GR SHA3127GR SHA3529AR SHA3529AR SHA3529AR



urf Smoothing Heads Rollers for RS48-11E machine	0.5 lb T00000050	20 455 hade 20 0058 shall 0/55	
2.5" smooth Urethane	9.5 lb T2222S25C	22.45" body, 22.625" shaft-3/8" taps	SHA2222ST
2.5" smooth Steel	9.2 lb T2222S25S	22.25" body, 22.625" shaft-3/8" taps	SHA2222ST
Irf Smoothing Heads Rollers for RB48-11A machine (4 shor 2.5" smooth Urethane	9.5 lb T2222R25C	22.45" body short rollers, 22.716" shaft (4 per machine)	SHA2222RT
2.5" smooth Steel	9.2 lb T2222R25S	22.25" body short rollers, 22.716" shaft (4 per machine)	SHA2222RT
2.5" smooth Green	10 lb T2524R25C	24.45" body long rollers, 25.078" shaft (2 per machine)	SHA2522RT
2.5" smooth Steel	9.6 lb T2524R25S	24.25" body long rollers, 25.078" shaft (2 per machine)	SHA2522RT
orf Smoothing Heads Rollers for R50-11 machine (4 short &		E-120 Dody long londing Easter o Shall (E-por Internity)	OTH ECELITY
2.5" smooth Urethane	9.5 lb T2222Y25C	22.45" body short rollers, 22.75" shaft (4 per machine)	SHA2222YT
2.5" smooth Steel	9.2 lb T2222Y25S	22.25" body short rollers, 22.75" shaft (4 per machine)	SHA2222YT
2.5" smooth Urethane	10 lb T2524Y25C	24.45" body long rollers, 25" shaft (2 per machine)	SHA2524YT
2.5" smooth Steel	9.6 lb T2524Y25S	24.25" body long rollers, 25" shaft (2 per machine)	SHA2524YT
orf Smoothing Heads Rollers for GR39 machine			
2.5" smooth Urethane	15.5 lb T3939S25C	39.45" body, 39.812" shaft-3/8" taps	SHA3939ST
2.5" smooth Steel	15.5 lb T3939S25S	39.25" body, 39.812" shaft-3/8" taps	SHA3939ST
orf Smoothing Heads Rollers for TR7000C machine			
2.5" smooth Urethane (2 bodies)	15.5 lb TT3939S25C2	2 body assembly at 39.5" total length, 39.812" shaft	SHA3939ST
2.5" smooth Steel (2 bodies)	15.5 lb TT3939S25S2	2 body assembly at 39.5" total length, 39.812" shaft	SHA3939ST
rf Smoothing Heads Rollers for R52 machine (9 rollers per	machine)		
2.5" smooth Urethane	9 lb T1818S25C	18.45" body, 18.5" shaft-3/8" taps (9 per machine)	SHA1818ST
2.5" smooth Steel	8.7 lb T1818S25S	18.25" body, 18.5" shaft-3/8" taps (9 per machine)	SHA1818ST
rf Smoothing Heads Rollers for TR66 Spikes machine			
2.5" smooth Urethane	9.5 lb TT2422S25C	22.45" body, 24.25" shaft-3/8" taps	SHA2422ST
2.5" smooth Steel	9.2 lb TT2422S25S	22.25" body, 24.25" shaft-3/8" taps	SHA2422ST
(DENNIO			
for DENNIS			
Walking mower - ALL ROLLERS (handlebar bushings nee	2 3 5 3 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5		
3.5" smooth Urethane	21 lb D3834G7C	34.45" body, 38.5" shaft-7/16" taps	SHA3834GD
Handlebar bushing (2 per roller)	2SLEEVE 1.25x.5x1.2 PU		
for CUIDALIDA & LUICTLED			
for SHIBAURA & HUSTLER		(Multi bady rallers also available)	
Ira G EXE 26 Greens Mower	10 lb S2826P25CG	(Multi-body rollers also available) 26.45° body, 28.375° shaft	SHA2826PS
2.5" grooved Urethane no flats			
2.5" smooth Urethane	12.5 lb S2826P25C	26.45" body, 28.375" shaft	SHA2826PS
2.5" smooth Steel	12.5 lb S2826P25S	26.25" body, 28.375" shaft	SHA2826PS
2" smooth Urethane	8.5 lb S2826P2C	26.25" body, 28.375" shaft	SHA2826PS
OF 11 O. 11 1444F W.			
2" smooth Steel heavy (1/4" wall)	12 lb S2826P2S	26.25" body, 28.375" shaft	SHA2826PS
ıra G Flow22 & MG70 & Hustler GM1500 Greens Mower		(Multi-body rollers also available)	
ura G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats	6.5 lb S2522P2CGF	(Multi-body rollers also available) 22.45" body, 25.75" shaft	SHA2522PS
ura G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane	6.5 lb S2522P2CGF 8 lb S2522P2C	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft	SHA2522PS SHA2522PS
ura G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall)	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft	SHA2522PS SHA2522PS SHA2522PS
ura G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P25CG	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft	SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P25CG 9 lb S2522P25NG	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P25CG 9 lb S2522P25NG 11.5 lb S2522P25C	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P25CG 9 lb S2522P25NG	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel Ira SR525 Fairway & Hustler 7500 & 7700 Fairway	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P2SG 9 lb S2522P25NG 11.5 lb S2522P25C 12 lb S2522P25S	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available)	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 4 SR525 Fairway & Hustler 7500 & 7700 Fairway 3" grooved Urethane no flats	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P25CG 9 lb S2522P25NG 11.5 lb S2522P25C 12 lb S2522P25S	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel Ira SR525 Fairway & Hustler 7500 & 7700 Fairway 3" grooved Urethane no flats 3" smooth Urethane	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P25CG 9 lb S2522P25NG 11.5 lb S2522P25C 12 lb S2522P25S	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ara G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel ara SR525 Fairway & Hustler 7500 & 7700 Fairway 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P25CG 9 lb S2522P25NG 11.5 lb S2522P25C 12 lb S2522P25S	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ara G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel ura SR525 Fairway & Hustler 7500 & 7700 Fairway 3" grooved Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Steel ura SR370	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P25CG 9 lb S2522P25NG 11.5 lb S2522P25C 12 lb S2522P25S 10.5 lb S2522P3CG 12.5 lb S2522P3C	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) (Multi-body rollers also available)	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ara G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel ara SR525 Fairway & Hustler 7500 & 7700 Fairway 3" grooved Urethane 3" smooth Urethane 3" smooth Steel ara SR370 3" grooved Urethane no flats	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P2SG 9 lb S2522P25CG 11.5 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3S	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 10 SR525 Fairway & Hustler 7500 & 7700 Fairway 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 10 SR370 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" grooved Urethane no flats 3" smooth Urethane	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P2SG 9 lb S2522P25NG 11.5 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) (Multi-body rollers also available)	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 10 SR525 Fairway & Hustler 7500 & 7700 Fairway 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 10 SR370 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" grooved Urethane no flats 3" smooth Urethane	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P2SG 9 lb S2522P25CG 11.5 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3S	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ara G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel ura SR525 Fairway & Hustler 7500 & 7700 Fairway 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Utethane 3" smooth Steel ura SR370	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P2SG 9 lb S2522P25NG 11.5 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft (Multi-body rollers also available) 26.45° body, 29.75° shaft 26.45° body, 29.75° shaft	SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 10 SR525 Fairway & Hustler 7500 & 7700 Fairway 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 10 SR370 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" grooved Urethane no flats 3" smooth Urethane	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P2SG 9 lb S2522P25NG 11.5 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft (Multi-body rollers also available) 26.45° body, 29.75° shaft 26.45° body, 29.75° shaft	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel Ira SR525 Fairway & Hustler 7500 & 7700 Fairway 3" grooved Urethane 3" smooth Urethane 3" smooth Steel Ira SR370 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Steel Ira SR370 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Steel	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P2SG 9 lb S2522P25NG 11.5 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft (Multi-body rollers also available) 26.45° body, 29.75° shaft 26.45° body, 29.75° shaft	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel 10 SR525 Fairway & Hustler 7500 & 7700 Fairway 3" grooved Urethane 3" smooth Urethane 3" smooth Steel 10 SR370 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Steel 10 SR370 3" grooved Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Steel	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P2SG 9 lb S2522P25NG 11.5 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 26.45° body, 29.75° shaft 26.45° body, 29.75° shaft 26.25° body, 29.75° shaft	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 10 SR525 Fairway & Hustler 7500 & 7700 Fairway 3" grooved Urethane no flats 3" smooth Steel 10 SR370 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 11 SR370 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Steel	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P25CG 9 lb S2522P25CG 11.5 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3CG 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3S	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft (Multi-body rollers also available) 26.45° body, 29.75° shaft 26.25° body, 29.75° shaft (Multi-body rollers also available)	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA252PS SHA2926PS SHA2926PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 10 SR525 Fairway & Hustler 7500 & 7700 Fairway 3" grooved Urethane no flats 3" smooth Steel 10 SR570 3" grooved Urethane no flats 3" smooth Steel 11 SR570 3" grooved Urethane 3" smooth Steel 12 SR570 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" grooved Urethane no flats	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P2SG 9 lb S2522P25CG 11.5 lb S2522P25CG 12 lb S2522P25C 12 lb S2522P3CG 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3S 12.5 lb S2926P3CG 14 lb S2926P3C 14 lb S2926P3S	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft 26.45° body, 29.75° shaft (Multi-body rollers also available) (Multi-body rollers also available) 25.45° body, 29.75° shaft	SHA2522PS
gra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 2.5" smooth Steel 2.5" smooth Urethane no flats 3" smooth Urethane	6.5 lb \$2522P2CGF 8 lb \$2522P2C 11.5 lb \$2522P2S 9 lb \$2522P25CG 9 lb \$2522P25NG 11.5 lb \$2522P25C 12 lb \$2522P25S 10.5 lb \$2522P2SS 10.5 lb \$2522P3CG 12.5 lb \$2522P3C 12.5 lb \$2522P3C 12.5 lb \$2522P3C 14.1b \$2926P3C 14 lb \$2926P3C 14 lb \$2926P3C 15 lb \$2522P3S	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft 26.45° body, 29.75° shaft 26.45° body, 29.75° shaft 26.25° body, 29.75° shaft 26.25° body, 29.75° shaft (Multi-body rollers also available) (Multi-body rollers also available) 25.45° body, 27° shaft-M10 taps 25.45° body, 27° shaft-M10 taps	SHA2522PS
ara G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3.5" smooth Urethane 4.5" smooth Steel 4.5" smooth Urethane 5.5" smooth Urethane 6.5" smooth Urethane	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P2SCG 9 lb S2522P25CG 11.5 lb S2522P25CG 12 lb S2522P25C 12 lb S2522P3CG 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3S 12.5 lb S2926P3CG 14 lb S2926P3C 14 lb S2926P3S	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.55° body, 25.75° shaft 26.45° body, 27.5° shaft 26.45° body, 29.75° shaft 26.45° body, 29.75° shaft 26.45° body, 29.75° shaft 26.45° body, 27° shaft (Multi-body rollers also available) 25.45° body, 27° shaft-M10 taps 25.45° body, 27° shaft-M10 taps 25.25° body, 27° shaft-M10 taps	SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3.5" smooth Urethane 3.5" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Steel 3" smooth Steel 3" smooth Steel 4" SR370 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 4" SR370 3" grooved Urethane no flats 3" smooth Urethane 2.5" grooved Urethane no flats 2.5" grooved Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P2SGG 9 lb S2522P25CG 11.5 lb S2522P25CG 12 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 14 lb S2926P3C 14 lb S2926P3C 14 lb S2926P3C 15 lb B2725H25CG 15 lb B2725H25C	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 26.45° body, 25.75° shaft (Multi-body rollers also available) 26.45° body, 29.75° shaft 26.45° body, 29.75° shaft 26.45° body, 29.75° shaft 26.45° body, 27° shaft-M10 taps 25.45° body, 27° shaft-M10 taps 25.45° body, 27° shaft-M10 taps 25.25° body, 27° shaft-M10 taps (Multi-body rollers also available)	SHA2522PS
ara G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3.5" smooth Urethane 4.5" smooth Urethane 5.5" smooth Urethane 6.5" smooth Urethane 7.5" smooth Urethane 8.5" smooth Urethane	6.5 lb \$2522P2CGF 8 lb \$2522P2C 11.5 lb \$2522P2S 9 lb \$2522P25CG 9 lb \$2522P25NG 11.5 lb \$2522P25C 12 lb \$2522P25S 10.5 lb \$2522P2SS 10.5 lb \$2522P3CG 12.5 lb \$2522P3C 12.5 lb \$2522P3C 12.5 lb \$2522P3C 14.1b \$2926P3C 14 lb \$2926P3C 14 lb \$2926P3C 15 lb \$2522P3S	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.55° body, 25.75° shaft 26.45° body, 27.5° shaft 26.45° body, 29.75° shaft 26.45° body, 29.75° shaft 26.45° body, 29.75° shaft 26.45° body, 27° shaft (Multi-body rollers also available) 25.45° body, 27° shaft-M10 taps 25.45° body, 27° shaft-M10 taps 25.25° body, 27° shaft-M10 taps	SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel 2.5" smooth Steel 2.5" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Steel 2.5" smooth Urethane 3" smooth Steel 3" smooth Steel 3" smooth Urethane 3" smooth Steel 2.5" smooth Steel	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P2SGG 9 lb S2522P25CG 11.5 lb S2522P25CG 12 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 14 lb S2926P3C 14 lb S2926P3C 14 lb S2926P3C 15 lb B2725H25CG 15 lb B2725H25C	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 26.45° body, 25.75° shaft (Multi-body rollers also available) 26.45° body, 29.75° shaft 26.45° body, 29.75° shaft 26.45° body, 29.75° shaft 26.45° body, 27° shaft-M10 taps 25.45° body, 27° shaft-M10 taps 25.45° body, 27° shaft-M10 taps 25.25° body, 27° shaft-M10 taps (Multi-body rollers also available)	SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel 2.5" smooth Steel 2.5" smooth Steel 2.5" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Steel 2.5" smooth Steel 3" smooth Steel 3" smooth Steel 3" smooth Urethane 3" smooth Steel 2.5" smooth Steel 2.5" smooth Urethane 3" smooth Urethane 4.5" smooth Urethane 5.5" smooth Urethane 6.5" smooth Urethane	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P25CG 9 lb S2522P25CG 11.5 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3S 12.5 lb S2926P3C 14 lb S2926P3C 14 lb S2926P3C 15 lb B2725H25CG 15 lb B2725H25C 15 lb B2725H25C	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 27.5° shaft (Multi-body rollers also available) 26.45° body, 29.75° shaft 26.25° body, 29.75° shaft (Multi-body rollers also available) 25.45° body, 27° shaft-M10 taps 25.45° body, 27° shaft-M10 taps 25.25° body, 27° shaft-M10 taps (Multi-body rollers also available) 27.45° body, 30° shaft-9/16° dia. ends	SHA2522PS
graa G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel 2.5" smooth Urethane no flats 3" smooth Urethane 2.5" grooved Urethane no flats 3" smooth Steel 2.5" grooved Urethane 2.5" smooth Urethane 3." smooth Urethane	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P25CG 9 lb S2522P25CG 11.5 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 14 lb S2926P3C 14 lb S2926P3C 15 lb B2725H25CG 15 lb B2725H25CG 15 lb B2725H25C 15 lb B2725H25C	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft (Multi-body rollers also available) 26.45° body, 29.75° shaft 26.25° body, 29.75° shaft (Multi-body rollers also available) 25.45° body, 27° shaft-M10 taps 25.25° body, 27° shaft-M10 taps (Multi-body rollers also available) 27.45° body, 30° shaft-9/16° dia. ends 27.45° body, 30° shaft-9/16° dia. ends	SHA2522PS
ra G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3.5" smooth Urethane no flats 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel FOR BARONESS BES LM66T Greens - ALL ROLLERS 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 3" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3" smooth Urethane 3" smooth Steel	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P25CG 9 lb S2522P25CG 11.5 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 14 lb S2926P3C 14 lb S2926P3C 15 lb B2725H25CG 15 lb B2725H25CG 15 lb B2725H25C 15 lb B2725H25C	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 27.5° shaft (Multi-body rollers also available) 26.45° body, 29.75° shaft 26.25° body, 29.75° shaft (Multi-body rollers also available) 25.45° body, 27° shaft-M10 taps 25.25° body, 27° shaft-M10 taps 25.25° body, 27° shaft-M10 taps (Multi-body rollers also available) 27.45° body, 30° shaft-916° dia. ends 27.45° body, 30° shaft-916° dia. ends 27.25° body, 30° shaft-916° dia. ends	SHA2522PS
ara G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Steel 2.5" smooth Urethane no flats 3" smooth Urethane 2.5" grooved Urethane no flats 3" smooth Steel 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Steel 2.5" smooth Urethane 3" smooth Steel 2.5" smooth Urethane 3" smooth Steel 3" grooved Urethane no flats 3" smooth Steel 3" smooth Steel 3" smooth Urethane 3" smooth Steel 3" smooth Steel 3" smooth Steel 3" smooth Steel	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P25CG 9 lb S2522P25CG 11.5 lb S2522P25CC 12 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 14 lb S2926P3C 14 lb S2926P3C 14 lb S2926P3C 15 lb B2725H25CG 15 lb B2725H25C 15 lb B2725H25C 15 lb B2725H25C 15 lb B3027K3C 15 lb B3027K3C 15 lb B3027K3C	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.55° body, 27.5° shaft (Multi-body rollers also available) 26.45° body, 29.75° shaft 26.25° body, 29.75° shaft (Multi-body rollers also available) 25.45° body, 27° shaft-M10 taps 25.45° body, 27° shaft-M10 taps 25.25° body, 27° shaft-M10 taps (Multi-body rollers also available) 27.45° body, 30° shaft-916° dia. ends 27.25° body, 30° shaft-916° dia. ends (Multi-body rollers also available)	SHA2522PS
graa G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 2.5" smooth Steel 2.5" smooth Urethane 3" smooth Steel 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Urethane 3" smooth Steel	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P2SGG 9 lb S2522P25GG 11.5 lb S2522P25GG 11.5 lb S2522P25C 12 lb S2522P25S 10.5 lb S2522P3CG 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 14.5 lb S2926P3C 14 lb S2926P3C 14 lb S2926P3C 15 lb B2725H25CG 15 lb B2725H25C 15 lb B2725H25C 15 lb B2725H25C 15 lb B3027K3C 15 lb B3027K3C 15 lb B3027K3S	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft 22.55° body, 27.5° shaft (Multi-body rollers also available) 26.45° body, 29.75° shaft 26.25° body, 29.75° shaft (Multi-body rollers also available) 25.45° body, 27° shaft-M10 taps 25.45° body, 27° shaft-M10 taps 25.25° body, 27° shaft-M10 taps (Multi-body rollers also available) 27.45° body, 30° shaft-916° dia, ends 27.45° body, 30° shaft-916° dia, ends (Multi-body rollers also available) 27.45° body, 30° shaft-916° dia, ends (Multi-body rollers also available) 27.45° body, 30° shaft-916° dia, ends	SHA2522PS
graa G Flow22 & MG70 & Hustler GM1500 Greens Mower 2" wide grooved Urethane 1" flats 2" smooth Urethane 2" smooth Steel heavy (1/4" wall) 2.5" wide grooved (1" spacing) Urethane no flats 2.5" narrow grooved (1/2" spacing) Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 2.5" smooth Steel 2.5" smooth Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Steel 2.5" smooth Steel 3" smooth Steel 3" smooth Urethane 3" smooth Steel 2.5" smooth Urethane 2.5" smooth Urethane 2.5" smooth Urethane 3" grooved Urethane no flats 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 2.5" smooth Steel 2.5" smooth Urethane 3" grooved Urethane no flats 3" grooved Urethane no flats 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane	6.5 lb S2522P2CGF 8 lb S2522P2C 11.5 lb S2522P2C 11.5 lb S2522P2S 9 lb S2522P25CG 9 lb S2522P25CG 11.5 lb S2522P25C 12 lb S2522P25C 12 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 12.5 lb S2522P3C 14 lb S2926P3C 14 lb S2926P3C 14 lb S2926P3C 15 lb B2725H25C 15 lb B2725H25C 15 lb B2725H25C 15 lb B3027K3C 15 lb B3027K3C 15 lb B3027K3C 15 lb B3027K3S	(Multi-body rollers also available) 22.45° body, 25.75° shaft 22.25° body, 25.75° shaft 22.45° body, 25.75° shaft (Multi-body rollers also available) 26.45° body, 27.5° shaft 26.45° body, 29.75° shaft 26.45° body, 29.75° shaft 27.45° body, 27° shaft-M10 taps (Multi-body rollers also available) 25.45° body, 27° shaft-M10 taps (Multi-body rollers also available) 27.45° body, 30° shaft-916° dia. ends 27.25° body, 30° shaft-916° dia. ends (Multi-body rollers also available) 27.45° body, 30° shaft-916° dia. ends (Multi-body rollers also available) 27.45° body, 30° shaft-916° dia. ends (Multi-body rollers also available) 27.45° body, 30° shaft-916° dia. ends 27.25° body, 27.625° shaft-7/16° taps 27.45° body, 27.625° shaft-7/16° taps	SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS SHA2522PS



trac MJ840 Contour Deck Rotary Mower		(Multi-body rollers also available)	
3" smooth Urethane (double row bearings)	11.8 lb 2V2422S3C	only available through Venture Products	SHA2422SV
3" smooth Steel	11.4 lb V2422S3S	22.05" body, 24.56" shaft-3/8" taps	SHA2422SV
3" dia. TWO body rollers		non-striping, non-skidding for tight turns & ground	undulations
lies 3" grooved Urethane (2x4" wide bodies) no flats	8 lb V2404S3CGt	2 short twin bodies at ends of a 24.56" shaft	SHA2404SVN
dies 3" smooth Urethane (2x4" wide bodies) (double row bearings)	8 lb 2V2404S3Ct	2 short twin bodies at ends of a 24.56" shaft	SHA2404SVN
dies 3" smooth Urethane (2x4" wide bodies)	8 lb V2404S3Ct	2 short twin bodies at ends of a 24.56" shaft	SHA2404SVN
dies 3" smooth Steel (2x4" wide bodies)	10 lb V2404S3St	2 short twin bodies at ends of a 24.56" shaft	SHA2404SVN
trac MR740 Triplex Reel Mower		(Multi-body rollers also available)	
3" grooved Urethane no flats	9.5 lb V2827S3CG	27.45" body, 28.78" shaft-3/8" taps, .545" dia ends	SHA2827SV
3" smooth Urethane	11.5 lb V2827S3C	27.45" body, 28.78" shaft-3/8" taps, .545" dia ends	SHA2827SV
3" smooth Steel	11.2 lb V2827S3S	27.25" body, 28.78" shaft-3/8" taps, .545" dia ends	SHA2827SV
for SISIS			
s Flexi-400 fairway rolling machine- ALL ROLLERS			
3" smooth Urethane	11.6 lb S2524S3C	24.45" body, 25.125" shaft-3/8" taps	SHA2524SS
3" smooth Steel	12 lb S2524S3S	24.25" body, 25.125" shaft-3/8" taps	SHA2524SS
3.5" smooth Urethane	16 lb S2524S7C	24.45" body, 25.125" shaft-3/8" taps	SHA2524SS
s Veemo MK2 Verticutter - ALL ROLLERS			
3" smooth Urethane	15 lb S3029G3C	29.45" body, 30.5" shaft-7/16" taps	SHA3029GS
3" smooth Steel	15 lb S3029G3S	29.25" body, 30.5" shaft-7/16" taps	SHA3029GS
for NATIONAL			
ional 68 & 84 TRIPLEX & PTO GANG - 30" REELS			
3" grooved Urethane no flats	13 lb N3429I3CG	29.45" body, 34.5" shaft	SHA3429IN
3" smooth Urethane	15 lb N3429I3C	29.45" body, 34.5" shaft	SHA3429IN
3" smooth Steel	15 lb N3429I3S	29.25" body, 34.5" shaft	SHA3429IN
3.5" smooth Urethane	18 lb N3429I7C	29.45" body, 34.5" shaft	SHA3429IN
4" smooth Urethane	23 lb N3429I4C	29.45" body, 34.5" shaft	SHA3229IN
4" smooth Steel	19 lb N3429I4S	29.25" body, 34.5" shaft	SHA3229IN
ional 68 & 84 TRIPLEX & PTO GANG - 25" OUTSIDE REELS			
3" smooth Urethane	11 lb N2420I3C	20.45" body, 24.875" shaft	SHA2420IN
3" smooth Steel	11 lb N2420I3S	20.25" body, 24.875" shaft	SHA2420IN
3.5" smooth Urethane	13 lb N2420I7C	20.45" body, 24.875" shaft	SHA2420IN
for BUNTON			
nton 22" WALKING GREENSMOWERS - FRONT		(Multi-body rollers also available)	
2" wide grooved Urethane 1" flats	6.5 lb B2422P2CGF	22.45" body, 24.5" shaft	SHA2422PB
2" smooth Urethane	8 lb B2422P2C	22.25" body, 24.5" shaft	SHA2422PB
2" smooth Steel heavy (1/4" wall)	11.5 lb B2422P2S	22.25" body, 24.5" shaft	SHA2422PB
2.5" grooved Urethane no flats	9 lb B2422P25CG	22.45" body, 24.5" shaft	SHA2422PB
2.5" smooth Urethane	9.5 lb B2422P25C	22.45" body, 24.5" shaft	SHA2422PB
2.5" smooth Steel	10 lb B2422P25S	22.25" body, 24.5" shaft	SHA2422PB
2.5" smooth Steel ton 26" WALKING GREENSMOWER - FRONT	10 lb B2422P25S	22.25" body, 24.5" shaft (Multi-body rollers also available)	SHA2422PB
	10 lb B2422P25S 10 lb B2726P25CG		SHA2422PB SHA2726PB
iton 26" WALKING GREENSMOWER - FRONT		(Multi-body rollers also available) 26.45° body 26.45° body	
aton 26" WALKING GREENSMOWER - FRONT 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel	10 lb B2726P25CG	(Multi-body rollers also available) 26.45° body	SHA2726PB
aton 26" WALKING GREENSMOWER - FRONT 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel aton 30" FAIRWAY GANG MOWER - FRONT & BACK ROLLERS	10 lb B2726P25CG 10.5 lb B2726P25C 11 lb B2726P25S	(Multi-body rollers also available) 26.45° body 26.45° body 26.25° body (Multi-body rollers also available)	SHA2726PB SHA2726PB SHA2726PB
aton 26" WALKING GREENSMOWER - FRONT 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel aton 30" FAIRWAY GANG MOWER - FRONT & BACK ROLLERS 3" grooved Urethane no flats	10 lb B2726P25CG 10.5 lb B2726P25C 11 lb B2726P25S 13 lb B3629H3CG	(Multi-body rollers also available) 26.45" body 26.45" body 26.25" body (Multi-body rollers also available) 29.45" body, 36.25" shaft	SHA2726PB SHA2726PB
aton 26" WALKING GREENSMOWER - FRONT 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel aton 30" FAIRWAY GANG MOWER - FRONT & BACK ROLLERS 3" grooved Urethane no flats 3" smooth Urethane	10 lb B2726P25CG 10.5 lb B2726P25C 11 lb B2726P25S 13 lb B3629H3CG 15 lb B3629H3C	(Multi-body rollers also available) 26.45° body 26.45° body 26.25° body (Multi-body rollers also available) 29.45° body, 36.25° shaft 29.45° body, 36° shaft	SHA2726PB SHA2726PB SHA2726PB SHA3629HB SHA3629HB
aton 26" WALKING GREENSMOWER - FRONT 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel aton 30" FAIRWAY GANG MOWER - FRONT & BACK ROLLERS 3" grooved Urethane no flats	10 lb B2726P25CG 10.5 lb B2726P25C 11 lb B2726P25S 13 lb B3629H3CG	(Multi-body rollers also available) 26.45" body 26.45" body 26.25" body (Multi-body rollers also available) 29.45" body, 36.25" shaft	SHA2726PB SHA2726PB SHA2726PB SHA3629HB
aton 26" WALKING GREENSMOWER - FRONT 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel aton 30" FAIRWAY GANG MOWER - FRONT & BACK ROLLERS 3" grooved Urethane no flats 3" smooth Urethane	10 lb B2726P25CG 10.5 lb B2726P25C 11 lb B2726P25S 13 lb B3629H3CG 15 lb B3629H3C	(Multi-body rollers also available) 26.45° body 26.45° body 26.25° body (Multi-body rollers also available) 29.45° body, 36.25° shaft 29.45° body, 36° shaft	SHA2726PB SHA2726PB SHA2726PB SHA3629HB SHA3629HB
aton 26" WALKING GREENSMOWER - FRONT 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel aton 30" FAIRWAY GANG MOWER - FRONT & BACK ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3.5" smooth Urethane	10 lb B2726P25CG 10.5 lb B2726P25C 11 lb B2726P25S 13 lb B3629H3CG 15 lb B3629H3C 15 lb B3629H3S	(Multi-body rollers also available) 26.45" body 26.45" body 26.25" body (Multi-body rollers also available) 29.45" body, 36.25" shaft 29.45" body, 36.25" shaft 29.25" body, 36.25" shaft	SHA2726PB SHA2726PB SHA2726PB SHA3629HB SHA3629HB SHA3629HB
aton 26" WALKING GREENSMOWER - FRONT 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel aton 30" FAIRWAY GANG MOWER - FRONT & BACK ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3.5" smooth Urethane	10 lb B2726P25CG 10.5 lb B2726P25C 11 lb B2726P25S 13 lb B3629H3CG 15 lb B3629H3C 15 lb B3629H3S	(Multi-body rollers also available) 26.45" body 26.45" body 26.25" body (Multi-body rollers also available) 29.45" body, 36.25" shaft 29.45" body, 36.25" shaft 29.25" body, 36.25" shaft	SHA2726PB SHA2726PB SHA2726PB SHA3629HB SHA3629HB SHA3629HB
2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel 3" grooved Urethane 2.5" smooth Steel 3" grooved Urethane no flats 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane for KESMAC mac GANG MOWER - ALL ROLLERS	10 lb B2726P25CG 10.5 lb B2726P25C 11 lb B2726P25S 13 lb B3629H3CG 15 lb B3629H3C 15 lb B3629H3C 15 lb B3629H7C	(Multi-body rollers also available) 26.45" body 26.45" body 26.25" body (Multi-body rollers also available) 29.45" body, 36.25" shaft 29.45" body, 36.25" shaft 29.25" body, 36.25" shaft	SHA2726PB SHA2726PB SHA2726PB SHA3629HB SHA3629HB SHA3629HB
aton 26" WALKING GREENSMOWER - FRONT 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel aton 30" FAIRWAY GANG MOWER - FRONT & BACK ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3.5" smooth Urethane	10 lb B2726P25CG 10.5 lb B2726P25C 11 lb B2726P25S 13 lb B3629H3CG 15 lb B3629H3C 15 lb B3629H3S	(Multi-body rollers also available) 26.45" body 26.45" body 26.25" body (Multi-body rollers also available) 29.45" body, 36.25" shaft 29.45" body, 36.25" shaft 29.25" body, 36.25" shaft	SHA2726PB SHA2726PB SHA2726PB SHA3629HB SHA3629HB SHA3629HB
aton 26" WALKING GREENSMOWER - FRONT 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel aton 30" FAIRWAY GANG MOWER - FRONT & BACK ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Steel 3.5" smooth Urethane for KESMAC amac GANG MOWER - ALL ROLLERS 3" grooved Urethane no flats	10 lb B2726P25CG 10.5 lb B2726P25C 11 lb B2726P25S 13 lb B3629H3CG 15 lb B3629H3C 15 lb B3629H3C 15 lb B3629H7C	(Multi-body rollers also available) 26.45" body 26.45" body 26.25" body (Multi-body rollers also available) 29.45" body, 36.25" shaft 29.45" body, 36.25" shaft 29.25" body, 36.25" shaft 29.25" body, 36.25" shaft	SHA2726PB SHA2726PB SHA2726PB SHA3629HB SHA3629HB SHA3629HB SHA3629HB
aton 26" WALKING GREENSMOWER - FRONT 2.5" grooved Urethane no flats 2.5" smooth Urethane 2.5" smooth Steel aton 30" FAIRWAY GANG MOWER - FRONT & BACK ROLLERS 3" grooved Urethane no flats 3" smooth Urethane 3" smooth Urethane 3" smooth Urethane for KESMAC amac GANG MOWER - ALL ROLLERS 3" grooved Urethane no flats 3" smooth Urethane	10 lb B2726P25CG 10.5 lb B2726P25C 11 lb B2726P25S 13 lb B3629H3CG 15 lb B3629H3C 15 lb B3629H7C 13 lb B3629H7C	(Multi-body rollers also available) 26.45" body 26.45" body 26.25" body (Multi-body rollers also available) 29.45" body, 36.25" shaft 29.45" body, 36.25" shaft 29.25" body, 36.25" shaft 29.25" body, 36.25" shaft	SHA2726PB SHA2726PB SHA2726PB SHA3629HB SHA3629HB SHA3629HB SHA3629HB

Don't see your machine listed? Call us about the possible roller options for your equipment.



GOLFCO INTERNATIONAL COMPETITION ROLLERS™ 2023

Competition Roller[™] Upgrade Options

Upgrade to Stainless Steel Bearings on Competition Rollers™ Upgrade to Double Row Bearings as our Competition2 Rollers™

-upgrade select Competition RollersTM to double row bearings with black oxide finish (per body)

BU-COMPSS

(designate by adding "2" to front of ro

-available for most rollers greater than 2" diameter (requires specially machined inner steel tube bearing housings)

Add Grease Fittings (set of 2 special flush mount grease fittings)

-grease fittings (set of two) for new Competition Rollers™ or new overhaul kits

GFFD316SET



-special yellow end seal (set of two) to accommodate grease fitting without new bearing kits

Bearing Installation Tool Set

2SEAL16CUGF SET

2TOOLSET

set of 2 tools - aids in installing bearings into roller housing and onto shaft

Super solid one piece Polyurethane Soft Blow Mallet - FULL SIZE

-add a botle opener to your full size mallet for \$12 extra

#MALLET1BO

#MALLET1



Super solid one piece Polyurethane Soft Blow Mallet - 3/4 SIZE Super solid one piece Polyurethane Soft Blow Mallet - 1/2 SIZE

-unique utility to add to your tool box

#MALLET.75 #MALLET.5



Competition Roller[™] Overhaul Kits - *ORIGINAL STYLE*

Standard overhaul kit for all single body rollers (except "H" style 2" grooved)

(with 2 alloy steel bearings, 6 seals, 2 stainless washers & 4 retainers)

Stainless steel bearing overhaul kit for all single body rollers (except 2" grooved)

(with 2 stainless bearings, 6 seals, 2 stainless washers & 4 retainers)

Overhaul kit for new "H" style 2" dia. grooved rollers shipped after 9/26/19

(with 2 alloy steel bearings, 6 seals, 2 stainless washers & 4 retainers)

Overhaul kit for twin body roller assemblies (one kit per body - call to confirm

Overhaul kit for 3 & 4 body roller assemblies (one kit per body - call to confirm)

OHCOMP

OHCOMPSS

ОНСОМРН

OHCOMPNt

OHCOMPN4

Competition2 Roller[™] Overhaul Kits *SERIES 2* with Double-Row Bearings

Kit with Double-Row Bearings with corrosion resistant black oxide finish

OHCOMP2BO

(with 2 bearings, 6 seals, 2 stainless washers & 4 retainers)

Only Golfco bearings are filled to over 90% with a special high performance extreme pressure rated grease

that has been time tested to maximize the life of the bearing for commerical mower applications.

Competition Roller[™] Shafts

Replacement shafts are listed to the right of each roller line item shown in our Competition Roller price list above.

(The shaft part number is derived from the first 6 digits of the roller part number as follows: Roller T2522S2CGF has shaft part SHA2522ST)

Each roller assembly listed in this offering catalog comes completely assembled with roller body or bodies, shaft and overhaul kits (bearings/seals/retainers).

Pro Roller TM Bearings (Water Pump Style)

Replaces Toro #21-8430

Water pump bearing-sealed (shaft is 1.8") Replaces Toro #52-3180 & 52-3210

Water pump bearing-sealed (shaft is 1.8" with 3/8-24 tap)

Replaces Jacobsen #101482

Water pump bearing-sealed (shaft is 1.0" with 7/16-20 tap)

Replaces Toro #75-1290, Jacobsen #101481 & John Deere #35741

Water pump bearing-sealed (shaft is 1.5")

BWP3

BWP4

BWP5

BWP7

Golfco Competition Roller Assembly Overhaul Kit 2024

(One kit per roller body)

(to add grease fittings insert "GF" to end of overhaul kit part number)

For single body rollers:

- 1					
	OHCOMP	standard bearing kit	<u>OHCOMPSS</u>	stainless bearing kit	
	kit components:		kit components:		
	2 2BCOMP	alloy ball bearing with black seals	2 2BCOMPSS	stainless ball bearing with blue seals	
	2 2SEAL16CU	yellow polyurethane housing seal	2 2SEAL16CU	yellow polyurethane housing seal	
	4 2SEAL62V	Shaft V seal black rubber	4 2SEAL62V	Shaft V seal black rubber	
	4 2RET62SR	snap ring retainer	4 2RET62SR	snap ring retainer	
	2 2WS99.63.03	stainless steel thin washer	2 2WS99.63.03	stainless steel thin washer	
	<u>OHCOMPH</u>	2" grooved roller bearing kit	ОНСОМР2ВО	double row bearing kit	
- 1		_ 8	OHICOMH ZDO	double four bearing kit	
١	kit components:	(for roller part # ending in "2CGH" sold after 9/30/19)	kit components:	double for bearing me	
	kit components: 2 2BCOMPH			double row ball bearing with yellow seals	
		(for roller part # ending in "2CGH" sold after 9/30/19)	kit components:	<u>~_</u> _	
	2 2BCOMPH	(for roller part # ending in "2CGH" sold after 9/30/19) reduced dia. alloy bearing with black seals	kit components: 2 2BCOMP2BO	double row ball bearing with yellow seals	
	2 2BCOMPH 2 2SEAL14CU	(for roller part # ending in "2CGH" sold after 9/30/19) reduced dia. alloy bearing with black seals yellow polyurethane housing seal	kit components: 2 2BCOMP2BO 2 2SEAL16CU	double row ball bearing with yellow seals yellow polyurethane housing seal	

ou E hady rollous with collar notainous (nor hady).

	For 2, 3, 4, or 5 body rollers with collar retainers (per body):				
	OHCOMPNt	standard bearing kit for each body		OHCOMPNtSS	stainless bearing kit for each body
	kit components:	(for 2" grooved rollers insert "H" after "COMP")		kit components:	
2	2BCOMP	alloy ball bearing with black seals	2	2BCOMPSS	stainless ball bearing with blue seals
2	2SEAL16CU	yellow polyurethane housing seal	2	2SEAL16CU	yellow polyurethane housing seal
4	2SEAL62V	Shaft V seal black rubber	4	2SEAL62V	Shaft V seal black rubber
2	2COLLAR625	retaining collar with set screw	2	2COLLAR625	retaining collar with set screw
2	2WS99.63.03	stainless steel thin washer	2	2WS99.63.03	stainless steel thin washer
2	2SPACER156PVC	white PVC spacer for nitro shaft	2	2SPACER156PVC	white PVC spacer for nitro shaft

For 4 body rollers with snap ring retainers (per body):

kit components: 2 2BCOMPSS

2 2SEAL16CU

2 2SEAL62V

2 2RET62SR

		TOT 4 DOGY TOTIETS WITH SIT
	OHCOMPN4int	standard bearing kit for inner body
	kit components:	(for 2" grooved rollers insert "H" after "COMP")
2	2BCOMP	alloy ball bearing with black seals
2	2SEAL16CU	yellow polyurethane housing seal
2	2SEAL62V	Shaft V seal black rubber
2	2RET62SR	snap ring retainer
2	2WC 120.628.110	hardened steel thick washer
1	2SPACER156PVC	white PVC spacer for nitro shaft
	OHCOMPN4ext	standard bearing kit for outer body
	kit components:	(for 2" grooved rollers insert "H" after "COMP")
2	2BCOMP	alloy ball bearing with black seals

2 2SEAL16CU

2 2SEAL62V

3 2RET62SR

1 2WS99.63.03

1 2WC 120.628.110

1 2SPACER156PVC **OHCOMPN4extSS** kit components: 2 2BCOMPSS alloy ball bearing with black seals yellow polyurethane housing seal 2 2SEAL16CU Shaft V seal black rubber 2 2SEAL62V 3 2RET62SR snap ring retainer hardened steel thick washer 1 2WC 120.628.110 stainless steel thin washer 1 2WS99.63.03

OHCOMPN4intSS stainless bearing kit for inner body stainless ball bearing with blue seals yellow polyurethane housing seal Shaft V seal black rubber snap ring retainer

stainless bearing kit for outer body

2 2WC 120.628.110 hardened steel thick washer white PVC spacer for nitro shaft

> stainless ball bearing with blue seals yellow polyurethane housing seal Shaft V seal black rubber snap ring retainer hardened steel thick washer

> > stainless steel thin washer

Distributed by:

2/1/2024



Hong Kong | Singapore | Malaysia | Australia Email: info@centaur-asiapacific.com Website: www.centaur-asiapacific.com