

Verti-Air® 400C

The Verti-Air® 400 is remarkably quiet, ideal for areas with noise restrictions. Requiring just 24 hp and compatible with various tractor linkages. The driver-controlled 180° rotatable spout, anti-scalping roll, and impact protection bar ensure durability for any job.



Specifications

| | |
|--------------------------|---------------------------------------|
| SKU | 145.400.002 |
| Weight (kg) | 245 |
| Weight (lbs) | 540 |
| Min. Tractor HP required | 24 |
| Rpm Max. | Hydraulically Driven 55L/min - 200bar |
| Lubricant | Ceran XM 220 |
| Dimensions (width mm) | 950 |
| Dimensions (height mm) | 1000 |
| Dimensions (length mm) | 1400 |
| Dimensions (width inch) | 37 |
| Dimensions (height inch) | 39 |
| Dimensions (length inch) | 55 |
| Drive | Hydraulic driven |
| Noise Level (dB) | |
| Air Capacity (m3 min) | 285 |
| Linkage | CAT 1 or II; 3-point |
| Hydraulics | Double acting hydraulic control valve |
| Exhaust Sprout | 180 degrees turning spout |
| Fan (Ø mm) | 400 |
| Exhaust Spout | 180 degrees turning spout |

