

Verti-Cut® 1600

The Verti-Cut 1600 is the ideal deep scarification tool, the 2mm (0.07") wide blades work to a depth of 50mm (1.9"). The front roller not only allows the Verti-Cut to cope with undulations but also controls the working depth with precision. Blade spacing can be changed with the optional spacer kit.





SKU 144.160.000 Working width (inch) 1.6 Max. Working depth (mm) 50 Max. Working depth (inch) 1.96 Max. Working speed (m h) 7 Working speed (mph) 4 Weight (lbg) 395 Weight (lbs) 871 Standard knife thickness (mm) 2 Distance between knifes (mnh) 30 Min. Tractor HP required 43 Min. Iffiting capacity (kg) 592 Min. lifting capacity (LBS) 300 Max. capacity (m² hr) 8000 Max. capacity (ft² hr) 86112 Three-point hitch Cat 1-2 Rpm Max. 540 Gearbox oil EP 2 Dimensions (width mm) 940 Dimensions (leight mm) 940 Dimensions (leight mm) 950 Dimensions (leight min) 951 Dimensions (leight min) 952 Dimensions (leight min) 940 Dimensions (leight min) 952 Dimensions (leight min) 952 <	Specifications	
Working width (inch) 63 Max. Working depth (inch) 50 Max. Working depth (inch) 1,96 Max. Working speed (km h) 7 Working speed (mph) 4 Weight (kg) 395 Weight (lbs) 871 Standard knife thickness (mm) 2 Distance between knifes (mm) 30 Distance between knifes (mm) 1,8 Min. Tractor HP required 43 Min. Ilifting capacity (kg) 592 Min. lifting capacity (rash) 8000 Max. capacity (m³ hr) 8000 Max. capacity (m² hr) 8000 Max. capacity (rash) 612 There-point hitch Cat 1-2 Rpm Max. 540 Gearbox oil 61-5 80W90 Lubricant EP 2 Dimensions (width mm) 940 Dimensions (leight mm) 850 Dimensions (leight mm) 79.1 Dimensions (leight inch) 79.1	SKU	144.160.000
Max. Working depth (inch) 50 Max. Working speed (km h) 1.96 Working speed (mph) 7 Working speed (mph) 4 Weight (kg) 871 Standard knife thickness (mm) 2 Distance between knifes (inch) 1.18 Min. Tractor HP required 43 Min. lifting capacity (kg) 592 Min. lifting capacity (laS) 8000 Max. capacity (m² hr) 8000 Max. capacity (f² br) 86112 Three-point hitch Cat 1-2 Rpm Max. 540 Gearbox oil Ep 2 Dimensions (width mm) 900 Dimensions (width mm) 900 Dimensions (leight mm) 64-58090 Dimensions (leight mm) 904 Dimensions (leight mm) 904 Dimensions (leight mm) 905 Dimensions (leight mm) 907 Dimensions (leight mm) 907 Dimensions (leight mm) 907 Dimensions (leight mm) 907 Dimensions (leight mm)	Working width (m)	1.6
Max. Working depth (inch) 1.96 Max. Working speed (km h) 7 Working speed (mph) 4 Weight (kg) 395 Weight (lbs) 871 Standard knife thickness (mm) 2 Distance between knifes (inch) 1.18 Min. Tractor HP required 43 Min. lifting capacity (kg) 592 Min. lifting capacity (LBS) 3000 Max. capacity (m² hr) 8000 Max. capacity (ft² hr) 80112 Three-point hitch Cat 1-2 Rpm Max. 540 Gearbox oil EP 2 Dimensions (width mm) 940 Dimensions (leight mm) 940 Dimensions (leight mm) 850 Dimensions (width inch) 79.1 Dimensions (height inch) 37	Working width (inch)	63
Max. Working speed (km h) 7 Working speed (mph) 4 Weight (kg) 395 Weight (lbs) 871 Standard knife thickness (mm) 2 Distance between knifes (imch) 30 Distance between knifes (inch) 1.18 Min. Trator HP required 43 Min. lifting capacity (kg) 592 Min. lifting capacity (las) 300 Max. capacity (m² hr) 8000 Max. capacity (ft² hr) 86112 Three-point hitch Cat 1-2 Rpm Max. 540 Gearbox oil 61-5 80W0 Lubricant FP 2 Dimensions (width mm) 2010 Dimensions (height mm) 940 Dimensions (length mm) 850 Dimensions (width inch) 99.1 Dimensions (width inch) 99.1 Dimensions (height inch) 37.0	Max. Working depth (mm)	50
Working speed (mph) 4 Weight (kg) 395 Weight (lbs) 871 Standard knife thickness (mm) 2 Distance between knifes (inch) 30 Distance between knifes (inch) 1.18 Min. Tractor HP required 43 Min. lifting capacity (kg) 592 Min. lifting capacity (m² hr) 8000 Max. capacity (m² hr) 8000 Max. capacity (ft² hr) 86112 Three-point hitch Cat 1-2 Rpm Max. 540 Gearbox oil GL-5 80W90 Lubricant EP 2 Dimensions (width mm) 2010 Dimensions (height mm) 940 Dimensions (length mm) 850 Dimensions (width inch) 79.1 Dimensions (height inch) 37	Max. Working depth (inch)	1.96
Weight (kg) 395 Weight (lbs) 871 Standard knife thickness (mm) 2 Distance between knifes (inch) 30 Distance between knifes (inch) 1.18 Min. Tractor HP required 43 Min. lifting capacity (kg) 592 Min. lifting capacity (m² hr) 8000 Max. capacity (f²² hr) 86112 Three-point hitch Cat 1-2 Rpm Max. 540 Gearbox oil GL-5 80W90 Lubricant EP 2 Dimensions (width mm) 2010 Dimensions (height mm) 940 Dimensions (length mm) 850 Dimensions (width inch) 79.1 Dimensions (height inch) 37	Max. Working speed (km h)	7
Weight (lbs) 871 Standard knife thickness (mm) 2 Distance between knifes (mm) 30 Distance between knifes (inch) 1.18 Min. Tractor HP required 43 Min. lifting capacity (kg) 592 Min. lifting capacity (LBS) 1305 Max. capacity (m² hr) 8000 Max. capacity (ft² hr) 66112 Three-point hitch Cat 1-2 Rpm Max. 540 Gearbox oil GL-5 80W90 Lubricant EP 2 Dimensions (width mm) 2010 Dimensions (height mm) 940 Dimensions (length mm) 850 Dimensions (width inch) 79.1 Dimensions (height inch) 37	Working speed (mph)	4
Standard knife thickness (mm) 2 Distance between knifes (mm) 30 Distance between knifes (inch) 1.18 Min. Tractor HP required 43 Min. lifting capacity (kg) 592 Min. lifting capacity (LBS) 1305 Max. capacity (m² hr) 8000 Max. capacity (ft² hr) 86112 Three-point hitch Cat 1-2 Rpm Max. 540 Gearbox oil GL-5 80W90 Lubricant EP 2 Dimensions (width mm) 2010 Dimensions (height mm) 940 Dimensions (length mm) 850 Dimensions (width inch) 79.1 Dimensions (height inch) 37	Weight (kg)	395
Distance between knifes (mm) 30 Distance between knifes (inch) 1.18 Min. Tractor HP required 43 Min. lifting capacity (kg) 592 Min. lifting capacity (BS) 1305 Max. capacity (m² hr) 8000 Max. capacity (ft² hr) 86112 Three-point hitch Cat 1-2 Rpm Max. 540 Gearbox oil GL-5 80W90 Lubricant EP 2 Dimensions (width mm) 2010 Dimensions (height mm) 940 Dimensions (length mm) 850 Dimensions (width inch) 79.1 Dimensions (height inch) 37	Weight (lbs)	871
Distance between knifes (inch)1.18Min. Tractor HP required43Min. lifting capacity (kg)592Min. lifting capacity (LBS)1305Max. capacity (m² hr)8000Max. capacity (ft² hr)86112Three-point hitchCat 1-2Rpm Max.540Gearbox oil6L-5 80W90LubricantEP 2Dimensions (width mm)2010Dimensions (height mm)940Dimensions (length mm)850Dimensions (width inch)79.1Dimensions (height inch)37	Standard knife thickness (mm)	2
Min. Tractor HP required 43 Min. lifting capacity (kg) 592 Min. lifting capacity (LBS) 1305 Max. capacity (m² hr) 8000 Max. capacity (ft² hr) 86112 Three-point hitch Cat 1-2 Rpm Max. 540 Gearbox oil GL-5 80W90 Lubricant EP 2 Dimensions (width mm) 2010 Dimensions (height mm) 940 Dimensions (length mm) 850 Dimensions (width inch) 79.1 Dimensions (height inch) 37	Distance between knifes (mm)	30
Min. lifting capacity (kg) 592 Min. lifting capacity (LBS) 1305 Max. capacity (m² hr) 8000 Max. capacity (ft² hr) 86112 Three-point hitch Cat 1-2 Rpm Max. 540 Gearbox oil GL-5 80W90 Lubricant EP 2 Dimensions (width mm) 2010 Dimensions (height mm) 940 Dimensions (length mm) 850 Dimensions (width inch) 79.1 Dimensions (height inch) 37	Distance between knifes (inch)	1.18
Min. lifting capacity (LBS) 1305 Max. capacity (m² hr) 8000 Max. capacity (ft² hr) 86112 Three-point hitch Cat 1-2 Rpm Max. 540 Gearbox oil GL-5 80W90 Lubricant EP 2 Dimensions (width mm) 2010 Dimensions (height mm) 940 Dimensions (length mm) 850 Dimensions (width inch) 79.1 Dimensions (height inch) 37	Min. Tractor HP required	43
Max. capacity (m² hr)8000Max. capacity (ft² hr)86112Three-point hitchCat 1-2Rpm Max.540Gearbox oilGL-5 80W90LubricantEP 2Dimensions (width mm)2010Dimensions (height mm)940Dimensions (length mm)850Dimensions (width inch)79.1Dimensions (height inch)37	Min. lifting capacity (kg)	592
Max. capacity (ft² hr)86112Three-point hitchCat 1-2Rpm Max.540Gearbox oilGL-5 80W90LubricantEP 2Dimensions (width mm)2010Dimensions (height mm)940Dimensions (length mm)850Dimensions (width inch)79.1Dimensions (height inch)37	Min. lifting capacity (LBS)	1305
Three-point hitch Rpm Max. Gearbox oil Lubricant Dimensions (width mm) Dimensions (length mm) Dimensions (width inch) Dimensions (width inch) Dimensions (height inch) Dimensions (height inch) Dimensions (height inch) Sat 1-2 Cat	Max. capacity (m² hr)	8000
Rpm Max.540Gearbox oilGL-5 80W90LubricantEP 2Dimensions (width mm)2010Dimensions (height mm)940Dimensions (length mm)850Dimensions (width inch)79.1Dimensions (height inch)37	Max. capacity (ft² hr)	86112
Gearbox oilGL-5 80W90LubricantEP 2Dimensions (width mm)2010Dimensions (height mm)940Dimensions (length mm)850Dimensions (width inch)79.1Dimensions (height inch)37	Three-point hitch	Cat 1-2
LubricantEP 2Dimensions (width mm)2010Dimensions (height mm)940Dimensions (length mm)850Dimensions (width inch)79.1Dimensions (height inch)37	Rpm Max.	540
Dimensions (width mm)2010Dimensions (height mm)940Dimensions (length mm)850Dimensions (width inch)79.1Dimensions (height inch)37	Gearbox oil	GL-5 80W90
Dimensions (height mm)940Dimensions (length mm)850Dimensions (width inch)79.1Dimensions (height inch)37	Lubricant	EP 2
Dimensions (length mm)850Dimensions (width inch)79.1Dimensions (height inch)37	Dimensions (width mm)	2010
Dimensions (width inch) 79.1 Dimensions (height inch) 37	Dimensions (height mm)	940
Dimensions (height inch) 37	Dimensions (length mm)	850
,	Dimensions (width inch)	79.1
Dimensions (length inch) 33.5	Dimensions (height inch)	37
	Dimensions (length inch)	33.5





Email: info@centaur-asiapacific.com Website: www.centaur-asiapacific.com

