Redexim

Verti-Drain® 2519

The all-new 2519 Verti-Drain combines robustness with versatility. This high-speed model can achieve a maximum working depth of 10"/250mm with a range of tines, while offering unrivalled productivity; this makes the 2519 the obvious choice for applications where agility and productivity are key.





Specifications	
SKU	111.251.904
Working width (m)	1.95
Working width (inch)	76.7
Max. Working depth (mm)	250
Max. Working depth (inch)	10
Working speed at hole spacing 65 mm	1.75
Working speed at hole spacing 2-1 2 inch (mph)	1.08
Weight (kg)	900
Weight (lbs)	1984
Max diameter solid tine (mm)	18 x 250
Max diameter solid tine (inch)	3/4 x 10
Max diameter hollow tine (mm)	25 x 250
Max diameter hollow tine (inch)	1 x 10
Min. Tractor HP required	60
Min. lifting capacity (kg)	920
Min. lifting capacity (LBS)	2028.25
Max. capacity with spacing 65 mm (m² hr)	3443
Max. capacity with spacing 2-1 2 inch (ft² hr)	37055
Three-point hitch	3-Point CAT 1/2
Rpm Max.	540
Gear case oil	80W90 - 1.2
Lubricant	EP 2
Slip clutch setting	800 Nm



Hong Kong | Singapore | Malaysia | Australia

Email: info@centaur-asiapacific.com Website: www.centaur-asiapacific.com

