

## Verti-Drain® 7212

The Verti-Drain® 7212 is well suited to lower HP tractors, this very capable model for aeration to a depth of 25cm / 10" on the more sensitive of turf areas. The 7212 is particularly popular hard to reach areas due to its overall dimensions while maintaining all the features of larger Verti-Drains



### Specifications

SKU	7212
Working width (m)	1.2
Working width (inch)	48
Max. Working depth (mm)	250
Max. Working depth (inch)	10
Working speed at hole spacing 65 mm	1
Weight (kg)	470
Weight (lbs)	1030
Hole distance with 12 mm tines (mm)	65
Hole distance with 1 2 x 6 inch tines (inch)	2.5
Hole distance with 18 mm tines (mm)	100
Hole distance with 3 4 x 9 inch tines (inch)	4
Hole spacing distance driving direction (mm)	25 - 165
Hole spacing distance driving direction (inch)	1 - 6-1/2
Max diameter solid tine (mm)	18 x 250
Max diameter solid tine (inch)	3/4 x 10
Max diameter hollow tine (mm)	25 x 250
Max diameter hollow tine (inch)	1 x 10
Min. Tractor HP required	18
Min. lifting capacity (kg)	570
Min. lifting capacity (LBS)	1250
Max. capacity with spacing 65 mm (m <sup>2</sup> hr)	1200
Max. capacity with spacing 2-1 2 inch (ft <sup>2</sup> hr)	11000
Three-point hitch	3-point CAT 1
Rpm Max.	500
Gear case oil	80W90
Lubricant	EP 2
Slip clutch setting	400 Nm



**Hong Kong | Singapore | Malaysia | Australia**

**Email: [info@centaur-asiapacific.com](mailto:info@centaur-asiapacific.com)**

**Website: [www.centaur-asiapacific.com](http://www.centaur-asiapacific.com)**

