

Verti-Drain® 7516

The Verti-Drain® 7516 packs a punch while remaining compact. Capable of working to a depth of 40cm / 16", the 7516 is well suited to work on sport fields, golf course and with municipalities. The tough chassis makes it the ideal Verti-Drain for a range of aeration tasks no more challenging ground



Specifications

SKU	7516
Working width (m)	1.6
Working width (inch)	63
Max. Working depth (mm)	400
Max. Working depth (inch)	16
Weight (kg)	1130
Weight (lbs)	2490
Hole distance with 12 mm tines (mm)	65
Hole distance with 1 2 x 6 inch tines (inch)	2.5
Hole distance with 24 mm tines (mm)	129
Hole distance with 1 x 16 inch tines (inch)	5
Hole spacing distance driving direction (mm)	50-195
Hole spacing distance driving direction (inch)	2 - 7-1/2
Max diameter solid tine (mm)	24 x 400
Max diameter solid tine (inch)	1 x 16
Max diameter hollow tine (mm)	32 x 300
Max diameter hollow tine (inch)	1-1/4 x 12
Min. Tractor HP required	45
Min. lifting capacity (kg)	1350
Min. lifting capacity (LBS)	3000
Max. capacity with spacing 65 mm (m ² hr)	1120
Max. capacity with spacing 2-1 2 inch (ft ² hr)	10200
Three-point hitch	3-point CAT 1-2
Rpm Max.	500
Gear case oil	80W90 - 5.8
Lubricant	EP 2
Slip clutch setting	800 Nm



Hong Kong | Singapore | Malaysia | Australia

Email: info@centaur-asiapacific.com

Website: www.centaur-asiapacific.com

