

## Verti-Quake® 2510

The Verti-Quake® de-compacts the soil profile with powered offset blades. The blades rotary action, combined with the forward speed created a wave motion to move the ground laterally and de-compact consistently from the top of the soil to full working depth with little playing surface disruption.



### Specifications

SKU	115.251.000
Working width (m)	1.1
Working width (inch)	43
Max. Working depth (mm)	250
Max. Working depth (inch)	9.8
Weight (kg)	470
Weight (lbs)	1189
Number of knives (blades)	12
Distance between knife discs (mm)	260
Distance between knife discs (inch)	10.2
Standard knife thickness (mm)	12
Min. Tractor HP required	20-30
Min. lifting capacity (kg)	650
Min. lifting capacity (LBS)	1432
Max. capacity ( m <sup>2</sup> hr)	1650
Max. capacity (ft <sup>2</sup> hr)	17760
Three-point hitch	3-point CAT 1-2
Rpm Max.	540
Gearbox oil	SAE 90
Lubricant	EP 2



**Hong Kong | Singapore | Malaysia | Australia**

**Email: [info@centaur-asiapacific.com](mailto:info@centaur-asiapacific.com)**

**Website: [www.centaur-asiapacific.com](http://www.centaur-asiapacific.com)**

