

Verti®-Rake 300

The Verti-Rake's spring tines work between the grass blades to loosen thatch. The adjustable tine angle allows for the aggression to altered while the working depth can be further adjusted for perfect results. The Verti-Rake can also be used to create a seed bed before overseeding.





Working width (inch) 118.1 Max. Working speed (km h) 12 Working speed (mph) 7.5 Weight (kg) 275 Weight (lbs) 606 Distance between pins (mm) 15 Min. Tractor HP required 18 Min. lifting capacity (kg) 400 Max. capacity (m² hr) 36000 Max. capacity (ft² hr) 387500 Three-point hitch 3-point CAT 1-2 Lubricant EP 2	Specifications	
Working width (inch) 118.1 Max. Working speed (km h) 12 Working speed (mph) 7.5 Weight (kg) 275 Weight (lbs) 606 Distance between pins (mm) 15 Min. Tractor HP required 18 Min. lifting capacity (kg) 400 Max. capacity (m² hr) 36000 Max. capacity (ft² hr) 387500 Three-point hitch 3-point CAT 1-2 Lubricant EP 2	SKU	161.300.000
Max. Working speed (km h) 12 Working speed (mph) 7.5 Weight (kg) 275 Weight (lbs) 606 Distance between pins (mm) 15 Min. Tractor HP required 18 Min. lifting capacity (kg) 400 Max. capacity (m² hr) 36000 Max. capacity (ft² hr) 387500 Three-point hitch 3-point CAT 1-2 Lubricant EP 2	Working width (m)	3
Working speed (mph) 7.5 Weight (kg) 275 Weight (lbs) 606 Distance between pins (mm) 15 Min. Tractor HP required 18 Min. lifting capacity (kg) 400 Max. capacity (m² hr) 36000 Max. capacity (ft² hr) 387500 Three-point hitch 3-point CAT 1-2 Lubricant EP 2	Working width (inch)	118.1
Weight (kg)275Weight (lbs)606Distance between pins (mm)15Min. Tractor HP required18Min. lifting capacity (kg)400Max. capacity (m² hr)36000Max. capacity (ft² hr)387500Three-point hitch3-point CAT 1-2LubricantEP 2	Max. Working speed (km h)	12
Weight (lbs)606Distance between pins (mm)15Min. Tractor HP required18Min. lifting capacity (kg)400Max. capacity (m² hr)36000Max. capacity (ft² hr)387500Three-point hitch3-point CAT 1-2LubricantEP 2	Working speed (mph)	7.5
Distance between pins (mm) Min. Tractor HP required Min. lifting capacity (kg) Max. capacity (m² hr) Max. capacity (ft² hr) Three-point hitch Lubricant 18 400 400 36000 387500 387500 3-point CAT 1-2 EP 2	Weight (kg)	275
Min. Tractor HP required Min. lifting capacity (kg) 400 Max. capacity (m² hr) 36000 Max. capacity (ft² hr) 387500 Three-point hitch Lubricant 18 400 36000 36000 387500 3-point CAT 1-2 EP 2	Weight (lbs)	606
Min. lifting capacity (kg) Max. capacity (m² hr) Max. capacity (ft² hr) Three-point hitch Lubricant 400 36000 387500 3-point CAT 1-2 EP 2	Distance between pins (mm)	15
Max. capacity (m² hr) Max. capacity (ft² hr) 387500 Three-point hitch 2-point CAT 1-2 Lubricant EP 2	Min. Tractor HP required	18
Max. capacity (ft² hr) 387500 Three-point hitch 3-point CAT 1-2 Lubricant EP 2	Min. lifting capacity (kg)	400
Three-point hitch 3-point CAT 1-2 Lubricant EP 2	Max. capacity (m² hr)	36000
Lubricant EP 2	Max. capacity (ft² hr)	387500
	Three-point hitch	3-point CAT 1-2
Min. lifting capacity (lbs) 882	Lubricant	EP 2
	Min. lifting capacity (lbs)	882





Email: info@centaur-asiapacific.com Website: www.centaur-asiapacific.com

