



Turfco TriWave™ 45 Overseeder

Specifications

Model	85858 - equipped with factory installed Standard Fairway Blades; 85859 - equipped with factory installed Greens Blades
Width	66" (1.67 m)
Height	56.5" (1.43 m)
Length	80.5" (2.05 m)
Capacity	3.2 ft ³ (0.09 m ³) Approx. 50 lb of grass seed
Seed Application Pattern	Seed spacing 1-1/2" (38.1 mm) apart
Seeding Width	40" (1.01 m)
Seed Gate	Automatic operation, adjustable variable opening
Ground Speed	Operating Speed: 3 MPH (4.8 km/h); Transport Speed: 6 MPH (9.6 km/h)
Transport Speed	Up to 6 MPH (9.6 km/h) (maximum)
Productivity	5,868 yards/hour at 3 mph (4,897 sq meters/h at 4.8 km/h)
Cutting Heads	2 heads, independently floating
Blade Assembly	2 WaveBlade sets, 20 blades total
Blade Assembly Operating Depth Range	0 to 1 3/8" (0 to 34.9 mm)
Engine	25 HP Briggs and Stratton Vanguard with electric start and 20 AMP charging system
Electrical	Fuse protected electric clutch and seed box motor. Requires customer supplied 12 volt DC group U1 battery
Hydraulics	Hydraulic cylinder to raise/lower the wheels. Hydraulic power supplied by the tow vehicle
Clutch	Electric clutch with double groove V-belt
Hitch	Standard 5/8" pin, equipped with jackstand
Weight	1,070 lbs (485 Kg) hopper empty
Optional Equipment	Hydraulic Power Kit (HPU) (hose kit not needed when equipped with HPU) #86196 Hydraulic Hose Kit for use with Cushman Truck (#86505) Hydraulic Hose Kit for use with Toro or John Deere Trucks (#86506)
Warranty	3 Years

Distributed by:



*Hong Kong, Macau and Singapore

www.centaur-asiapacific.com
info@centaur-asiapacific.com